

Index

A

- Abiotic degradation, environmental characteristics, 889-890
- Abrasive wear, 435, 930-931
- Accepted Reference Values, 1047-1048
- Accumulation processes, environmental characteristics, 894-895
- Acid catchers, refrigeration lubricants, 419
- Acidity, automotive lubricants, 474-475
- Acid neutralizing agents, 221
- Acid number
 - compressor lubricants, 400
 - gear lubricants, 456
 - mineral oil heat transfer fluids, 582
 - quench oils, 609-610
 - turbine lubricating oils and hydraulic fluids, 329, 331
- Acids
 - formation, 790
 - for lubricants, 272
- Acoustical measurements, steel quenching, 600-602
- Active oxygen method, 820-821
- Additives, 199-246
 - antiseize, 218
 - aviation fuels, 104-105
 - classification, 951-957
 - demulsifiers, 232-233, 366
 - detergents, 208-211
 - dispersants, 203-208
 - dispersant viscosity modifiers, 228-229, 231
 - dyes, 234
 - emulsifiers, 232-233
 - environmental impact, 234
 - ester polymers, 225-228
 - film-forming agents, 211-223
 - filterability, 368
 - friction modifiers, 211-213, 441, 949, 951-952
 - gear lubricants, 439-443, 447
 - hydraulic fluids, 363
 - introduction of new, 234
 - metalworking and machining fluids, 511-519
 - alkalinity agents, 516
 - antimicrobial agents, 517-518
 - anti-misting agents, 516
 - corrosion inhibitors, 516-517
 - coupling agents, 513
 - dispersants, 516
 - dyes, 519
 - emulsion promoters, 512-513
 - film-forming agents, 513-515
 - foam inhibitor, 518
 - inorganic/organic solids, 519
 - odor control agents, 519
 - oxidation inhibitors, 518-519
 - multifunctional nature, 234
 - olefin-based polymers, 224-226
 - performance package, 200-201
 - performance testing, 235-242
 - engine oils, 237-239
 - finished formulations, 235-236
 - gear oils, 239-240
 - greases, 242
 - hydraulic fluids, 240-241
 - individual additives, 235
 - machine tests, 236
 - metalworking fluids, 241
 - miscellaneous industrial oils, 241-242
 - physical tests, 236
 - transmission fluids, 239
 - viscosity tests, 237
 - polymeric, 223-233
 - pour point depressants, 230-232, 373
 - primary functions, 200
 - refrigeration lubricants, 418-420
 - rust and corrosion inhibitors, 218, 220-223, 318-320
 - stabilizers/deposit control agents, 201-211
 - standard, 243-246
 - for turbines, 312-323
 - antifoams, 321-323
 - antioxidants, 312-318
 - antiwear and extreme-pressure, 319-321
 - rust and corrosion inhibitors, 318-320
 - viscosity modifiers, 223-224
 - see also* Antifoam additives; Antiwear additives; Antioxidants; Corrosion inhibitors
- Adhesion, friction due to, 911
- Adhesives, viscosity, 870-872
- Adhesive wear, 435, 923, 927-930, 979-982
 - resistance ranking, 980-981
 - testing, oil evaluation, 981-982
 - test method, 979
 - traction test plots, 980
- Adiabatic flame temperature, gasoline, 84
- Adiabatic operation, 384
- Adipic acids, synthesis, 276, 279
- Adsorption, environmental characteristics, 888
- Adsorption efficiency, steric hinderance, 952-953
- Adsorption isotherms, 953-954
- Aeration, hydraulic fluids, 366-367
- Aero-derivative gas turbines, 301-302
- Aerospace, engine thermodynamics, 730-732
- Aerospace fuels, 729-756
 - air dilution, 742
 - bouyancy in air, 732
 - calorific values, 739-740
 - combustion emissions, 743
 - density, 735-736
 - flame stabilization, 742

- flammability, 738
- fueling fire safety, 744
- future trends, 747-748
- handling characteristics, 743-747
- health issues in handling, 747
- ignition, 741
- lubricity, 744-745
- maximum combustion temperature, 735, 740-741
- molecular structure, 732-734
- oxidation heat release, 735
- performance of rocket fuels and oxidants, 731
- physical state, 733
- preparation and mixing, 741
- properties, 735-736
- reformation, 747
- smoke tendency, 741
- solidification, 737-738
- specifications, 748
- specific impulse, 742-743
- spontaneous ignitability, 733-734, 738
- standards, 749
- stoichiometry, 734-735, 738-739
- storage stability, 732, 745
- substitute fuels, 748
- supplemental fuels, 747
- surface tension, 738
- thermal stability, 745-746
- turbine entry temperature distribution, 742
- viscosity, 737
- volatility, 736-737
- water content, 746-747
- Aging, Baader aging test, 821-822
- Air conditioning lubricants, 484
- Aircraft, sumping procedure, 111
- Aircraft range, aviation fuels, 100-101
- Air-fuel ratio, octane number requirement, 76
- Airport
 - fuel systems, 106
 - quality control, 110-111
- Air release
 - compressor lubricants, 398
 - gear lubricants, 460
 - turbine lubricating oils and hydraulic fluids, 332-334
- Alcohol bonds, environmentally friendly oils, 271-272
- Alcohols
 - hydrogen bond, 270
 - for lubricants, 271-273
- Algae, acute toxicity tests, 901-902
- Alkalinity agents
 - automotive lubricants, 474-475
 - metalworking and machining fluids, 516
- Alkanes
 - lattice transition, 534
 - physical properties, 532
- Alkenylsuccinates, synthesis, 206
- Alkylated cyclopentanes, 260
- Alkylation, 15-17
- Alkylbenzene
 - compressor lubricants, 395
 - refrigeration lubricants, 415
- Alkyl lead
 - history, 62
 - phasedown, 63
- Alkyl lead content, 68
 - ASTM D 4814, 82
- Alkylphenols, 209
- Alkyl phosphates, synthesis, 216, 218
- Alkyl phosphites, synthesis, 216-217
- Alternative fuels, diesel engines, 138-139
- Aluminum, production, carbon anodes, 781-782
- Aluminum beaker oxidation test, 810, 813
- Aluminum complex soap greases, 559
- Aluminum soap greases, 558
- Ammonia, in LPG, 50
- Amonton's Law, 383
- Aniline point, hydrocarbon base oil, 181
- "Anti-dumping" provisions, 65
- Antifoam additives, 233-234
 - gear lubricants, 441
 - hydraulic fluids, 367
 - metalworking and machining fluids, 518
 - refrigeration lubricants, 419-420
 - for turbines, 321-323
- Anti Knock Index, 73-74
 - ASTM D 4814, 78
- Antimicrobial agents, metalworking and machining fluids, 517-518
- Anti-misting agents, metalworking and machining fluids, 516
- Antioxidants, 201-202, 793-796
 - arylamine, 795
 - gasoline, 69, 82-83
 - gear lubricants, 441, 445
 - hindered phenols, 794
 - hydraulic fluids, 356-358
 - metalworking and machining fluids, 518-519
 - refrigeration lubricants, 419
 - structures, 314
 - synergistic combination, 315
 - turbine lubricating oils and hydraulic fluids, 312-318
 - zinc dialkyl dithiophosphate, 794
- Antiseize additives, 218
- Antiwear additives, 69, 213-216, 955-956
 - gear lubricants, 440, 444
 - hydraulic fluids, 363
 - refrigeration lubricants, 419
 - surface reactions, 954-955
 - turbines, 319-321
- Antiwear performance testing, hydraulic fluids, 361-364
- Antiwear properties, compressor lubricants, 402-406
- API CF oils, 473
- API CG-4 oils, 473-474
- API CH-4 oils, 474
- API gravity

- diesel fuel, 117-118
- fuel oils, 758-759
- gear lubricants, 456
- API service designation, gear lubricants, 448-453
- Appledoorn equation, 919
- Approximate *F*-test, 1059-1060
- Aquatic toxicity tests, acute, 901
- Aqueous polymer quenchants, 605-606
- Archard's equation, 930
- Aromatic esters, 249-250
- Aromatics, 28
 - determination, 195
 - diesel fuel, 131-132
 - saturation, 17-20
- Arrhenius equation, 127-128
- Arylamine, oxidation inhibition, 795
- Aryl phosphates, synthesis, 216, 218
- Aryl phosphites, synthesis, 216-217
- Ash content
 - diesel fuel, 135
 - fuel oils, 761-762
 - marine petroleum fuels, 150
 - petroleum coke, 775
 - petroleum pitch, 768
 - quench oils, 614
- Ash modifiers, marine petroleum fuels, 154
- Asphaltene content, marine fuels, 151
- Association of Natural Gasoline Manufacturers, 36
- ASTM D 4814, 77-83
 - alkyl lead content, 82
 - anti-knock index, 78
 - copper corrosion test, 82
 - driveability index, 78-79
 - gasoline and gasohol blending, 80, 82
 - oxidation stability, 82-83
 - phosphorus content, 82
 - soluble gum, 83
 - sulfur content, 82
 - vapor pressure specifications, 78- 81
 - volatility, 78-80
 - class specifications, 82
 - water tolerance, 83
- ASTM proficiency testing, elemental analysis, 714
- Atmospheric gas oil, 3
- Atomic absorption spectrometry, elemental analysis, 709
- Austenite, 587
- Autoignition
 - compressor lubricants, 399
 - mineral oil heat transfer fluids, 581
 - temperature, gasoline, 83-84
- Automatic tank gauging, 645
- Automatic transmission fluids
 - aluminum beaker oxidation test, 810, 813
 - hydraulic fluids, 374
 - performance testing, 239
- Automotive wheel bearing grease, 807
- Automotive engine oils, 467-470
 - ASTM standard test methods, 469-470
 - corrosion tests, 828-829
 - issues in test method development, 469
 - performance standards, 467-468
 - performance tests, 468-469
- Automotive gear lubricants, 442, 446, 448
 - oxidation stability, 803-804
 - performance testing, 239-240
- Automotive lubricants, 465-494
 - additional fluids, 484
 - air conditioning lubricants, 484
 - axle lubricants, 483
 - brake fluids, 483
 - composition, 466-467
 - extent of oxidation, 476-477
 - functions, 465-466
 - greases, 478-481
 - ILSAC GF-2 and API SJ standard tests, 470-476
 - acidity and alkalinity, 474-475
 - ball rust test, 472-473
 - city service engine sludge and valve train wear, 470-471
 - corrosiveness, 475
 - diesel engine oil, 473-474
 - energy conserving characteristics, 471
 - entry of water, 475
 - foaming tendency, 471
 - high temperature copper-lead bearing water, 470
 - phosphorus content, 471
 - short-trip-service engine rusting, 471
 - standard tests, 472
 - viscosity, 475-476
 - volatility, 471
 - solid lubricants, 483-484
 - standards, 485-494
 - test methods, 466-467
- Automotive transmission fluids, 477-478
 - oxidation stability, 804
- Auto-Oil Air Quality Improvement Research Program, 65
- Auto propane, 51-52
- Auto-refrigeration, 46
- Autoxidation, ester based fluids, 277, 279
- Aviation fuels, 89-113
 - additives, 104-105
 - aircraft range, 100-101
 - combustion, 97-98
 - corrosion tests, 828
 - corrosivity, 101-102
 - freezing point, 880-881
 - gasoline, 89-92
 - high temperature, 95-97
 - history, 89
 - jet fuel, 89, 91-93
 - low temperature
 - fuel related, 93-95

water related, 95
 lubricity, 102-103
 manufacturing, 103-104
 metering, 99-100
 oxidation
 stability, 813
 standards, 823
 quality control, 106-111
 aviation gasoline, 107
 contaminants, 106
 contamination detection equipment, 109-110
 contamination removal equipment, 107-109
 jet fuel, 107
 procedures, 110-111
 standards, 112-113
 static electricity, 103
 storage stability, 102
 transportation, 105-106
 volatility and flammability, 98-99
 Aviation gas turbine oils
 basestocks, 1012, 1014
 corrosion inhibited MIL-PRF-23699 oils, 1011
 gear testing, 988
 high load-carrying DOD-L-85734 oils, 1011- 1012
 high thermal stability MIL-PRF-23699 oils, 1011
 load capacity database, 1011-1015
 master chart, 1012, 1014
 selected MIL-PRF-7808 grade 3 and grade 4 oils, 1012-1013
 standard MIL-PRF-23699 oils, 1011
 Aviation turbine fuels, thermal oxidation stability, 815-816
 Avogadro's Law, 383
 Axle lubricants, 483

B

Baader aging test, 821-822
 Back pressure control, 164-165
 Bainite, 587
 Ball bearings, greases, at elevated temperatures, 565-566
 Ball on Cylinder Lubrication Evaluator, 102
 Ball rust test, 472-473
 Band area methods, infrared spectroscopy, 668
 Barus equation, 917-918
 Base number, gear lubricants, 458
 Base oil, *see* Hydrocarbon base oil
 Bearing contacts, performance maps and, 972-973
 Beer-Lambert law, 667
 Beer's law, 661
 Beeswax, 525-526
 Bench test, 1020-1021
 Block-on-Ring test, 1029-1030
 four ball extreme pressure test, 1028-1029
 four ball tests, 1026-1027
 four ball wear test, 1027-1028
 linear reciprocation, 1031-1033
 multi-specimen test machine, 1030-1031
 pin and vee block tester, 1025-1026
 Pin-on-Disk test, 1026
 selection, 1019
 tapping torque test, 1030
 Timken extreme pressure test machine, 1030- 1031
 Bench test modeling, *see* Ryder gear; Systematic tribology
 Bending-beam rheometer, 870, 872
 Benzene, 28
 Benzene Emission Number, 66
 Bessemer Gas Engine Company, 37
 Bias
 measurement process, 1044-1045
 monitoring, 1047-1048
 Bioaccumulation factor, 894-895
 Biocides, marine petroleum fuels, 154
 Bioconcentration factor, 894-895
 Biodegradability
 diesters, 252
 environmental characteristics, 890-894
 hydrocarbon base oil, 182
 polyolesters, 252
 synthetic lubricants, 263
 Biodegradable lubricants, oxidation
 standards, 823
 testing, 820-822
 Biodiesel, 138-139
 Biological properties, hydrocarbon base oil, 181-182
 Biological stability, polymer quenchants, 620-623
 Biota-sediment accumulation factor, 894-895
 Bituminous materials, viscosity, 870-872
 Black deposits, LPG, 49-50
 Black penetration, lubricating greases, 561
 "Blaugas", 35-36
 Blending
 marine fuel oils, 147-148
 petroleum oil, 28
 Blocking point, petroleum waxes, 552-553
 Block-on-Ring test, 1029-1030
 Boeing 747-400 fuel tankage, 93
 Boiling point, 28
 Boiling range, synthetic hydrocarbons, 195
 Bomb combustion methods, elemental analysis, 709
 Bomb oxidation test, lubricating greases, 565
 Bonded fuel, aviation fuels, 106
 Boost systems, diesel fuel system, 164
 Borsoff effect, 936
 Boundary lubrication, 214, 498, 949
 Bouyancy, aerospace fuels, 732
 Brake fluids, 483
 standards, 493
 Brayton cycle, 730-731
 Broomwade 2050H Compressor Rig Test, 403
 Brush drag of latex paints, 868
 Btx recovery, 14-15
 Bubble tubes, 868
 Bulk material properties, flow properties, 921-922, 925-926
 Bunsen Coefficient, 406
 Bureau of Mines Correlation Index, 186

- Butadiene
 analysis, 193
 production, 190-192
 purity, 193
 Butane, 46
 Butane-butene mixtures, chlorides in, 194
 Butylene
 analysis, 193
 production, 190-192
- C**
- Cadmium corrosivity, aviation fuels, 102
 Calcium complex soap greases, 559
 Calcium soap greases, 558-559
 Calorific values, aerospace fuels, 739-740
 Canadian Environmental Protection Act, 66
 Candelilla wax, 525-526
 Carbon acids, hydrogen bond, 270
 Carbon anodes, for aluminum production, 781-782
 Carbon blacks, 779-781
 Carbon fibers, petroleum pitch, 781
 Carbonizable substances, petroleum waxes, 549
 Carbon residue
 compressor lubricants, 399
 diesel fuel, 135-136
 fuel oils, 761
 marine petroleum fuels, 151-152
 mineral oil heat transfer fluids, 580
 quench oils, 611-613
 standards, 783-784
 Carbonyls, in C₄ hydrocarbons, 194
 Carbonyl sulfide, in propylene, 193
 Carboxylic acids
 environmentally friendly oils, 272-273
 isomers, 270
 Carnauba, 525-526
 Carreau viscosity equation, 948-949
 Casinghead gasoline, 36-37
 Catalytic reforming, 12-15
 yield/octane relationship, 14
 Caterpillar micro-oxidation test, 810-811, 813-814
 Cat fines, marine petroleum fuels, 150
 "Cat" gasoline, 11
 Cavitation corrosion, 932
 Cavitation erosion, 932-933
 Cavitation erosion corrosion, 933
 Cavitation wear, 931-941
 corrosion, 931-932
 delamination, 937-938
 erosion, 931-932
 fatigue, 933-936
 oxidational, 933
 scuffing, 936-937
 tribochemical, 933
 CCT diagrams, 589
 Cementite, 587
 Centrifugal compressor, 389-390
 Centrifuges, diesel fuel system, 161, 163
 Centrifuge tests, 365
 lubricating greases, 564-565
 Cetane index, 119-120
 Cetane number, 119
 diesel fuel oils, 721-723
 Channel point FTM, gear lubricants, 459
 Chemical analysis, lubricating greases, 569
 Chemical corrosion, 220
 Chi-square test, 1059
 Chlorine content
 butane-butene mixtures, 194
 gear lubricants, 457
 turbine lubricating oils and hydraulic fluids, 334
 City service engine sludge and valve train wear, 470-471
 Clay treatment vessels, 108-109
 Clean Air Act of 1963, 63
 Clean Air Act of 1970, 64
 Clean Air Act Amendments of 1977, 64
 Clean Air Act Amendments of 1990, 65-66, 135
 Cleanliness
 diesel fuel, 124-125
 turbine lubricating oils and hydraulic fluids, 341-343
 Cleveland Open Cup, 692
 Cloud point, 881-882
 diesel fuel, 121-122
 petroleum waxes, 545-546
 polymer quenchant, 619
¹³C NMR spectrometry, hydrocarbon analysis, 650-651
 CNS effects, LPG, 54-55
 Coalescer Blocking Tendency Test, compressor lubricants, 404-406
 Coatings, flow-related instruments, 867
 CoBr test, 47-48
 Coefficient of kinetic friction, petroleum waxes, 552, 554
 Cogeneration, 28
 Coking, delayed, 21-23
 Coking value, petroleum pitch, 767-768
 Cold crank simulator, 850
 gear lubricants, 458
 Cold Filter Plugging Point, diesel fuel, 123-124
 Cold flow properties, 879-883
 aviation fuels freezing point, 880-881
 cloud point, 881-882
 high-shear tests of lubricants, 882
 pour point, 879-880
 pumpability of lubricants, 882
 standards, 883
 wax appearance point, 881-882
 Color, petroleum waxes, 549-551
 Combustion, diesel fuel, 118-119
 Combustion products, dissociated, 753-754
 Combustion temperature, aerospace fuels, 735, 740-741
 Compatibility
 gear lubricants, 460
 marine petroleum fuels, 152
 turbine lubricating oils and hydraulic fluids, 343-346

- see also* Seal compatibility
- Compressibility factor, 384
- Compression, power requirement, 385-386
- Compression ignition engines, 115-116
- Compression ratio, octane number requirement, 76
- Compressor lubricants, 383-411
 - acid number, 400
 - air release, 398
 - antiwear properties, 402-406
 - autoignition, 399
 - basestocks, 392-395
 - carbon residue, 399
 - classification, 391
 - copper corrosion, 398
 - corrosion, 398-399
 - demulsibility, 397-398
 - elastomeric seals compatibility, 409
 - evaporation, 399
 - Filter Bowl Compatibility Test, 410
 - fire point, 398-399
 - flash point, 398-399
 - fluid oxidation, 400-401
 - foaming tendency, 398
 - gas solubility, 395-396, 406-409
 - heat transfer efficiency, 408-409
 - hydrolytic stability, 398
 - infra-red spectroscopy, 400-401
 - iron corrosion, 398
 - kinematic viscosity, 396-397
 - Liquid Heptane Washing Test, 401-402
 - oxidation stability, 802
 - Paint Compatibility Test, 409-410
 - performance demands, 389-392
 - pour point, 397
 - precipitation number, 399-400
 - solubility in the gas, 396, 398
 - specific gravity, 397
 - specific heat, 408-409
 - standards, 410-411
 - thermal conductivity, 408-409
 - viscosity of gas/liquid mixtures under pressure, 408
 - water content, 397
- Compressor tests, 403
- Concentric cylinder viscometer, 835-836
- Conductance, polymer quenchants, 618-619
- Conductivity, gasoline, 85
- Cone-and-plate viscometer, 835
- Cone penetration, lubricating greases, 561
- Congealing point, petroleum waxes, 545
- Conradson carbon residue, compressor lubricants, 399
- Consistency, lubricating greases, 560-561
- Consistency stability, lubricating greases, 561-562
- Construction materials, gas turbine fuel system, 166-167
- Contact stress, 966
 - simulation, Ryder gear, 997-1000
- Contamination
 - aviation fuels, 106
 - detection equipment, aviation fuels, 109-110
 - gasoline, 69
 - lubricating greases, 568-569
 - quench oils, 610-614
 - removal equipment, aviation fuels, 107-109
- Continuous cooling transformation diagrams, 589
- Control chart, 1055-1056
- Conventional Oxidation Catalyst, 63-64
- Coolants, secondary, 574
- Coolant separability, hydraulic fluids, 370-371
- Cooling curve analysis, polymer quenchants, 621-623
- Copper corrosion, 826
 - aviation fuels, 101-102
 - compressor lubricants, 398
 - lubricating greases, 567-568
- Copper corrosion inhibitors, 69
- Copper corrosion test, ASTM D 4814, 82
- Copper deactivation, 221
- Copper passivators, 221-222
- Copper strip corrosion, diesel fuel, 134-135
- Copper strip tarnish test, 827-828
 - gear lubricants, 454, 456
- Corrosion, 825-832
 - compressor lubricants, 398-399
 - in LPG, 49
 - specifications, 827
- Corrosion behavior, turbine lubricating oils and hydraulic fluids, 340-341
- Corrosion inhibitors, 218, 220-223
 - gear lubricants, 441
 - hydraulic fluids, 369-370
 - metalworking and machining fluids, 516-517
 - polymer quenchants, 619-620
 - surface activity, 826-827
 - for turbines, 318-320
- Corrosion protection, hydraulic fluids, 368-370
- Corrosion tests, 827-832
 - automotive engine oils, 828-829
 - aviation gasolines, 828
 - diesel fuel oils, 828
 - gear oils, 829
 - greases, 831-832
 - lubricants, 827-828, 829-831
- Corrosion wear, 931-932
- Corrosivity
 - aviation fuels, 101-102
 - diesel engine oil, 475
- Coupling agents, metalworking and machining fluids, 513
- Cracking, crude oil, 146-148
- Critical pressure, 384
- Critical temperature, 384
- Crude oil gases, 3
 - disposition, 5
- Crude oils, 6-7, 145-148
 - classification, 526-527, 575-576
 - cracking, 146-148
 - distillation, 146-147

- distillation, 696-698
 - preparation and separation, 9-10
 - refinery blending and storage, 147-148
 - refining, 528-529
 - vapor pressure, 702
 - waxy, 527-528
 - Crystalline structure, petroleum coke, 775-776
 - Crystallization, esters, 289-291
 - Cyclic durability test, gear lubricants, 458
 - Cyclohexane derivatives, 260
- D**
- Dalton's Law, 383
 - Defoamers, *see* Antifoam additives
 - Deformation, friction due to, 911
 - Degree of overbasing, 208
 - De-icers, 68
 - Delamination wear, 937-938
 - Delayed coking, 21-23
 - Demulsibility
 - compressor lubricants, 397-398
 - gear lubricants, 457-458
 - hydraulic fluids, 366
 - Demulsifiers, 232-233
 - gear lubricants, 441
 - marine petroleum fuels, 154
 - Density
 - aerospace fuels, 735-736
 - crude oil, 6
 - diesel fuel, 117-118
 - marine petroleum fuels, 149
 - petroleum coke, 775
 - petroleum pitch, 768
 - refrigeration lubricants, 421
 - turbine lubricating oils and hydraulic fluids, 332
 - Deposit control additives, 69-70
 - Desorption, environmental characteristics, 888
 - Detergents, 208-211
 - gear lubricants, 440, 444
 - hydraulic fluids, 358
 - micellar structure, 210-211
 - synthesis, 210
 - Dewaxing, hydrocarbon base oil, 171-172
 - Dewaxing process variables, 530-531
 - Dew Point test, 47-48
 - Dialkyl dithiophosphoric acid derivatives, synthesis, 215
 - Dibasic acid esters, refrigeration lubricants, 416
 - Diesel engines
 - alternative fuels, 138-139
 - history, 115-116
 - Diesel fuel oils, 9
 - API gravity, 117-118
 - aromatics, 131-132
 - ash, 135
 - carbon residue, 135-136
 - cetane index, 119-120
 - cetane number, 119
 - cleanliness, 124-125
 - Cloud Point, 121-122
 - Cold Filter Plugging Point, 123-124
 - composition/performance correlations, 178-179
 - copper strip corrosion, 134-135
 - corrosion tests, 829
 - corrosiveness, 475
 - density, 117-118
 - distillation, 120-121
 - dyed, 135-137
 - Flash point, 128-129
 - formation of insolubles, 125
 - grades, 116-117
 - heat content, 132-134
 - heat of combustion, 132-134
 - ignition and combustion characteristics, 118-119
 - low-sulfur, 135-137
 - Low-Temperature Flow Test, 123
 - lubricity, 129-131
 - oxidation stability, 126-127
 - performance categories, 473-474
 - Pour Point, 122-123
 - premium, 137-138
 - requirements, 118
 - specifications, 116-117
 - stability, 125-126
 - storage stability, 127-128
 - thermal stability, 126
 - total sulfur, 134
 - viscosity, 121
 - volatility, 120-121
 - World Wide Fuel Charter, 137
 - Diesel fuel combustion, 717-727
 - combustion process, 718-719
 - emissions, 719-721
 - fuel injection, 717-718
 - ignition, 718
 - Diesel fuel oils
 - cetane number, 721-723
 - corrosion tests, 828
 - CVCA/IQT method, 724-727
 - ignition quality, 721-727
 - proposed alternatives to ASTM D 613, 723-724
 - specifications, 718
 - standards, 727
 - Diesel fuel system, 161, 163-165
 - back pressure control, 164-165
 - boost systems and deaeration, 164
 - centrifuges, 161, 163
 - emulsifiers, 165
 - filters and strainers, 163-164
 - fuel final filter, 164
 - fuel service heaters, 164
 - fuel supply flowmeter, 164
 - homogenizer, 165
 - viscosity control, 164
 - waste heat economizers, 165

- Diesel index, 118
- Diesel-injector nozzle, shear resistance, turbine lubricating oils and hydraulic fluids, 340
- Diesel plant fuel system, 161-162
- Diesters, 249-252
 application and performance characteristics, 252
 biodegradability, 252
 chemical characteristics, 251
 chemistry and manufacturing, 249-251
 manufacturing technology, 250-251
 physical properties, 251
- Difference method, infrared spectroscopy, 668
- Differential scanning calorimetry
 petroleum waxes, 539-542
 transition temperatures, 548
- Dip cups, 867-868
- Dispersants, 203-208
 bridged structure, 206-207
 gear lubricants, 440-441, 445
 hydraulic fluids, 358
 in marine petroleum fuels, 153
 metalworking and machining fluids, 516
 performance, 204-205
 structural features, 205-206
 uses, 206, 208
- Dispersant viscosity modifiers, 206, 228-229, 231
- Dispersive-type infrared spectrometers, 667
- Disposition tendencies, liquids in thin films and vapors, 819-820
- Dissociation constant, environmental characteristics, 888
- Distillate fuels
 high temperature stability, 817-818
 oxidation stability, 816-817
 storage stability, 817-818
- Distillation, 675-682
 atmospheric pressure, 676-680
 crude oils, 146-147, 696-698
 diesel fuel, 120-121
 fuel oils, 761
 hydraulic fluids, 365
 hydrocarbon base oil, 171
 international standards, 689
 mineral oil heat transfer fluids, 582
 reduced pressure, 680-690
- Distillation fractions, 3-4
 2,6-Ditertiarybutyl-4-methylphenol, 314-315
- DOD-L-85734 oils, 1011-1012
- Driveability index, 78-79
- Dropping point, lubricating greases, 563-564
- Dyes, 234, 519
- Dynamic seals test, gear lubricants, 460
- Dynamic shear rheometer, 870
- E**
- Ecological tests, environmentally friendly oils, 289, 291-292
- Elastohydrodynamic contact, functional regions, 965
- Elastohydrodynamic film-forming capability, engine oil, 983-987
 optical thickness measurement, 984-985
 pressure-viscosity coefficients, 985-987
- Elastohydrodynamic lubrication, 413, 968
 film thickness, 1007
 measurements by interferometry, 947-948
 mixed film lubrication, 949
 non-Newtonian, 948-949
 Reynolds equation, 948
- Elastomeric seals, *see* Seal compatibility
- Elastomers, turbine lubricating oils and hydraulic fluids
 compatibility, 344
- Electric-arc furnaces, graphic electrodes, 782
- Electrochemical corrosion, 218, 220
- Electrostatic stabilization, 204-205
- Elemental analysis, 707-716
 ASTM proficiency testing, 714
 atomic absorption spectrometry, 709
 bomb combustion methods, 709
 classical wet chemistry methods, 709
 DO2 test methods, 709-710
 future developments, 715-716
 graphite furnace atomic absorption spectrometry, 709-711
 inductively coupled plasma-atomic emission spectrometry, 711-712
 inductively coupled plasma-mass spectrometry, 712
 international test methods harmonization, 714-715
 ion chromatography, 712
 microelemental analysis methods, 712
 neutron activation analysis, 712-713
 sample preparation, 707
 standard reference materials, 714
 wear metals in used oils, 707-709
 X-ray fluorescence spectrometry, 713
- Elemental content, gear lubricants, 458
- Emissions
 aerospace fuels, 743
 diesel fuel combustion, 719-721
- Emulsifiers, 232-233
 diesel fuel system, 165
 gear lubricants, 441-442
- Emulsion promoters, metalworking and machining fluids, 512-513
- Energy conserving characteristics, 471
- Energy content, gasoline, 72
- Energy equation, 756
- Engine deposits, effect on octane number requirement, 77
- Engine management systems, 71
- Engine oils
 adhesive wear testing, 981-982
 elastohydrodynamic film-forming capability, 983-987
 hydraulic fluids, 374
 oxidation
 standards, 823
 testing, 807-811
 performance tests, 237-239

- standards, 485-488
 thermo oxidation engine oil simulation test, 808-812
 traction and scuffing failure characteristics, 1008-1009
 traction characteristics, 1003, 1005
 WAM high speed load capacity test method, 1010
 Engine spark timing, octane number requirement, 76-77
 Engine tests, engine oils, 823
 Entraining velocity, 966-967
 Environmental acceptability, synthetic lubricants, 262-263
 Environmental characteristics, 885-906
 abiotic degradation, 889-890
 accumulation processes, 894-895
 acute toxicity tests, 894, 901-902
 adsorption, 888
 biodegradation, 890-894
 chemical structure and, 886-887
 chronic and subchronic tests, 894, 903-904
 complex mixture toxicity, 900-901
 desorption, 888
 dissociation constant, 888
 exposures, 895-896, 900-901
 hazard and risk, 904
 Henry's Law Constant, 888
 low solubility materials, 900
 non-aquatic toxicity tests, 903-904
 octanol/water partition coefficient, 887
 rationale for standardized testing, 885-886
 standardized tests, 895-899
 terminology, 904-906
 transformation processes, 889
 transport processes, 888-889
 vapor pressure, 888
 volatility, 896, 900
 water solubility, 887
 Environmental considerations, marine petroleum fuels, 156
 Environmental impact, 234
 Environmentally acceptable hydraulic fluids, 377-378
 Environmentally friendly oils, 267-294
 alcohol bonds, 271-272
 carboxylic acids, 272-273
 chemical properties, 273-276
 crystallizing, 289-291
 ecologically toxic properties, 289, 291-292
 esterification, 270-271
 functional groups and elementary compound, 269-270
 functions and requirements, 267-268
 future developments, 291-293
 hydrolysis, 274
 low temperature properties, 289-291
 native esters, 275, 277-278
 oxidation stability, 274-275
 standards, 293-294
 synthetic esters, 276, 278-279
 viscosity, 273, 289-290
see also Pressure media
 Equation-of-state approach, 423, 535-539
 Equipment line sizing, refrigeration lubricants, 426
 Erosion corrosion, 933
 Erosion wear, 931-932
 Ester fluids, viscosity vs. temperature, 289-290
 Esterification, 249-250
 catalysis, 251
 mechanism, 270-271
 Ester polymers, 225-228
 Esters
 compressor lubricants, 394
 native, environmentally friendly oils, 275, 277-278
 native and synthetic
 chemical bases, 269-273
 chemical properties, 273-276
 pour points, 273
 synthetic
 environmentally friendly oils, 276, 278-279
 turbines, 309-311
 Ethanol, in propane, 47
 Ethylene
 characterization, 192
 production, 186-190
 commercial production, 188-190
 feedstock, 186-188
 thermal cracking reaction, 188
 Ethyl mercaptan, as odourant, 52, 55
 Evaporation, compressor lubricants, 399
 Evaporation loss, lubricating greases, 564
 EWMA overlay, 1056
 Exhaust emissions, marine petroleum fuels impact, 154
 Exponentially Weighted Moving Average values, 1056
 Exposures, environmental characteristics, 895-896, 900-901
 Extreme pressure additives, 213-214, 216-219, 955-957
 gear lubricants, 440, 444
 hydraulic fluids, 363
 metalworking and machining fluids, 513-515
 standards, 1036
 surface reactions, 954-955
 turbines, 319-321, 457, 1030-1031
 Extreme pressure Timken method, lubricating greases, 566
- F**
- Failure, parameters controlling, 965-966
 Falling needle, 868-869
 Falling viscometer, 836
 Fatigue wear, 933-936
 Fat solubility, 820-821
 Ferrite, 587
 Ferrous corrosion inhibitors, 69
 Film boiling, shock, steel, 599-602
 Film-forming agents, 211-223
 metalworking and machining fluids, 513-515
 Filterability, hydraulic fluids, 367-368
 Filter Bowl Compatibility Test, compressor lubricants, 410
 Filters, diesel fuel system, 163-164
 Filter-separators, 107-108
 Fire point
 Cleveland Open Cup, 692

- compressor lubricants, 398-399
- gear lubricants, 454
- quench oils, 609
- Tag Open cup, 693
- Fire-resistance tests, turbine lubricating oils and hydraulic fluids, 334-337
- Fire resistant fluids, hydraulic fluids, 375-377
- Fischer-Tropsch diesel fuels, 138
- Fischer-Tropsch process, 525-526
- Fish, toxicity tests, 902-903
- Fixed bed hydrocracking, 24
- Flame ionization detector, 653
- Flammability, 682, 690-696
 - aerospace fuels, 738
 - aviation fuels, 98-101
 - gasoline, 84
 - LPG, 52
 - see also* Fire point; Flash point
- Flash point
 - bias among test methods, 692
 - Cleveland Open Cup, 692
 - compressor lubricants, 398-399
 - continuously closed cup, 694
 - diesel fuel, 128-129
 - equilibrium method with closed cup, 693-694
 - fuel oils, 761
 - gear lubricants, 454
 - international test methods, 694-695
 - marine petroleum fuels, 150
 - Pensky-Martens Closed Cup Tester, 692-694
 - quench oils, 609
 - Setaflash Closed Cup, 693
 - small scale closed cup, 693
 - Tag Open cup, 693
 - test methods, 690-691
 - verification fluids, 691
- Flash temperatures, 941-942
- Fluorescent indicator adsorption, hydrocarbon analysis, 659
- Fluorinated basestocks, compressor lubricants, 395
- Flow properties, 833-875
 - ASTM procedures, 853-854
 - bulk material properties, 921-922, 925-926
 - flash temperatures, 941-942
 - high-temperature high-shear, 843-845
 - kinematic viscosity, 837-841
 - history, 841-843
 - temperature relationship, 854-856
 - low temperature tests, 851
 - lubricating greases, at high temperatures, 562
 - near surface structure, 919, 923
 - nomenclature, 833-835
 - non-petroleum materials, 867-872
 - pressure-viscosity coefficient, 916-920
 - standards, 072-875
 - sub-surface structure, 919-920, 924
 - surface conformity, 914-916
 - surface films, 919, 921-923
 - viscometer geometries, 835-836
 - wear maps, 942-945
 - wear surfaces, 911-913
 - see also* Cold flow properties; Viscosity
- Fluid biodeterioration, polymer quenchants, 620-621
- Fluid catalytic cracking, 9-12
 - yields, 11
- Fluid coking, 770
- Fluidized bed hydrocracking, 24-25
- Fluid oxidation, compressor lubricants, 400-401
- Foaming
 - automotive lubricants, 471
 - compressor lubricants, 398
 - gear lubricants, 456-457
 - hydraulic fluids, 366-367
 - turbine lubricating oils and hydraulic fluids, 332-334
- Foam inhibitors, *see* Antifoam additives
- Foam testing, polymer quenchants, 620
- Four ball extreme pressure test, 457, 1028-1029
 - compressor lubricants, 402
 - lubricating greases, 566-567
- Four ball tests, 1026-1027
- Four ball wear test, 457, 1027-1028
- Fourier transform infrared spectroscopy, 667
- Free water, 639-640, 646
 - in aviation fuels, 109-110
- Fretting wear, 567, 934-936
- Friction, 909-911
 - area of true contact, 909-911
 - due to adhesion, 911
 - due to deformation, 911
 - due to ploughing, 911-912
 - standards, 1035-1037
 - types of, 497
- Friction coefficient, 945
 - effect of hydrocarbon chain length, 954
- Friction modifiers, 211-213, 949, 951-952
 - gear lubricants, 441
- F*-test, 1059-1060
- Fuel additives, marine petroleum fuels, 153-154
- Fuel-injection system, 115-116
- Fuel injector shear stability test, 852
 - standards, 875
- Fuel oils, 8, 757-762
 - API gravity, 758-759
 - ash, 761-762
 - carbon residue, 761
 - compatibility of blended, 762
 - distillation, 761
 - flash point, 761
 - heating value, 759-760
 - instability, 762
 - pour point, 761
 - specifications and applications, 757-759
 - sulfur content, 762
 - viscosity, 760-761
- Fuels, oxidation testing, 811, 813, 815-818

- Fuel service heaters, diesel fuel system, 164
- Fuel treatment, gas turbine fuel system, 165-166
- Fuses, aviation fuels, 108
- FZG Gear Test Machine, 320, 322, 1033-1035
 - compressor lubricants, 402-403
- FZG Pits C i80 TS, gear lubricants, 459
- FZG scuffing test, gear lubricants, 458
- FZG test, 362

- G**
- Galling wear, 923, 929-930
- Galvanic corrosion, 932
- Gas chromatography
 - hydrocarbon analysis, 652-657
 - liquified petroleum gas, 40
 - petroleum waxes composition, 549
 - principles, 652-653
- Gas chromatography-mass spectrometry,
 - hydrocarbon analysis, 664
- Gas compression cycle, 384-386
- Gas compressors, 386-389
- Gas hydrates, 44-46
- Gas laws, 383-384
- Gas line anti-freeze, 68
- Gasohol, blending with gasoline, 80, 82
- Gasoline, 7-8, 61-86
 - additives, 68-70
 - adiabatic flame temperature, 84
 - autoignition temperature, 83-84
 - aviation, 89, 91-92
 - additives, 105
 - combustion, 97
 - history, 89-90
 - knock resistance, 97
 - low temperature, 94-95
 - manufacturing, 103
 - quality control, 107
 - volatility and flammability, 98
 - combustion, 70-77
 - air-fuel ratio and stoichiometry, 71-72
 - engine management systems, 71
 - gasoline energy content, 72-73
 - spark ignition engines, 70-71
 - composition, 66-68
 - conductivity, 85
 - flammability, 84
 - heat capacity, thermal conductivity, and heat of vaporization, 84
 - heat of combustion, 84
 - history, 61-66
 - 2004+ vehicle and fuel regulation, 66
 - alkyl lead, 62
 - Clean Air Act of 1963, 63
 - Clean Air Act of 1970 and 1977 amendment, 64
 - Clean Air Act Amendments of 1990, 65-66
 - leaded gasoline, 61-62
 - nonleaded gasoline, 63-64
 - octane ratings, 62-63
 - vapor controls, 64-65
 - nonleaded, 63-64
 - octane performance properties, 73-77
 - anti-knock ratings, 73-74
 - combustion and knock, 73
 - motor octane number, 73-74
 - octane distribution through fuel boiling range, 75
 - octane number requirement, 75-78
 - on-line analyzer octane rating, 74-75
 - research octane rating, 74
 - oxidation
 - stability, 813, 815-817
 - standards, 823
 - testing, 811, 813, 815-818
 - oxygenates in, 68
 - performance additives, 69-70
 - reformulated, 65-66
 - specifications, *see* ASTM D 4814
 - standards, 85-86
 - static electricity, 85
 - trace constituents and contaminants, 69
 - vapor pressure, 699, 701
 - viscosity and lubricity, 84-85
- Gasoline-oxygenate blends, vapor pressure, 699, 701
- Gas solubility
 - compressor lubricants, 395-396, 406-408
 - petroleum oils, 406-407
- Gas turbine engines, 115, 298-299
 - development, 302-303
 - lubrication system, 301-302
- Gas turbine fuels, 139-142
 - requirements, 140-141
 - standards, 142-143
 - trace metal limits, 141-142
 - see also* Ryder gear
- Gas turbine fuel system, 165-166
 - construction materials, 166-167
- Gearbox oils, *see* Ryder gear
- Gear contacts, performance maps and, 972-973
- Gear corrosion test, gear lubricants, 460
- Gear lubricants, 431-462, 481-483
 - acid number, 456
 - additives, 439-443, 447
 - air release, 460
 - antiwear agents, 440, 444
 - API gravity, 456
 - API service designation, 448-453
 - base number, 458
 - channel point FTM, 459
 - chlorine level, 457
 - cold crank simulator, 458
 - compatibility, 460
 - compounded, 439
 - Copper Strip Tarnish Test, 454, 456
 - corrosion inhibitors, 441
 - cyclic durability test, 458

demulsibility, 457-458
 demulsifiers, 441
 detergents, 440, 444
 dispersants, 440-441, 445
 dynamic seals test, 460
 early, 431-432
 elemental content, 458
 emulsifiers, 441-442
 extreme pressure, 439
 oxidation, 458
 extreme pressure agents, 440, 444
 fire point, 454
 flash point, 454
 foam characteristics, 456-457
 foam inhibitors, 441
 four ball EP, 457
 four ball wear, 457
 friction modifiers, 441
 function, 431
 future trends, 460-461
 FZG Pits C i80 TS, 459
 FZG scuffing test, 458
 gear corrosion test, 460
 gear scoring test, 459-460
 GFC oxidation, 459
 greases, 439
 high temperature foam inhibition, 459
 insolubles in used oils, 457
 kinematic viscosity, 456
 low speed high torque hypoid test, 459
 low temperature Brookfield viscosity, 458
 MIL-PRF-2105E, 451-452
 nitrogen level, 458
 OEM specifications, 451, 453
 open gear compounds, 439
 oxidation inhibitors, 441, 445
 phosphorus level, 457
 polymeric thickeners, 441-442
 pour point, 454
 pour point depressants, 441
 precipitation number, 453
 rust and oxidation inhibited, 439
 rust inhibition, 456
 Ryder gear test conditions, 988-990
 SAE 3306 viscosity classification, 449-451
 scuffing
 front, propagation, 992-993
 initiation, 990-992
 seal compatibility, 459
 shear stability, 459
 standards, 461-462, 493
 standard tests, 482-483
 storage solubility, 460
 sulfur level, 457
 synchronizer SSP 180 test, 459
 systematic tribology, 988-996
 thermal and oxidation test, 458

Timken EP Tester, 457
 tribological features, microscopic examination, 991-992
 tribological processes, 993-996
 types, 437, 439
 viscosity index, 457
 water content, 457
 Gear oils
 corrosion tests, 829
 oxidation, standards, 822
 oxidation testing, 802-804
 performance testing, 239-240
 Gears
 failure modes, 434-436
 lubrication, 434, 436-438
 types, 432-434
 Gear scoring test, gear lubricants, 459-460
 Gear testing, aviation gas turbine oil, 988
 GFC oxidation, gear lubricants, 459
 Glass capillary vacuum viscometers, 870-871
 Gloss retention, petroleum waxes, 549
 GM quenchometer cooling times, 604-606
 Graphitic electrodes, for electric-arc furnaces, 782
 Graphite furnace atomic absorption spectrometry, elemental analysis, 709-711
 Greases, *see* Lubricating greases
 Grossmann hardenability, 592-593
 Gum content, gasolines and fuels, 811, 813, 815

H

Halocarbons, in LPG, 50
 Hardenability, steel, 589-591
 measurement, 591-593
 Hardness, petroleum waxes, 547-548
 Hazard, environmental characteristics, 904
 Health effects, LPG exposure, 54-55
 Health issues, aerospace fuels handling, 747
 Heat capacity, gasoline, 84
 Heat content, diesel fuel, 132-134
 Heating value
 fuel oils, 759-760
 marine petroleum fuels, 149-150
 Heat of adsorption, wear reduction and, 954
 Heat of combustion, 72
 diesel fuel, 132-134
 gasoline, 84
 Heat of vaporization, gasoline, 84
 Heat resistance, lubricating greases, 563-565
 Heat transfer
 efficiency, compressor lubricants, 408-409
 hydraulic fluids, 353-354
 Heat transfer coefficient, 573-575
 Heat transfer fluids, *see* Mineral oil heat transfer fluids
 Heat transfer fluid system, design and construction, 583-584
 HEES fluids, 377
 Henry's Law Constant, 888
 HEPG fluids, 378
 HEPR type fluids, 378

- Hertzian contact, 914, 946-949, 965-966
- Heteroatom, removal, 17-20
- HETG fluids, 377
- HFA fluids, 375-376
- HFB fluids, 376
- HFC fluids, 376
- HFD fluids, 376-377
- High frequency reciprocating rig, 129, 131
- High Pressure Differential Scanning Calorimetry, 258
- High-shear
 - high-temperature, 843-845
 - low-temperature, lubricants, 846-848
- High temperature copper-lead bearing wear, 470
- High temperature foam inhibition, gear lubricants, 459
- High temperature stability, distillate fuels, 817-818
- Hindered phenols, oxidation inhibition, 794
- ¹H NMR spectroscopy, hydrocarbon analysis, 651
- Homogenizer, diesel fuel system, 165
- Hot surface tests, turbine lubricating oils and hydraulic fluids, 335
- Hot tack, petroleum waxes, 552
- HSR, 3
- HVAC cycle, refrigeration lubricants, 424-426
- Hydraulic fluids, 353-379
 - aeration and foam, 366-367
 - antifoam additives, 367
 - antioxidants, 356-358
 - antiwear and extreme pressure additives, 363
 - antiwear performance testing, 361-364
 - automatic transmission fluids, 374
 - boundary conditions, 360-361
 - coolant separability, 370-371
 - corrosion inhibitors, 369-370
 - corrosion protection, 368-370
 - demulsibility, 366
 - detergents, 358
 - dispersants, 358
 - engine oils, 374
 - environmentally acceptable, 377-378
 - filterability, 367-368
 - fire-resistant, 301-302, 375-377
 - frictional properties, 212-213
 - heat transfer, 353-354
 - hydrolytic stability testing, 365-366
 - low temperature pumpability, 372-373
 - lubrication, 353
 - machine builder specifications, 364
 - metal passivators, 369-370
 - mineral oils, 374-375
 - oxidation
 - stability, 355-359, 801
 - standards, 822
 - tests, 356-357
 - performance testing, 240-241
 - petroleum base stocks, 355
 - pour point depressants, 373
 - power transfer, 353-354
 - rust inhibitors, 369-370
 - seal compatibility, 370
 - shear stability, 371-372
 - standards, 378-379
 - thermal stability, 355-359
 - tractor fluids, 374
 - trends, 353-355
 - types, 268-269
 - viscosity, 359-360
 - viscosity index improvers, 371-372
 - water content, 363, 365
 - wear protection, 359-364
 - see also* Pressure media
- Hydraulic oils
 - oxidation characteristics, 797-798
 - thermal stability, 799-800, 830
- Hydrocarbon analysis, 649-672
 - ¹³C NMR spectrometry, 650-651
 - fluorescent indicator adsorption, 659
 - gas chromatography, 652-657
 - gas chromatography-mass spectrometry, 664
 - infrared spectrometry, 668-670
 - liquid chromatography, 657-660
 - mass spectrometry, 664-665
 - NMR spectrometry, 649-652
 - standards, 671-672
 - super critical fluid chromatography, 659-660
 - ultraviolet spectrometry, 661-662
- Hydrocarbon base oil, 169-183
 - biodegradability, 182
 - biological properties, 181-182
 - composition/performance correlations, 178-179
 - effects in industrial lubricants, 179-180
 - hydrocarbon type analysis, 172-173
 - impact of sulfur compounds on chemistry, 176-177
 - market, 169-170
 - molecular structures, 174-175
 - naphthenic vs. paraffinic, 172
 - nitrogen compound reactivity, 177-178
 - NMR spectrometry, 174-175
 - olefins, 178
 - oxidation, 175-176
 - refining and processing technology, 170-172
 - refining capacity, United States, 169-170
 - rheology and composition, 178
 - rubber compatibility, 181
 - solvency effects, 181
 - spectrometric identification components, 173-174
 - standards, 182-183
 - structures with high susceptibility to oxidation, 788
 - viscosity-pressure coefficient composition effect, 180-181
- Hydrocarbon oils, turbines, 305-306
- Hydrocarbon-oxygenate mixtures, vapor pressure, 702-703
- Hydrocarbons
 - crude oil composition, 6
 - in gasoline, 66-67
 - physical adsorption, 921

- terminology, 5-6
 - see also* Synthetic hydrocarbons
 - Hydrocracked basestocks, turbines, 307-308
 - Hydrocracking
 - fixed bed, 24
 - fluidized bed, 24-25
 - hydrocarbon base oil, 171
 - Hydrodynamic film region, 963
 - Hydrodynamic lubrication, 214, 413, 498, 949
 - Hydrofinishing hydrocarbon base oil, 172
 - Hydrogen
 - in petroleum fractions, 195
 - classification in organic molecules, 788
 - Hydrogen production, 25-26
 - Hydrogen refining, hydrocarbon base oil, 171
 - Hydrolysis
 - environmental characteristics, 889-890
 - environmentally friendly oils, 274
 - pressure media, 279-281
 - Hydrolytic stability
 - compressor lubricants, 398
 - diesters, 251-252
 - polyolesters, 251-252
 - pressure media
 - laboratory aging, 285-287
 - test stand aging, 287-289
 - turbine lubricating oils and hydraulic fluids, 339-340
 - Hydrolytic stability testing, hydraulic fluids, 365-366
 - Hydroperoxide
 - decomposers, 791-792
 - decomposition, 790, 793
 - oxidation rate and, 790
 - Hydroprocessing
 - options, 19
 - terminology, 18
 - Hydrostatic tank gauges, 645
 - Hydrotreated basestocks, turbines, 307-308
 - Hyfinishing, hydrocarbon base oil, 172
- I**
- I*-Chart, 1055-1056
 - Icing, in LPG systems, 45
 - Ideal Gas Law, 383
 - Ignition quality, marine petroleum fuels, 149-150
 - Indiana Stirring Oxidation Test, compressor lubricants, 401
 - Induction Period Method, 813, 815-817
 - Inductively coupled plasma-atomic emission spectrometry, elemental analysis, 711-712
 - Inductively coupled plasma-mass spectrometry, elemental analysis, 712
 - Industrial gear lubricants, 453-456
 - performance testing, 240
 - Industrial hydraulic fluids, performance testing, 241
 - Industrial lubricants, base oil effects, 179-180
 - Infrared spectroscopy, 665-671
 - achieving reproducible baselines, 668
 - analysis of multicomponent solutions, 667-668
 - band area methods, 668
 - Beer-Lambert law, 667
 - compressor lubricants, 400-401
 - difference method, 668
 - dispersive-type infrared spectrometers, 667
 - Fourier transform, 667
 - gas analysis, 668
 - hydrocarbon analysis, 668-670
 - inorganic characterization, 670-671
 - quench oils, 610
 - standards, 671
 - wavelength, wavenumber and frequency, 666-667
 - Inhibitor content, determination, 194
 - Inorganic/organic solids, metalworking and machining fluids, 519
 - Insolubles, in used oils, 457
 - Instability, fuel oils, 762
 - Insulation fires, mineral oil heat transfer fluids, 583
 - International Harvester oxidation corrosion, 811
 - Invertebrates
 - acute toxicity tests, 902
 - chronic and subchronic toxicity tests, 903
 - Ion chromatography, elemental analysis, 712
 - Iron based organo-metallics, in gasoline, 69
 - Iron carboxylate, oxidation rate and, 790
 - Iron chip corrosion, metalworking fluids, 831
 - Iron corrosion, compressor lubricants, 398
 - Isomerization, 14, 16
 - Iso-propanol, in propane, 47
 - Isothermal operation, 384
 - Isothermal transformation diagrams, 589
- J**
- Jet fuel, 8, 92-93
 - additives, 104-105
 - combustion, 97-98
 - history, 89, 91
 - low temperature, 93-94
 - manufacturing, 103-104
 - product color, 109
 - quality control, 107
 - Smoke Point, 98
 - visual appearance, 109
 - volatility and flammability, 98-101
 - Jet Fuel Thermal Oxidation Tester, 96, 815-816
 - Jominy bar end-quench test, 591-592
 - Joule-Thomson cooling, 46
- K**
- Karl Fisher Titration Test, 365
 - Kerosine, 3
 - Kinematic viscosity, 837-841
 - compressor lubricants, 396-397
 - gear lubricants, 456
 - history, 841-843
 - quench oils, 608-609
 - standards, 875

temperature relationship, 854-856
Kinetic coefficient of friction, 909

L

- Laboratory aging
 hydrolysis stability, 285-287
 oxidation stability, 281-283
Lambda values, 912-913
Lattice transition, alkanes, 534
Lead corrosion, 221
Leakage, lubricating greases, from wheel bearings, 565
Leidenfrost temperature, 593
"Liedenfrost effect", 53
Light hydrocarbons
 high temperature vapor pressure, 32
 low-temperature vapor pressures, 33
Linear reciprocation, 1031-1033
Liquid chromatography
 fluorescent indicator adsorption, 659
 hydrocarbon analysis, 657-660
 principles, 657-658
 standards, 660
 super critical fluid chromatography, 659-660
Liquid Heptane Washing Test, compressor lubricants, 401-402
Liquified petroleum gas, 31-56
 auto propane, 51-52
 exposure, 54-55
 flammability, 52
 gas hydrates, 44-46
 handling, 52-54
 history, 31-32, 35-38
 industry, 32, 35
 use, 35-37
 odorization, 55
 properties and thermodynamics, history, 37-38
 sample cylinder approvals, 54
 specifications, 38-50
 composition, 40
 contaminants, 49-50
 density, 40
 dryness of propane, 42-49
 history of ASTM standards, 38-39
 naturally occurring radioactive materials, 50
 octane, 40
 olefins, 40-41
 residual matter, 49
 sampling, 39-40
 sulfur content, 49
 vapor pressure, 40-42
 volatility residue, 42
 uses, 56
 vapor, 53
 vapor pressure, 703-704
 volume correction factors, 50-51
 water in, 47-49
LISCIC/NANMAC quench probe, 623-625
Lithium soap greases, 559
Low speed high torque hypoid test, gear lubricants, 459
Low temperature Brookfield viscosity, gear lubricants, 458
Low-temperature flow test, diesel fuel, 123
Low-temperature high-shear tests, lubricants, 882
Low temperature properties
 diesters and polyolesters, 251
 environmentally friendly oils, 289-291
Low temperature pumpability
 hydraulic fluids, 372-373
 lubricants, 882
Low temperature storage stability, turbine lubricating oils
 and hydraulic fluids, 329
Low-temperature torque, lubricating greases, 563
LPG injector systems, 52
LSR, 3
Lube oil base stock production, 25
Lubricant base oil, market, 169-170
Lubricants
 basestocks, 199-200
 category chronology, 853
 composition, 199
 corrosion tests, 827-831
 function, 413
 high-temperature degradation model, 791
 low-temperature high-shear tests, 846-848, 882
 low temperature pumpability, 848-851, 882
 low temperature requirements, 845-848
 oxidation
 standards, 823
 testing, 818-821
 quality ranking, 915-916
Lubricating greases, 439, 478-481, 557-572
 accelerated corrosion tests, 568
 aluminum soap, 558
 apparent viscosity, 562-563
 in ball bearings at elevated temperatures, 565-566
 black penetration, 561
 bomb oxidation test, 565
 calcium soap, 558-559
 chemical analysis, 569
 chemical properties, 478-479
 classification, 560
 compatibility of blends, 569
 complex soap, 559
 composition, 557-558
 cone penetration, 561
 consistency, 560-561
 consistency stability, 561-562
 contamination, 568-569
 copper corrosion, 567-568
 corrosion tests, 831-832
 dropping point, 563-564
 elastomer compatibility, 569
 evaporation loss, 564
 extreme pressure four-ball test, 566-567
 extreme pressure Timken method, 566

- flow properties, at high temperatures, 562
 - fretting wear, 567
 - heat resistance, 563-565
 - leakage from steel bearings, 565
 - lithium soap, 559
 - low-temperature torque, 563
 - NLGI consistency numbers, 561
 - oil separation, 564-565
 - organo-clay, 560
 - oscillating motion, 567
 - oscillating wear test, 567
 - oxidation
 - induction time, 806-807
 - stability, 565-566
 - standards, 823
 - testing, 804-807
 - PDSC oxidation test, 565
 - performance, 480-481
 - performance testing, 242
 - polyurea, 559-560
 - roll stability, 562
 - rust prevention, 568
 - selection, 558
 - in small bearings, 566
 - sodium soap, 559
 - specifications, 560
 - standards, 570-572
 - discontinued, 570
 - under development, 570
 - static bleed test, 569
 - viscosity, 479-480
 - water spray-off, 568
 - water washout, 568
 - wear preventive characteristics, 567
 - wheel bearing grease life, 566
 - Lubricating oil
 - additives, 952
 - extreme pressure, oxidation testing, 802
 - oxidation induction time, 818
 - Lubrication, 497-500, 909-957
 - boundary, 949
 - elastohydrodynamic, 947-949
 - friction, 909-911
 - friction modifiers, 949, 951-952
 - Hertzian contact, 946-949
 - hydraulic fluids, 353
 - hydrodynamic, 949
 - parameters controlling, 965-966
 - performance, turbine lubricating oils and hydraulic fluids, 341-342
 - Petroff's law, 949
 - regions, thermal considerations, 970
 - standards, 957
 - synthetic lubricants, 261-262
 - types, 214
 - Lubricity
 - aerospace fuels, 744-745
 - aviation fuels, 102-103
 - diesel fuel, 129-131
 - gasoline, 85
 - Lubricity additives, 69
 - Luminometer, 98
- M**
- MacCoull equation, 854
 - MacCoull-Walther equation, 919
 - Macroemulsions, metalworking and machining fluids, 503
 - Magnetic quencher method, quench oils, 614-615
 - Magnetic residues, LPG, 49-50
 - Manifold, air temperature and pressure, octane number requirement and, 76
 - Mannich products, synthesis, 206-207
 - Marine petroleum fuels, 145-167
 - ash, 150
 - ash modifiers, 154
 - biocides, 154
 - carbon residue, 151-152
 - cat fines, 150
 - compatibility, 152
 - demulsifiers, 154
 - density, 149
 - diesel plant fuel system, 161-162
 - environmental considerations, 156
 - flash point, 150
 - fuel additives, 153-154
 - heating value, 149-150
 - ignition quality, 149-150
 - impact on exhaust emissions, 154
 - on board testing, 157
 - oxidation, 152
 - pour point, 150
 - sampling, 156
 - sediment, 152-153
 - shore side analysis, 156
 - sodium in, 152-153
 - specifications, 154-156
 - stabilizers and dispersants, 153
 - standards, 167
 - steam plant fuel service system, 157, 161
 - storage systems, 157-160
 - sulfur, 151
 - toxicity, 154
 - transfer systems, 157
 - vanadium and nickel in, 152
 - viscosity, 148-149
 - water in, 151
 - Marine transport, aviation fuels, 105-106
 - Mass spectrometry, 662-665
 - hydrocarbon analysis, 664-665
 - instrumentation, 663-664
 - standards, 665
 - theory, 662-663
 - Master chart, aviation gas turbine oils, 1012, 1014
 - McMillan/Murphy pumpability apparatus, 848

- Measurement process
 - bias, 1044-1045
 - manufacturing process control, 1043
 - precision, 1044-1045
 - product property conformance to specification, 1043-1044
 - self-monitoring, 1044
 - see also* Quality assurance
- Melting point, petroleum waxes, 542-545
- Mercaptan odorants, 55
- Metal content, mineral oil heat transfer fluids, 580-581
- Metal deactivators, 795-796
- Metal forming fluids, 509, 520
- Metal passivators, 319-320, 369-370
- Metal preservatives, 830
- Metal protecting fluids, 510
- Metal ratio, 208
- Metal removal fluids, 505-509, 519
- Metals
 - crude oil, 6
 - oxidation potentials, 220
 - significance in petroleum products, 707-708
- Metal treating fluids, 510
- Metalworking and machining fluids, 234, 497-524
 - additives, 511-519
 - alkalinity agents, 516
 - antimicrobial agents, 517-518
 - anti-misting agents, 516
 - corrosion inhibitors, 516-517
 - coupling agents, 513
 - dispersants, 516
 - dyes, 519
 - emulsion promoters, 512-513
 - film-forming agents, 513-515
 - foam inhibitors, 518-519
 - inorganic/organic solids, 519
 - odor control agents, 519
 - base fluid, 510-511
 - classification based on end-use, 505-510
 - formulations, 519-521
 - metal forming fluids, 509
 - metal protecting fluids, 510
 - metal treating fluids, 510
 - oil-based, 501
 - performance testing, 241
 - semisynthetic fluids, 504-505
 - slideway lubricants, 510
 - solid dispersions, 505
 - soluble oils, 503
 - synthetic fluids, 503-504
 - tests, 521-523
 - used, recycling, 521-522, 524
 - water-based, 501-503
 - classification, 503-505
- Metering, aviation fuels, 99-100
- Methane, structure, 732
- Methanol
 - in propane, phase behavior, 46-47
 - in propylene, 193
- Methylcyclopentadienyl manganese tricarbonyl, in gasoline, 68-69
- Micellar solutions, metalworking and machining fluids, 501-502
- Micro-elastohydrodynamic lubrication, 948-949
- Microelemental analysis methods, 712
- Microemulsions, metalworking and machining fluids, 504-505
- Microfilters, 109
- "Micro Method" for carbon residue, compressor lubricants, 399
- Micronic filters prefilters, 109
- Microorganisms, in aviation fuels, 110
- Micropitting, 434-435, 977, 979
- Micro-scuffing
 - engine oil performance, 1009-1010
 - failure criteria, 1001
- Military fuel specifications, marine petroleum fuels, 155-156
- MIL-PRF-2105E, gear lubricants, 451-452
- MIL-PRF-7808 oils, 1012-1013
- MIL-PRF-23699 oils, 1011
- Mineral gas turbine oils, 317-318
- Mineral oil heat transfer fluids, 573-585
 - acid number, 582
 - autoignition, 581
 - carbon residue, 580
 - classification, 575
 - composition, 575-578
 - distillation, 582
 - elastomeric seal compatibility, 581
 - fluid maintenance, 581
 - metal content, 580-581
 - oxidative stability, 580
 - physical properties, 578-581
 - pumpability, 579
 - safety, 583
 - sampling, 581-583
 - specific gravity, 580
 - specific heat, 581
 - standards, 584-585
 - thermal conductivity, 581
 - thermal stability, 579-580
 - viscosity, 579, 582-583
 - water content, 583
- Mineral oils
 - aero-engine lubricants, 301
 - compressor lubricants, 392
 - hydraulic fluids, 374-375
 - inhibited
 - oxidation characteristics, 797-798
 - oxidation stability, 798-799
 - rust-preventing characteristics, 829-830
 - sludging and corrosion tendencies, 798, 830-831
 - metalworking and machining fluids, 501

- organic structures, 576
 - refrigeration lubricants, 414-415
 - Mini-rotary viscometer, 849-850
 - Mixed-film lubrication, 214
 - Modified Ostwald viscometers, 838-841
 - Monitors, aviation fuels, 108
 - Motor gasoline, *see* Gasoline
 - Motor octane number, 73-74
 - MR-Chart, 1056
 - MTBE, 16-17, 66
 - Multi-specimen test machine, 1030-1031
- N**
- Naphthenic base oils, 172
 - Naphthenic hydrocarbon fractions, 527
 - Naphthene, determination, 195
 - Natural gas liquids volume correlation factors, 50-51
 - Natural Gasoline Association of America, 37
 - Naturally occurring radioactive materials, in LPG, 50
 - Near-surface region, 964
 - Neutron activation analysis, elemental analysis, 712-713
 - Nickel content, 152, 775
 - Nitrogen, crude oil, 6
 - Nitrogen compound reactivity, hydrocarbon base oil, 177-178
 - Nitrogen level, gear lubricants, 458
 - NLGI consistency numbers, 561
 - Nonleaded gasoline, 63-64
 - Non-lubricating process fluids, 587-632
 - aqueous polymer quenchants, 605-606
 - standards, 630-632
 - temperature gradient quenchant analysis, 623-629
 - see also* Quench oils
 - Non-petroleum materials using ASTM flow properties, 867-872
 - Normality checks, 1052-1055
 - NO_x, Clean Air Act, 64
 - Nuclear magnetic resonance spectroscopy
 - hydrocarbon analysis, 649-652
 - hydrocarbon base oil, 174-175
 - principles, 649-650
 - standards, 651-652
- O**
- Occupational exposure limits, LPG, 54
 - Octane
 - distribution throughout fuel boiling range, 75
 - liquified petroleum gas, 40
 - Octane number requirement, 75-78
 - air-fuel ratio, 76
 - compression ratio, 76
 - effect of engine deposits, 77
 - engine design parameters, 76
 - engine spark timing, 76-77
 - manifold air temperature and pressure, 76
 - Octane rating, history, 62-63
 - Octane rating analyzers, on-line, 74-75
 - Octanol/water partition coefficient, 887
 - Odor, petroleum waxes, 549, 551
 - Odor control agents, metalworking and machining fluids, 519
 - Odorization, LPG, 55
 - OEM specifications, gear lubricants, 451, 453
 - Oil blending calculations, 856
 - Oil content, petroleum waxes, 546
 - Oil film wash-oil resistance, compressor lubricants, 401-402
 - Oil-off testing, 982-983
 - Oil separation, lubricating greases, 564-565
 - Oil-soluble dye, in gasoline, 69
 - Oil stability index, 821
 - Oil stain, LPG, 49
 - Olefin
 - saturation, 17-20
 - sulfurization, 216
 - Olefin-based polymers, 224-226
 - Olefin content, 28
 - hydrocarbon base oil, 178
 - liquified petroleum gas, 40-41
 - Optical texture, petroleum coke, 775-776
 - Organo-clay greases, 560
 - Organo-metallics, iron based, in gasoline, 69
 - Orifice viscometers, 864-865
 - Oscillating motion, lubricating greases, 567
 - Oscillating wear test, lubricating greases, 567
 - Oxidation, 787-823
 - automotive lubricants, 476-477
 - aviation fuels, standards, 823
 - biodegradable lubricants, standards, 823
 - engine oils, standards, 823
 - extreme pressure oils, 458
 - gasolines, standards, 823
 - gear oils, standards, 822
 - grease, standards, 823
 - hydraulic fluids, standards, 822
 - hydrocarbon base oil, 175-176
 - hydroperoxide decomposers, 791-792
 - lubricants, 787-796
 - standards, 823
 - marine petroleum fuels, 152
 - mechanism, 789
 - pressure media, 277, 279
 - radical scavengers, 791-792
 - role of metal ions, 793-794
 - turbine oils, standards, 822
 - Oxidational wear, 933
 - Oxidation heat release, 752-753
 - aerospace fuels, 735
 - Oxidation induction time, lubricating oils, 818
 - Oxidation inhibitors, *see* Antioxidants
 - Oxidation potentials, metals, 220
 - Oxidation stability
 - ASTM D 4814, 82-83
 - automotive gear oils, 803-804
 - automotive transmission fluids, 804

aviation fuels, 813
 diesel fuel, 126-127
 distillate fuel oil, 816-817
 environmentally friendly oils, 274-275
 gasoline, 813, 815-817
 lubricating greases, 565-566
 mineral oil heat transfer fluids, 580
 pressure media, 281-284
 laboratory aging, 281-283
 test stand aging, 282-284
 synthetic lubricants, 258, 260-261
 turbine lubricating oils and hydraulic fluids, 338-339
 Oxidation Stability test, aviation fuels, 102
 Oxidation testing, 315, 317, 796-822
 antiwear, 797-798
 biodegradable lubricants, 820-822
 engine oils, 807-811
 fuels, 811, 813, 815-818
 gasolines, 811, 813, 815-818
 gear oils, 802-804
 grease, 804-807
 hydraulic fluids, 356-357
 lubricants, 818-821
 purpose of testing, 796
 using universal glassware, 802-803
 Oxygen, crude oil, 6-7
 Oxygenated polymer, formation, 790
 Oxygenates, 7, 29
 addition to gasoline, 65-66
 in gasoline, 68

P

Paddle type rotational viscometer, 835-836
 Paint Compatibility Test, compressor lubricants, 409-410
 Paints, flow-related instruments, 867
 Panel Coker Test, 818-819
 Paraffin, determination, 195
 Paraffinic base oils, 172
 Paraffinic hydrocarbon fractions, 527
 Partial least squares modeling, 179
 Partial oxidation, 26
 Particulate emissions, diesel engines, 720
 Particulates, in LPG, 49-50
 PDSC oxidation test, lubricating greases, 565
 Pearlite, 587
 Peng-Robinson Equation of State, 81
 Penn State micro-oxidation test apparatus, 807
 Pensky-Martens Closed Cup Tester, 692-694
 Perfluoroalkyl ethers, 259
 Performance additives, gasoline, 69-70
 Performance maps, 945, 968-969
 bearing and gear contacts and, 972-973
 generalized, 987-988
 lubrication attributes, 967
 wear and traction within, 968, 970
 Performance package, 235
 Performance testing, *see* Additives
 Permanent shear stability index, 853
 Peroxide number, petroleum waxes, 549
 Peroxides, in butadiene, 193-194
 Petroff's law, 949
 Petroleum coke, 768-778
 ash, 775
 classification, 773
 crystalline structure, 775-776
 density, 775
 feedstocks, 772
 microtexture formation, 770-772
 optical texture, 775-776
 production processes, 768-770
 properties, 773-774
 reactivity, 778
 standards, 783-784
 sulfur content, 775
 thermal expansion, 777
 trace metals contents, 775
 volatile matter, 774-775
 Petroleum fractions, hydrogen in, 195
 Petroleum gas, sulfur content, 194-195
 Petroleum industry, history, 145
 Petroleum oil, 3-29
 classification, 576
 alkylation, 15-17
 capacity as percent of crude, 5
 catalytic reforming, 12-15
 cogeneration, 28
 crude oil, 6-7
 preparation and separation, 9-10
 fluid catalytic cracking, 9-12
 future, 28-29
 gas solubility in, 406-407
 heteroatom removal and aromatic/olefin saturation, 17-20
 hydrogen production, 25-26
 isomerization, 14, 16
 lube oil base stock production, 25
 MTBE, 16-17
 pollution control, 27-28
 product blending, 28
 products, 7-9
 refinery flow plan, 3-5
 resid conversion and upgrading, 20-25
 sulfur recovery, 26-27
 Petroleum pitch, 763-768
 ash, 768
 carbon fibers, 781
 coking value, 767-768
 density, 768
 production processes and applications, 763
 properties, 763-764
 softening point, 764
 solvent fractionation, 765-767
 standards, 783-784
 sulfur content, 768
 viscosity, 764-765

- Petroleum waxes, 525-555
 additive effect, 542
 blocking point, 552-553
 carbonizable substances, 549
 cloud point, 545-546
 coefficient of kinetic friction, 552, 554
 color, 549-551
 composition, gas chromatography, 549
 compositional and molecular characteristics, 531-533
 congealing point, 545
 crystal structure, 533-535
 dewaxing process variables, 530-531
 differential scanning calorimetry, 539-542
 equations of state, 535-539
 gloss retention, 549
 hardness, 547-548
 hot tack, 552
 melting point, 542-545
 odor, 549, 551
 oil content, 546
 peroxide number, 549
 physical properties, 533
 pour point, 545
 solvent dewaxing process, 529-530
 solvent solubility, 546
 specular gloss, 549, 552
 standards, 554-555
 surface wax, 549, 551
 total wax content, 552
 transition temperatures, differential scanning calorimetry, 548
 types of, 531
 viscosity, 546-547
 wax finishing process, 531
 weight of wax applied during coating, 552
 pH determination, polymer quenchants, 617-618
 Philippoff rotary viscometer, 849
 Phosphate esters, compressor lubricants, 395
 Phosphonic acid dispersants, synthesis, 206-207
 Phosphorus content
 ASTM D 4814, 82
 automotive lubricants, 471
 gear lubricants, 457
 Photolysis, environmental characteristics, 890
 Photooxidation, environmental characteristics, 890
 Pin and Vee Block tester, 1025-1026
 Pin-on-Disk test, 1026
 Pitting, 434
 Pipelines, aviation fuels, 105
 Plants, toxicity tests, 903
 Plastics, viscosity, 869-870
 Plate-to-plate geometry, 835
 Ploughing, friction due to, 911-912
 Polar additives, adsorption on metal surface, 211-212
 Polishing wear, 923, 929
 Pollution control, petroleum oil refining, 27-28
 Polyalkylene glycols, 252-256
 application and performance characteristics, 255-256
 chemical characteristics, 254-255
 chemistry, 253
 compressor lubricants, 392-393
 physical properties, 254
 refrigeration lubricants, 417-418
 synthesis, 253-254
 Polyalphaolefins, 257-258
 compressor lubricants, 393-394
 refrigeration lubricants, 415-416
 for turbines, 308-309
 Poly(ethylene) waxes, 525
 Polymer, viscosity, 869
 loss due to degradation, 228-230
 Polymer-containing oils, shear stability, 851-853
 Polymeric additives, 223-233
 Polymeric thickeners, gear lubricants, 441-442
 Polymer molecular weight analysis, polymer quenchants, 620
 Polymer quenchants
 appearance, 616
 biological stability, 620-623
 cloud point, 619
 conductance, 618-619
 cooling curve analysis, 621-623
 corrosion inhibitor, 619-620
 fluid biodeterioration, 620-621
 foam testing, 620
 pH determination, 617-618
 polymer molecular weight analysis, 620
 refractive index, 616-617
 viscosity, 617-618
 water content, 617
 Polyolesters, 249-252
 application and performance characteristics, 252
 biodegradability, 252
 chemical characteristics, 251
 chemistry and manufacturing, 249-251
 manufacturing technology, 250-251
 physical properties, 251
 refrigeration lubricants, 416-417
 Polyphenyl ethers, 259-260
 Polyurea greases, 559-560
 Polyvinylethers, refrigeration lubricants, 418
 Potential Residue Method, 815
 Pour point, 879-880
 compressor lubricants, 397
 diesel fuel, 122-123
 effect of double bonds, 273
 esters, 273
 fuel oils, 761
 gear lubricants, 454
 marine petroleum fuels, 150
 petroleum waxes, 545
 standards, 874
 turbine lubricating oils and hydraulic fluids, 329
 Pour point depressants, 205, 230-232

gear lubricants, 441
 hydraulic fluids, 373
 Power transfer, hydraulic fluids, 353-354
 Power transmission fluids, performance testing, 239
 Precipitation number
 compressor lubricants, 399-400
 gear lubricants, 453
 quench oils, 613-614
 Precision
 measurement process, 1044-1045
 monitoring, 1045-1047
 Pressure differential scanning calorimetry, 806, 818
 Pressure drop, 574-576
 Pressure media, 267
 hydrolysis, 279-281
 hydrolysis stability, aging, 285-289
 oxidation, 277, 279
 oxidation stability, aging, 281-284
 type, 268-269
 see also Hydraulic fluids
 Pressure-viscosity coefficient, 916- 920, 985-987
 Propane
 auto, 51-52
 depressurized, 46
 dryness, 42-49
 auto-refrigeration, 46
 dissolved water, phase of behavior, 43-44
 gas hydrates, 44-46
 methanol, phase behavior, 46-47
 water measurement, 47-49
 water sources, 47
 liquid, 53
 phase behavior of dissolved water in, 43-44
 Propane deasphalting, hydrocarbon base oil, 171
 Propane hydrates, 45
 Propane P-H diagram, 34
 Propylene
 characterization, 192-193
 production, 190
 Pumpability
 low temperature, lubricants, 848- 851
 mineral oil heat transfer fluids, 579
 PV curves, 384

Q

Quality assurance, 1043-1060
 approximate *F*-test, 1059-1060
 ARV assignment, 1048
 batch change of material, 1047
 check standard composition, 1048
 chi-square test, 1059
 control chart, 1055-1056
 data treatment, 1046-1047
 estimate process precision and bias, 1048
 EWMA overlay, 1056
 implementation aspects, 1049
 interlaboratory exchange testing, 1049

 material selection, preparation and storage, 1046
 material testing, 1046
 monitoring bias, 1047-1048
 monitoring stability and precision, 1045-1047
 MR-Chart, 1056
 normality checks, 1052-1055
 run chart, 1051-1052
 standards, 1050
 statistical tools, 1050-1051
 system validation, 1049
 t-test, 1058-1059
 Quality control
 aviation fuels, *see* Aviation fuels
 airport, 110-111
 elemental analysis, 716
 Quench oils, 602-605
 acid number, 609-610
 ash content, 614
 carbon residue, 611-613
 contamination, 610-614
 fire and flash points, 609
 infra-red spectroscopy, 610
 kinematic viscosity, 608-609
 magnetic quencher method, 614-615
 precipitation number, 613-614
 properties, 604
 saponification number, 610
 specific gravity, 609
 water content, 610-611

R

Rabinowitz abrasive wear model, 930
 Radical scavengers, 791-792
 Rail transport, aviation fuels, 106
 Ramsbottom carbon residue, compressor lubricants, 399
 RBOT test, 315-316
 compressor lubricants, 401
 Reaction temperature, maximum, 754-756
 Reactivity, petroleum coke, 778
 Reavell VHP 15 Compressor Rig Test, 403
 Reciprocating compressors, 386-388
 Recycling, used lubricants, 521-522, 524
 Redlich-Kwong equation, 536
 Reference gauge point, 636
 Reformulated gasoline, 65-66
 Refractive index, polymer quenchants, 616-617
 Refrigeration lubricants, 413-429
 acid catchers, 419
 additives, 418-420
 alkylbenzene, 415
 antifoaming agents, 419-420
 antioxidants, 419
 antiwear additives, 419
 chemical structure, 414-418
 choice, 413-414
 circulation, 424-428
 density, 421

dibasic acid esters, 416
 equipment line sizing, 426
 HVAC cycle, 424-426
 mineral oils, 414-415
 performance effects, 428
 polyalkylene glycols, 417-418
 polyalphaolefins, 415-416
 polyolesters, 416-417
 polyvinylethers, 418
 properties, 415, 420
 selection, 426-427
 solubility, 422-424
 standards, 428-429
 system operational envelope, 427
 viscosity, 420-422
 Reid method, 698-700
 Reid vapor pressure, 99
 Remaining useful life evaluation rig, 820-821
 Repressed oil, refining process, 278
 Re-refining, hydrocarbon base oil, 172
 Research Octane Rating, 62, 74
 Resid, 20-25
 delayed coking, 21-23
 fixed bed hydrocracking, 24
 fluid coking/flexicoking, 24
 fluidized bed hydrocracking, 24-25
 solvent deasphalting, 21-22
 visbreaking, 20-21
 Residual matter, LPG, 49
 Reverse-flow viscometers, 838
 Reynolds equation, 948
 Rheology, 833-835
 hydrocarbon base oil, 178
 Risk, environmental characteristics, 904
 Road transport, aviation fuels, 106
 Rolling ball viscometer, 836
 Rolling velocity, Ryder gear, 997-1000
 Roll stability, lubricating greases, 562
 R & O oils, performance testing, 241-242
 Rotary compressors, 388-389
 Rotary lobe compressor, 389
 Rotary Pressure Vessel Test, 281, 798
 Rotary screw compressor, 388-390
 Rubber, base oil compatibility, 181
 RULER, 820-821
 Run chart, 1051-1052
 Rust, chemistry, 825-826
 Rust formation, electrochemical nature, 825-827
 Rusting behavior, turbine lubricating oils and hydraulic fluids, 340-341
 Rust inhibitors, 218, 220-223
 gear lubricants, 456
 hydraulic fluids, 369-370
 lubricating greases, 568
 for turbines, 318-320
 Ryder gear

 applicability of WAM high speed load capacity test method, 1010
 background of load capacity testing, 1001
 contact stress simulation, 997-1000
 data processing and traction behavior, 1003, 1004-1007
 failure criteria in terms of scuffing and micro-scuffing, 1001
 link to service performance, 1008-1009
 OEM proposed criteria, 1009-1010
 oil evaluation, 1000-1010
 performance criteria, 1007-1008
 procedure, 1003
 rolling and sliding velocities across tooth face, 997-1000
 simulation approach, 1001-1003
 surface film formation, 1007
 test description, 1003-1005
 tooth temperatures, 996-997
 Ryder gear scuffing
 criteria, 995-996
 effect of oil chemistry, 992-994
 effect of load stage, 993-994
 initiation, 990-992
 Ryder Gear Test, 320-321
 simulation conditions, 996-1000
 test conditions, 988-990

S

SAE 3306 viscosity classification, gear lubricants, 449-451
 Safety
 aerospace fuels fueling, 744
 mineral oil heat transfer fluids, 583
 Salt spray, 829
 Sampling, LPG, 39-40, 48
 Saponification, esters, 280
 Saponification number, quench oils, 610
 Sasol distillate fuels, 138
 Saybolt patent, 37
 Saybolt viscometer, 842, 865, 870
 Saybolt viscosity, standards, 874
 Scuffing, 435, 458, 936-937
 boundary, 968-969
 engine oil performance, 1009-1010
 failure criteria, 1001
 front, propagation, 992-993
 initiation features on Ryder gears, 990-992
 oil chemistry effect, 992-994
 progression, tribological processes, 993-996
 Scuffing load ball-on-cylinder lubricity evaluator, 129-130
 Seal compatibility
 compressor lubricants, 409
 gear lubricants, 459
 hydraulic fluids, 370
 lubricating greases, 569
 Seals, functions, 233-234
 Seal swell agents, hydraulic fluids, 370
 Sediment, marine petroleum fuels, 152-153
 Sediment toxicity tests, 903

- Semisynthetic fluids, metalworking and machining fluids, 504-505
- Servo-operated automated tank gauge, 645
- Setaflash Closed Cup, 693
- Shear stability
 gear lubricants, 459
 hydraulic fluids, 371-372
 polymer-containing oils, 851-853
 requirements, 228-229
 turbine lubricating oils and hydraulic fluids, 340
- Short capillary viscometers, 865
- Short-trip-service engine rusting, 471
- Silicones, 258-259
 compressor lubricants, 394-395
- Slideway lubricants, 510
- Sliding
 gross, surface distress testing, 975-977
 incipient, surface distress testing, 974-975
 velocity, 966, 997-1000
- Sludge, formation by zinc dialkyldithiophosphate, 356-357
- Small scale closed cup, 693
- Smearing wear, 923, 929
- Smoke Point, 98
- Smoke tendency, aerospace fuels, 741
- Snelling, Walter, 36
- Soap content, detergents, 208
- Soave-Redlich-Kwong equation, 536
- Sodium, in marine petroleum fuels, 152
- Sodium soap greases, 559
- Softening point, petroleum pitch, 764
- Solid dispersions, metalworking and machining fluids, 505
- Solidification, aerospace fuels, 737-738
- Solid lubricants, 483-484
- Solid particles, in aviation fuels, 109
- Solubility, refrigeration lubricants, 422-424
- Soluble gum, ASTM D 4814, 83
- Soluble oils, metalworking and machining fluids, 503
- Solvent
 deasphalting, 21-22
 dewaxing process, 529-530
 fractionation, petroleum pitch, 765-767
 refining
 hydrocarbon base oil, 171
 process, 306-307
 solubility, petroleum waxes, 546
- Sommerfeld number, 1022-1023
- Sonic shear, turbine lubricating oils and hydraulic fluids, 340
- Soot, 203-2-4, 720-721
- "Space velocity", 18
- Spark-ignition engine fuels
 specifications, see ASTM D 4814
 vapor-liquid ratio, 703
- Spark ignition engines, 70-71
- Specific gravity
 compressor lubricants, 397
 mineral oil heat transfer fluids, 580
 quench oils, 609
- Specific heat
 compressor lubricants, 408-409
 mineral oil heat transfer fluids, 581
- Specific impulse, aerospace fuels, 742-743
- Spectrometric identification, base oil components, 172-174
- Specular gloss, petroleum waxes, 549, 552
- Sponge coke, removal, 23
- Spontaneous ignitability, aerospace fuels, 733-734, 738
- Spray ignition tests, turbine lubricating oils and hydraulic fluids, 334-336
- Squeeze films, 499
- Stability, diesel fuel, 125-126
- Stabilization patent, 37
- Stabilizers, in marine petroleum fuels, 153
- Stabilizers/deposit control agents, 201-211
- Standard platinum resistance thermometers, 866-867
- Standard reference materials, elemental analysis, 714
- Surfactants, in aviation fuels, 110
- Static bleed test, lubricating greases, 564, 569
- Static electricity, 85, 103
- Static gases, thermodynamic properties, 749-750
- Static petroleum measurement, 635-648
 automatic tank gauging, 645
 bottom sample, 641-642
 examples, 644-645
 free water, 639-640
 gauging diagram, 636
 gross observed volume, 646-647
 innage gauge, 643-644
 official sample, 641, 643
 on-board quantity/remaining on board, 645
 other standards, 648
 pipeline samples, 642
 representative sample, 641
 spot samples, 641-642
 standards, 656-657
 tapes and bobs, 636-638
 temperature in tank, 638, 643
 weighted bottle sampler, 640-641
- Statistical quality control tools, 1050-1051
- Steam cracking, ethylene, 188-190
- Steam plant fuel service system, 157, 161
- Steam reforming, 25-26
- Steam turbine, 297-298
 control fluid system, 301
 shaft driven lubrication system, 300
- Steam turbine oil
 oxidation stability, 798
 rust-preventing characteristics, 830
- Steel
 cooling behavior, wetting process impact, 594-595, 597
 cooling curve analysis, standards, 606-607
 cooling curve data acquisition and analysis, 595-598
 cooling time and rate parameters, 597, 599
 corrosivity, aviation fuels, 102
 film boiling, factors influencing, 594, 596

- hardenability, 589-591
 - measurement, 591-593
 - hardening capability, 599
 - shock film boiling, 599-602
 - transformation, 587-589
 - wetting kinetics, 593-596
 - Steel quenching
 - acoustical measurements, 600-602
 - bath maintenance, 607-608
 - process analysis example, 626-629
 - Steric stabilization, 204-205
 - Stoichiometry, aerospace fuels, 734-735, 738-739
 - Storage stability
 - aerospace fuels, 732
 - aviation fuels, 102
 - diesel fuel, 127-128
 - distillate fuel, 817-818
 - gear lubricants, 460
 - low temperature, 329
 - Stormer viscometer, 868
 - Strainers, diesel fuel system, 163-164
 - Stribeck curve, 945-946, 949, 1022-1023
 - Styrene-diene polymers, 225
 - Subsurface region, 964-965
 - Sulfur content, 19, 28-29
 - ASTM D 4814, 82
 - diesel fuel, 134
 - crude oil, 6
 - fuel oils, 762
 - gear lubricants, 457
 - impact on base oil chemistry, 176-177
 - LPG, 49
 - marine petroleum fuels, 151
 - petroleum coke, 775
 - petroleum gas, 194-195
 - petroleum pitch, 768
 - Sulfur recovery, 26-27
 - Super critical fluid chromatography, hydrocarbon analysis, 659-660
 - Surface analysis, methods, 950-951
 - Surface conformity, 914-916
 - Surface distress testing
 - other types, 976-978
 - under incipient sliding, 974-975
 - Surface energy, 922
 - Surface fatigue, impact of oil attributes, 972, 974
 - Surface film region, 963-964
 - Surface films, 919, 921-923
 - Surface roughness, 911-913
 - data analysis, 913-916
 - Surface tension, aerospace fuels, 738
 - Surface wax, 549, 551
 - Synchronizer SSP 180 test, gear lubricants, 459
 - Synthetic basestocks, compressor lubricants, 392
 - Synthetic ester fluids, for turbines, 309-311
 - Synthetic fluids, metalworking and machining fluids, 503-504
 - Synthetic hydrocarbons, 185-196
 - analytical test methods, 192
 - basestocks, 185-186
 - boiling range, 195
 - butylene and butadiene production, 190-192
 - C-4 product, characterization, 193-194
 - ethylene, 186-190, 192
 - propylene, 190, 192-193
 - standards, 195-196
 - Synthetic lubricants, 249-264
 - alkylated cyclopentanes, 260
 - biodegradability, 263
 - classes, 249
 - cyclohexane derivatives, 260
 - environmental acceptability, 262-263
 - FDA incidental food contact approval, 263
 - lubrication, 261-262
 - perfluoroalkyl ethers, 259
 - polyalkylene glycols, 252-256
 - polyalphaolefins, 257-258
 - polyphenyl ethers, 259-260
 - raw materials, 249-250
 - relative cost, 263
 - silicones, 258-259
 - standards, 263-264
 - Synthetic waxes, 525
 - System operational envelope, refrigeration lubricants, 427
- T**
- Tag Open cup, 693
 - TAME, 17
 - Tankage, gas turbine fuel system, 165
 - Tapping torque test, 1030
 - Temkin isotherm, 953-954
 - Temperature, kinematic viscosity relationship, 854-856
 - Temperature gradient method, 623, 625
 - Temperature gradient quenchant analysis, 623-629
 - Terminology, 1038-1041
 - Terrestrial toxicity tests, 903
 - Test stand aging
 - hydrolysis stability, 287-289
 - oxidation stability, 282-284
 - Thermal and oxidation test, gear lubricants, 458
 - Thermal conductivity
 - compressor lubricants, 408-409
 - gasoline, 84
 - mineral oil heat transfer fluids, 581
 - Thermal cracking reaction mechanism, ethylene, 188
 - Thermal expansion, petroleum coke, 777
 - Thermal oxidation stability, aviation turbine fuels, 815-816
 - Thermal stability
 - aerospace fuels, 745-746
 - diesel fuel, 126
 - diesters, 251
 - hydraulic oils, 799-800, 830
 - mineral oil heat transfer fluids, 579-580
 - polyolesters, 251

- turbine lubricating oils and hydraulic fluids, 339
- Thermodynamic properties, 750
 - static gases, 749-750
- Thermo oxidation engine oil simulation test, 808-812
- Thickening efficiency, 225-226
- Thin film oxygen uptake test, 807-809
- Three-terminal resistivity cell, 343
- Thrust washer tester, 1030-1031
- Timken extreme pressure test machine, 1030-1031
 - lubricating greases, 457, 566
- Tool wear, metal removal fluids, 507-509
- TOST test, 315
- Total base number, detergents, 208-209
- Total wax content, petroleum waxes, 552
- Toxicity
 - acute tests, 894, 901-902
 - chronic tests, 894
 - complex mixture, environmental characteristics, 900-901
 - marine petroleum fuels, 154
- Trace metal contents
 - limits, gas turbine fuels, 141-142
 - petroleum coke, 775
 - turbine lubricating oils and hydraulic fluids, 343
- Traction, within performance maps, 968, 970
- Traction coefficient, 970-972
- Traction test plots, 980
- Tractor fluids, 374
- Tractor hydraulic fluids, performance testing, 240-241
- Transformation processes, environmental characteristics, 889
- Transition metals, as both oxidation promoters and inhibitors, 793, 795
- Transmission fluids, 477-478
 - frictional properties, 212-213
 - performance tests, 239
 - standards, 489-490
- Transport processes, environmental characteristics, 888-889
- Triaryl phosphates, for turbines, 310, 312
- Tribochemical wear, 933
- Tribochemistry, lubricated wear contact, 949
- Tribological aspect number, 1024-1025
- Tribological features, microscopic examination, 991-992
- Tribological processes, scuff progression, 993-996
- Tribology
 - definition, 909
 - history, 1017
 - systematic
 - dynamic mechanisms, 963-965
 - gear lubrication, 988-996
 - hydrodynamic film region, 963
 - impact of oil attributes on surface fatigue, 972, 974
 - lubrication regions, thermal considerations, 970
 - micro-pitting results, 977, 979
 - multi-dimensional oil characterization, 968-969
 - near-surface region, 964
 - oil-off testing, 982-983
 - parameters controlling lubrication and failure
 - mechanisms, 965-966
 - performance maps, generalized, 987-988
 - subsurface region, 964-965
 - surface distress testing, 974-976
 - under gross sliding, 975-977
 - under incipient sliding, 974-975
 - surface film region, 963-964
 - testing for adhesive wear, 979-982
 - traction coefficient, 970-972
 - WAM test machine technology, 967-968
- Tribology test systems, 1017-1018
 - component test design, 1021
 - designing, 1018-1020
 - duration, 1023
 - economic comparison, 1018
 - load, 1022
 - materials, 1023
 - parameter selection, 1021-1024
 - selecting, 1020-1021, 1024-1025
 - special atmospheres, 1023
 - special testing, 1024
 - speed, 1022-1023
 - temperature, 1021-1022
 - test fluids, 1023-1024
- Tribo-system, *see* Tribology, systematic *t*-test, 1058-1059
- TTT diagrams, 589
- Turbine lubricating oils and hydraulic fluids, 297-349
 - acid number, 329, 331
 - additives, 312-323
 - antifoams, 321-323
 - antioxidants, 312-318
 - antiwear and extreme-pressure, 319-321
 - rust and corrosion inhibitors, 318-320
 - air release, 332-334
 - basestocks, 305-312
 - hydrocarbon oils, 305-306
 - hydrocracked/hydrotreated, 307-308
 - polyalphaolefins, 308-309
 - solvent-refined types, 306-307
 - synthetic ester fluids, 309-311
 - triaryl phosphates, 310, 312
 - chlorine content, 334
 - classification, 323-324
 - cleanliness, 341-343
 - compatibility with system materials, 343-346
 - density, 332
 - duty cycle, 304
 - effect of maintenance, 304
 - fire-resistance tests, 334-337
 - fire-resistant, 301, 311
 - foaming, 332-334
 - function, 300
 - future trends, 349
 - hot surface tests, 335
 - hydrolytic stability, 339-340
 - importance of system cleanliness, 346-347

low temperature storage stability, 329
lubrication performance, 341-342
maintenance, 347-348
oil types, 305
operating environment, 300-305
oxidation
 characteristics, 797-798
 stability, 801
 standards, 822
oxidative stability, 338-339
performance requirements, 326-328
performance testing, 241-242
pour point, 329
resistance to shear in a diesel-injector nozzle, 340
rusting and corrosion behavior, 340-341
shear stability, 340
sonic shear, 340
spray ignition tests, 334-336
stability testing, 317, 400-401
standards, 323-326
thermal/oxidative stress, 303
thermal stability, 339
top-up rates, 304
trace metals, 343
viscosity, 326-330
volatility, 346
volume resistivity, 343-345
water content, 331-332
water separability, 335-336, 338
wick tests, 335, 337
Turbine oil system, in service monitoring, 798-802
Turbines
 gas, 298-299
 steam, 297-298
 system cleanliness, 346-347
 water, 298-299
 wind, 299
Turbofan combustion system, 97

U

Ultraviolet spectroscopy
 Beer's law, 661
 hydrocarbon analysis, 661-662
 principles, 660-661
 standards, 662
Unique process line, 750-752
Used oils, wear metals, 707-709

V

Vacuum gas oils, 4
Vacuum potstill method, 696-697
Vacuum resid, 4
Vanadium content, 152-153, 775
Vane pump wear test, 362-363
Vapor control systems, 64-65
Vapor-liquid ratio, 78, 703
Vapor lock temperature, 79

Vapor pressure, 697-704
 automatic method, 701
 crude oils, 702
 environmental characteristics, 888
 evacuated chamber method, 703
 gasoline, 699, 701
 gasoline-oxygenate blends, 699, 701
 liquified petroleum gas, 40-42, 703-704
 mini-method, 701-702
 mini-method-atmospheric, 702
 Reid method, 698-700
 triple-expansion method, 702-703
 vapor-liquid ratio
Vegetable waxes, 525
Vehicle emission standards, history, 63
Vickers pump stand, 1035
Visbreaking, 20-21
Viscometer geometries, 835-836
Viscosity, 500-501
 absolute, water, 863-864
 adhesives, 870-872
 aerospace fuels, 737
 apparent, lubricating greases, 562-563
 automotive lubricants, 475-476
 bituminous materials, 870-872
 bubble tubes, 868
 coatings, 867
 diesel fuel, 121
 diesters, 251
 dip cups, 867-868
 environmentally friendly oils, 273, 289-290
 falling needle, 868-869
 fuel oils, 760-761
 gas/liquid mixtures under pressure, 408
 gasoline, 84-85
 greases, 479-480
 hydraulic fluids, 359-360
 jet fuel, 94
 loss
 due to polymer degradation, 228-230
 shear-related, 225, 227-228
 marine petroleum fuels, 148-149
 mineral oil heat transfer fluids, 579, 582-583
 paints, 867
 petroleum pitch, 764-765
 petroleum waxes, 546-547
 plastics, 869-870
 polymer quenchants, 617-618
 polyolesters, 251
 refrigeration lubricants, 420-422
 rubber, 872
 standards, 864-867, 872-875
 temperature measurement considerations, 866-867
 tests, 237
 turbine lubricating oils and hydraulic fluids, 326-330
 visualization, 835
see also Kinematic viscosity

Viscosity control, diesel fuel system, 164
 Viscosity index, 856-863
 calculation, 858-863
 gear lubricants, 457
 pressure considerations, 859, 862-863
 Viscosity index improvers, hydraulic fluids, 371-372
 Viscosity modifiers, 223-224, 235
 Viscosity-pressure coefficient, effect of base oil composition, 180-181
 Volatile matter, petroleum coke, 774-775
 Volatility, 675-705
 aerospace fuels, 736-737
 automotive lubricants, 471
 aviation fuels, 98-101
 class specifications, ASTM D 4814, 82
 crude oil distillation, 696-698
 diesel fuel, 120-121
 diesters, 251
 distillation, 675-682
 environmental characteristics, 896, 900
 flammability, 682, 690-696
 gasoline, 78-80
 polyolesters, 251
 standards, 704-705
 turbine lubricating oils and hydraulic fluids, 346
 vapor pressure, 697-704
 Volatility residue, LPG, 42
 Volume correction factors, liquefied petroleum gas, 50-51
 Volume resistivity, turbine lubricating oils and hydraulic fluids, 343-345

W

Walther equation, 917
 WAM configuration, optical EHD film thickness measurement, 984-985
 WAM high speed load capacity test method, engine oils, 1010
 WAM test machine technology, 967-968
 Waste heat economizers, diesel fuel system, 165
 Water, absolute viscosity, 863-864
 Water-absorbing cartridges, 108
 Water-based, metalworking and machining fluids, 501-503
 Water content
 aerospace fuels, 746-747
 compressor lubricants, 397
 dissolved in propane, phase behavior, 43-44
 gear lubricants, 457
 hydraulic fluids, 363, 365
 LPG, 42-49
 marine petroleum fuels, 151

 mineral oil heat transfer fluids, 583
 polymer quenchants, 617
 quench oils, 610-611
 turbine lubricating oils and hydraulic fluids, 331-332
 Water separability, turbine lubricating oils and hydraulic fluids, 335-336, 338
 Water solubility, environmental characteristics, 887
 Water spray-off, lubricating greases, 568
 Water tolerance, ASTM D 4814, 83
 Water turbines, 298-299
 Water washout, lubricating greases, 568
 Wax appearance point, 881-882
 Waxy crude oil, 527-528
 Wear
 combinations of cavitation/erosion/corrosion wear, 932-933
 debris analysis, 939-941
 mechanisms, 923, 927-931
 standards, 1035-1037
 testing, 938-941
 within performance maps, 968, 970
 Wear contact, material structure, 916-925
 Wear maps, 942-945
 Wear material, surfaces, 949
 Wear metals, used oils, 707-709
 Wear preventive characteristics, lubricating greases, 567
 Wear protection, hydraulic fluids, 359-364
 Wear reduction, heat of adsorption, 954
 Wear surfaces, 911-913
 Weathering, liquified petroleum gas, 42
 Weighted bottle sampler, 640-641
 Wheel bearing grease life, 566
 Wheel bearings, grease leakage, 565
 Wick tests, turbine lubricating oils and hydraulic fluids, 335, 337
 Wind turbines, 299
 Wolf Strip Oxidation Test, compressor lubricants, 401
 World Wide Fuel Charter, 137
 Worms, toxicity tests, 903-904

X

X-ray fluorescence spectrometry, elemental analysis, 713

Y

Yellow metal corrosion, 221

Z

Zinc dialkyldithiophosphate, 314
 oxidation inhibition, 794
 sludge formation, 356-357