

Index

A

- Abiotic degradation, environmental characteristics, 889-890
- Abrasive wear, 435, 930-931
- Accepted Reference Values, 1047-1048
- Accumulation processes, environmental characteristics, 894-895
- Acid catchers, refrigeration lubricants, 419
- Acidity, automotive lubricants, 474-475
- Acid neutralizing agents, 221
- Acid number
 - compressor lubricants, 400
 - gear lubricants, 456
 - mineral oil heat transfer fluids, 582
 - quench oils, 609-610
 - turbine lubricating oils and hydraulic fluids, 329, 331
- Acids
 - formation, 790
 - for lubricants, 272
- Acoustical measurements, steel quenching, 600-602
- Active oxygen method, 820-821
- Additives, 199-246
 - antiseize, 218
 - aviation fuels, 104-105
 - classification, 951-957
 - demulsifiers, 232-233, 366
 - detergents, 208-211
 - dispersants, 203-208
 - dispersant viscosity modifiers, 228-229, 231
 - dyes, 234
 - emulsifiers, 232-233
 - environmental impact, 234
 - ester polymers, 225-228
 - film-forming agents, 211-223
 - filterability, 368
 - friction modifiers, 211-213, 441, 949, 951-952
 - gear lubricants, 439-443, 447
 - hydraulic fluids, 363
 - introduction of new, 234
 - metalworking and machining fluids, 511-519
 - alkalinity agents, 516
 - antimicrobial agents, 517-518
 - anti-misting agents, 516
 - corrosion inhibitors, 516-517
 - coupling agents, 513
 - dispersants, 516
 - dyes, 519
 - emulsion promoters, 512-513
 - film-forming agents, 513-515
 - foam inhibitor, 518
 - inorganic/organic solids, 519
 - odor control agents, 519
 - oxidation inhibitors, 518-519
 - multifunctional nature, 234
 - olefin-based polymers, 224-226
 - performance package, 200-201
 - performance testing, 235-242
 - engine oils, 237-239
 - finished formulations, 235-236
 - gear oils, 239-240
 - greases, 242
 - hydraulic fluids, 240-241
 - individual additives, 235
 - machine tests, 236
 - metalworking fluids, 241
 - miscellaneous industrial oils, 241-242
 - physical tests, 236
 - transmission fluids, 239
 - viscosity tests, 237
 - polymeric, 223-233
 - pour point depressants, 230-232, 373
 - primary functions, 200
 - refrigeration lubricants, 418-420
 - rust and corrosion inhibitors, 218, 220-223, 318-320
 - stabilizers/deposit control agents, 201-211
 - standard, 243-246
 - for turbines, 312-323
 - antifoams, 321-323
 - antioxidants, 312-318
 - antiwear and extreme-pressure, 319-321
 - rust and corrosion inhibitors, 318-320
 - viscosity modifiers, 223-224
 - see also* Antifoam additives; Antiwear additives; Antioxidants; Corrosion inhibitors
- Adhesion, friction due to, 911
- Adhesives, viscosity, 870-872
- Adhesive wear, 435, 923, 927-930, 979-982
 - resistance ranking, 980-981
 - testing, oil evaluation, 981-982
 - test method, 979
 - traction test plots, 980
- Adiabatic flame temperature, gasoline, 84
- Adiabatic operation, 384
- Adipic acids, synthesis, 276, 279
- Adsorption, environmental characteristics, 888
- Adsorption efficiency, steric hinderance, 952-953
- Adsorption isotherms, 953-954
- Aeration, hydraulic fluids, 366-367
- Aero-derivative gas turbines, 301-302
- Aerospace, engine thermodynamics, 730-732
- Aerospace fuels, 729-756
 - air dilution, 742
 - bouyancy in air, 732
 - calorific values, 739-740
 - combustion emissions, 743
 - density, 735-736
 - flame stabilization, 742

- flammability, 738
- fueling fire safety, 744
- future trends, 747-748
- handling characteristics, 743-747
- health issues in handling, 747
- ignition, 741
- lubricity, 744-745
- maximum combustion temperature, 735, 740-741
- molecular structure, 732-734
- oxidation heat release, 735
- performance of rocket fuels and oxidants, 731
- physical state, 733
- preparation and mixing, 741
- properties, 735-736
- reformation, 747
- smoke tendency, 741
- solidification, 737-738
- specifications, 748
- specific impulse, 742-743
- spontaneous ignitability, 733-734, 738
- standards, 749
- stoichiometry, 734-735, 738-739
- storage stability, 732, 745
- substitute fuels, 748
- supplemental fuels, 747
- surface tension, 738
- thermal stability, 745-746
- turbine entry temperature distribution, 742
- viscosity, 737
- volatility, 736-737
- water content, 746-747
- Aging, Baader aging test, 821-822
- Air conditioning lubricants, 484
- Aircraft, sumping procedure, 111
- Aircraft range, aviation fuels, 100-101
- Air-fuel ratio, octane number requirement, 76
- Airport
 - fuel systems, 106
 - quality control, 110-111
- Air release
 - compressor lubricants, 398
 - gear lubricants, 460
 - turbine lubricating oils and hydraulic fluids, 332-334
- Alcohol bonds, environmentally friendly oils, 271-272
- Alcohols
 - hydrogen bond, 270
 - for lubricants, 271-273
- Algae, acute toxicity tests, 901-902
- Alkalinity agents
 - automotive lubricants, 474-475
 - metalworking and machining fluids, 516
- Alkanes
 - lattice transition, 534
 - physical properties, 532
- Alkenylsuccinates, synthesis, 206
- Alkylated cyclopentanes, 260
- Alkylation, 15-17
- Alkylbenzene
 - compressor lubricants, 395
 - refrigeration lubricants, 415
- Alkyl lead
 - history, 62
 - phasedown, 63
- Alkyl lead content, 68
 - ASTM D 4814, 82
- Alkylphenols, 209
- Alkyl phosphates, synthesis, 216, 218
- Alkyl phosphites, synthesis, 216-217
- Alternative fuels, diesel engines, 138-139
- Aluminum, production, carbon anodes, 781-782
- Aluminum beaker oxidation test, 810, 813
- Aluminum complex soap greases, 559
- Aluminum soap greases, 558
- Ammonia, in LPG, 50
- Amonton's Law, 383
- Aniline point, hydrocarbon base oil, 181
- "Anti-dumping" provisions, 65
- Antifoam additives, 233-234
 - gear lubricants, 441
 - hydraulic fluids, 367
 - metalworking and machining fluids, 518
 - refrigeration lubricants, 419-420
 - for turbines, 321-323
- Anti Knock Index, 73-74
 - ASTM D 4814, 78
- Antimicrobial agents, metalworking and machining fluids, 517-518
- Anti-misting agents, metalworking and machining fluids, 516
- Antioxidants, 201-202, 793-796
 - arylamine, 795
 - gasoline, 69, 82-83
 - gear lubricants, 441, 445
 - hindered phenols, 794
 - hydraulic fluids, 356-358
 - metalworking and machining fluids, 518-519
 - refrigeration lubricants, 419
 - structures, 314
 - synergistic combination, 315
 - turbine lubricating oils and hydraulic fluids, 312-318
 - zinc dialkyl dithiophosphate, 794
- Antiseize additives, 218
- Antiwear additives, 69, 213-216, 955-956
 - gear lubricants, 440, 444
 - hydraulic fluids, 363
 - refrigeration lubricants, 419
 - surface reactions, 954-955
 - turbines, 319-321
- Antiwear performance testing, hydraulic fluids, 361-364
- Antiwear properties, compressor lubricants, 402-406
- API CF oils, 473
- API CG-4 oils, 473-474
- API CH-4 oils, 474
- API gravity

- diesel fuel, 117-118
- fuel oils, 758-759
- gear lubricants, 456
- API service designation, gear lubricants, 448-453
- Appledoorn equation, 919
- Approximate F -test, 1059-1060
- Aquatic toxicity tests, acute, 901
- Aqueous polymer quenchants, 605-606
- Archard's equation, 930
- Aromatic esters, 249-250
- Aromatics, 28
 - determination, 195
 - diesel fuel, 131-132
 - saturation, 17-20
- Arrhenius equation, 127-128
- Arylamine, oxidation inhibition, 795
- Aryl phosphates, synthesis, 216, 218
- Aryl phosphites, synthesis, 216-217
- Ash content
 - diesel fuel, 135
 - fuel oils, 761-762
 - marine petroleum fuels, 150
 - petroleum coke, 775
 - petroleum pitch, 768
 - quench oils, 614
- Ash modifiers, marine petroleum fuels, 154
- Asphaltene content, marine fuels, 151
- Association of Natural Gasoline
 - Manufacturers, 36
- ASTM D 4814, 77-83
 - alkyl lead content, 82
 - anti-knock index, 78
 - copper corrosion test, 82
 - driveability index, 78-79
 - gasoline and gasohol blending, 80, 82
 - oxidation stability, 82-83
 - phosphorus content, 82
 - soluble gum, 83
 - sulfur content, 82
 - vapor pressure specifications, 78- 81
 - volatility, 78-80
 - class specifications, 82
 - water tolerance, 83
- ASTM proficiency testing, elemental
 - analysis, 714
- Atmospheric gas oil, 3
- Atomic absorption spectrometry, elemental analysis, 709
- Austenite, 587
- Autoignition
 - compressor lubricants, 399
 - mineral oil heat transfer fluids, 581
 - temperature, gasoline, 83-84
- Automatic tank gauging, 645
- Automatic transmission fluids
 - aluminum beaker oxidation test, 810, 813
 - hydraulic fluids, 374
 - performance testing, 239
- Automotive wheel bearing grease, 807
- Automotive engine oils, 467-470
 - ASTM standard test methods, 469-470
 - corrosion tests, 828-829
 - issues in test method development, 469
 - performance standards, 467-468
 - performance tests, 468-469
- Automotive gear lubricants, 442, 446, 448
 - oxidation stability, 803-804
 - performance testing, 239-240
- Automotive lubricants, 465-494
 - additional fluids, 484
 - air conditioning lubricants, 484
 - axle lubricants, 483
 - brake fluids, 483
 - composition, 466-467
 - extent of oxidation, 476-477
 - functions, 465-466
 - greases, 478-481
 - ILSAC GF-2 and API SJ standard
 - tests, 470-476
 - acidity and alkalinity, 474-475
 - ball rust test, 472-473
 - city service engine sludge and valve train wear, 470-471
 - corrosiveness, 475
 - diesel engine oil, 473-474
 - energy conserving characteristics, 471
 - entry of water, 475
 - foaming tendency, 471
 - high temperature copper-lead bearing water, 470
 - phosphorus content, 471
 - short-trip-service engine rusting, 471
 - standard tests, 472
 - viscosity, 475-476
 - volatility, 471
 - solid lubricants, 483-484
 - standards, 485-494
 - test methods, 466-467
- Automotive transmission fluids, 477-478
 - oxidation stability, 804
- Auto-Oil Air Quality Improvement Research Program, 65
- Auto propane, 51-52
- Auto-refrigeration, 46
- Autoxidation, ester based fluids, 277, 279
- Aviation fuels, 89-113
 - additives, 104-105
 - aircraft range, 100-101
 - combustion, 97-98
 - corrosion tests, 828
 - corrosivity, 101-102
 - freezing point, 880-881
 - gasoline, 89-92
 - high temperature, 95-97
 - history, 89
 - jet fuel, 89, 91-93
 - low temperature
 - fuel related, 93-95

- water related, 95
- lubricity, 102-103
- manufacturing, 103-104
- metering, 99-100
- oxidation
 - stability, 813
 - standards, 823
- quality control, 106-111
 - aviation gasoline, 107
 - contaminants, 106
 - contamination detection equipment, 109-110
 - contamination removal equipment, 107-109
 - jet fuel, 107
 - procedures, 110-111
 - standards, 112-113
 - static electricity, 103
 - storage stability, 102
 - transportation, 105-106
 - volatility and flammability, 98-99
- Aviation gas turbine oils
 - basestocks, 1012, 1014
 - corrosion inhibited MIL-PRF-23699 oils, 1011
 - gear testing, 988
 - high load-carrying DOD-L-85734 oils, 1011- 1012
 - high thermal stability MIL-PRF-23699 oils, 1011
 - load capacity database, 1011-1015
 - master chart, 1012, 1014
 - selected MIL-PRF-7808 grade 3 and grade 4 oils, 1012-1013
 - standard MIL-PRF-23699 oils, 1011
- Aviation turbine fuels, thermal oxidation stability, 815-816
- Avogadro's Law, 383
- Axle lubricants, 483

B

- Baader aging test, 821-822
- Back pressure control, 164-165
- Bainite, 587
- Ball bearings, greases, at elevated temperatures, 565-566
- Ball on Cylinder Lubrication Evaluator, 102
- Ball rust test, 472-473
- Band area methods, infrared spectroscopy, 668
- Barus equation, 917-918
- Base number, gear lubricants, 458
- Base oil, *see* Hydrocarbon base oil
- Bearing contacts, performance maps and, 972-973
- Beer-Lambert law, 667
- Beer's law, 661
- Beeswax, 525-526
- Bench test, 1020-1021
 - Block-on-Ring test, 1029-1030
 - four ball extreme pressure test, 1028-1029
 - four ball tests, 1026-1027
 - four ball wear test, 1027-1028
 - linear reciprocation, 1031-1033
 - multi-specimen test machine, 1030-1031
 - pin and vee block tester, 1025-1026

- Pin-on-Disk test, 1026
 - selection, 1019
 - tapping torque test, 1030
 - Timken extreme pressure test machine, 1030- 1031
- Bench test modeling, *see* Ryder gear; Systematic tribology
- Bending-beam rheometer, 870, 872
- Benzene, 28
- Benzene Emission Number, 66
- Bessemer Gas Engine Company, 37
- Bias
 - measurement process, 1044-1045
 - monitoring, 1047-1048
- Bioaccumulation factor, 894-895
- Biocides, marine petroleum fuels, 154
- Bioconcentration factor, 894-895
- Biodegradability
 - diesters, 252
 - environmental characteristics, 890-894
 - hydrocarbon base oil, 182
 - polyolesters, 252
 - synthetic lubricants, 263
- Biodegradable lubricants, oxidation
 - standards, 823
 - testing, 820-822
- Biodiesel, 138-139
- Biological properties, hydrocarbon base oil, 181-182
- Biological stability, polymer quenchant, 620-623
- Biota-sediment accumulation factor, 894-895
- Bituminous materials, viscosity, 870-872
- Black deposits, LPG, 49-50
- Black penetration, lubricating greases, 561
- "Blaugas", 35-36
- Blending
 - marine fuel oils, 147-148
 - petroleum oil, 28
- Blocking point, petroleum waxes, 552-553
- Block-on-Ring test, 1029-1030
- Boeing 747-400 fuel tankage, 93
- Boiling point, 28
- Boiling range, synthetic hydrocarbons, 195
- Bomb combustion methods, elemental analysis, 709
- Bomb oxidation test, lubricating greases, 565
- Bonded fuel, aviation fuels, 106
- Boost systems, diesel fuel system, 164
- Borsoff effect, 936
- Boundary lubrication, 214, 498, 949
- Bouyancy, aerospace fuels, 732
- Brake fluids, 483
 - standards, 493
- Brayton cycle, 730-731
- Broomwade 2050H Compressor Rig Test, 403
- Brush drag of latex paints, 868
- Btx recovery, 14-15
- Bubble tubes, 868
- Bulk material properties, flow properties, 921-922, 925-926
- Bunsen Coefficient, 406
- Bureau of Mines Correlation Index, 186

- Butadiene
 analysis, 193
 production, 190-192
 purity, 193
 Butane, 46
 Butane-butene mixtures, chlorides in, 194
 Butylene
 analysis, 193
 production, 190-192
- C**
- Cadmium corrosivity, aviation fuels, 102
 Calcium complex soap greases, 559
 Calcium soap greases, 558-559
 Calorific values, aerospace fuels, 739-740
 Canadian Environmental Protection Act, 66
 Candelilla wax, 525-526
 Carbon acids, hydrogen bond, 270
 Carbon anodes, for aluminum production, 781-782
 Carbon blacks, 779-781
 Carbon fibers, petroleum pitch, 781
 Carbonizable substances, petroleum waxes, 549
 Carbon residue
 compressor lubricants, 399
 diesel fuel, 135-136
 fuel oils, 761
 marine petroleum fuels, 151-152
 mineral oil heat transfer fluids, 580
 quench oils, 611-613
 standards, 783-784
 Carbonyls, in C₄ hydrocarbons, 194
 Carbonyl sulfide, in propylene, 193
 Carboxylic acids
 environmentally friendly oils, 272-273
 isomers, 270
 Carnauba, 525-526
 Carreau viscosity equation, 948-949
 Casinghead gasoline, 36-37
 Catalytic reforming, 12-15
 yield/octane relationship, 14
 Caterpillar micro-oxidation test, 810-811, 813-814
 Cat fines, marine petroleum fuels, 150
 "Cat" gasoline, 11
 Cavitation corrosion, 932
 Cavitation erosion, 932-933
 Cavitation erosion corrosion, 933
 Cavitation wear, 931-941
 corrosion, 931-932
 delamination, 937-938
 erosion, 931-932
 fatigue, 933-936
 oxidational, 933
 scuffing, 936-937
 tribochemical, 933
 CCT diagrams, 589
 Cementite, 587
 Centrifugal compressor, 389-390
 Centrifuges, diesel fuel system, 161, 163
 Centrifuge tests, 365
 lubricating greases, 564-565
 Cetane index, 119-120
 Cetane number, 119
 diesel fuel oils, 721-723
 Channel point FTM, gear lubricants, 459
 Chemical analysis, lubricating greases, 569
 Chemical corrosion, 220
 Chi-square test, 1059
 Chlorine content
 butane-butene mixtures, 194
 gear lubricants, 457
 turbine lubricating oils and hydraulic fluids, 334
 City service engine sludge and valve train wear, 470-471
 Clay treatment vessels, 108-109
 Clean Air Act of 1963, 63
 Clean Air Act of 1970, 64
 Clean Air Act Amendments of 1977, 64
 Clean Air Act Amendments of 1990, 65-66, 135
 Cleanliness
 diesel fuel, 124-125
 turbine lubricating oils and hydraulic fluids, 341-343
 Cleveland Open Cup, 692
 Cloud point, 881-882
 diesel fuel, 121-122
 petroleum waxes, 545-546
 polymer quenchants, 619
¹³C NMR spectrometry, hydrocarbon analysis, 650-651
 CNS effects, LPG, 54-55
 Coalescer Blocking Tendency Test, compressor lubricants, 404-406
 Coatings, flow-related instruments, 867
 CoBr test, 47-48
 Coefficient of kinetic friction, petroleum waxes, 552, 554
 Cogeneration, 28
 Coking, delayed, 21-23
 Coking value, petroleum pitch, 767-768
 Cold crank simulator, 850
 gear lubricants, 458
 Cold Filter Plugging Point, diesel fuel, 123-124
 Cold flow properties, 879-883
 aviation fuels freezing point, 880-881
 cloud point, 881-882
 high-shear tests of lubricants, 882
 pour point, 879-880
 pumpability of lubricants, 882
 standards, 883
 wax appearance point, 881-882
 Color, petroleum waxes, 549-551
 Combustion, diesel fuel, 118-119
 Combustion products, dissociated, 753-754
 Combustion temperature, aerospace fuels, 735, 740-741
 Compatibility
 gear lubricants, 460
 marine petroleum fuels, 152
 turbine lubricating oils and hydraulic fluids, 343-346

- see also* Seal compatibility
- Compressibility factor, 384
- Compression, power requirement, 385-386
- Compression ignition engines, 115-116
- Compression ratio, octane number requirement, 76
- Compressor lubricants, 383-411
 - acid number, 400
 - air release, 398
 - antiwear properties, 402-406
 - autoignition, 399
 - basestocks, 392-395
 - carbon residue, 399
 - classification, 391
 - copper corrosion, 398
 - corrosion, 398-399
 - demulsibility, 397-398
 - elastomeric seals compatibility, 409
 - evaporation, 399
 - Filter Bowl Compatibility Test, 410
 - fire point, 398-399
 - flash point, 398-399
 - fluid oxidation, 400-401
 - foaming tendency, 398
 - gas solubility, 395-396, 406-409
 - heat transfer efficiency, 408-409
 - hydrolytic stability, 398
 - infra-red spectroscopy, 400-401
 - iron corrosion, 398
 - kinematic viscosity, 396-397
 - Liquid Heptane Washing Test, 401-402
 - oxidation stability, 802
 - Paint Compatibility Test, 409-410
 - performance demands, 389-392
 - pour point, 397
 - precipitation number, 399-400
 - solubility in the gas, 396, 398
 - specific gravity, 397
 - specific heat, 408-409
 - standards, 410-411
 - thermal conductivity, 408-409
 - viscosity of gas/liquid mixtures under pressure, 408
 - water content, 397
- Compressor tests, 403
- Concentric cylinder viscometer, 835-836
- Conductance, polymer quenchants, 618-619
- Conductivity, gasoline, 85
- Cone-and-plate viscometer, 835
- Cone penetration, lubricating greases, 561
- Congealing point, petroleum waxes, 545
- Conradson carbon residue, compressor lubricants, 399
- Consistency, lubricating greases, 560-561
- Consistency stability, lubricating greases, 561-562
- Construction materials, gas turbine fuel system, 166-167
- Contact stress, 966
 - simulation, Ryder gear, 997-1000
- Contamination
 - aviation fuels, 106
 - detection equipment, aviation fuels, 109-110
 - gasoline, 69
 - lubricating greases, 568-569
 - quench oils, 610-614
 - removal equipment, aviation fuels, 107-109
- Continuous cooling transformation diagrams, 589
- Control chart, 1055-1056
- Conventional Oxidation Catalyst, 63-64
- Coolants, secondary, 574
- Coolant separability, hydraulic fluids, 370-371
- Cooling curve analysis, polymer quenchants, 621-623
- Copper corrosion, 826
 - aviation fuels, 101-102
 - compressor lubricants, 398
 - lubricating greases, 567-568
- Copper corrosion inhibitors, 69
- Copper corrosion test, ASTM D 4814, 82
- Copper deactivation, 221
- Copper passivators, 221-222
- Copper strip corrosion, diesel fuel, 134-135
- Copper strip tarnish test, 827-828
 - gear lubricants, 454, 456
- Corrosion, 825-832
 - compressor lubricants, 398-399
 - in LPG, 49
 - specifications, 827
- Corrosion behavior, turbine lubricating oils and hydraulic fluids, 340-341
- Corrosion inhibitors, 218, 220-223
 - gear lubricants, 441
 - hydraulic fluids, 369-370
 - metalworking and machining fluids, 516-517
 - polymer quenchants, 619-620
 - surface activity, 826-827
 - for turbines, 318-320
- Corrosion protection, hydraulic fluids, 368-370
- Corrosion tests, 827-832
 - automotive engine oils, 828-829
 - aviation gasolines, 828
 - diesel fuel oils, 828
 - gear oils, 829
 - greases, 831-832
 - lubricants, 827-828, 829-831
- Corrosion wear, 931-932
- Corrosivity
 - aviation fuels, 101-102
 - diesel engine oil, 475
- Coupling agents, metalworking and machining fluids, 513
- Cracking, crude oil, 146-148
- Critical pressure, 384
- Critical temperature, 384
- Crude oil gases, 3
 - disposition, 5
- Crude oils, 6-7, 145-148
 - classification, 526-527, 575-576
 - cracking, 146-148
 - distillation, 146-147

- distillation, 696-698
 - preparation and separation, 9-10
 - refinery blending and storage, 147-148
 - refining, 528-529
 - vapor pressure, 702
 - waxy, 527-528
 - Crystalline structure, petroleum coke, 775-776
 - Crystallization, esters, 289-291
 - Cyclic durability test, gear lubricants, 458
 - Cyclohexane derivatives, 260
- D**
- Dalton's Law, 383
 - Defoamers, *see* Antifoam additives
 - Deformation, friction due to, 911
 - Degree of overbasing, 208
 - De-icers, 68
 - Delamination wear, 937-938
 - Delayed coking, 21-23
 - Demulsibility
 - compressor lubricants, 397-398
 - gear lubricants, 457-458
 - hydraulic fluids, 366
 - Demulsifiers, 232-233
 - gear lubricants, 441
 - marine petroleum fuels, 154
 - Density
 - aerospace fuels, 735-736
 - crude oil, 6
 - diesel fuel, 117-118
 - marine petroleum fuels, 149
 - petroleum coke, 775
 - petroleum pitch, 768
 - refrigeration lubricants, 421
 - turbine lubricating oils and hydraulic fluids, 332
 - Deposit control additives, 69-70
 - Desorption, environmental characteristics, 888
 - Detergents, 208-211
 - gear lubricants, 440, 444
 - hydraulic fluids, 358
 - micellar structure, 210-211
 - synthesis, 210
 - Dewaxing, hydrocarbon base oil, 171-172
 - Dewaxing process variables, 530-531
 - Dew Point test, 47-48
 - Dialkyl dithiophosphoric acid derivatives, synthesis, 215
 - Dibasic acid esters, refrigeration lubricants, 416
 - Diesel engines
 - alternative fuels, 138-139
 - history, 115-116
 - Diesel fuel oils, 9
 - API gravity, 117-118
 - aromatics, 131-132
 - ash, 135
 - carbon residue, 135-136
 - cetane index, 119-120
 - cetane number, 119
 - cleanliness, 124-125
 - Cloud Point, 121-122
 - Cold Filter Plugging Point, 123-124
 - composition/performance correlations, 178-179
 - copper strip corrosion, 134-135
 - corrosion tests, 829
 - corrosiveness, 475
 - density, 117-118
 - distillation, 120-121
 - dyed, 135-137
 - Flash point, 128-129
 - formation of insolubles, 125
 - grades, 116-117
 - heat content, 132-134
 - heat of combustion, 132-134
 - ignition and combustion characteristics, 118-119
 - low-sulfur, 135-137
 - Low-Temperature Flow Test, 123
 - lubricity, 129-131
 - oxidation stability, 126-127
 - performance categories, 473-474
 - Pour Point, 122-123
 - premium, 137-138
 - requirements, 118
 - specifications, 116-117
 - stability, 125-126
 - storage stability, 127-128
 - thermal stability, 126
 - total sulfur, 134
 - viscosity, 121
 - volatility, 120-121
 - World Wide Fuel Charter, 137
 - Diesel fuel combustion, 717-727
 - combustion process, 718-719
 - emissions, 719-721
 - fuel injection, 717-718
 - ignition, 718
 - Diesel fuel oils
 - cetane number, 721-723
 - corrosion tests, 828
 - CVCA/IQT method, 724-727
 - ignition quality, 721-727
 - proposed alternatives to ASTM D 613, 723-724
 - specifications, 718
 - standards, 727
 - Diesel fuel system, 161, 163-165
 - back pressure control, 164-165
 - boost systems and deaeration, 164
 - centrifuges, 161, 163
 - emulsifiers, 165
 - filters and strainers, 163-164
 - fuel final filter, 164
 - fuel service heaters, 164
 - fuel supply flowmeter, 164
 - homogenizer, 165
 - viscosity control, 164
 - waste heat economizers, 165

- Diesel index, 118
 - Diesel-injector nozzle, shear resistance, turbine lubricating oils and hydraulic fluids, 340
 - Diesel plant fuel system, 161-162
 - Diesters, 249-252
 - application and performance characteristics, 252
 - biodegradability, 252
 - chemical characteristics, 251
 - chemistry and manufacturing, 249-251
 - manufacturing technology, 250-251
 - physical properties, 251
 - Difference method, infrared spectroscopy, 668
 - Differential scanning calorimetry
 - petroleum waxes, 539-542
 - transition temperatures, 548
 - Dip cups, 867-868
 - Dispersants, 203-208
 - bridged structure, 206-207
 - gear lubricants, 440-441, 445
 - hydraulic fluids, 358
 - in marine petroleum fuels, 153
 - metalworking and machining fluids, 516
 - performance, 204-205
 - structural features, 205-206
 - uses, 206, 208
 - Dispersant viscosity modifiers, 206, 228-229, 231
 - Dispersive-type infrared spectrometers, 667
 - Disposition tendencies, liquids in thin films and vapors, 819-820
 - Dissociation constant, environmental characteristics, 888
 - Distillate fuels
 - high temperature stability, 817-818
 - oxidation stability, 816-817
 - storage stability, 817-818
 - Distillation, 675-682
 - atmospheric pressure, 676-680
 - crude oils, 146-147, 696-698
 - diesel fuel, 120-121
 - fuel oils, 761
 - hydraulic fluids, 365
 - hydrocarbon base oil, 171
 - international standards, 689
 - mineral oil heat transfer fluids, 582
 - reduced pressure, 680-690
 - Distillation fractions, 3-4
 - 2,6-Ditertiarybutyl-4-methylphenol, 314-315
 - DOD-L-85734 oils, 1011-1012
 - Driveability index, 78-79
 - Dropping point, lubricating greases, 563-564
 - Dyes, 234, 519
 - Dynamic seals test, gear lubricants, 460
 - Dynamic shear rheometer, 870
- E**
- Ecological tests, environmentally friendly oils, 289, 291-292
 - Elastohydrodynamic contact, functional regions, 965
 - Elastohydrodynamic film-forming capability, engine oil, 983-987
 - optical thickness measurement, 984-985
 - pressure-viscosity coefficients, 985-987
 - Elastohydrodynamic lubrication, 413, 968
 - film thickness, 1007
 - measurements by interferometry, 947-948
 - mixed film lubrication, 949
 - non-Newtonian, 948-949
 - Reynolds equation, 948
 - Elastomeric seals, *see* Seal compatibility
 - Elastomers, turbine lubricating oils and hydraulic fluids compatibility, 344
 - Electric-arc furnaces, graphic electrodes, 782
 - Electrochemical corrosion, 218, 220
 - Electrostatic stabilization, 204-205
 - Elemental analysis, 707-716
 - ASTM proficiency testing, 714
 - atomic absorption spectrometry, 709
 - bomb combustion methods, 709
 - classical wet chemistry methods, 709
 - DO2 test methods, 709-710
 - future developments, 715-716
 - graphite furnace atomic absorption spectrometry, 709-711
 - inductively coupled plasma-atomic emission spectrometry, 711-712
 - inductively coupled plasma-mass spectrometry, 712
 - international test methods harmonization, 714-715
 - ion chromatography, 712
 - microelemental analysis methods, 712
 - neutron activation analysis, 712-713
 - sample preparation, 707
 - standard reference materials, 714
 - wear metals in used oils, 707-709
 - X-ray fluorescence spectrometry, 713
 - Elemental content, gear lubricants, 458
 - Emissions
 - aerospace fuels, 743
 - diesel fuel combustion, 719-721
 - Emulsifiers, 232-233
 - diesel fuel system, 165
 - gear lubricants, 441-442
 - Emulsion promoters, metalworking and machining fluids, 512-513
 - Energy conserving characteristics, 471
 - Energy content, gasoline, 72
 - Energy equation, 756
 - Engine deposits, effect on octane number requirement, 77
 - Engine management systems, 71
 - Engine oils
 - adhesive wear testing, 981-982
 - elastohydrodynamic film-forming capability, 983-987
 - hydraulic fluids, 374
 - oxidation
 - standards, 823
 - testing, 807-811
 - performance tests, 237-239

- standards, 485-488
thermo oxidation engine oil simulation test, 808-812
traction and scuffing failure characteristics, 1008-1009
traction characteristics, 1003, 1005
WAM high speed load capacity test method, 1010
Engine spark timing, octane number requirement, 76-77
Engine tests, engine oils, 823
Entraining velocity, 966-967
Environmental acceptability, synthetic lubricants, 262-263
Environmental characteristics, 885-906
abiotic degradation, 889-890
accumulation processes, 894-895
acute toxicity tests, 894, 901-902
adsorption, 888
biodegradation, 890-894
chemical structure and, 886-887
chronic and subchronic tests, 894, 903-904
complex mixture toxicity, 900-901
desorption, 888
dissociation constant, 888
exposures, 895-896, 900-901
hazard and risk, 904
Henry's Law Constant, 888
low solubility materials, 900
non-aquatic toxicity tests, 903-904
octanol/water partition coefficient, 887
rationale for standardized testing, 885-886
standardized tests, 895-899
terminology, 904-906
transformation processes, 889
transport processes, 888-889
vapor pressure, 888
volatility, 896, 900
water solubility, 887
Environmental considerations, marine petroleum fuels, 156
Environmental impact, 234
Environmentally acceptable hydraulic fluids, 377-378
Environmentally friendly oils, 267-294
alcohol bonds, 271-272
carboxylic acids, 272-273
chemical properties, 273-276
crystallizing, 289-291
ecologically toxic properties, 289, 291-292
esterification, 270-271
functional groups and elementary compound, 269-270
functions and requirements, 267-268
future developments, 291-293
hydrolysis, 274
low temperature properties, 289-291
native esters, 275, 277-278
oxidation stability, 274-275
standards, 293-294
synthetic esters, 276, 278-279
viscosity, 273, 289-290
see also Pressure media
Equation-of-state approach, 423, 535-539
Equipment line sizing, refrigeration lubricants, 426
Erosion corrosion, 933
Erosion wear, 931-932
Ester fluids, viscosity vs. temperature, 289-290
Esterification, 249-250
catalysis, 251
mechanism, 270-271
Ester polymers, 225-228
Esters
compressor lubricants, 394
native, environmentally friendly oils, 275, 277-278
native and synthetic
chemical bases, 269-273
chemical properties, 273-276
pour points, 273
synthetic
environmentally friendly oils, 276, 278-279
turbines, 309-311
Ethanol, in propane, 47
Ethylene
characterization, 192
production, 186-190
commercial production, 188-190
feedstock, 186-188
thermal cracking reaction, 188
Ethyl mercaptan, as odourant, 52, 55
Evaporation, compressor lubricants, 399
Evaporation loss, lubricating greases, 564
EWMA overlay, 1056
Exhaust emissions, marine petroleum fuels impact, 154
Exponentially Weighted Moving Average values, 1056
Exposures, environmental characteristics, 895-896, 900-901
Extreme pressure additives, 213-214, 216-219, 955-957
gear lubricants, 440, 444
hydraulic fluids, 363
metalworking and machining fluids, 513-515
standards, 1036
surface reactions, 954-955
turbines, 319-321, 457, 1030-1031
Extreme pressure Timken method, lubricating greases, 566
- F**
- Failure, parameters controlling, 965-966
Falling needle, 868-869
Falling viscometer, 836
Fatigue wear, 933-936
Fat solubility, 820-821
Ferrite, 587
Ferrous corrosion inhibitors, 69
Film boiling, shock, steel, 599-602
Film-forming agents, 211-223
metalworking and machining fluids, 513-515
Filterability, hydraulic fluids, 367-368
Filter Bowl Compatibility Test, compressor lubricants, 410
Filters, diesel fuel system, 163-164
Filter-separators, 107-108
Fire point
Cleveland Open Cup, 692

- compressor lubricants, 398-399
- gear lubricants, 454
- quench oils, 609
- Tag Open cup, 693
- Fire-resistance tests, turbine lubricating oils and hydraulic fluids, 334-337
- Fire resistant fluids, hydraulic fluids, 375-377
- Fischer-Tropsch diesel fuels, 138
- Fischer-Tropsch process, 525-526
- Fish, toxicity tests, 902-903
- Fixed bed hydrocracking, 24
- Flame ionization detector, 653
- Flammability, 682, 690-696
 - aerospace fuels, 738
 - aviation fuels, 98-101
 - gasoline, 84
 - LPG, 52
 - see also* Fire point; Flash point
- Flash point
 - bias among test methods, 692
 - Cleveland Open Cup, 692
 - compressor lubricants, 398-399
 - continuously closed cup, 694
 - diesel fuel, 128-129
 - equilibrium method with closed cup, 693-694
 - fuel oils, 761
 - gear lubricants, 454
 - international test methods, 694-695
 - marine petroleum fuels, 150
 - Pensky-Martens Closed Cup Tester, 692-694
 - quench oils, 609
 - Setaflash Closed Cup, 693
 - small scale closed cup, 693
 - Tag Open cup, 693
 - test methods, 690-691
 - verification fluids, 691
- Flash temperatures, 941-942
- Fluorescent indicator adsorption, hydrocarbon analysis, 659
- Fluorinated basestocks, compressor lubricants, 395
- Flow properties, 833-875
 - ASTM procedures, 853-854
 - bulk material properties, 921-922, 925-926
 - flash temperatures, 941-942
 - high-temperature high-shear, 843-845
 - kinematic viscosity, 837-841
 - history, 841-843
 - temperature relationship, 854-856
 - low temperature tests, 851
 - lubricating greases, at high temperatures, 562
 - near surface structure, 919, 923
 - nomenclature, 833-835
 - non-petroleum materials, 867-872
 - pressure-viscosity coefficient, 916-920
 - standards, 072-875
 - sub-surface structure, 919-920, 924
 - surface conformity, 914-916
 - surface films, 919, 921-923
 - viscometer geometries, 835-836
 - wear maps, 942-945
 - wear surfaces, 911-913
 - see also* Cold flow properties; Viscosity
- Fluid biodeterioration, polymer quenchant, 620-621
- Fluid catalytic cracking, 9-12
 - yields, 11
- Fluid coking, 770
- Fluidized bed hydrocracking, 24-25
- Fluid oxidation, compressor lubricants, 400-401
- Foaming
 - automotive lubricants, 471
 - compressor lubricants, 398
 - gear lubricants, 456-457
 - hydraulic fluids, 366-367
 - turbine lubricating oils and hydraulic fluids, 332-334
- Foam inhibitors, *see* Antifoam additives
- Foam testing, polymer quenchant, 620
- Four ball extreme pressure test, 457, 1028-1029
 - compressor lubricants, 402
 - lubricating greases, 566-567
- Four ball tests, 1026-1027
- Four ball wear test, 457, 1027-1028
- Fourier transform infrared spectroscopy, 667
- Free water, 639-640, 646
 - in aviation fuels, 109-110
- Fretting wear, 567, 934-936
- Friction, 909-911
 - area of true contact, 909-911
 - due to adhesion, 911
 - due to deformation, 911
 - due to ploughing, 911-912
 - standards, 1035-1037
 - types of, 497
- Friction coefficient, 945
 - effect of hydrocarbon chain length, 954
- Friction modifiers, 211-213, 949, 951-952
 - gear lubricants, 441
- F-test, 1059-1060
- Fuel additives, marine petroleum fuels, 153-154
- Fuel-injection system, 115-116
- Fuel injector shear stability test, 852
 - standards, 875
- Fuel oils, 8, 757-762
 - API gravity, 758-759
 - ash, 761-762
 - carbon residue, 761
 - compatibility of blended, 762
 - distillation, 761
 - flash point, 761
 - heating value, 759-760
 - instability, 762
 - pour point, 761
 - specifications and applications, 757-759
 - sulfur content, 762
 - viscosity, 760-761
- Fuels, oxidation testing, 811, 813, 815-818

Fuel service heaters, diesel fuel system, 164
 Fuel treatment, gas turbine fuel system, 165-166
 Fuses, aviation fuels, 108
 FZG Gear Test Machine, 320, 322, 1033-1035
 compressor lubricants, 402-403
 FZG Pits C i80 TS, gear lubricants, 459
 FZG scuffing test, gear lubricants, 458
 FZG test, 362

G

Galling wear, 923, 929-930
 Galvanic corrosion, 932
 Gas chromatography
 hydrocarbon analysis, 652-657
 liquified petroleum gas, 40
 petroleum waxes composition, 549
 principles, 652-653
 Gas chromatography-mass spectrometry,
 hydrocarbon analysis, 664
 Gas compression cycle, 384-386
 Gas compressors, 386-389
 Gas hydrates, 44-46
 Gas laws, 383-384
 Gas line anti-freeze, 68
 Gasohol, blending with gasoline, 80, 82
 Gasoline, 7-8, 61-86
 additives, 68-70
 adiabatic flame temperature, 84
 autoignition temperature, 83-84
 aviation, 89, 91-92
 additives, 105
 combustion, 97
 history, 89-90
 knock resistance, 97
 low temperature, 94-95
 manufacturing, 103
 quality control, 107
 volatility and flammability, 98
 combustion, 70-77
 air-fuel ratio and stoichiometry, 71-72
 engine management systems, 71
 gasoline energy content, 72-73
 spark ignition engines, 70-71
 composition, 66-68
 conductivity, 85
 flammability, 84
 heat capacity, thermal conductivity, and heat of
 vaporization, 84
 heat of combustion, 84
 history, 61-66
 2004+ vehicle and fuel regulation, 66
 alkyl lead, 62
 Clean Air Act of 1963, 63
 Clean Air Act of 1970 and 1977 amendment, 64
 Clean Air Act Amendments of 1990, 65-66
 leaded gasoline, 61-62
 nonleaded gasoline, 63-64
 octane ratings, 62-63
 vapor controls, 64-65
 nonleaded, 63-64
 octane performance properties, 73-77
 anti-knock ratings, 73-74
 combustion and knock, 73
 motor octane number, 73-74
 octane distribution through fuel boiling range, 75
 octane number requirement, 75-78
 on-line analyzer octane rating, 74-75
 research octane rating, 74
 oxidation
 stability, 813, 815-817
 standards, 823
 testing, 811, 813, 815-818
 oxygenates in, 68
 performance additives, 69-70
 reformulated, 65-66
 specifications, *see* ASTM D 4814
 standards, 85-86
 static electricity, 85
 trace constituents and contaminants, 69
 vapor pressure, 699, 701
 viscosity and lubricity, 84-85
 Gasoline-oxygenate blends, vapor pressure, 699, 701
 Gas solubility
 compressor lubricants, 395-396, 406-408
 petroleum oils, 406-407
 Gas turbine engines, 115, 298-299
 development, 302-303
 lubrication system, 301-302
 Gas turbine fuels, 139-142
 requirements, 140-141
 standards, 142-143
 trace metal limits, 141-142
 see also Ryder gear
 Gas turbine fuel system, 165-166
 construction materials, 166-167
 Gearbox oils, *see* Ryder gear
 Gear contacts, performance maps and, 972-973
 Gear corrosion test, gear lubricants, 460
 Gear lubricants, 431-462, 481-483
 acid number, 456
 additives, 439-443, 447
 air release, 460
 antiwear agents, 440, 444
 API gravity, 456
 API service designation, 448-453
 base number, 458
 channel point FTM, 459
 chlorine level, 457
 cold crank simulator, 458
 compatibility, 460
 compounded, 439
 Copper Strip Tarnish Test, 454, 456
 corrosion inhibitors, 441
 cyclic durability test, 458

demulsibility, 457-458
 demulsifiers, 441
 detergents, 440, 444
 dispersants, 440-441, 445
 dynamic seals test, 460
 early, 431-432
 elemental content, 458
 emulsifiers, 441-442
 extreme pressure, 439
 oxidation, 458
 extreme pressure agents, 440, 444
 fire point, 454
 flash point, 454
 foam characteristics, 456-457
 foam inhibitors, 441
 four ball EP, 457
 four ball wear, 457
 friction modifiers, 441
 function, 431
 future trends, 460-461
 FZG Pits C i80 TS, 459
 FZG scuffing test, 458
 gear corrosion test, 460
 gear scoring test, 459-460
 GFC oxidation, 459
 greases, 439
 high temperature foam inhibition, 459
 insolubles in used oils, 457
 kinematic viscosity, 456
 low speed high torque hypoid test, 459
 low temperature Brookfield viscosity, 458
 MIL-PRF-2105E, 451-452
 nitrogen level, 458
 OEM specifications, 451, 453
 open gear compounds, 439
 oxidation inhibitors, 441, 445
 phosphorus level, 457
 polymeric thickeners, 441-442
 pour point, 454
 pour point depressants, 441
 precipitation number, 453
 rust and oxidation inhibited, 439
 rust inhibition, 456
 Ryder gear test conditions, 988-990
 SAE 3306 viscosity classification, 449-451
 scuffing
 front, propagation, 992-993
 initiation, 990-992
 seal compatibility, 459
 shear stability, 459
 standards, 461-462, 493
 standard tests, 482-483
 storage solubility, 460
 sulfur level, 457
 synchronizer SSP 180 test, 459
 systematic tribology, 988-996
 thermal and oxidation test, 458

Timken EP Tester, 457
 tribological features, microscopic examination, 991-992
 tribological processes, 993-996
 types, 437, 439
 viscosity index, 457
 water content, 457
 Gear oils
 corrosion tests, 829
 oxidation, standards, 822
 oxidation testing, 802-804
 performance testing, 239-240
 Gears
 failure modes, 434-436
 lubrication, 434, 436-438
 types, 432-434
 Gear scoring test, gear lubricants, 459-460
 Gear testing, aviation gas turbine oil, 988
 GFC oxidation, gear lubricants, 459
 Glass capillary vacuum viscometers, 870-871
 Gloss retention, petroleum waxes, 549
 GM quenchometer cooling times, 604-606
 Graphic electrodes, for electric-arc furnaces, 782
 Graphite furnace atomic absorption spectrometry, elemental analysis, 709-711
 Greases, *see* Lubricating greases
 Grossmann hardenability, 592-593
 Gum content, gasolines and fuels, 811, 813, 815

H

Halocarbons, in LPG, 50
 Hardenability, steel, 589-591
 measurement, 591-593
 Hardness, petroleum waxes, 547-548
 Hazard, environmental characteristics, 904
 Health effects, LPG exposure, 54-55
 Health issues, aerospace fuels handling, 747
 Heat capacity, gasoline, 84
 Heat content, diesel fuel, 132-134
 Heating value
 fuel oils, 759-760
 marine petroleum fuels, 149-150
 Heat of adsorption, wear reduction and, 954
 Heat of combustion, 72
 diesel fuel, 132-134
 gasoline, 84
 Heat of vaporization, gasoline, 84
 Heat resistance, lubricating greases, 563-565
 Heat transfer
 efficiency, compressor lubricants, 408-409
 hydraulic fluids, 353-354
 Heat transfer coefficient, 573-575
 Heat transfer fluids, *see* Mineral oil heat transfer fluids
 Heat transfer fluid system, design and construction, 583-584
 HEES fluids, 377
 Henry's Law Constant, 888
 HEPG fluids, 378
 HEPR type fluids, 378

- Hertzian contact, 914, 946-949, 965-966
 Heteroatom, removal, 17-20
 HETG fluids, 377
 HFA fluids, 375-376
 HFB fluids, 376
 HFC fluids, 376
 HFD fluids, 376-377
 High frequency reciprocating rig, 129, 131
 High Pressure Differential Scanning Calorimetry, 258
 High-shear
 high-temperature, 843-845
 low-temperature, lubricants, 846-848
 High temperature copper-lead bearing wear, 470
 High temperature foam inhibition, gear lubricants, 459
 High temperature stability, distillate fuels, 817-818
 Hindered phenols, oxidation inhibition, 794
¹H NMR spectroscopy, hydrocarbon analysis, 651
 Homogenizer, diesel fuel system, 165
 Hot surface tests, turbine lubricating oils and hydraulic fluids, 335
 Hot tack, petroleum waxes, 552
 HSR, 3
 HVAC cycle, refrigeration lubricants, 424-426
 Hydraulic fluids, 353-379
 aeration and foam, 366-367
 antifoam additives, 367
 antioxidants, 356-358
 antiwear and extreme pressure additives, 363
 antiwear performance testing, 361-364
 automatic transmission fluids, 374
 boundary conditions, 360-361
 coolant separability, 370-371
 corrosion inhibitors, 369-370
 corrosion protection, 368-370
 demulsibility, 366
 detergents, 358
 dispersants, 358
 engine oils, 374
 environmentally acceptable, 377-378
 filterability, 367-368
 fire-resistant, 301-302, 375-377
 frictional properties, 212-213
 heat transfer, 353-354
 hydrolytic stability testing, 365-366
 low temperature pumpability, 372-373
 lubrication, 353
 machine builder specifications, 364
 metal passivators, 369-370
 mineral oils, 374-375
 oxidation
 stability, 355-359, 801
 standards, 822
 tests, 356-357
 performance testing, 240-241
 petroleum base stocks, 355
 pour point depressants, 373
 power transfer, 353-354
 rust inhibitors, 369-370
 seal compatibility, 370
 shear stability, 371-372
 standards, 378-379
 thermal stability, 355-359
 tractor fluids, 374
 trends, 353-355
 types, 268-269
 viscosity, 359-360
 viscosity index improvers, 371-372
 water content, 363, 365
 wear protection, 359-364
 see also Pressure media
 Hydraulic oils
 oxidation characteristics, 797-798
 thermal stability, 799-800, 830
 Hydrocarbon analysis, 649-672
 ¹³C NMR spectrometry, 650-651
 fluorescent indicator adsorption, 659
 gas chromatography, 652-657
 gas chromatography-mass spectrometry, 664
 infrared spectroscopy, 668-670
 liquid chromatography, 657-660
 mass spectrometry, 664-665
 NMR spectroscopy, 649-652
 standards, 671-672
 super critical fluid chromatography, 659-660
 ultraviolet spectroscopy, 661-662
 Hydrocarbon base oil, 169-183
 biodegradability, 182
 biological properties, 181-182
 composition/performance correlations, 178-179
 effects in industrial lubricants, 179-180
 hydrocarbon type analysis, 172-173
 impact of sulfur compounds on chemistry, 176-177
 market, 169-170
 molecular structures, 174-175
 naphthenic vs. paraffinic, 172
 nitrogen compound reactivity, 177-178
 NMR spectroscopy, 174-175
 olefins, 178
 oxidation, 175-176
 refining and processing technology, 170-172
 refining capacity, United States, 169-170
 rheology and composition, 178
 rubber compatibility, 181
 solvency effects, 181
 spectrometric identification components, 173-174
 standards, 182-183
 structures with high susceptibility to oxidation, 788
 viscosity-pressure coefficient composition effect, 180-181
 Hydrocarbon oils, turbines, 305-306
 Hydrocarbon-oxygenate mixtures, vapor pressure, 702-703
 Hydrocarbons
 crude oil composition, 6
 in gasoline, 66-67
 physical adsorption, 921

- terminology, 5-6
 - see also* Synthetic hydrocarbons
 - Hydrocracked basestocks, turbines, 307-308
 - Hydrocracking
 - fixed bed, 24
 - fluidized bed, 24-25
 - hydrocarbon base oil, 171
 - Hydrodynamic film region, 963
 - Hydrodynamic lubrication, 214, 413, 498, 949
 - Hydrofinishing hydrocarbon base oil, 172
 - Hydrogen
 - in petroleum fractions, 195
 - classification in organic molecules, 788
 - Hydrogen production, 25-26
 - Hydrogen refining, hydrocarbon base oil, 171
 - Hydrolysis
 - environmental characteristics, 889-890
 - environmentally friendly oils, 274
 - pressure media, 279-281
 - Hydrolytic stability
 - compressor lubricants, 398
 - diesters, 251-252
 - polyolesters, 251-252
 - pressure media
 - laboratory aging, 285-287
 - test stand aging, 287-289
 - turbine lubricating oils and hydraulic fluids, 339-340
 - Hydrolytic stability testing, hydraulic fluids, 365-366
 - Hydroperoxide
 - decomposers, 791-792
 - decomposition, 790, 793
 - oxidation rate and, 790
 - Hydroprocessing
 - options, 19
 - terminology, 18
 - Hydrostatic tank gauges, 645
 - Hydrotreated basestocks, turbines, 307-308
 - Hyfinishing, hydrocarbon base oil, 172
- I**
- I-Chart, 1055-1056
 - Icing, in LPG systems, 45
 - Ideal Gas Law, 383
 - Ignition quality, marine petroleum fuels, 149-150
 - Indiana Stirring Oxidation Test, compressor lubricants, 401
 - Induction Period Method, 813, 815-817
 - Inductively coupled plasma-atomic emission spectrometry, elemental analysis, 711-712
 - Inductively coupled plasma-mass spectrometry, elemental analysis, 712
 - Industrial gear lubricants, 453-456
 - performance testing, 240
 - Industrial hydraulic fluids, performance testing, 241
 - Industrial lubricants, base oil effects, 179-180
 - Infrared spectroscopy, 665-671
 - achieving reproducible baselines, 668
 - analysis of multicomponent solutions, 667-668
 - band area methods, 668
 - Beer-Lambert law, 667
 - compressor lubricants, 400-401
 - difference method, 668
 - dispersive-type infrared spectrometers, 667
 - Fourier transform, 667
 - gas analysis, 668
 - hydrocarbon analysis, 668-670
 - inorganic characterization, 670-671
 - quench oils, 610
 - standards, 671
 - wavelength, wavenumber and frequency, 666-667
 - Inhibitor content, determination, 194
 - Inorganic/organic solids, metalworking and machining fluids, 519
 - Insolubles, in used oils, 457
 - Instability, fuel oils, 762
 - Insulation fires, mineral oil heat transfer fluids, 583
 - International Harvester oxidation corrosion, 811
 - Invertebrates
 - acute toxicity tests, 902
 - chronic and subchronic toxicity tests, 903
 - Ion chromatography, elemental analysis, 712
 - Iron based organo-metallics, in gasoline, 69
 - Iron carboxylate, oxidation rate and, 790
 - Iron chip corrosion, metalworking fluids, 831
 - Iron corrosion, compressor lubricants, 398
 - Isomerization, 14, 16
 - Iso-propanol, in propane, 47
 - Isothermal operation, 384
 - Isothermal transformation diagrams, 589
- J**
- Jet fuel, 8, 92-93
 - additives, 104-105
 - combustion, 97-98
 - history, 89, 91
 - low temperature, 93-94
 - manufacturing, 103-104
 - product color, 109
 - quality control, 107
 - Smoke Point, 98
 - visual appearance, 109
 - volatility and flammability, 98-101
 - Jet Fuel Thermal Oxidation Tester, 96, 815-816
 - Jominy bar end-quench test, 591-592
 - Joule-Thomson cooling, 46
- K**
- Karl Fisher Titration Test, 365
 - Kerosine, 3
 - Kinematic viscosity, 837-841
 - compressor lubricants, 396-397
 - gear lubricants, 456
 - history, 841-843
 - quench oils, 608-609
 - standards, 875

temperature relationship, 854-856
Kinetic coefficient of friction, 909

L

Laboratory aging

hydrolysis stability, 285-287
oxidation stability, 281-283

Lambda values, 912-913

Lattice transition, alkanes, 534

Lead corrosion, 221

Leakage, lubricating greases, from wheel bearings, 565

Leidenfrost temperature, 593

"Liedenfrost effect", 53

Light hydrocarbons

high temperature vapor pressure, 32
low-temperature vapor pressures, 33

Linear reciprocation, 1031-1033

Liquid chromatography

fluorescent indicator adsorption, 659
hydrocarbon analysis, 657-660
principles, 657-658
standards, 660
super critical fluid chromatography, 659-660

Liquid Heptane Washing Test, compressor lubricants, 401-402

Liquified petroleum gas, 31-56

auto propane, 51-52
exposure, 54-55
flammability, 52
gas hydrates, 44-46
handling, 52-54
history, 31-32, 35-38
industry, 32, 35
use, 35-37

odorization, 55

properties and thermodynamics, history, 37-38

sample cylinder approvals, 54

specifications, 38-50

composition, 40

contaminants, 49-50

density, 40

dryness of propane, 42-49

history of ASTM standards, 38-39

naturally occurring radioactive materials, 50

octane, 40

olefins, 40-41

residual matter, 49

sampling, 39-40

sulfur content, 49

vapor pressure, 40-42

volatility residue, 42

uses, 56

vapor, 53

vapor pressure, 703-704

volume correction factors, 50-51

water in, 47-49

LISCIC/NANMAC quench probe, 623-625

Lithium soap greases, 559

Low speed high torque hypoid test, gear lubricants, 459

Low temperature Brookfield viscosity, gear lubricants, 458

Low-temperature flow test, diesel fuel, 123

Low-temperature high-shear tests, lubricants, 882

Low temperature properties

diesters and polyolesters, 251

environmentally friendly oils, 289-291

Low temperature pumpability

hydraulic fluids, 372-373

lubricants, 882

Low temperature storage stability, turbine lubricating oils and hydraulic fluids, 329

Low-temperature torque, lubricating greases, 563

LPG injector systems, 52

LSR, 3

Lube oil base stock production, 25

Lubricant base oil, market, 169-170

Lubricants

basestocks, 199-200

category chronology, 853

composition, 199

corrosion tests, 827-831

function, 413

high-temperature degradation model, 791

low-temperature high-shear tests, 846-848, 882

low temperature pumpability, 848-851, 882

low temperature requirements, 845-848

oxidation

standards, 823

testing, 818-821

quality ranking, 915-916

Lubricating greases, 439, 478-481, 557-572

accelerated corrosion tests, 568

aluminum soap, 558

apparent viscosity, 562-563

in ball bearings at elevated temperatures, 565-566

black penetration, 561

bomb oxidation test, 565

calcium soap, 558-559

chemical analysis, 569

chemical properties, 478-479

classification, 560

compatibility of blends, 569

complex soap, 559

composition, 557-558

cone penetration, 561

consistency, 560-561

consistency stability, 561-562

contamination, 568-569

copper corrosion, 567-568

corrosion tests, 831-832

dropping point, 563-564

elastomer compatibility, 569

evaporation loss, 564

extreme pressure four-ball test, 566-567

extreme pressure Timken method, 566

flow properties, at high temperatures, 562
 fretting wear, 567
 heat resistance, 563-565
 leakage from steel bearings, 565
 lithium soap, 559
 low-temperature torque, 563
 NLGI consistency numbers, 561
 oil separation, 564-565
 organo-clay, 560
 oscillating motion, 567
 oscillating wear test, 567
 oxidation
 induction time, 806-807
 stability, 565-566
 standards, 823
 testing, 804-807
 PDSC oxidation test, 565
 performance, 480-481
 performance testing, 242
 polyurea, 559-560
 roll stability, 562
 rust prevention, 568
 selection, 558
 in small bearings, 566
 sodium soap, 559
 specifications, 560
 standards, 570-572
 discontinued, 570
 under development, 570
 static bleed test, 569
 viscosity, 479-480
 water spray-off, 568
 water washout, 568
 wear preventive characteristics, 567
 wheel bearing grease life, 566
 Lubricating oil
 additives, 952
 extreme pressure, oxidation testing, 802
 oxidation induction time, 818
 Lubrication, 497-500, 909-957
 boundary, 949
 elastohydrodynamic, 947-949
 friction, 909-911
 friction modifiers, 949, 951-952
 Hertzian contact, 946-949
 hydraulic fluids, 353
 hydrodynamic, 949
 parameters controlling, 965-966
 performance, turbine lubricating oils and hydraulic fluids,
 341-342
 Petroff's law, 949
 regions, thermal considerations, 970
 standards, 957
 synthetic lubricants, 261-262
 types, 214
 Lubricity
 aerospace fuels, 744-745

aviation fuels, 102-103
 diesel fuel, 129-131
 gasoline, 85
 Lubricity additives, 69
 Luminometer, 98

M

MacCoul equation, 854
 MacCoul-Walther equation, 919
 Macroemulsions, metalworking and machining fluids, 503
 Magnetic quenchometer method, quench oils, 614-615
 Magnetic residues, LPG, 49-50
 Manifold, air temperature and pressure, octane number
 requirement and, 76
 Mannich products, synthesis, 206-207
 Marine petroleum fuels, 145-167
 ash, 150
 ash modifiers, 154
 biocides, 154
 carbon residue, 151-152
 cat fines, 150
 compatibility, 152
 demulsifiers, 154
 density, 149
 diesel plant fuel system, 161-162
 environmental considerations, 156
 flash point, 150
 fuel additives, 153-154
 heating value, 149-150
 ignition quality, 149-150
 impact on exhaust emissions, 154
 on board testing, 157
 oxidation, 152
 pour point, 150
 sampling, 156
 sediment, 152-153
 shore side analysis, 156
 sodium in, 152-153
 specifications, 154-156
 stabilizers and dispersants, 153
 standards, 167
 steam plant fuel service system, 157, 161
 storage systems, 157-160
 sulfur, 151
 toxicity, 154
 transfer systems, 157
 vanadium and nickel in, 152
 viscosity, 148-149
 water in, 151
 Marine transport, aviation fuels, 105-106
 Mass spectrometry, 662-665
 hydrocarbon analysis, 664-665
 instrumentation, 663-664
 standards, 665
 theory, 662-663
 Master chart, aviation gas turbine oils, 1012, 1014
 McMillan/Murphy pumpability apparatus, 848

- Measurement process
 - bias, 1044-1045
 - manufacturing process control, 1043
 - precision, 1044-1045
 - product property conformance to specification, 1043-1044
 - self-monitoring, 1044
 - see also* Quality assurance
- Melting point, petroleum waxes, 542-545
- Mercaptan odorants, 55
- Metal content, mineral oil heat transfer fluids, 580-581
- Metal deactivators, 795-796
- Metal forming fluids, 509, 520
- Metal passivators, 319-320, 369-370
- Metal preservatives, 830
- Metal protecting fluids, 510
- Metal ratio, 208
- Metal removal fluids, 505-509, 519
- Metals
 - crude oil, 6
 - oxidation potentials, 220
 - significance in petroleum products, 707-708
- Metal treating fluids, 510
- Metalworking and machining fluids, 234, 497-524
 - additives, 511-519
 - alkalinity agents, 516
 - antimicrobial agents, 517-518
 - anti-misting agents, 516
 - corrosion inhibitors, 516-517
 - coupling agents, 513
 - dispersants, 516
 - dyes, 519
 - emulsion promoters, 512-513
 - film-forming agents, 513-515
 - foam inhibitors, 518-519
 - inorganic/organic solids, 519
 - odor control agents, 519
 - base fluid, 510-511
 - classification based on end-use, 505-510
 - formulations, 519-521
 - metal forming fluids, 509
 - metal protecting fluids, 510
 - metal treating fluids, 510
 - oil-based, 501
 - performance testing, 241
 - semisynthetic fluids, 504-505
 - slideway lubricants, 510
 - solid dispersions, 505
 - soluble oils, 503
 - synthetic fluids, 503-504
 - tests, 521-523
 - used, recycling, 521-522, 524
 - water-based, 501-503
 - classification, 503-505
- Metering, aviation fuels, 99-100
- Methane, structure, 732
- Methanol
 - in propane, phase behavior, 46-47
 - in propylene, 193
- Methylcyclopentadienyl manganese tricarbonyl, in gasoline, 68-69
- Micellar solutions, metalworking and machining fluids, 501-502
- Micro-elastohydrodynamic lubrication, 948-949
- Microelemental analysis methods, 712
- Microemulsions, metalworking and machining fluids, 504-505
- Microfilters, 109
- "Micro Method" for carbon residue, compressor lubricants, 399
- Micronic filters prefilters, 109
- Microorganisms, in aviation fuels, 110
- Micropitting, 434-435, 977, 979
- Micro-scuffing
 - engine oil performance, 1009-1010
 - failure criteria, 1001
- Military fuel specifications, marine petroleum fuels, 155-156
- MIL-PRF-2105E, gear lubricants, 451-452
- MIL-PRF-7808 oils, 1012-1013
- MIL-PRF-23699 oils, 1011
- Mineral gas turbine oils, 317-318
- Mineral oil heat transfer fluids, 573-585
 - acid number, 582
 - autoignition, 581
 - carbon residue, 580
 - classification, 575
 - composition, 575-578
 - distillation, 582
 - elastomeric seal compatibility, 581
 - fluid maintenance, 581
 - metal content, 580-581
 - oxidative stability, 580
 - physical properties, 578-581
 - pumpability, 579
 - safety, 583
 - sampling, 581-583
 - specific gravity, 580
 - specific heat, 581
 - standards, 584-585
 - thermal conductivity, 581
 - thermal stability, 579-580
 - viscosity, 579, 582-583
 - water content, 583
- Mineral oils
 - aero-engine lubricants, 301
 - compressor lubricants, 392
 - hydraulic fluids, 374-375
 - inhibited
 - oxidation characteristics, 797-798
 - oxidation stability, 798-799
 - rust-preventing characteristics, 829-830
 - sludging and corrosion tendencies, 798, 830-831
 - metalworking and machining fluids, 501

- organic structures, 576
 - refrigeration lubricants, 414-415
 - Mini-rotary viscometer, 849-850
 - Mixed-film lubrication, 214
 - Modified Ostwald viscometers, 838-841
 - Monitors, aviation fuels, 108
 - Motor gasoline, *see* Gasoline
 - Motor octane number, 73-74
 - MR-Chart, 1056
 - MTBE, 16-17, 66
 - Multi-specimen test machine, 1030-1031
- N**
- Naphthenic base oils, 172
 - Naphthenic hydrocarbon fractions, 527
 - Naphthene, determination, 195
 - Natural gas liquids volume correlation factors, 50-51
 - Natural Gasoline Association of America, 37
 - Naturally occurring radioactive materials, in LPG, 50
 - Near-surface region, 964
 - Neutron activation analysis, elemental analysis, 712-713
 - Nickel content, 152, 775
 - Nitrogen, crude oil, 6
 - Nitrogen compound reactivity, hydrocarbon base oil, 177-178
 - Nitrogen level, gear lubricants, 458
 - NLGI consistency numbers, 561
 - Nonleaded gasoline, 63-64
 - Non-lubricating process fluids, 587-632
 - aqueous polymer quenchants, 605-606
 - standards, 630-632
 - temperature gradient quenchant analysis, 623-629
 - see also* Quench oils
 - Non-petroleum materials using ASTM flow properties, 867-872
 - Normality checks, 1052-1055
 - NO_x, Clean Air Act, 64
 - Nuclear magnetic resonance spectroscopy
 - hydrocarbon analysis, 649-652
 - hydrocarbon base oil, 174-175
 - principles, 649-650
 - standards, 651-652
- O**
- Occupational exposure limits, LPG, 54
 - Octane
 - distribution throughout fuel boiling range, 75
 - liquified petroleum gas, 40
 - Octane number requirement, 75-78
 - air-fuel ratio, 76
 - compression ratio, 76
 - effect of engine deposits, 77
 - engine design parameters, 76
 - engine spark timing, 76-77
 - manifold air temperature and pressure, 76
 - Octane rating, history, 62-63
 - Octane rating analyzers, on-line, 74-75
 - Octanol/water partition coefficient, 887
 - Odor, petroleum waxes, 549, 551
 - Odor control agents, metalworking and machining fluids, 519
 - Odorization, LPG, 55
 - OEM specifications, gear lubricants, 451, 453
 - Oil blending calculations, 856
 - Oil content, petroleum waxes, 546
 - Oil film wash-oil resistance, compressor lubricants, 401-402
 - Oil-off testing, 982-983
 - Oil separation, lubricating greases, 564-565
 - Oil-soluble dye, in gasoline, 69
 - Oil stability index, 821
 - Oil stain, LPG, 49
 - Olefin
 - saturation, 17-20
 - sulfurization, 216
 - Olefin-based polymers, 224-226
 - Olefin content, 28
 - hydrocarbon base oil, 178
 - liquified petroleum gas, 40-41
 - Optical texture, petroleum coke, 775-776
 - Organo-clay greases, 560
 - Organo-metallics, iron based, in gasoline, 69
 - Orifice viscometers, 864-865
 - Oscillating motion, lubricating greases, 567
 - Oscillating wear test, lubricating greases, 567
 - Oxidation, 787-823
 - automotive lubricants, 476-477
 - aviation fuels, standards, 823
 - biodegradable lubricants, standards, 823
 - engine oils, standards, 823
 - extreme pressure oils, 458
 - gasolines, standards, 823
 - gear oils, standards, 822
 - grease, standards, 823
 - hydraulic fluids, standards, 822
 - hydrocarbon base oil, 175-176
 - hydroperoxide decomposers, 791-792
 - lubricants, 787-796
 - standards, 823
 - marine petroleum fuels, 152
 - mechanism, 789
 - pressure media, 277, 279
 - radical scavengers, 791-792
 - role of metal ions, 793-794
 - turbine oils, standards, 822
 - Oxidational wear, 933
 - Oxidation heat release, 752-753
 - aerospace fuels, 735
 - Oxidation induction time, lubricating oils, 818
 - Oxidation inhibitors, *see* Antioxidants
 - Oxidation potentials, metals, 220
 - Oxidation stability
 - ASTM D 4814, 82-83
 - automotive gear oils, 803-804
 - automotive transmission fluids, 804

aviation fuels, 813
 diesel fuel, 126-127
 distillate fuel oil, 816-817
 environmentally friendly oils, 274-275
 gasoline, 813, 815-817
 lubricating greases, 565-566
 mineral oil heat transfer fluids, 580
 pressure media, 281-284
 laboratory aging, 281-283
 test stand aging, 282-284
 synthetic lubricants, 258, 260-261
 turbine lubricating oils and hydraulic fluids, 338-339
 Oxidation Stability test, aviation fuels, 102
 Oxidation testing, 315, 317, 796-822
 antiwear, 797-798
 biodegradable lubricants, 820-822
 engine oils, 807-811
 fuels, 811, 813, 815-818
 gasolines, 811, 813, 815-818
 gear oils, 802-804
 grease, 804-807
 hydraulic fluids, 356-357
 lubricants, 818-821
 purpose of testing, 796
 using universal glassware, 802-803
 Oxygen, crude oil, 6-7
 Oxygenated polymer, formation, 790
 Oxygenates, 7, 29
 addition to gasoline, 65-66
 in gasoline, 68

P

Paddle type rotational viscometer, 835-836
 Paint Compatibility Test, compressor lubricants, 409-410
 Paints, flow-related instruments, 867
 Panel Coker Test, 818-819
 Paraffin, determination, 195
 Paraffinic base oils, 172
 Paraffinic hydrocarbon fractions, 527
 Partial least squares modeling, 179
 Partial oxidation, 26
 Particulate emissions, diesel engines, 720
 Particulates, in LPG, 49-50
 PDSC oxidation test, lubricating greases, 565
 Pearlite, 587
 Peng-Robinson Equation of State, 81
 Penn State micro-oxidation test apparatus, 807
 Pensky-Martens Closed Cup Tester, 692-694
 Perfluoroalkyl ethers, 259
 Performance additives, gasoline, 69-70
 Performance maps, 945, 968-969
 bearing and gear contacts and, 972-973
 generalized, 987-988
 lubrication attributes, 967
 wear and traction within, 968, 970
 Performance package, 235
 Performance testing, *see* Additives

Permanent shear stability index, 853
 Peroxide number, petroleum waxes, 549
 Peroxides, in butadiene, 193-194
 Petroff's law, 949
 Petroleum coke, 768-778
 ash, 775
 classification, 773
 crystalline structure, 775-776
 density, 775
 feedstocks, 772
 microtexture formation, 770-772
 optical texture, 775-776
 production processes, 768-770
 properties, 773-774
 reactivity, 778
 standards, 783-784
 sulfur content, 775
 thermal expansion, 777
 trace metals contents, 775
 volatile matter, 774-775
 Petroleum fractions, hydrogen in, 195
 Petroleum gas, sulfur content, 194-195
 Petroleum industry, history, 145
 Petroleum oil, 3-29
 classification, 576
 alkylation, 15-17
 capacity as percent of crude, 5
 catalytic reforming, 12-15
 cogeneration, 28
 crude oil, 6-7
 preparation and separation, 9-10
 fluid catalytic cracking, 9-12
 future, 28-29
 gas solubility in, 406-407
 heteroatom removal and aromatic/olefin saturation, 17-20
 hydrogen production, 25-26
 isomerization, 14, 16
 lube oil base stock production, 25
 MTBE, 16-17
 pollution control, 27-28
 product blending, 28
 products, 7-9
 refinery flow plan, 3-5
 resid conversion and upgrading, 20-25
 sulfur recovery, 26-27
 Petroleum pitch, 763-768
 ash, 768
 carbon fibers, 781
 coking value, 767-768
 density, 768
 production processes and applications, 763
 properties, 763-764
 softening point, 764
 solvent fractionation, 765-767
 standards, 783-784
 sulfur content, 768
 viscosity, 764-765

- Petroleum waxes, 525-555
 - additive effect, 542
 - blocking point, 552-553
 - carbonizable substances, 549
 - cloud point, 545-546
 - coefficient of kinetic friction, 552, 554
 - color, 549-551
 - composition, gas chromatography, 549
 - compositional and molecular characteristics, 531-533
 - congealing point, 545
 - crystal structure, 533-535
 - dewaxing process variables, 530-531
 - differential scanning calorimetry, 539-542
 - equations of state, 535-539
 - gloss retention, 549
 - hardness, 547-548
 - hot tack, 552
 - melting point, 542-545
 - odor, 549, 551
 - oil content, 546
 - peroxide number, 549
 - physical properties, 533
 - pour point, 545
 - solvent dewaxing process, 529-530
 - solvent solubility, 546
 - specular gloss, 549, 552
 - standards, 554-555
 - surface wax, 549, 551
 - total wax content, 552
 - transition temperatures, differential scanning calorimetry, 548
 - types of, 531
 - viscosity, 546-547
 - wax finishing process, 531
 - weight of wax applied during coating, 552
- pH determination, polymer quenchant, 617-618
- Philippoff rotary viscometer, 849
- Phosphate esters, compressor lubricants, 395
- Phosphonic acid dispersants, synthesis, 206-207
- Phosphorus content
 - ASTM D 4814, 82
 - automotive lubricants, 471
 - gear lubricants, 457
- Photolysis, environmental characteristics, 890
- Photooxidation, environmental characteristics, 890
- Pin and Vee Block tester, 1025-1026
- Pin-on-Disk test, 1026
- Pitting, 434
- Pipelines, aviation fuels, 105
- Plants, toxicity tests, 903
- Plastics, viscosity, 869-870
- Plate-to-plate geometry, 835
- Ploughing, friction due to, 911-912
- Polar additives, adsorption on metal surface, 211-212
- Polishing wear, 923, 929
- Pollution control, petroleum oil refining, 27-28
- Polyalkylene glycols, 252-256
 - application and performance characteristics, 255-256
 - chemical characteristics, 254-255
 - chemistry, 253
 - compressor lubricants, 392-393
 - physical properties, 254
 - refrigeration lubricants, 417-418
 - synthesis, 253-254
- Polyalphaolefins, 257-258
 - compressor lubricants, 393-394
 - refrigeration lubricants, 415-416
 - for turbines, 308-309
- Poly(ethylene) waxes, 525
- Polymer, viscosity, 869
 - loss due to degradation, 228-230
- Polymer-containing oils, shear stability, 851-853
- Polymeric additives, 223-233
- Polymeric thickeners, gear lubricants, 441-442
- Polymer molecular weight analysis, polymer quenchant, 620
- Polymer quenchant
 - appearance, 616
 - biological stability, 620-623
 - cloud point, 619
 - conductance, 618-619
 - cooling curve analysis, 621-623
 - corrosion inhibitor, 619-620
 - fluid biodeterioration, 620-621
 - foam testing, 620
 - pH determination, 617-618
 - polymer molecular weight analysis, 620
 - refractive index, 616-617
 - viscosity, 617-618
 - water content, 617
- Polyolesters, 249-252
 - application and performance characteristics, 252
 - biodegradability, 252
 - chemical characteristics, 251
 - chemistry and manufacturing, 249-251
 - manufacturing technology, 250-251
 - physical properties, 251
 - refrigeration lubricants, 416-417
- Polyphenyl ethers, 259-260
- Polyurea greases, 559-560
- Polyvinylethers, refrigeration lubricants, 418
- Potential Residue Method, 815
- Pour point, 879-880
 - compressor lubricants, 397
 - diesel fuel, 122-123
 - effect of double bonds, 273
 - esters, 273
 - fuel oils, 761
 - gear lubricants, 454
 - marine petroleum fuels, 150
 - petroleum waxes, 545
 - standards, 874
 - turbine lubricating oils and hydraulic fluids, 329
- Pour point depressants, 205, 230-232

gear lubricants, 441
 hydraulic fluids, 373
 Power transfer, hydraulic fluids, 353-354
 Power transmission fluids, performance testing, 239
 Precipitation number
 compressor lubricants, 399-400
 gear lubricants, 453
 quench oils, 613-614
 Precision
 measurement process, 1044-1045
 monitoring, 1045-1047
 Pressure differential scanning calorimetry, 806, 818
 Pressure drop, 574-576
 Pressure media, 267
 hydrolysis, 279-281
 hydrolysis stability, aging, 285-289
 oxidation, 277, 279
 oxidation stability, aging, 281-284
 type, 268-269
 see also Hydraulic fluids
 Pressure-viscosity coefficient, 916-920, 985-987
 Propane
 auto, 51-52
 depressurized, 46
 dryness, 42-49
 auto-refrigeration, 46
 dissolved water, phase of behavior, 43-44
 gas hydrates, 44-46
 methanol, phase behavior, 46-47
 water measurement, 47-49
 water sources, 47
 liquid, 53
 phase behavior of dissolved water in, 43-44
 Propane deasphalting, hydrocarbon base oil, 171
 Propane hydrates, 45
 Propane P-H diagram, 34
 Propylene
 characterization, 192-193
 production, 190
 Pumpability
 low temperature, lubricants, 848-851
 mineral oil heat transfer fluids, 579
 PV curves, 384

Q

Quality assurance, 1043-1060
 approximate *F*-test, 1059-1060
 ARV assignment, 1048
 batch change of material, 1047
 check standard composition, 1048
 chi-square test, 1059
 control chart, 1055-1056
 data treatment, 1046-1047
 estimate process precision and bias, 1048
 EWMA overlay, 1056
 implementation aspects, 1049
 interlaboratory exchange testing, 1049

 material selection, preparation and storage, 1046
 material testing, 1046
 monitoring bias, 1047-1048
 monitoring stability and precision, 1045-1047
 MR-Chart, 1056
 normality checks, 1052-1055
 run chart, 1051-1052
 standards, 1050
 statistical tools, 1050-1051
 system validation, 1049
 t-test, 1058-1059
 Quality control
 aviation fuels, *see* Aviation fuels
 airport, 110-111
 elemental analysis, 716
 Quench oils, 602-605
 acid number, 609-610
 ash content, 614
 carbon residue, 611-613
 contamination, 610-614
 fire and flash points, 609
 infra-red spectroscopy, 610
 kinematic viscosity, 608-609
 magnetic quenchemeter method, 614-615
 precipitation number, 613-614
 properties, 604
 saponification number, 610
 specific gravity, 609
 water content, 610-611

R

Rabinowitz abrasive wear model, 930
 Radical scavengers, 791-792
 Rail transport, aviation fuels, 106
 Ramsbottom carbon residue, compressor lubricants, 399
 RBOT test, 315-316
 compressor lubricants, 401
 Reaction temperature, maximum, 754-756
 Reactivity, petroleum coke, 778
 Reavell VHP 15 Compressor Rig Test, 403
 Reciprocating compressors, 386-388
 Recycling, used lubricants, 521-522, 524
 Redlich-Kwong equation, 536
 Reference gauge point, 636
 Reformulated gasoline, 65-66
 Refractive index, polymer quenchants, 616-617
 Refrigeration lubricants, 413-429
 acid catchers, 419
 additives, 418-420
 alkylbenzene, 415
 antifoaming agents, 419-420
 antioxidants, 419
 antiwear additives, 419
 chemical structure, 414-418
 choice, 413-414
 circulation, 424-428
 density, 421

- dibasic acid esters, 416
 - equipment line sizing, 426
 - HVAC cycle, 424-426
 - mineral oils, 414-415
 - performance effects, 428
 - polyalkylene glycols, 417-418
 - polyalphaolefins, 415-416
 - polyolesters, 416-417
 - polyvinylethers, 418
 - properties, 415, 420
 - selection, 426-427
 - solubility, 422-424
 - standards, 428-429
 - system operational envelope, 427
 - viscosity, 420-422
 - Reid method, 698-700
 - Reid vapor pressure, 99
 - Remaining useful life evaluation rig, 820-821
 - Repressed oil, refining process, 278
 - Re-refining, hydrocarbon base oil, 172
 - Research Octane Rating, 62, 74
 - Resid, 20-25
 - delayed coking, 21-23
 - fixed bed hydrocracking, 24
 - fluid coking/flexicoking, 24
 - fluidized bed hydrocracking, 24-25
 - solvent deasphalting, 21-22
 - visbreaking, 20-21
 - Residual matter, LPG, 49
 - Reverse-flow viscometers, 838
 - Reynolds equation, 948
 - Rheology, 833-835
 - hydrocarbon base oil, 178
 - Risk, environmental characteristics, 904
 - Road transport, aviation fuels, 106
 - Rolling ball viscometer, 836
 - Rolling velocity, Ryder gear, 997-1000
 - Roll stability, lubricating greases, 562
 - R & O oils, performance testing, 241-242
 - Rotary compressors, 388-389
 - Rotary lobe compressor, 389
 - Rotary Pressure Vessel Test, 281, 798
 - Rotary screw compressor, 388-390
 - Rubber, base oil compatibility, 181
 - RULER, 820-821
 - Run chart, 1051-1052
 - Rust, chemistry, 825-826
 - Rust formation, electrochemical nature, 825-827
 - Rusting behavior, turbine lubricating oils and hydraulic fluids, 340-341
 - Rust inhibitors, 218, 220-223
 - gear lubricants, 456
 - hydraulic fluids, 369-370
 - lubricating greases, 568
 - for turbines, 318-320
 - Ryder gear
 - applicability of WAM high speed load capacity test method, 1010
 - background of load capacity testing, 1001
 - contact stress simulation, 997-1000
 - data processing and traction behavior, 1003, 1004-1007
 - failure criteria in terms of scuffing and micro-scuffing, 1001
 - link to service performance, 1008-1009
 - OEM proposed criteria, 1009-1010
 - oil evaluation, 1000-1010
 - performance criteria, 1007-1008
 - procedure, 1003
 - rolling and sliding velocities across tooth face, 997-1000
 - simulation approach, 1001-1003
 - surface film formation, 1007
 - test description, 1003-1005
 - tooth temperatures, 996-997
 - Ryder gear scuffing
 - criteria, 995-996
 - effect of oil chemistry, 992-994
 - effect of load stage, 993-994
 - initiation, 990-992
 - Ryder Gear Test, 320-321
 - simulation conditions, 996-1000
 - test conditions, 988-990
- S**
- SAE 3306 viscosity classification, gear lubricants, 449-451
 - Safety
 - aerospace fuels fueling, 744
 - mineral oil heat transfer fluids, 583
 - Salt spray, 829
 - Sampling, LPG, 39-40, 48
 - Saponification, esters, 280
 - Saponification number, quench oils, 610
 - Sasol distillate fuels, 138
 - Saybolt patent, 37
 - Saybolt viscometer, 842, 865, 870
 - Saybolt viscosity, standards, 874
 - Scuffing, 435, 458, 936-937
 - boundary, 968-969
 - engine oil performance, 1009-1010
 - failure criteria, 1001
 - front, propagation, 992-993
 - initiation features on Ryder gears, 990-992
 - oil chemistry effect, 992-994
 - progression, tribological processes, 993-996
 - Scuffing load ball-on-cylinder lubricity evaluator, 129-130
 - Seal compatibility
 - compressor lubricants, 409
 - gear lubricants, 459
 - hydraulic fluids, 370
 - lubricating greases, 569
 - Seals, functions, 233-234
 - Seal swell agents, hydraulic fluids, 370
 - Sediment, marine petroleum fuels, 152-153
 - Sediment toxicity tests, 903

- Semisynthetic fluids, metalworking and machining fluids, 504-505
- Servo-operated automated tank gauge, 645
- Setaflash Closed Cup, 693
- Shear stability
 gear lubricants, 459
 hydraulic fluids, 371-372
 polymer-containing oils, 851-853
 requirements, 228-229
 turbine lubricating oils and hydraulic fluids, 340
- Short capillary viscometers, 865
- Short-trip-service engine rusting, 471
- Silicones, 258-259
 compressor lubricants, 394-395
- Slideway lubricants, 510
- Sliding
 gross, surface distress testing, 975-977
 incipient, surface distress testing, 974-975
 velocity, 966, 997-1000
- Sludge, formation by zinc dialkyldithiophosphate, 356-357
- Small scale closed cup, 693
- Smearing wear, 923, 929
- Smoke Point, 98
- Smoke tendency, aerospace fuels, 741
- Snelling, Walter, 36
- Soap content, detergents, 208
- Soave-Redlich-Kwong equation, 536
- Sodium, in marine petroleum fuels, 152
- Sodium soap greases, 559
- Softening point, petroleum pitch, 764
- Solid dispersions, metalworking and machining fluids, 505
- Solidification, aerospace fuels, 737-738
- Solid lubricants, 483-484
- Solid particles, in aviation fuels, 109
- Solubility, refrigeration lubricants, 422-424
- Soluble gum, ASTM D 4814, 83
- Soluble oils, metalworking and machining fluids, 503
- Solvent
 deasphalting, 21-22
 dewaxing process, 529-530
 fractionation, petroleum pitch, 765-767
 refining
 hydrocarbon base oil, 171
 process, 306-307
 solubility, petroleum waxes, 546
- Sommerfeld number, 1022-1023
- Sonic shear, turbine lubricating oils and hydraulic fluids, 340
- Soot, 203-2-4, 720-721
- "Space velocity", 18
- Spark-ignition engine fuels
 specifications, see ASTM D 4814
 vapor-liquid ratio, 703
- Spark ignition engines, 70-71
- Specific gravity
 compressor lubricants, 397
 mineral oil heat transfer fluids, 580
 quench oils, 609
- Specific heat
 compressor lubricants, 408-409
 mineral oil heat transfer fluids, 581
- Specific impulse, aerospace fuels, 742-743
- Spectrometric identification, base oil components, 172-174
- Specular gloss, petroleum waxes, 549, 552
- Sponge coke, removal, 23
- Spontaneous ignitability, aerospace fuels, 733-734, 738
- Spray ignition tests, turbine lubricating oils and hydraulic fluids, 334-336
- Squeeze films, 499
- Stability, diesel fuel, 125-126
- Stabilization patent, 37
- Stabilizers, in marine petroleum fuels, 153
- Stabilizers/deposit control agents, 201-211
- Standard platinum resistance thermometers, 866-867
- Standard reference materials, elemental analysis, 714
- Surfactants, in aviation fuels, 110
- Static bleed test, lubricating greases, 564, 569
- Static electricity, 85, 103
- Static gases, thermodynamic properties, 749-750
- Static petroleum measurement, 635-648
 automatic tank gauging, 645
 bottom sample, 641-642
 examples, 644-645
 free water, 639-640
 gauging diagram, 636
 gross observed volume, 646-647
 innage gauge, 643-644
 official sample, 641, 643
 on-board quantity/remaining on board, 645
 other standards, 648
 pipeline samples, 642
 representative sample, 641
 spot samples, 641-642
 standards, 656-657
 tapes and bobs, 636-638
 temperature in tank, 638, 643
 weighted bottle sampler, 640-641
- Statistical quality control tools, 1050-1051
- Steam cracking, ethylene, 188-190
- Steam plant fuel service system, 157, 161
- Steam reforming, 25-26
- Steam turbine, 297-298
 control fluid system, 301
 shaft driven lubrication system, 300
- Steam turbine oil
 oxidation stability, 798
 rust-preventing characteristics, 830
- Steel
 cooling behavior, wetting process impact, 594-595, 597
 cooling curve analysis, standards, 606-607
 cooling curve data acquisition and analysis, 595-598
 cooling time and rate parameters, 597, 599
 corrosivity, aviation fuels, 102
 film boiling, factors influencing, 594, 596

- hardenability, 589-591
 - measurement, 591-593
 - hardening capability, 599
 - shock film boiling, 599-602
 - transformation, 587-589
 - wetting kinetics, 593-596
 - Steel quenching
 - acoustical measurements, 600-602
 - bath maintenance, 607-608
 - process analysis example, 626-629
 - Steric stabilization, 204-205
 - Stoichiometry, aerospace fuels, 734-735, 738-739
 - Storage stability
 - aerospace fuels, 732
 - aviation fuels, 102
 - diesel fuel, 127-128
 - distillate fuel, 817-818
 - gear lubricants, 460
 - low temperature, 329
 - Stormer viscometer, 868
 - Strainers, diesel fuel system, 163-164
 - Stribeck curve, 945-946, 949, 1022-1023
 - Styrene-diene polymers, 225
 - Subsurface region, 964-965
 - Sulfur content, 19, 28-29
 - ASTM D 4814, 82
 - diesel fuel, 134
 - crude oil, 6
 - fuel oils, 762
 - gear lubricants, 457
 - impact on base oil chemistry, 176-177
 - LPG, 49
 - marine petroleum fuels, 151
 - petroleum coke, 775
 - petroleum gas, 194-195
 - petroleum pitch, 768
 - Sulfur recovery, 26-27
 - Super critical fluid chromatography, hydrocarbon analysis, 659-660
 - Surface analysis, methods, 950-951
 - Surface conformity, 914-916
 - Surface distress testing
 - other types, 976-978
 - under incipient sliding, 974-975
 - Surface energy, 922
 - Surface fatigue, impact of oil attributes, 972, 974
 - Surface film region, 963-964
 - Surface films, 919, 921-923
 - Surface roughness, 911-913
 - data analysis, 913-916
 - Surface tension, aerospace fuels, 738
 - Surface wax, 549, 551
 - Synchronizer SSP 180 test, gear lubricants, 459
 - Synthetic basestocks, compressor lubricants, 392
 - Synthetic ester fluids, for turbines, 309-311
 - Synthetic fluids, metalworking and machining fluids, 503-504
 - Synthetic hydrocarbons, 185-196
 - analytical test methods, 192
 - basestocks, 185-186
 - boiling range, 195
 - butylene and butadiene production, 190-192
 - C-4 product, characterization, 193-194
 - ethylene, 186-190, 192
 - propylene, 190, 192-193
 - standards, 195-196
 - Synthetic lubricants, 249-264
 - alkylated cyclopentanes, 260
 - biodegradability, 263
 - classes, 249
 - cyclohexane derivatives, 260
 - environmental acceptability, 262-263
 - FDA incidental food contact approval, 263
 - lubrication, 261-262
 - perfluoroalkyl ethers, 259
 - polyalkylene glycols, 252-256
 - polyalphaolefins, 257-258
 - polyphenyl ethers, 259-260
 - raw materials, 249-250
 - relative cost, 263
 - silicones, 258-259
 - standards, 263-264
 - Synthetic waxes, 525
 - System operational envelope, refrigeration lubricants, 427
- T**
- Tag Open cup, 693
 - TAME, 17
 - Tankage, gas turbine fuel system, 165
 - Tapping torque test, 1030
 - Temkin isotherm, 953-954
 - Temperature, kinematic viscosity relationship, 854-856
 - Temperature gradient method, 623, 625
 - Temperature gradient quenchant analysis, 623-629
 - Terminology, 1038-1041
 - Terrestrial toxicity tests, 903
 - Test stand aging
 - hydrolysis stability, 287-289
 - oxidation stability, 282-284
 - Thermal and oxidation test, gear lubricants, 458
 - Thermal conductivity
 - compressor lubricants, 408-409
 - gasoline, 84
 - mineral oil heat transfer fluids, 581
 - Thermal cracking reaction mechanism, ethylene, 188
 - Thermal expansion, petroleum coke, 777
 - Thermal oxidation stability, aviation turbine fuels, 815-816
 - Thermal stability
 - aerospace fuels, 745-746
 - diesel fuel, 126
 - diesters, 251
 - hydraulic oils, 799-800, 830
 - mineral oil heat transfer fluids, 579-580
 - polyolesters, 251

- turbine lubricating oils and hydraulic fluids, 339
- Thermodynamic properties, 750
 - static gases, 749-750
- Thermo oxidation engine oil simulation test, 808-812
- Thickening efficiency, 225-226
- Thin film oxygen uptake test, 807-809
- Three-terminal resistivity cell, 343
- Thrust washer tester, 1030-1031
- Timken extreme pressure test machine, 1030-1031
 - lubricating greases, 457, 566
- Tool wear, metal removal fluids, 507-509
- TOST test, 315
- Total base number, detergents, 208-209
- Total wax content, petroleum waxes, 552
- Toxicity
 - acute tests, 894, 901-902
 - chronic tests, 894
 - complex mixture, environmental characteristics, 900-901
 - marine petroleum fuels, 154
- Trace metal contents
 - limits, gas turbine fuels, 141-142
 - petroleum coke, 775
 - turbine lubricating oils and hydraulic fluids, 343
- Traction, within performance maps, 968, 970
- Traction coefficient, 970-972
- Traction test plots, 980
- Tractor fluids, 374
- Tractor hydraulic fluids, performance testing, 240-241
- Transformation processes, environmental characteristics, 889
- Transition metals, as both oxidation promoters and inhibitors, 793, 795
- Transmission fluids, 477-478
 - frictional properties, 212-213
 - performance tests, 239
 - standards, 489-490
- Transport processes, environmental characteristics, 888-889
- Triaryl phosphates, for turbines, 310, 312
- Tribochemical wear, 933
- Tribochemistry, lubricated wear contact, 949
- Tribological aspect number, 1024-1025
- Tribological features, microscopic examination, 991-992
- Tribological processes, scuff progression, 993-996
- Tribology
 - definition, 909
 - history, 1017
 - systematic
 - dynamic mechanisms, 963-965
 - gear lubrication, 988-996
 - hydrodynamic film region, 963
 - impact of oil attributes on surface fatigue, 972, 974
 - lubrication regions, thermal considerations, 970
 - micro-pitting results, 977, 979
 - multi-dimensional oil characterization, 968-969
 - near-surface region, 964
 - oil-off testing, 982-983
 - parameters controlling lubrication and failure mechanisms, 965-966
 - performance maps, generalized, 987-988
 - subsurface region, 964-965
 - surface distress testing, 974-976
 - under gross sliding, 975-977
 - under incipient sliding, 974-975
 - surface film region, 963-964
 - testing for adhesive wear, 979-982
 - traction coefficient, 970-972
 - WAM test machine technology, 967-968
- Tribology test systems, 1017-1018
 - component test design, 1021
 - designing, 1018-1020
 - duration, 1023
 - economic comparison, 1018
 - load, 1022
 - materials, 1023
 - parameter selection, 1021-1024
 - selecting, 1020-1021, 1024-1025
 - special atmospheres, 1023
 - special testing, 1024
 - speed, 1022-1023
 - temperature, 1021-1022
 - test fluids, 1023-1024
- Tribo-system, *see* Tribology, systematic *t*-test, 1058-1059
- TTT diagrams, 589
- Turbine lubricating oils and hydraulic fluids, 297-349
 - acid number, 329, 331
 - additives, 312-323
 - antifoams, 321-323
 - antioxidants, 312-318
 - antiwear and extreme-pressure, 319-321
 - rust and corrosion inhibitors, 318-320
 - air release, 332-334
 - basestocks, 305-312
 - hydrocarbon oils, 305-306
 - hydrocracked/hydrotreated, 307- 308
 - polyalphaolefins, 308-309
 - solvent-refined types, 306-307
 - synthetic ester fluids, 309-311
 - triaryl phosphates, 310, 312
 - chlorine content, 334
 - classification, 323-324
 - cleanliness, 341-343
 - compatibility with system materials, 343-346
 - density, 332
 - duty cycle, 304
 - effect of maintenance, 304
 - fire-resistance tests, 334-337
 - fire-resistant, 301, 311
 - foaming, 332-334
 - function, 300
 - future trends, 349
 - hot surface tests, 335
 - hydrolytic stability, 339-340
 - importance of system cleanliness, 346-347

- low temperature storage stability, 329
 - lubrication performance, 341-342
 - maintenance, 347-348
 - oil types, 305
 - operating environment, 300-305
 - oxidation
 - characteristics, 797-798
 - stability, 801
 - standards, 822
 - oxidative stability, 338-339
 - performance requirements, 326-328
 - performance testing, 241-242
 - pour point, 329
 - resistance to shear in a diesel-injector nozzle, 340
 - rusting and corrosion behavior, 340-341
 - shear stability, 340
 - sonic shear, 340
 - spray ignition tests, 334-336
 - stability testing, 317, 400-401
 - standards, 323-326
 - thermal/oxidative stress, 303
 - thermal stability, 339
 - top-up rates, 304
 - trace metals, 343
 - viscosity, 326-330
 - volatility, 346
 - volume resistivity, 343-345
 - water content, 331-332
 - water separability, 335-336, 338
 - wick tests, 335, 337
 - Turbine oil system, in service monitoring, 798-802
 - Turbines
 - gas, 298-299
 - steam, 297-298
 - system cleanliness, 346-347
 - water, 298-299
 - wind, 299
 - Turbofan combustion system, 97
- U**
- Ultraviolet spectroscopy
 - Beer's law, 661
 - hydrocarbon analysis, 661-662
 - principles, 660-661
 - standards, 662
 - Unique process line, 750-752
 - Used oils, wear metals, 707-709
- V**
- Vacuum gas oils, 4
 - Vacuum potstill method, 696-697
 - Vacuum resid, 4
 - Vanadium content, 152-153, 775
 - Vane pump wear test, 362-363
 - Vapor control systems, 64-65
 - Vapor-liquid ratio, 78, 703
 - Vapor lock temperature, 79
 - Vapor pressure, 697-704
 - automatic method, 701
 - crude oils, 702
 - environmental characteristics, 888
 - evacuated chamber method, 703
 - gasoline, 699, 701
 - gasoline-oxygenate blends, 699, 701
 - liquified petroleum gas, 40-42, 703-704
 - mini-method, 701-702
 - mini-method-atmospheric, 702
 - Reid method, 698-700
 - triple-expansion method, 702-703
 - vapor-liquid ratio
 - Vegetable waxes, 525
 - Vehicle emission standards, history, 63
 - Vickers pump stand, 1035
 - Visbreaking, 20-21
 - Viscometer geometries, 835-836
 - Viscosity, 500-501
 - absolute, water, 863-864
 - adhesives, 870-872
 - aerospace fuels, 737
 - apparent, lubricating greases, 562-563
 - automotive lubricants, 475-476
 - bituminous materials, 870-872
 - bubble tubes, 868
 - coatings, 867
 - diesel fuel, 121
 - diesters, 251
 - dip cups, 867-868
 - environmentally friendly oils, 273, 289-290
 - falling needle, 868-869
 - fuel oils, 760-761
 - gas/liquid mixtures under pressure, 408
 - gasoline, 84-85
 - greases, 479-480
 - hydraulic fluids, 359-360
 - jet fuel, 94
 - loss
 - due to polymer degradation, 228-230
 - shear-related, 225, 227-228
 - marine petroleum fuels, 148-149
 - mineral oil heat transfer fluids, 579, 582-583
 - paints, 867
 - petroleum pitch, 764-765
 - petroleum waxes, 546-547
 - plastics, 869-870
 - polymer quenchants, 617-618
 - polyolesters, 251
 - refrigeration lubricants, 420-422
 - rubber, 872
 - standards, 864-867, 872-875
 - temperature measurement considerations, 866-867
 - tests, 237
 - turbine lubricating oils and hydraulic fluids, 326-330
 - visualization, 835
 - see also* Kinematic viscosity

Viscosity control, diesel fuel system, 164
 Viscosity index, 856-863
 calculation, 858-863
 gear lubricants, 457
 pressure considerations, 859, 862-863
 Viscosity index improvers, hydraulic fluids, 371-372
 Viscosity modifiers, 223-224, 235
 Viscosity-pressure coefficient, effect of base oil
 composition, 180-181
 Volatile matter, petroleum coke, 774-775
 Volatility, 675-705
 aerospace fuels, 736-737
 automotive lubricants, 471
 aviation fuels, 98-101
 class specifications, ASTM D 4814, 82
 crude oil distillation, 696-698
 diesel fuel, 120-121
 diesters, 251
 distillation, 675-682
 environmental characteristics, 896, 900
 flammability, 682, 690-696
 gasoline, 78-80
 polyolesters, 251
 standards, 704-705
 turbine lubricating oils and hydraulic fluids, 346
 vapor pressure, 697-704
 Volatility residue, LPG, 42
 Volume correction factors, liquefied petroleum gas, 50-51
 Volume resistivity, turbine lubricating oils and hydraulic
 fluids, 343-345

W

Walther equation, 917
 WAM configuration, optical EHD film thickness
 measurement, 984-985
 WAM high speed load capacity test method, engine oils,
 1010
 WAM test machine technology, 967-968
 Waste heat economizers, diesel fuel system, 165
 Water, absolute viscosity, 863-864
 Water-absorbing cartridges, 108
 Water-based, metalworking and machining fluids, 501-503
 Water content
 aerospace fuels, 746-747
 compressor lubricants, 397
 dissolved in propane, phase behavior, 43-44
 gear lubricants, 457
 hydraulic fluids, 363, 365
 LPG, 42-49
 marine petroleum fuels, 151

mineral oil heat transfer fluids, 583
 polymer quenchants, 617
 quench oils, 610-611
 turbine lubricating oils and hydraulic fluids, 331-332
 Water separability, turbine lubricating oils and hydraulic
 fluids, 335-336, 338
 Water solubility, environmental characteristics, 887
 Water spray-off, lubricating greases, 568
 Water tolerance, ASTM D 4814, 83
 Water turbines, 298-299
 Water washout, lubricating greases, 568
 Wax appearance point, 881-882
 Waxy crude oil, 527-528
 Wear
 combinations of cavitation/erosion/corrosion wear, 932-
 933
 debris analysis, 939-941
 mechanisms, 923, 927-931
 standards, 1035-1037
 testing, 938-941
 within performance maps, 968, 970
 Wear contact, material structure, 916-925
 Wear maps, 942-945
 Wear material, surfaces, 949
 Wear metals, used oils, 707-709
 Wear preventive characteristics, lubricating greases, 567
 Wear protection, hydraulic fluids, 359-364
 Wear reduction, heat of adsorption, 954
 Wear surfaces, 911-913
 Weathering, liquified petroleum gas, 42
 Weighted bottle sampler, 640-641
 Wheel bearing grease life, 566
 Wheel bearings, grease leakage, 565
 Wick tests, turbine lubricating oils and hydraulic fluids,
 335, 337
 Wind turbines, 299
 Wolf Strip Oxidation Test, compressor lubricants, 401
 World Wide Fuel Charter, 137
 Worms, toxicity tests, 903-904

X

X-ray fluorescence spectrometry, elemental analysis, 713

Y

Yellow metal corrosion, 221

Z

Zinc dialkyldithiophosphate, 314
 oxidation inhibition, 794
 sludge formation, 356-357