

Index

A

- AASHTO T 26, 26
- Acceptance tests, test laboratory requirements, 88
- Admixtures, 13, 16
- air-entraining, 30–31
- C 260, 30
- anti-washout, 32
- bacteriocidal, 32
- batch/delivery ticket information, 79–80
- chemical
- C 494/C 494M, 13, 15, 31, 32, 72
- C 1017/C 1017M, 13, 15, 31–32
- plasticizing, 31
- retarding, 31
- Type B, 31
- Type C, 31
- coloring, 32
- corrosion-inhibiting, 32
- dispensers, 49–50
- dosages, 15, 49
- hydration control, 32
- measurement, 46
- mineral, 13–15, 28, 41, 46, 49, 74
- C 1240, 13, 30
- shrinkage-reducing, 32
- viscosity modifying, 32
- water-repellent, 32
- Aggregates, 21, 23–25, 71
- alkali-reactive, 23, 24
- batch control, computer, 52
- batch/delivery ticket information, 81
- batch plant bin storage, 51
- batching tolerances, 44–45
- C 33, 1, 8, 14, 19, 23–25
- C 88, 24
- C 136, 109
- C 330, 14, 23, 24
- C 566, 44
- C 637, 23, 24–25
- coarse, 24
- coarse, content, 109, 111–112
- coarse, sampling, 60
- coarse, size(s) designation, 8
- D 75, 24
- deicing and, 24
- discharge to weighing hopper, 51
- heavyweight, 24
- lightweight, 24
- manufacturer information about, 15–16
- mass measurement, 44
- materials for, 24
- moisture, 34, 44, 45, 80
- purchaser's specification, 1
- reactivity evaluation, 24
- saturated-surface-dry masses, 13
- scales, 52, 53
- size, 25
- source, 16
- sulfate test of, 24
- Agitating equipment, use of, 66
- Agitating speed, 70
- Agitators, truck
- central-mixed concrete, 64
- discharge drums, 56
- inspection, 62
- placard information, 56–60
- capacity, 56, 60
- gross volume, 56, 60
- speeds, mixing, 56, 60, 70
- sampling, 61
- slump tests, 61
- Truck Mixer Manufacturers Bureau, 57
- see also* mixers
- Air content, 8–10, 21, 26, 29–31, 37–40, 85–86, 96–98, 111
- ACI 301, 1, 11, 14, 17, 24, 39
- C 138/C 138M, 37, 85, 99, 110
- C 173/C 173M, 37, 85, 99, 110
- C 231, 37, 94, 97, 99, 109, 110
- C 260, 13, 15, 21, 30
- carbon content effects, 29
- changes, responsibility for, 38
- definition, 8–9
- factors affecting, 37
- testing, 38
- weather, 38
- feed system, 52
- mixing effects on, 66
- point of discharge measurement, 38
- recommended, 9
- responsibility for, 39
- sampling, 39, 60
- specification compliance, 39
- Air pressure air content method, 86
- Alkali content, 21, 26
- Alkali oxides, 19
- Alkali-silica reactivity, 29, 32
- American Association of State Highway and Transportation Officials, 4
- American Concrete Institute (ACI)
- ACI 211.1, 8, 9, 12, 16, 24, 33
- exposure definitions, 8–9
- ACI 211.2, 12, 16
- ACI 214.4R-03, 102
- ACI 214R, 100
- ACI 225 R-99, 19
- ACI 228.1R-95, 102
- ACI 301-99, 1, 11, 14, 17, 24, 39, 95
- ACI 305R, 74
- ACI 306R, 72
- calcium chloride use, 47
- ACI 318-02, 20, 22, 26, 95, 100, 101, 102, 104
- certified testing technicians, 89, 92
- concrete field testing, 89, 93, 99
- concrete laboratory testing, 89
- referenced standards, 3–4
- Arbitration
- panel
- composition, 106
- engineers, 106
- selection process, 106
- process, Uniform Arbitration Act, 107
- strength requirement failure, 106
- Aspdin, J., 18
- ASTM Standard Specifications for Ready Mixed Concrete (1935), 117–126
- ASTM standards
- A 820, 32
- C 31/C 31M, 3, 67, 84, 99, 113
- C 33, 1, 8, 14, 19, 23–25, 27
- C 39/C 39M, 3, 84, 100
- C 42/C 42M, 102
- C 88, 24
- C 109/C 109M, 25
- C 125, 13, 25
- C 127, 112
- C 136, 109
- C 138/C 138M, 5, 6, 7, 11, 37, 83, 85, 94, 99, 110
- C 143/C 143M, 3, 8, 33, 87, 94, 99
- C 150, 13, 14, 18, 19–20, 22, 23, 44
- C 172, 3, 5, 6, 40, 67, 69, 76, 87, 92, 93, 96, 99, 109
- C 173/C 173M, 37, 85, 99
- C 191, 25
- C 231, 37, 94, 97, 99, 109, 110
- C 260, 13, 15, 21, 30, 79
- C 330, 14, 23, 24
- C 494/C 494M, 13, 15, 31, 32, 72
- C 511, 3, 99
- C 566, 44
- C 567, 10–11
- C 595, 13, 14, 21–23
- C 618, 13, 22, 28–29, 79
- C 637, 23, 24–25
- C 670, 100
- C 672/C 672M, 27
- C 685/C 685M, 41, 64
- C 845, 32
- C 979, 32
- C 989, 13, 22, 30, 79
- C 1017/C 1017M, 13, 15, 31
- C 1064/C 1064M, 87, 88, 94, 99
- C 1077, 88
- C 1116, 32
- C 1157, 1, 13, 14, 18, 23
- C 1240, 13, 30
- D 75, 24
- D 516, 26
- referenced standards, 3–4

B

Bacteriocidal admixtures, 32
 Bagged cement, 43, 44
 Batch characteristics, 110–113
 Batch mass, 44
 Batch moisture, 45
 Batch plant
 aggregate discharge, 51
 bin compartments, 51
 central mix, 76
 computer control, aggregate, 52
 indicators, operator access, 52–53
 mixing methods, 64
 central-mixed concrete, 64–66
 shrink-mixed concrete, 64, 68
 truck-mixed concrete, 64, 68–69
 mixture proportion information, 16–17
 National Ready Mixed Concrete
 Association certification program, 54, 55
 scales, 52, 53
 accuracy, 53–54
 calibration test weights, 54
 indicators, 54
 preventive maintenance, 54
 sensitivity, 54
 specification, 51–55
 water measurement, added, 54
 calibrated tanks, 54
 measuring devices, 54
 weigh hopper, 51–53
 vibrator, 52
 Batch ticket information, 78–82
 admixtures information, 79–80
 aggregate information, 80–81
 cement information, 79
 certification information, 78–79, 81–82
 fiber reinforcement information, 80
 mandatory, 78
 pozzolans information, 79
 slag information, 79
 slurry, recycled, information, 80
 water information, 78, 79, 80
 Batch variation determination, 109
 Batching accuracy, 42
 Batching devices, 41
 Batching hopper, 41
 Batching sequence, 61
 Batching temperature, 73
 Batching tolerances, 42, 43
 Batching, volumetric C 685/C 685M, 41, 64
 Bessel's correction, 104
 Boyle's law, 87
 Building code requirements, ACI 318-02, 20, 22, 26, 95, 100, 101, 102, 104
 Bureau of Reclamation, 109
 Concrete Manual, 4, 5, 74, 110

C

C₃A, 19
 C₄AF, 19
 Calcium-aluminate cements, 32
 Calcium chloride, 74
 flaked, admixture, 46–47
 dosage calculations, 47, 49
 Calcium oxide, 19
 Calcium silicates, 18
 Calcium sulfate, 19
 Calibration, 45
 scale test weights, 54
 Carbon content, Class "F" fly ash, 29

Cement
 bagged, 43
 partial, 44
 batch/delivery ticket information, 79
 blast-furnace slag, 21
 Cement, calcium-aluminate, 32
 Cement content, 14
 minimum, 16
 Cement, hydraulic
 C 109/C 109M, 25
 C 219, 18
 C 511, 3, 99
 C 845, 32
 C 1157, 1, 13, 14, 18, 23
 Option R, 23
 Type GU, 23
 Type HE, 23
 Type HS, 23
 Type LH, 23
 Type MH, 23
 Type MS, 23
 performance requirements, 23
 selection and use, ACI 225 R-99, 19
 Cement, hydraulic, blended, 21
 C 595, 13, 14, 18, 21–23
 Type IP, 22
 Type I (PM), 22
 Type IS, 21
 Type I (SM), 22
 Type P, 22
 Type S, 22
 Cement materials
 argillaceous, 19
 calcareous, 19
 Cement, portland, 18–23
 C 150, 13, 14, 18, 19–20, 22, 23, 24
 C 150 classifications
 air entrained, 21
 Type I, 19–20
 Type I (PM), 22
 Type II, 20
 Type I/II, 20
 Type III, 20
 Type IV, 20
 Type V, 20
 C₃A, 18, 19, 20, 74
 C₂S, 18, 19
 C₃S, 18, 19, 20, 74
 general construction, 20, 22
 general purpose, 19
 hydration, low heat of, 20
 modified, 22
 origin, 18
 pozzolan modified, 22
 slag modified, 22
 Cement scales, 41
 Cement weigh hoppers, 41
 Cementitious mineral admixtures, 41, 49
 Certification information
 batch/delivery ticket, 78–79, 81–82
 proportions, 16–17
 Certification, ACI technicians, 89, 93, 99
 Certification, test information, 13
 Chloride ion measurement, 49
 Chlorides, 26
 Coal, 28, 29
 Coloring admixtures
 C 979, 32
 Compacting sample, slump test, 33
 compliance testing, 92–94
 certified testing technicians, 89, 92, 96
 specification, 17
 Compression test
 C 39/C 39M, 3, 84, 100
 Compressive strength, 9, 11–12, 16, 102, 113
 C 109/C 109M, 25

 sampling, 60
 Computer controlled batching, 52
 Concrete Plant Manufacturers Bureau, 41, 44, 53, 56, 64
 Consistency, mixture, 8
 Construction cement, general, 20
 Cores, drilled, 102
 Covers, nonagitator transportation
 equipment, 76
 C₂S, 18, 19
 C₃S, 18, 19
 Curing, 12, 100

D

Deicing salts, 8–9
 C 672/C 672M, 27
 Delivery ticket information, 78–82, 101
 admixtures information, 79–80
 aggregate information, 81
 cement information, 79
 certification information, 78–79, 81–82
 fiber reinforcement information, 80
 mandatory, 78
 pozzolans information, 79
 slag information, 79
 slurry, recycled, information, 80
 water information, 78, 79, 80
 Density
 C 127, 112
 C 138/C 138 M, 5, 6, 7, 11, 85, 94, 110
 determination of, 5–7, 111
 mortar, 109, 112
 relative, 16
 structural lightweight concrete, 10
 testing procedures, 11
 Discharge
 completion, 70, 71
 mixer structure, 65
 sampling point, 62, 67, 69, 77
 Dispensers, admixture, 49
 Durability, 6, 12, 16, 23

E

Exposure, definition, 8–9

F

Fiber reinforcement batch/delivery
 ticket information, 80
 Flexural strength (beams) specimens, 101
 Flowing concrete, 31
 Fly ash
 C 618, 13, 22, 28–29
 Class "C", 28–29
 Class "F", 29
 carbon content, 29
 Foaming agents, 32
 Footnotes and notes, use in C 94/C 94M, 2
 Freeze-thaw cycle
 conditions, 21, 37
 considerations, 7–10
 aggregates and, 24
 freeze-thaw resistance, 8–9

G

Geographic area, effect on materials
 specification, 18
 German Commission for Reinforced
 Concrete, 27
 Grading, 16
 Ground granulated blast furnace slag
 (GGBF), 14, 21–23, 30, 104

- C 989, 13, 22, 30, 79
 permeability, 22
 Gypsum, 19
- H**
- Hydration, heat of, 19, 20, 23
 Hydration, rate of, 19
- I**
- Ice, measurement, 46
 Inspection, 83, 92
- J**
- Johnson, I. C., 18
- K**
- Kaolinite, 19, 29
 Keywords, C 94/C 94M, 108
- L**
- Lime, 28
 Limestone, 19
 Lithium-based additives, 32
 Load cell, 42, 49
- M**
- Magnesium sulfate, 88
 Manufacturer
 defined, 2
 responsibility, 1, 10–17
 information statement for
 purchaser, 13
 term use, 2
 Mass, 10–11, 13, 16
 aggregate, 81
 determining, 5–7, 41–45, 52, 60
 determining, admixtures, 46–47
 determining, aggregates, 44–45
 mass per unit volume
 C 138/C 138M, 5, 6, 7, 11, 37, 83,
 85, 94, 99, 109, 110
 mix methods and, 64
 Measurement units used, 2
 Metakaolin, 29–30
 Mixers, 56–63
 blade wear, 62, 63
 buildup, 63
 central-mixed concrete, 64
 described, 56
 discharge drums, 56
 discharge rate, 69
 drum revolution, 71
 recording, 59–60
 inspection, 62
 National Ready Mixed Concrete
 Association, 57
 mixing time, minimum, 66
 performance tests, 66, 67
 placard information, 56–60
 drum capacity, 56–57, 60
 drum volume, 56–57, 59, 60
 mixing speed, 56–57
 sampling, 60, 61, 66
 stationary, 56, 64
 capacity, 56
 central mixing, 56, 66
 speed, 56
 types, 65
 Truck Mixer Manufacturers Bureau,
 57
- uniformity, charging effects on, 61
 uniformity, performance test, 61
 Mixing methods
 central-mixed concrete, 64–66
 shrink-mixed concrete, 64, 68
 truck-mixed concrete, 64, 68–69
 Mixing time, minimum, 66
 Mixture proportions
 disclosure, 13, 16
 manufacturer responsibility for, 10–17
 purchaser responsibility for, 8–17
 Mixture types
 central-mixed concrete, 64–66
 shrink-mixed concrete, 64, 68
 truck-mixed concrete, 64, 68–69
 Moist cabinets and rooms
 C 511, 3, 99
 Moisture content
 see Water
 Mortar cubes, 25
 Mortar, unit weight, 112
- N**
- National Institute of Standards and
 Technology (NIST), Handbook 44
 on Weights and Measures, 53
 National Ready Mixed Concrete
 Association, 27, 57, 61, 68
 blade wear, 63
 Plant Certification program, 54, 55,
 61, 76, 83
 Nonagitating equipment, 65, 76–77
 covers, 76
 discharge gate, 76
 test requirements, 77
 Non-chloride accelerators, 47
 Notes and footnotes, use in C 94/C 94M,
 2
- O**
- Ordering information, 8–17
 manufacturer responsibility, 10–17
 purchaser responsibility, 8–17
- P**
- Pavements, 19
 Performance aspects, hydraulic cement
 C 1157, 23
 Plant inspection, 83
 access, 83
 National Ready Mixed Concrete
 Association Plant Certification
 Checklist, 83
 sampling by inspector, 83
 Polymer modifiers, 32
 Polypropylene
 C 1116, 32
 admixture, 46
 Portland cement
 see Cement, portland
 Portland Cement Association
 Design and Control of Concrete
 Mixtures, 73
 U.S. and Canadian Portland Cement
 Industry Plant Summary, 21
 Potassium oxide, 19
 Powdered admixtures, measuring, 46
 Pozzolans, 13, 22
 batch/delivery ticket information, 79
 C 618, 13, 22, 28
 Class “N”, 29
 rice-husk ash, 30
 Precision and bias statements
 C 670, 100
- Producer, term use in C 94/C 94M, 2
 Pump line, 38
 Pumping aids, 32
 Purchase, basis of, 5–7
 Purchaser
 identified, 2
 rights, 1
 responsibility, 10–12, 14, 15
 material specification, 18
 quality assurance testing, 17
 Purchasing method, concrete, 5
 mass, 5–6
- R**
- Radiation shielding concrete, 24
 aggregates for
 C 637, 24
 Referenced documents list, 3–4
 Roll-a-meter test, 97
 C 173, 37, 85, 99
- S**
- Sampling, 66–67, 69–70, 92–98
 C 172, 3, 5, 6, 40, 67, 69, 76, 87, 92,
 93, 96, 99, 109
 hand, 70
 integrity, 70
 procedure example, 67
 representative, 93–94
 truck mixed concrete tests, 60, 62
 Sand, 27
 Scales
 accuracy, 43, 53–54
 National Ready Mixed Concrete
 Association program, 55
 calibration, test weights, 54
 hoppers, 44
 indicators, 54
 preventive maintenance, 54
 sensitivity, 54
 Scaling, 8
 C 672/C 672M, 27
 Scope, C 94, 1–2
 Shrinkage-compensating expansive
 cements, 32
 Sieve analysis, 16
 Silica fume, 79
 C 1240, 13, 30
 Silt, 27
 Slab on grade variation, effects of, 7
 Slabs, interior, 1914, 21–23, 30, 104
 Slag, 14, 21–22, 104
 batch/delivery ticket information, 79
 C 989, 13, 22, 30, 79
 Slump, 31, 32, 70–71, 96–98
 C 143/C 143M, 3, 8, 33, 87, 94, 99
 standard deviation, 34
 control, water management for, 34
 flow, 33
 heat effects on, 74
 nominal, 35
 responsibility, 36, 39
 temperature effects on, 35
 tests, 61, 76–77, 95, 111
 tolerances in, 33–36
 measurement of, 8
 Slurry, 27
 recycled, batch/delivery ticket
 information, 80
 wash water and, 28
 Sodium sulfate, 88
 Specific gravity, 16
 Specification, defined, 1
 Specimens
 C 31/C 31M, 3, 67, 84, 99, 113

C 42/C 42M, 102
 cores, 102
 ACI 214.4R-03, 102
 cylinders, 12, 14, 84, 90, 99, 101–102, 113
 flexural strength (beams), 99, 101
 mortar cubes, 25
 Standard deviation, 103–104
 variables, 104
 Standard test weights, 53–54
 Standards, 53
 see ASTM standards
 see also specific groups
 Steel fibers
 A 820, 32
 C 1116, 32
 Strength, 99–105
 applied, 101
 C 31/C31M, 99
 changes with entrained air, 9
 compressive, 9, 11–12, 16, 102, 113
 overdesign, 104
 overdesign safety factor, 105
 design, 12
 estimated, ACI 228.1R-95, 102
 field, 12
 high early strength cement, 20
 minimum cement content, relation with, 16
 requirements, failure to meet, 106–107
 arbitration, 106
 slump, relation with, 33
 test result evaluation
 ACI 214R, 100
 tests, 14, 90, 95
 Structural concrete
 ACI 211.1, 8, 9, 12, 16, 24
 exposure definitions, 8–9
 Structural lightweight concrete, 10
 C 567, 10–11
 Sulfate ion test
 D 516, 26
 Sulfate resistant cement, 20–22
 C 88, 24
 C 1157, 23
 Supplementary cementitious materials (SCM), 13–15, 28, 41, 46, 49, 74
 C 1240, 13, 30
 Supplier, term use in C 94/C 94M, 2

T

Temperature considerations, 95
 C 1064/C 1064M, 87–88, 94, 99
 cold weather, 72–73
 delivery, 72–75
 freezing and thawing, 7–10, 21, 24, 37
 hot weather, 73–74
 Terminology
 C 125, 13, 25
 C 219, 18
 Testing laboratory requirements
 C 1077, 88
 Thawing and freezing resistance, 8–10, 24
 Time of set, 22, 23, 28, 29, 30, 46, 74
 accelerating, 74
 C 191, 25
 weather effects on, 72–75
 Transportation unit, 38
 Tricalcium aluminate, 20
 Truck Mixer Manufacturers Bureau, 57, 113
 Turbine water meters, 45
 calibration, 45

U

Uniform Arbitration Act, 107
 Uniformity, 66, 110
 batch variation determination, 109
 sampling procedure, 67
 shrink-mixed concrete, 68
 truck-mixed concrete, 60–61, 68–69
 U.S. and Canadian Portland Cement Industry Plant Summary, 21
 U.S. Geological Survey, 21

V

Variance, 103–104
 Vicat needle, 25
 Voids, 9
 Volume, concrete purchasing method, 5
 changes, 7
 mass to determine, 5–6

W

Water
 additions, job site, 35, 71, 97
 batch/delivery ticket information, 78, 79, 80
 batch mixing, 25, 27, 45, 70
 C 511, 99
 chlorides, 26
 computation, 15
 content, 15, 16
 durability and, 71
 measurement, added, 54
 calibrated tanks, 54
 devices for, 54
 meters, turbine, 45
 pressures, 54
 quality, 25
 AASHTO T 26, 26
 acceptance criteria, 25
 reducers, 32
 C 494/C 494M, 31–32
 C 1017, 31–32
 storage tanks, C 511, 3, 99
 use of hot, 73
 wash water, 25–28, 45, 46
 clarified, 27
 Weather
 cold weather, 72–73
 ACI 306R, 72
 C 1064/C 1064M, 87–88, 94, 99
 calcium chloride use, 47
 cold weather protection, 20
 delivery, 72–75
 freezing and thawing, 7–10, 21, 24, 37
 hot weather, 73–74
 ACI 305R, 74
 Weigh batchers, 44
 Weigh hoppers, 51–53
 vibrator, 52
 Workability, 70

Y

Yield, concrete, determination of, 6–7
 C 138/C 138M, 83, 85
 relative, calculations, 6–7