

Author Index

A-C

Abdallah, M. G., 231
Bakis, C. E., 180
Bigelow, C. A., 261
Bowles, K., 31
Chamis, C. C., editor, vii
Chou, T.-W., 45, 75

D-H

Daniel, I. M., 16, 276
Dannemann, K. A., 3
Foley, G. E., 208
Friedrich, K., 75
Gascoigne, H. E., 231
Grande, D. H., 3
Harris, B., 136
Houghton, W. W., 208

I-M

Illg, W., 150
Johnson, W. S., 261
Lagace, P. A., 197
Lee, J. W., 276
Mandell, J. F., 3
Mody, P. B., 75

Munjal, A. K., 93

N-R

Neal, D., 136
Outwater, J. O., 224
Peimanidis, G., 16
Poe, C. C., Jr., 150
Roylance, M. E., 208
Rust, S. W., 136

S-T

Shyprykevich, P., 111
Simonds, R. A., 180
Stinchcomb, W. W., 180
Todt, F. R. K., 136
Tsiang, T.-H., 55

V-Y

Vangel, M., 136
Vannucci, R. D., 31
Weems, D. B., 197
Yaniv, G., 16, 276
Yau, S.-S., 45

Subject Index

A

Abrasive wear, 75-89
 AP-orientation, 81-83
 comparison of experimental and predicted rates, 87-88
 crossover point, 83-85
 materials, 76
 minimum and maximum wear rates, 86
 modified rule-of-mixtures, 87-89
 N/AP woven composite, 85
 N-orientation, 82-83
 N/P woven composite, 84-85
 P/AP woven composite, 83-84
 P-orientation, 81-83
 scanning electron microscopy, 79
 sliding directions, 77-78
 specimen area effect, 79-80
 testing procedures, 78
 two-dimensional woven fiber system, 82-86
 unidirectional continuous fiber composite, 79-82
 variation of properties with orientation, 82-83
 wear equation, 78
 Adhesive bonding, 31
 Advanced Communications Technology Satellite, 31
 Aluminum
 honeycomb, 31
 matrix, 261
 mechanical properties, 263
 Analysis of variance method, 137
 Anderson-Darling test
 k-sample, 136, 139-141
 lognormality, 144-145
 normality, 144
 statistic, 141, 143-144
 Weibullness, 143
 Anisotropy, 224
 ANOVA method, 145-147
 ASTM D 638, 111, 113-114
 ASTM D 648, 96
 ASTM D 695, 99-101, 111, 113, 117, 132, 180
 ASTM D 790, 35
 ASTM D 792, 96
 ASTM D 2290, 98
 ASTM D 2344, 35, 104-105, 111, 113, 120
 ASTM D 2584, 96
 ASTM D 2585, 99

ASTM D 2586, 100-101
 ASTM D 2719, 41
 ASTM D 2734, 96
 ASTM D 3039, 96, 111, 113, 132
 ASTM D 3171, 96
 ASTM D 3410, 100-103, 111, 113, 120, 181
 ASTM D 3518, 104, 106, 108
 ASTM D 3846, 104-108
 ASTM D 4065, 96
 ASTM D 4255, 104, 107-108
 ASTM E 399, 46
 Asymmetric four-point bend test fixture, 233-234
 tab configurations used with, 233
 Axial extensometer, 9
 Axial modulus, 276-277

B

B basis factors, 130, 132-134
 Bending modulus, 39
 Bismaleimide, 55
 BMAS glass-ceramic matrices, 5
 Boron/aluminum laminate, moire fringes, 268-269
 Buckling study, torsion tubes, 212-216

C

Carbon, 45
 Celanese compression fixture, 101-102
 Ceramic composites, 3
 Characterization, 83
 problems unique to composites, 94-95
 Complementary shear, 228
 Composite plaque, 46-47
 Composite sandwich materials, 31-44
 composite three-point bend tests, 35-36, 42
 crippling failure, 36, 39
 critical lengths, 39
 failure mode, 43
 flexural properties, 39-40
 laminate strengths, 41
 lap shear strength, 34
 material properties, 33
 material test matrix, 32, 34
 materials and fabrication procedures, 32-33
 picture-frame tests, 34-35, 41-42

Composite sandwich materials (*cont.*)
 sandwich flexure tests, 35-36
 sandwich structure tests, 43
 shear properties, 42
 shear stiffness, 43
 tensile properties, 36, 38
 tension specimens, 34, 37
 Composite three-point bend tests, composite sandwich materials, 35-36, 42
 Compression, 45, 93, 180
 properties, short-fiber reinforced thermoplastics, 50
 Compression stiffness, 183
 Compression testing, 183
 cylinders, 101
 fiber reinforced composites, 99-103
 statistical data reduction, 116-121, 124-125
 Compressive strength, ultimate, 118, 124
 Computer analysis, 31
 Contact diameter, 169, 171
 Contact pressure, versus impact force, 171-172
 Crippling failure, 36, 39
 Crossbeam shear specimen, 107
 Crossover point, abrasive wear, 83-85
 Cut depth, equivalent, 173-175

D

Damage, 180
 contours, Love's solution, hemispherical contact pressure, 169-170
 depth
 versus mean contact pressure, 169-170
 prediction, 171
 development, 276
 Debonding energy, 228-229
 Deflection, relationship with load, 37
 Delamination, 197
 depth
 after loading, 174-177
 comparison with equivalent cut depth, 175
 Design allowables, 93, 96
 factors/conditions affecting, 107-108
see also Statistical data reduction; Statistical methods, design allowables calculation
 Double-rotating-disk testing device, 59
 Double V-notch shear specimen, 105-106

E

Effective stress-effective plastic strain curve, 274

Elastic moduli, 263
 Elastic-plastic stress, 261-274
 comparison of rectangular and radial mesh results, 268, 270
 distribution ahead of slit tip, 268
 experimental procedures, 262
 fiber stress concentrations for layups containing 0° plies, 272
 homogeneous materials, 267
 material model, 268, 273-274
 mesh description, 268-269
 metal matrix composites, 267-272
 specimens, materials, and preparations, 262
 strain, front of slit tip, 264-267, 270-271
 End caps test fixture, 99-101
 Environmental effects, 16
 Epoxy, 55
 adhesive, lap shear strength, 34
 final failure mode, 246
 Erosion, 58
 Erosion test chamber, 57
 Extensometers, 9-11

F

Failure mode, composite sandwich materials, 43
 Failure stress, 263-264
 Fatigue, 180
 Fatigue testing, 276
 Fiber reinforced composites, 93-109
 characterization, 94-95
 compression testing, 99-103
 factors/conditions affecting design allowables, 107-108
 hoop fiber stress, 99
 in-plane shear testing, 106-107
 interlaminar shear testing, 104-106
 Morton Thiokol test fixture, 97-98
 NOL ring split disk method, 98
 physical property testing, 96
 shear testing, 103-107
 specimen fabrication and preparation, 95
 tension testing, 96-99
 transverse tension testing, 97-98
 Filament-wound composites, 150, 208
 membrane region, 152
 Finite element analysis, 231
 Iosipescu shear test, 247, 250-257
 modeling, 238-239
 isochromatic fringe patterns, 240-242
 material properties used in, 239
 meshes, 268-268
 three dimensional, 261, 267-268
 Flatwise tension, 197-198

Flexural properties, composite sandwich materials, 39-40
 Flexural rigidity, 37, 39
 Four-point ring twist testing, 106
 Four-point shear test method, 104-105
 Fracture energy, 224
 Fracture modes, short-fiber reinforced thermoplastics, 50-51, 53
 Fracture toughness, 45
 short-fiber reinforced thermoplastics, 50, 52-53
 Friction, 75
 FTMS-406, 99-100

G

Glass, 45
 Glass/ceramic matrix composites, 3-14
 materials and apparatus, 5-6
 mechanical properties, 3-4
 off-axis properties, 13
 stress-strain curves, 10, 12-14
 tension specimens and testing, 6-10
 test method development, 4-5
 unidirectional composite properties, 11
 Glass/epoxy composites, 198-199
 sand erosion, 60-62
 Glass fiber composites, 55
 Glass transition temperature, 96
 Goodness-of-fit test, 138
 lamina tests, 113
 Graphite/bismaleimide, sand erosion, 62, 68
 Graphite/epoxy composite, 16-30, 111, 150-178, 180, 197
 clamped in cutting jig, 201
 conditioning procedure, 17-18
 failure modes, 191
 first ligament failure, 165-167
 hoop-fiber stress, 164
 hygrothermal test conditions, 19
 impact damage
 delamination depths after loading, 174-177
 equivalent cut depth, 173-174
 predictions and radiographs, 169-173
 impact tests, 153-155, 158-164
 initial shear modulus 20, 251
 in-plane shear properties, 27-29
 longitudinal tensile properties, 25-27
 material, 152-153
 properties, 178
 specimen preparation, 17-18
 mixed amplitude cyclic loading, 189-190
 penetrant-enhanced x-ray, 187, 189
 photoelastic isochromatic fringe pattern, 236, 238-242

 post-failure appearance, 184-186
 ratio of impact strength to undamaged strength versus impact force, 166-168
 residual strengths, 155-156, 187-188
 shear strength, 175-176
 shear stress versus shear strain, 280-282
 static compliance tests, 155, 157-158
 statistical properties, 131
 stiffness response, 187-188
 strength tests, 155-156
 impacted specimens, 165-169
 undamaged specimens, 157, 164-165
 stress-life, fully reversed cyclic loads, 185, 187
 test procedure, 19
 time-temperature-moisture master curves, 22-23, 25-29
 time-temperature moisture shift factor, 27, 29
 time-temperature shift factor, 23-25
 transverse stress-strain curves, 20-21
 transverse tensile properties, 20-25
 X-radiographs, 281, 283
 X-ray tests, 155
 Graphite fiber composites, 31, 55
 Graphite fiber/polyetheretherketone composites, 180
 post-failure appearance, 184-186
 residual strengths, 187-188
 stiffness response, 187-188
 see also Abrasive wear
 Graphite/nylon, sand erosion, 72
 Graphite/polyimide, sand erosion, 60-62, 67
 Graphite/polyphenylene sulfide, sand erosion, 62, 69, 71

H

Hertz law, 157, 163-164
 High temperatures, 3
 Hoop fiber stress, 99
 graphite/epoxy composite, 164
 Hybrid laminate, 127
 Hygrothermal characterization, 16

I

IITRI compression test fixture, 102
 Impact damage, 150
 graphite/epoxy composite
 delamination depths after loading, 174-177
 equivalent cut depth, 173-174
 predictions and radiographs, 169-173
 Impacted rings, mass and kinetic energies, 153-154

Impact force, versus contact pressure, 171-172

Impact tests
force, 163
graphite/epoxy composite, 153-155, 158-164
impacter force versus energy, 162-163
impacter mass effect, 160-161
kinetic energy effect, 159-160
maximum force, 158-159
rebound velocity versus impacter mass, 161-162

In-plane shear, 208
properties, graphite/epoxy composite, 27-29
testing, fiber reinforced composites, 106-107
torsion tubes, 216-222

In-plane shear modulus, 276-283
evaluation of method, 280-281
fixture description, 277-279
jig and assembly of fixture, 278-279
rail shear fixture, 278
test procedure, 279-280

In-plane shear strain, 280

In-plane shear stress, variation, 250-251, 254

Interlaminar stresses, 197

Iosipescu shear test, 231-259
final failure mode, 246
finite element analysis, 247, 250-257
finite-element modeling, 238-239
fixture behavior during testing, 243-244, 246-247
in-plane shear stress, 250-251, 254
45° isoclinic, 237
loading fixtures, 233-235
longitudinal stress, 250, 253, 256
material properties, 247-249
moire interferometry, 238, 240, 243-245
photoelastic measurements, 235-238
photoelastic coating, 238-240
shear stress
along notch flank, 250, 257-258
distribution between notches, 250, 259
specimens, 105-106, 232-233
stress ratio, 250, 259
tab configurations used with AFPB fixture, 233
testing and instrumentation, 235
test matrix, 235-236
transverse stress, 250, 252, 255

K

Kevlar
fiber composites, 55

machining, 95

Kevlar/epoxy
sand erosion, 61, 64
tubes, 210
buckled, 212-213
filament winding patterns, 211
in-plane shear behavior, 217, 220
shear stress-strain curve, 217-218, 221
shear stress versus tensile and compressive strain, 218, 222

Kolmogorov-Smirnov comparative tests, 112-115

k-sample Anderson-Darling test, 136, 139-141

L

Lamina constants, graphite/epoxy composite, 178

Laminates
strengths, composite sandwich materials, 41
wrinkle-free and wrinkled, 164

Lamina tests, 111-126
batch-to-batch variability, 113-114
compression test results
fabric, 116-119
tape, 120-121, 124-125
goodness-of-fit test, 113
Kolmogorov-Smirnov comparative tests, 112-115
matrix, 112-113
pooling of data, 112-113
short beam shear test results
fabric, 120-123
tape, 125-126
tension test results
fabric, 114-116
tape, 120, 123-124

Laminate tests, 111, 126-130
B basis factors, 130, 132-134
open-hole tension test specimen, 128
rail shear test specimen, 129
sandwich compression test specimen, 128
single shear test specimen, 129
test matrix, 127

Lap shear strength, epoxy adhesive, 34

Life, 180

Load, relationship with deflection, 37

Lognormal analysis procedure, 148

Lognormality, Anderson-Darling test, 144-145

Longitudinal extensometer, 9-10

Longitudinal stress, 250, 253, 256

Love's solution, 169

Low temperature, 45

M

- Material model, 268, 273-274
- Matrix cracking, 10
- Matrix materials, reinforced
 - graphite UD tape, sand erosion, 61-62, 65
 - graphite-woven fabric, sand erosion, 61-62, 66
- Maximum normed residual test, 138-139
- Mechanical properties, 31, 231
 - lamina, test matrix, 112-113
- Metal matrix composites, elastic-plastic stress, 267-272
- Metals testing, versus composites, 93-94
- Moire fringes, boron/aluminum laminate, 268-269
- Moire interferometry, Iosipescu shear test, 238, 240, 243-245
- Motor case, 150

N

- NBS compression test fixture, 102-103
- Nicalon/BMAS glass-ceramic, stress-strain curves, 12, 14
- Nicalon ceramic fibers, 5
- Nicalon/1723 glass, stress-strain curves, 12-13
- Nonparametric analysis procedure, 148-149
- Normal analysis procedure, 148
- Normality test
 - Anderson-Darling test, 144
 - multiple batches, 141
- Nylon, 55

O

- Observed significance level, 141-144
- Open-hole tension test specimen, 128
- Outlier, detection, 138-139

P

- PEEK. *See* Graphite/polyetheretherketone composites; Polyetheretherketone
- Photoelectric coating, Iosipescu shear test, 238-240
- Physical property testing, fiber reinforced composites, 96
- Picture frame testing, 106
 - composite sandwich materials, 34-35, 41-42
- Plate twist testing, 106
- Polyetheretherketone, 45, 55
 - brittle fracture bands, 53
 - compressive strength, 51

- fracture toughness, 53
- tensile strength, 49
- unreinforced, abrasive wear, 85-86
- see also* Graphite/polyetheretherketone composites

- Polyetherimide, 45
 - compressive strength, 51
 - fracture toughness, 52
 - tensile strength, 48
- Polyethersulfone, 45
 - brittle fracture bands, 53
 - compressive strength, 51
 - fracture toughness, 52
 - tensile strength, 49
- Polyimide, 55
- Polymer matrix, 31
- Polyphenylene sulfide, 55
 - matrix, erosion resistance, 62-63, 70
- Pultruded rod, 224-230
 - data analysis, 227-229
 - diametral fracturing, 227-228
 - preparation, 225-227
 - torque-displacement curve, 225, 227
- Pultrusion process, 225

Q

- Quasi-static tension tests, 183

R

- Rail shear testing, 106, 276
 - fixture, 278
 - specimen, 129
- Release agents, 224
- Reserved cyclic loads, 180-192
 - anti-buckling fixture, 183-184
 - constant amplitude, 185, 187-189
 - mixed amplitude cyclic loading, 189-191
 - monotonic tests and specimen design, 183-185
 - specimen gripping configuration, 181-182
 - supporting equipment and procedures, 181-183
 - unsupported length effect, 184-185
- Residual strength, 150
 - tests, graphite/epoxy composite, 155-156
- Rocket motor case, 150
- Rule of mixtures, 75
 - modified, 87-89

S

- Sand erosion, 55-74
 - background, 55-56
 - materials, 60

- Sand erosion (*cont.*)
 mechanisms, 56
 rate versus particle impingement angles, 63, 73
 resistance effects, different fibers, 61
 test conditions, 59
 test method, 56–59
- Sandwich compression test specimen, 128
- Sandwich flexure tests, composite sandwich materials, 35–36
- Sandwich structures, 31
 tests, composite sandwich materials, 43
- S-glass/epoxy
 shear stress-strain curve, 212–214
 shear stress versus tensile and compressive strain, 214–215
 tubes
 buckling, 212, 217–218
 failure modes, 215–216
 in-plane shear behavior, 216, 219
- Shear, 93, 224
 properties, composite sandwich materials, 42
- Shear modulus, 224, 227
 initial, 250
- Shear stiffness, 37, 39
 composite sandwich materials, 43
- Shear stress
 along notch flank, 250, 257–258
 distribution between notches, 250, 259
 versus shear strain, 280–282
 versus tensile and compressive strains, 214–215, 218, 222
- Shear stress-strain curve
 Kevlar/epoxy tubes, 217–218, 221
 S-glass/epoxy, 212–214
- Shear testing, 231, 276
 fiber reinforced composites, 103–107
- Short beam shear testing, 104
 statistical data reduction, 120–123, 125–126
- Short-fiber reinforced thermoplastics, 45–54
 compression properties, 50
 fracture modes, 50–51, 53
 fracture toughness, 50, 52–53
 L and T orientations, 47–49
 materials, 46
 specimens, 46–47
 stress-strain curves, 48
 tensile properties, 47–50
 test methods, 47
- Silicon carbide, 261
 abrasive wear, 80
 mechanical properties, 263
- Single shear test specimen, 129
- Sliding directions, 77–78
- Space antenna, 31
- Standardization, 93
- Static compliance tests, graphite/epoxy composite, 155, 157–158
- Statistical data reduction, 111–134
 graphite/epoxy, 131
 laminate tests, 126–130
see also Lamina tests
- Statistical methods, design allowables calculation, 136–149
 ANOVA method, 145–147
 between-batch variance, 146
 computational procedure, 137–138
 detecting outliers, 138–139
 distribution identification, 142–145
 goodness-of-fit tests, 138
k-sample Anderson-Darling test, 139–141
 lognormal analysis procedure, 148
 maximum normed residual test, 138–139
 nonparametric analysis procedure, 148–149
 normal analysis procedure, 148
 normality test, multiple batches, 141
 observed significance level, 141–144
 test for equality of variances, 141–142
 two-parameter Weibull analysis procedure, 147
- Stiffness, 180, 208
 degradation, 187–188, 276
- Strain gage, 182
 configurations, 235
 embedded, 17–18
- Strain rate
 effects, 16
 transverse modulus as function of, 22
- Strength, 180, 208
- Strength tests, graphite/epoxy composite impacted specimens, 165–169
 undamaged specimens, 157, 164–165
- Stress concentrations, 261
- Stress ratio, 250, 259
- Stress-strain curves
 glass/ceramic matrix composites, 10, 12–14
 short-fiber reinforced thermoplastics, 48
 transverse, graphite/epoxy composite, 20–21
- T**
- Tensile properties, short-fiber reinforced thermoplastics, 47–50
- Tensile strength
 through-the-thickness strength specimen, 203
 ultimate, 116, 123
- Tension, 45, 93

- Tension specimens, composite sandwich materials, 34, 37
 - Tension stiffness, 183
 - Tension testing
 - fiber reinforced composites, 96-99
 - statistical data reduction, 114-116, 120, 123-124
 - Testing facility, high temperature composites, 6
 - Test methods, 93, 180
 - Thermoplastics, 45; *see also* Sand erosion
 - Thermoset composites. *See* Sand erosion
 - Through-the-thickness strength specimen, 197-206
 - development, 198-199
 - failure surfaces, 204-205
 - fiber and loading directions, 202
 - final specimen configuration, 199-200
 - preparation and testing, 200-202
 - recommendations, 205-206
 - tensile strength, 203
 - test matrix, 202-203
 - Time-temperature-moisture master curves, 22-23, 25-29
 - Time-temperature moisture shift factor, 27, 29
 - Time-temperature shift factor, 23-25
 - Torque-displacement curve, pultruded rod, 225, 227
 - Torsion, 224
 - potential energy, 228
 - Torsion tubes, 208-223
 - analytical approach, 208-209
 - buckling study, 212-216
 - in-plane shear, 216-222
 - materials and preparation, 209-211
 - test procedure, 211-212
 - Transverse extensometer, 9
 - Transverse modulus, as function of strain rate, 22
 - Transverse shear, 228
 - Transverse stress, 250, 252, 255
 - Transverse tension testing, fiber reinforced composites, 97-98
 - Two-parameter Weibull analysis procedure, 147
- U-V**
- Unidirectional continuous fiber, 75
 - abrasive wear, 79-82
 - Variance, test for equality, 141-142
- W-Y**
- Weibull analysis, two-parameter, 147
 - Weibull distribution, 113, 142
 - Weibullness, Anderson-Darling test, 143
 - Width-tapered specimen geometry, 8-9
 - Woven fabrics, 75
 - Woven fiber system, two-dimensional, abrasive wear, 82-86
 - X-ray tests, graphite/epoxy composite, 155
 - Yielding, 261