

# Index

## A

- AC1 temperature
  - Effect of chromium equivalent, 372
- Aging
  - Activation energy of, 168
  - Comparison of austenitic versus martensitic steels, 434
  - Effect on ductile to brittle transition, 176
  - Effect on impact properties, 167, 172, 432
  - Effect on microhardness, 173
  - Influence of molybdenum, 188
  - Parameter for, 172
  - Prediction of, 186
  - Weld metal, 430, 433
- Alloy grades
  - CA15, 369
  - CA6NM, 216, 315, 333, 395, 403
  - CB7Cu-1, 85, 356
  - CF3, 20, 27, 105
  - CF3A, 27
  - CF3M, 15, 105
  - CF8, 27, 105, 165
  - CF8C, 85, 93, 105
  - CF8M, 27, 63, 87, 105, 167, 245
  - CF20, 87
  - HE, 261
  - HD, 261
  - HF, 225, 269, 275
  - HK35, 278
  - HK40, 245
  - HK42, 278
  - HK44, 278
  - HP44, 278

HP45, 275

HP47, 278

HP50, 278

Alloy nomenclature, 6

Alloy trade names

16Cr-5Ni, 382

17Cr-4Ni, 201, 382

Uranus 50, 52

AOD process, 216, 405

## B

Boiling water reactor components, 26

Butterfly value, 22

## C

Carbide precipitation, 342

Carbon content

Effect on ferrite, 37

Effect on IGSCC, 44

Effect on impact strength, 99, 323

Carburization, 310

Casting imperfections (flaws)

Gas porosity (cavities), 95

Hot tears (cracks), 94

Nonmetallic inclusions, 95

Shrinkage, 94, 226

Corrosion

Abrasion, 57, 212

Fatigue, 206, 365, 390, 420

Pitting, 56, 212, 364

Corrosion resistance

Acetic acid, 389

Hydrogen sulfide, 262, 219

Phosphoric acid, 54  
 Reducing flue gas, 262  
 Seawater, 214, 366  
 Sodium chloride, 364  
 Sulfuric acid, 54  
 Creep strength, 271, 272, 273, 292,  
 299, 373

**D**

De-embrittlement, 339  
 Delta ferrite, 19, 31  
 Dilatometry, 116  
 Dimensional stability, 15  
 Directional solidification, 94

**E**

Electron microscopy, 37  
 Electroslag casting, 60  
   Slag compositions for, 63  
 Embrittlement, 166  
 Embrittlement rate, 186, 339  
 Equilibrium diagram, 109  
 Erosion (cavitation), 374  
 Expansion coefficients, 117

**F**

Failure mode  
   Ductile rupture, 37  
   Mixed, 37  
   Transgranular cleavage, 37  
 Fracture appearance transition tem-  
   perature, 345, 352, 361  
 Ferricyanide test, 23  
 Ferrite distribution  
   Aging effects, 173  
   Effect on IGSCC, 44  
   Effect on mechanical properties, as,  
     73, 274  
   Function of chemical composition, as,  
     106

Function of expansion coefficients,  
   as, 123  
 Function of heat treatment, as, 52,  
   106  
 Function of nickel and chromium  
   equivalents, as, 131  
 Function of nitrogen, as, 261  
 Function of solidification, as, 106  
 Function of thickness, as, 112, 115  
 Microhardness of, 173  
 Number, 69, 113, 127  
 Parameter for, 45  
 Predicting content of, 105, 150

Ferrite measurement  
   Dilatometry, 106  
   Ferritescope, 31, 130  
   Magnegage, 31, 130, 260  
   Metallographic, 31, 109, 129, 141  
 Fluidity, 204  
 Fractography, 39, 339

**G**

Gas content, 320, 413  
 Gating practice, 96

**H**

Hardness  
   Function of austenite, as, 386  
   Function of chromium as, 359  
 Heat treatments  
   Effects on weld hardness, 324  
   Normalize and temper, 322  
   Precipitation hardening, 50, 204  
   Solution anneal, 18, 28, 50  
   Stress relief, 18, 28  
 Hot tearing, 52, 106, 202, 226  
 Hydrogen embrittlement, 218  
 Hydrogen sulfide, 329

## I

- Impact strength
  - Effect of AOD process, 321
  - Effect of carbon and niobium, 99
  - Effect of silicon and molybdenum, 353
  - Frequency distribution, 100
  - Function of cooling rate, as, 337, 344
  - Function of tempering temperature, as, 205, 344
  - Influence of tin, 190
  - 17-4 steel, 206
  - Weld metal, 104
- Impact transition curve, 361, 388
- Intergranular stress corrosion cracking, 27, 41
- Investment casting, 79, 226
- Isothermal transformation diagram, 335

## L

- Larson-Miller parameter, 302, 376

## M

- Mechanical properties
  - Aging effects, 290
  - Effect of AOD process, 406
  - Effect of composition, 411
  - Effect of cooling rate, 370, 418
  - Effect of ferrite content, 52
  - Effect of molybdenum, 353
  - Effect of nitrogen, 266
  - Effect of silicon, 353
  - Effect of tempering temperature, 205, 343, 347, 371, 386
  - Effect of thickness, 102, 207
  - Elastic modulus, 286, 291
  - Elevated temperature 208, 267, 281, 286, 372

- Impact, 284
  - Low temperature, 209, 427
  - Martensitic steels, of, 360, 385
  - Weld metal, of, 424
- Microhardness, 19
- Microstructure
  - After creep-rupture, 308
  - Cracking, 19, 338
  - Duplex, austenite plus ferrite, 31, 42, 48, 105, 110, 126
  - Effect of treatment, 50
  - Hot tears, 232
  - Martensite, 202
  - Retained austenite, 204
  - Shrinkage, 238
  - Stability, 302
  - Welds, 257

## N

- Nil ductility transition temperature, 206
- Nitrogen
  - Effect on elevated temperature strength, 269, 271
  - Effect on room temperature strength, 266, 268

## O

- Oxalic test, 23

## P

- Poisson's ratio, 291
- Potential dynamic polarization, 366

## Q

- Quantitative metallography, 141

**R**

Repair welding, 99, 395, 420  
 Residual elements, 191  
 Retained austenite, 341, 351, 362,  
 373, 386  
 Runner systems, 96  
 Rupture strength, 271, 273, 292, 297,  
 300

**S**

Schaeffler diagram, 357  
 Schaeffler diagram-modified, 108  
 Segregation, 70, 234, 419  
 Sensitization, 18  
 Sigma phase, 19, 50  
 Solidification, 6  
 Sulfide stress cracking, 327  
 Sulfur content, 407  
 Surface iron contamination, 22  
 Surface hardening  
   Hardfacing (welding), 28  
   Nitriding, 28  
 Stress corrosion, 30, 56, 214  
 Stress corrosion tests  
   C-ring, 374  
   Constant-load, 30  
   Constant-extension rate, 30  
   Cyclic tension, 30  
   Variable-load, 30

**T**

Tin effects, 190  
 Turbine shells, 376

**U**

Ultrasonic testing, 93

**V**

Valve body, 16

**W****Weldability**

  Implant tests, 216, 363  
   Variable restraint test, 241  
**Welding**, 21, 363, 387, 395  
   Composition, 253, 255  
   Hardness, 399  
   Heat-affected-zone, 399  
   Mechanical properties, 424  
   Microstructures, 252, 254, 257  
   Post-weld-heat-treatment, 28, 54,  
     324, 401, 423  
   Strain versus cracking, 249  
 Welding overlay, 21  
 Weld metal composition, 397, 424  
 Whirlgate, 96

**X**

X-ray diffraction, 341

**Y**

**Yield strength**  
   Elevated temperature, 206