

# Index

- A**
- Applications
    - Automotive, 3
    - Nonautomotive, 7
- B**
- Bernoulli law, 19
- C**
- Cure time, 33
- D**
- Definitions
    - Microcellular, 32
    - Reaction injection molding, 32
  - Dynamic mechanical testing
    - Dynamic modulus, 71
    - Effect of temperature, 80-84
    - Flexural modulus versus shear strength, 70
    - Impact, 69
    - Poisson's ratio, 76, 73
    - Static modulus, 69
- F**
- Fillers, 23
  - Flexural modulus, 70
- H**
- Heat sag, 46-55
    - Fascia, 55
    - High modulus, 55
    - Molding specimens, 49
    - Statistics, 49
  - Test fixture, 48
  - Test results, 50
- I**
- Impact testing, 3, 69, 87
    - Bumperette, 91
    - Falling weight, 88-89
    - High speed tension, 88
    - Pendulum, 88
    - Variable rate, 89
  - Impingement mixing, 4, 6, 15-23, 35
- L**
- Loss modulus, 75
- M**
- Machine, reaction injection molding
    - Cleaning and flushing, 29
    - Lance metering pump, 16, 24
    - Lead lag phenomena, 24
    - Output, 33
  - Mini units, 26
    - Piston metering pumps, 28, 34
    - Pressure, 4, 15
    - Ratio controls, 26
  - Mixing
    - Effect of Bernoulli law, 19
    - Effect of Reynolds number, 15, 19
    - Effect of viscosity, 19
    - Head, 29, 35
    - Impingement, 4, 6, 15-23, 35
  - Molds
    - Carriers, 40
    - Clamp pressure, 5

Clamps, 40  
Description, 5, 45

**N**

Nucleation, 37

**P**

Poisson's ratio, 76, 81  
Processing temperature, 5  
Production rates, 5

**R**

Reynolds number, 16, 19

**S**

Shear modulus, 69, 85  
Static modulus, 73  
Storage modulus, 75

**T**

Thermal expansion test  
Effect of specimen orientation, 60  
Effect of post cure, 60  
Effect of relative humidity, 61  
Round robin results, 68  
Test results, 60-67