

Index

- A**
- Acoustic emission, 38
 Aircraft storage environment, 192
 Aircraft structures, 78, 116
 Analysis of variance, 263
- B**
- Biaxial failure, 23
 Bolt clampup, 5
 Bolted joint, 5
 Boron/aluminum laminates, 160
 Boron fibers, 175
 Box beam, 55, 69
 Buckling, 157
- C**
- Carbon fiber/epoxy laminates (*see*
 Graphite/epoxy laminates)
 Chain bundle theory, 39
 Characteristic damage states, 140
 Clampup forces, 5
 Compliance, 5
 Compression fatigue, 95, 116, 136, 225
 Compression strength, 103, 225
 Constant-amplitude loading, 55, 95,
 116, 225
 Creep, 38
 Creep compliance, 23
 Cycles to failure, 55
 Cyclic hardening, 160
- D**
- Delamination, 55, 95, 116, 157
 Diffusion model, 192
 Double-lap joint, 5
- E**
- E-glass/epoxy laminates, 55
 Empirical equation, 5
 Environmental cycling, 194
 Equilibrium free volume, 190
- F**
- Failure modes, 225
 Failure theory, 139
 Fatigue
 Damage, 95, 116, 136, 160
 Life, 55, 78, 95
 Threshold, 134
 Fiber breaks, 39
 Fiber bundle chain, 38
 Fiberglass, 55
 Fickian diffusion, 201
 Filament wound, 38
 Flexure strength, 206
 Flexure test, 206
 Frequency effects, 55, 78
- G**
- Graphite/epoxy laminates, 5, 23, 38,
 78, 95, 116, 136, 179, 192,
 225, 246
 Graphite/polyimide composites, 206

H

Heating effects, 75
 Heavy water vapor, 192
 Hygrothermal shift factors, 5

I

Impact, 116
 Damage, 116
 Energy, 116
 Internal damage, 116
 Isothermal aging, 208

K

Kaiser effect, 39
 Kevlar 49 epoxy, 263
 Knife-edge supports, 116

L

Least-squares regression, 5
 Load sequence effects, 246
 Lognormal distribution, 225
 Low-velocity impact, 116

M

Material memory effect, 246
 Matrix cracking, 55, 95, 157, 160
 Matrix degradation, 78
 Mean failure time, 263
 Microcracks, 190
 Moisture, 5
 Absorption, 179
 Distributions, 192
 Transport model, 195
 Moisture-saturated composites, 179

N

Nondestructive tests, 136
 Notched laminates, 95
 Nuclear reaction analysis, 192
 Numerical stability, 23

P

Power law, 263
 Pressure vessels, 38, 263

R

Relaxation rate, 5
 Replication, 95
 Residual strength, 103, 136, 157, 225
 Reverse thermal effect, 190

S

Scanning electron microscopy (SEM),
 202, 215
 Short beam shear, 206
S-N curve, 55, 100, 116, 174
 Spike loading, 55
 Spool variation, 274
 Square wave, 55
 Stacking sequence effects, 95
 Statistical dispersion, 246
 Steady state, 5
 Stiffness loss, 95, 136, 160
 Strength reduction, 95, 116, 157
 Stress ratio, 55
 Stress rupture, 56
 Sudden failure, 39
 Supersonic flight, 192

T

Temperature, 5
 Temperature profiles, 192
 Tension-compression fatigue, 116,
 225
 Tension fatigue, 55, 116, 136, 246
 Tetrabromoethane (TBE), 95
 Thermal oxidative stability, 206
 Thermal spike, 179, 192
 Thick laminates, 95
 Time under load, 55

U

Ultrasonics, 116
Unidirectional composites, 38, 160,
206

V

Vacuum anneal, 179
Viscoelastic analysis, 5, 23
Viscoelastic properties, 38
Visible impact damage, 116
Void nucleation and growth, 190
Volume changes, 190
von Mises criterion, 175

W

Waveform, 75
Weakest-link model, 38
Weibull distribution, 39

X

X-ray radiography, 95

Y

Yield stress, 160