

Index

A

- Accept/reject criteria, 260
- Aircraft structure, 272
- Alignment, 123, 324, 345
- Alloy data
 - Aluminum, 8, 10-12, 17, 19, 21, 22, 24-26, 31, 33, 35, 36, 197-199, 209-215
 - Nickel-based, 15, 79, 80
 - Steel, 13, 18, 31, 37, 47, 49, 50, 122, 131, 132, 135, 136, 150, 163, 302-304
 - Titanium, 15, 259
- American Association of State Highway and Transportation Officials (AASHTO), 300
- American Society for Testing and Materials (ASTM)
 - Method E 647-78 T on Constant Load Amplitude Fatigue Crack Growth Rates Above 10^{-3} m/Cycle, 1, 5, 6, 7, 46, 56, 71, 86, 98, 100-102, 321-339
 - Subcommittee E24.04 on Subcritical Crack Growth, 6
 - Task Group E24.04.03 on Near-Threshold FCGR Testing, 6
 - Task Group E24.04.04 on FCGR Relationship, 205
- American Society of Mechanical Engineers (ASME) Boiler and Pressure Vessel Code, 281

- American Welding Society (AWS), 301
- Anomalous ("False") fatigue crack growth rates, 18, 20
- Apparatus, 323, 343

B

- Boiling Water Reactor (BWR) environment, 139
- Bridges, 300

C

- Clip gage, 86
- Compliance relationship, 51, 62
- Computer controlled testing, 58
- Constant amplitude loading, 9, 321
- Constant deflection loading, 9
- Crack closure, 18, 217
- Crack closure model (*see* Fatigue crack growth rate descriptions)
- Crack curvature, 39, 42, 53, 90, 204, 327, 353
- Crack geometry/length, effect of, 18
- Crack growth
 - Errors in measurement of, 169, 195
 - Increment (Δa), 39, 196-203, 327, 352
 - Monitoring techniques, systems
 - Acoustic emission, 139-160

Compliance, 86-90, 100-102, 143
 Electropotential, 103-119, 123-125, 136
 Visual, 31, 196
 Prediction of 256, 283-285
 Crack opening load, 20, 21
 Critical flaw size, 282
 Curve fitting procedures-relationships (*see also* Regression analysis, Fatigue crack growth rate descriptions), 23, 24, 27, 173-175
 Cyclic plastic zone, 44

D

Data processing (*see also* Statistical analysis of crack growth data, Regression analysis, Secant method, Incremental polynomial method of da/dn data reduction), 1, 32, 125, 194-203, 353
 Definitions, 322, 342

E

Effective stress-intensity factor, 20
 Elastic perfectly plastic material, 53
 Electronic circuitry, 60, 64
 Embedded defect, 283
 Endurance limit, 37
 Environmental effects, 23, 30, 34
 Estimate of error of variance in growth rates, 172, 187, 199
 Experimental scatter, 35-38, 42, 90, 131

F

Fail safe design philosophy, 272
 Fatigue crack growth rate descriptions, 6, 23, 29, 205-251, 293

Crack closure model, 217
 Five-parameter model, 217, 220
 Four-parameter Weibull distribution function, 24, 220, 243
 Hyperbolic sine equation, 220, 236-243
 Modified power law equation, 216, 217
 Power law equation, 206, 283
 Tabular procedure, 221, 248-250
 Tensile ligament instability model, 221, 246
 Three-component model, 221, 246
 Fatigue crack growth rate measurement, 14, 327, 353
 Fatigue crack growth retardation, 6
 Flow stress, 46, 56
 Fracture control, 1
 Fracture toughness, 6, 260
 French Metallurgical Society, 30, 42
 Frequency of cyclic loading, 30, 42
 Effect of, 33, 122

G

Grain orientation, effect of, 33, 36
 Grain size, effect on threshold, 43
 Grips and fixtures, 323, 343
 Ground vehicle industry, 171

H

Hall-Petch relationship, 44

I

Incremental polynomial method of da/dN data reduction, 90-93, 100, 125, 172, 188, 196-198, 202, 333, 353
 Interruptions in testing, 17

J

J-Integral, 292

K

- K*-decreasing method, 7, 21, 59, 342
 - Normalized rate of *K*-decrease, 14, 342, 350
 - Requirement on rate of *K*-decrease, 14, 39, 59, 351
- K*-increasing method, 7, 21, 342, 350

L

- Life prediction, 206, 256, 260
- Load shedding (*see* Programmed load shedding)
- Load versus crack opening displacement
 - Measurement of, 51, 85-102, 337
 - Relationship of (*see* Compliance relationship)
- Long cracks, 18
- Low fatigue crack growth rates (*see* Near-threshold crack growth rates)

M

- Material data (*see* Alloy data)
- Mathematical models (*see also* Fatigue crack growth rate descriptions), 1
- Metallurgical effects, 37
- Microstructure, 7, 43, 147

N

- Near-threshold crack growth rates, 1, 5
 - Method of test, 1, 5, 340
- Nondestructive inspection, 256, 264, 313
- Nonlinear regression, 24
- Notch
 - Effect on crack growth rates, 133
 - Preparation of, 325, 347
- Nuclear components, 281

O

- Overloads, 15

P

- Part-through crack, 125, 283, 286-293
- Plastic deformation, 45, 337, 338
- Plastic zone (size), 14, 46, 134
- Precracking, 7, 14
 - Minimum length requirement, 20, 27, 54, 56, 325, 349
- Probabilistic fracture mechanics, 268, 272
- Programmed load shedding (*see also* *K*-decreasing method), 9, 10, 30, 37, 42

R

- Random process theory, 203
- Regression analysis (*see also* Curve fitting procedures-relationships), 25, 26, 48, 78, 173-180, 189, 230
- Reliability/risk, 255, 280
- Remaining ligament criteria (*see* Specimen size requirements)
- Reporting requirements, 328, 354
- Residual stresses, 256
- Retirement for cause, 266, 267
- Rolling direction (*see* Grain orientation)
- R*-value (*see* Stress ratio)

S

- Safe life design philosophy, 272
- Scatter (*see* Experimental scatter)
- Secant method, 31, 48, 75, 90, 100-102, 196-198, 202, 333, 353
- Small cracks, 18, 120-137, 313
- Society of Automotive Engineers (SAE), 171

Specimen configuration/size, effect of, 33, 34, 39, 42
 Specimen size requirements, 1, 45, 56, 324, 337, 347
 Specimen type
 Center-crack tension (CCT), 9, 324, 329, 344-347
 Compact (CT), 9, 81, 324, 329, 343-347
 Round compact, 70-82
 WOL, 86
 Spectrum loading, 6
 Standardization of fatigue crack growth rate testing, 6
 Statistical analysis of crack growth data, 163-170, 172-186, 199-202, 363
 Statistical nature of crack growth, 164
 Steady-state fatigue crack growth rates, 18, 26
 Step loading, 93-98
 Strain hardening material, 46, 53, 56, 337
 Stress-intensity factor solutions, 71-74, 257, 327, 328, 354
 Stress ratio (R), 7, 10, 260
 Effect of, 11-13, 20, 21, 30, 34, 36, 42, 51, 231
 Surface flaw (*see* Part-through crack)

T

Test procedures, general, 359

Thickness, effect of (*see* Specimen configuration/size)
 Threshold
 False interpretation of, 20
 Operational definition, 23, 354
 Stress-intensity factor range (ΔK_{TH}), 1, 5, 6, 29, 30, 42, 205, 354
 Transient fatigue crack growth rates, 7, 9, 17, 37
 Effect of crack size and geometry on, 18
 Effect of environment on, 23
 Minimizing effect of, 17-23
 Tunnelling (*see* Crack curvature)

U

U.S. Airforce Damage Tolerant Design Handbook, 283

V

Vacuum, tests in, 30, 34

W

Waveform of cyclic loading, 30, 42
 Welded components, 301
 Weldments, fatigue behavior of, 304-309

Y

Yield strength, 46