

# Index

- A**
- Adsit, Norman R., 175-186
- Aluminum
- Axial compression of 6061-T651, 44-47
  - Axial compression of 7075-T6, 44, 47-48
  - Grain size, 48
  - Pure aluminum ring test, 83-90
  - Strain to fracture of 2024-T351, 286
- Avva, V. Sharma, 140-154
- B**
- Barreling
- Hot compressed steel rings, 69-70
  - Stress computation, 42
  - Stress-strain state, 15-16
  - Upset tests of OFHC copper, 28
- Buckling
- Dynamic in graphite/epoxy composites, 145
  - Euler, 165, 169-172, 249
  - Failure threshold, 143-145
  - Isogrid damaged panel, 193
- Bulging (*see* Barreling)
- C**
- Ceramic fiber board, 109-115
- Ceramics testing (*see* Eccentrically loaded column)
- Chait, Richard, editor, 1-3
- Chamos, Christos C., 155-174
- Clark, Ronald K., 200-220
- Complementary energy solution, 204
- Composites, metal matrix
- Depleted uranium/tungsten, 258
  - FP alumina/aluminum, 249-251
  - FP alumina/magnesium, 249-251
- Composite, resin matrix
- AS/PR288, 156
  - AS/3501, 177
  - E-glass/1002, 177
  - Kevlar 285-weave/Cycom 5143, 243
  - Kevlar 49/Narmco 5208, 223
  - Kevlar 49/Narmco 5209, 223
  - S2-glass/SP250, 243
  - SP288/AS, 122
  - SP288/T300, 122
  - T300/934, 177
  - T300/5208, 141, 156, 177, 243
- Computer simulation of axial compression (*see* HEMP code)
- Copper
- Isothermal forging of OFHC, 28-33
  - Lubrication effect on ring test deformation, 92
- Cracking in compression
- Al 6061-T651, 46-47
  - Al 7075-T6, 47-48
  - Arrest in ceramics, 98-99
  - As a failure criterion, 41
  - Ceramic column specimens, 99-100
  - Detection by dye penetrant, 15, 43
  - Internal in 97% tungsten alloy, 56-57
  - Shear microcracking, 47, 61-62

- Cracking in compression (*continued*)
  - Steel 4340, 49–52
  - Textured titanium Ti-4Al-4V, 60
  - Tungsten alloys, 54–60
- Creep of vacuum formed board, 113, 117

## D

- Dadras, Parviz, 24–39
- Daniel, Isaac M., 121–139
- Dead zone
  - Effect of die chilling on, 38
  - Experimental, 13, 52, 55
  - Inhomogeneous compression of copper, 30
  - Theoretical description, 12, 14
- Devenpeck, Marshall L., 64–77
- Die chilling in forging, 38
- Dye penetrant test, 42, 43, 55–56, 62

## E

- Eccentrically loaded ceramic column, 98–103
- Edge-loading theory
  - Bending, 209–211
  - Compression, 205–209
- Edge loading numerical results
  - Cross-ply laminates, 215–217
  - Quasi-isotropic laminates, 211–215
  - Unidirectional laminates, 217–218
  - Young's modulus, 218
- Ericksen, Richard H., 221–240
- Erman, Emin, 279–290

## F

- Failure modes in composites
  - Brooming, 256
  - Dynamic, 145–148
  - Static, 164–167, 234–237
- Finite element analysis, 195
- Fitzsimons, Guillermo, 279–290
- Fixture, specimen loading
  - ASTM D 695, 177, 178

- ASTM D 3410, 177–179, 242
- Celanese (*see* ASTM D 3410)
- Direct compression, 246, 257
- Dynamic impact, 142–143
- Dynamic ring compression, 123–124
- Eccentric column, 99–102
- IITRI, 157, 177, 180
- Panel support, 141–142
- Sandwich beam, 177, 180

## Flow stress

- Aluminum alloys, 44
- Isothermal forging, 26
- Ring-test, 78–80

Fold over (*see* Roll over)

## Forging

- Isothermal, 26
- Loads for, 27
- Nonisothermal, 26, 35

Fracture (*See also* Cracking)

- Criteria, 15, 19, 21, 41, 53
- Ductile tensile, 8
- Localized thinning model, 280
- Void growth model, 281
- Zones of origination, 14, 19–20

## Fracture strains, experimental

- Al 2024-T351, 286, 288
- Sintered 4640 steel powder, 287
- Steel 1045, 287

Friction factor (*See* Specimen-anvil friction)

## G

- Guess, Tommy R., 221–240

## H

- Haag, Richard S., 187–199
- Halo in ring test, 70–71, 74
- Hansen, Anna M., 40–63
- HEMP code
  - Analytical technique, 9
  - Computation results for steel 4340, 11–17, 43

Friction boundary conditions, 9-10  
 Provision for roll over, 10  
 High strain-rate testing of composites, 122-128

## I

Interface friction factor (*See* Specimen-anvil friction)

## J

Johnson, Thomas A., 109-118

## K

Kim, Chulko, 254-275  
 Kuhn, Howard A., 279-290

## L

La Bedz, Ralph H., 121-139  
 Lamothe, Roger M., 241-253  
 Load-displacement  
   Copper OFHC, 28, 30  
   Steel 4340, 49-50  
   Titanium Ti-6Al-2Sn-4Zr-2Mo, 34  
 Load-height reduction (*See* Load-displacement)  
 Lubricants  
   Bl semisynthetic oil, 68  
   Caprylic and oleic acid, 1  
   Graphite, 68, 69  
   Graphite grease, 2  
   Hydrograph, 86  
   Lead, 1  
   Mineral oil, 1  
   Molybdenum disulfide powder, 2  
   Petroleum motor oil 20-W, 68  
   Powdered glass, 2  
   Silicone-free lecithin, 68  
   Sodium stearate soap, 1  
   Stearic acid, 1  
   Teflon, 1, 28, 83

## M

Mack, Steve, 97-108  
 Martorell, Ivan A., 78-94  
 McLaughlin, James, 7-23  
 Mescall, John, 7-23, 40-63  
 Modulus of composites, 227-230, 252, 264-266, 270

## N

Neutral radius in ring test, 81-82  
 Nunes, John, 241-253

## O

Okada, Tatsuo, 97-108  
 Orange peel effect (*See* Surface wrinkling)  
 Ovality in ring test, 69-70

## P

Papirno, Ralph, editor, 7-23, 40-63  
 Pattnaik, Amitav, 254-275  
 Poisson's ratio in Kevlar/Narmco composites, 231-232

## R

Reddy, Ambur, 187-199  
 Rehfield, Lawrence W., 187-199  
 Reiss, Robert, 200-220  
 Restricted deformation conical zone (*See* Dead zone)  
 Rigo, Jane H., 64-77  
 Roll over  
   Copper, 29-30  
   HEMP code prediction, 10, 12  
   Nonisothermal forging, 35  
   Steel 4340, 13, 55  
 Round robin test results, 181-182

## S

Schenck, Steven R., 109-118  
 Shear zone

Shear zone (*continued*)

- Fracture in tungsten alloy, 57
- HEMP description, 10-12
- Sinclair, John H., 155-174
- Sines, George, 97-108
- Spalling, 98
- Specimen-anvil friction
  - Effect on deformation of aluminum rings, 84-88
  - Effect on forging pressure, 88-90
  - Effect on hardness in copper, 30, 32
  - Effect on stress-strain behavior, 26-28, 32-33, 36
  - End grooves, 2
  - Factor from ring tests, 71-74, 80-81
  - HEMP code modeling, 9-10
  - Historical attempts to control, 1
  - Sticking in ring tests, 74
- Steel
  - Axial compression of 4340, 49-53, 62
  - Fracture strains
    - In 1045, 283
    - In 4640 sintered powder, 287
  - HEMP code results for 4340, 11-17, 51-53
  - Low-carbon hot-rolled, 67
  - Strength differential effect, 2
  - Stress function, 25, 38
  - Stress-height reduction
    - Experimental for
      - Al 6061-T651, 45, 46
      - Al 7075-T6, 45
      - DU/45W(305), 262, 264
      - DU/45W-3Re(305), 262, 264
      - Steel 4340, 51
    - Theoretical for steel 4340, 18, 52, 53

## Stress-strain curves for

- Ceramic, 107
- Graphite/epoxy dynamic, 131-132, 137
- Graphite/epoxy static, 160-161
- Kevlar 49/Narmco, 227, 233
- Narmco 5209 resin, 227, 233
- Surface wrinkling for
  - Aluminum, 45, 47-48
  - Tungsten, 54, 56, 58-60, 61

## T

- Thomas, Joseph T., Jr., 24-39
- Titanium
  - Fracture of Ti-4Al-6V, 60
  - Isothermal forging of Ti-6Al-2Sn-4Zr-2Mo, 26, 33-35
  - Nonisothermal forging of Ti-6Al-2Sn-4Zr-2Mo, 37-38
- Tungsten alloys, 54-59

## U

- Upset test
  - HEMP code simulation (*See* HEMP code)
  - Isothermal stress distribution, 26-28
  - OFHC copper at room temperature, 28-33
  - Nonisothermal predictions, 36-38
  - Ti-6Al-2Sn-4Zr-2Mo, 33-35

## W

- Weimer, Raymond J., 254-275
- Widman, Carolyn G., 187-199

## Y

- Yao, Tse-Min, 200-220