

Subject Index

A

Accelerated tests, 235
 Acoustical computer sensing, residual strength prediction, 285
 Art, fatigue and fracture, 301

B

Biaxial tests, carbon fiber composites, 19
 BMI, 179
 Bond strength, 97
 Bridging stress-intensity factor, 122

C

Carbon epoxy composites
 biaxial tests, 19
 fatigue debonding, 97
 tensile preload effects, 249
 Carbon fiber composites, biaxial test results, 19
 Center crack, 122
 Ceramic matrix composites, life prediction at elevated temperatures, 165
 Chemical aging, 179
 Composites
 art, fatigue and fracture, 301
 carbon fiber, 19
 ceramic matrix, life prediction at elevated temperatures, 165
 fatigue debonding, 97
 IM6/3501-6, 145
 with in-plane fiber waviness, 76
 interlaminar shear fracture toughness, 3
 titanium matrix, 55
 Compression strength, composites with in-plane fiber waviness, 76
 Compression testing, 76
 Contact force, 273
 Coulomb friction-based fiber-bridging model, 55
 Crack growth rate, Ti-6Al-4V with SiC fibers, 122
 Crack opening displacement, Ti-6Al-4V with SiC fibers, 122
 Cyclic loading, Ti-6Al-4V with SiC fibers, 122

D

Damage resistance, 249

Damage tolerance, 165
 Deflection, maximum, 273
 Delamination, 249
 fatigue-induced growth, graphite/epoxy laminates, 34
 Design, debonding, 97

E

Energy absorption, 273
 Environmental fatigue, pultruded glass-fiber-reinforced composites, 217
 Epoxy, toughened, 249

F

Fatigue crack growth, titanium matrix composites, 55
 Fatigue testing, debonding, 97
 Fiber bridging, 55, 122
 Fiber/matrix interface, titanium matrix composites, 55
 Fiber/matrix interphase, 217
 Filament wound, 263
 Finite element analysis, in-plane fiber waviness, 76
 Flexural fatigue, 145
 Four-point-bend fatigue, 217
 Fracture in art, 301
 Fracture toughness, composite interlaminar, 3
 Free-edge delamination model, 249

G

Glass-fiber-reinforced composites, pultruded, 217
 Glass-reinforced epoxy resin, accelerated hot-wet aging tests, 235
 Graphite/bismaleimide composite, open-hole tension fatigue behavior, 179
 Graphite/epoxy composites
 cylinders, impact response mechanisms, 263
 laminates, fatigue-induced delamination growth, 34
 transverse tension fatigue, 145

H

Hot-wet aging conditions, 235

Hygrothermal effects, 235

I

IM6/3501-6 composite materials, transverse tension fatigue, 145
 Impact damage, residual strength prediction, 285
 Impact loading, laminated composites subjected to, 273
 Impact testing
 carbon/epoxy laminates, 249
 graphite/epoxy composite cylinders, 263
 In-plane fiber waviness, 76
 Instrumented impact, 249
 Interfacial wear effects, fatigue crack growth modeling, 55
 Interlaminar fracture toughness, 3

L

Laminated composites, impact loading, 273
 Launch tube, 263
 Layer waviness, 76
 Life prediction
 ceramic matrix composites at elevated temperatures, 165
 Ti-6Al-4V with SiC fibers, 122
 Longitudinal fatigue, 199
 Low-cycle fatigue, temperature and stress ratio effect, 199
 Low-energy impact, 263
 Low-velocity impact, laminated composites, 273

M

Mechanical testing, 199
 Metal matrix composite, with SiC fibers, 122
 Mural, fatigue and fracture, 301

N

Neural network techniques, residual strength prediction, 285
 Nondestructive evaluation, 249, 285

O

Open-hole tension, 179
 Optical computer sensing, residual strength prediction, 285

P

Ply waviness, 76
 Polymeric composites, 235
 Pressure vessels, 28

R

Remaining strength, 165
 Residual strength, 263
 prediction, optical and acoustical computer sensing, 285
 Rocket motors, 263, 285

S

Salt solution, environmental fatigue, 217
 Sculpture, fatigue and fracture, 301
 Secondary bonding, 97
 Shear, 3
 Shear lag model, 122
 Silicon-carbide fibers, 55
 Skin/flange interface, 97
 Stochastic model, fatigue-induced delamination growth, 34
 Strain, 285
 Strain energy release rates, 3
 Stress
 effect on open-hole tension fatigue behavior, 179
 ratio, effect on low-cycle fatigue behavior, Trimarc-1/Ti-6Al-2Sn-4Zr-2Mo, 199

T

Temperature
 ceramic matrix composites, life prediction, 165
 effect on low-cycle fatigue behavior, Trimarc-1/Ti-6Al-2Sn-4Zr-2Mo, 199
 effect on open-hole tension fatigue behavior, 179
 Tensile preloads, effects on impact response of carbon/epoxy laminates, 249
 Ti-6Al-2Sn-4Zr-2Mo, temperature and stress ratio effect on low-cycle fatigue behavior, 199
 Ti-6Al-4V with SiC fibers, fatigue crack growth, 122
 Titanium matrix composites
 fatigue crack growth modeling, 55
 with SiC fibers, 122
 temperature and stress ratio effect, 199
 Transverse fatigue, 199

Transverse tensile strength, IM6/3501-6
composite materials, 145
Trimarc-1, temperature and stress ratio
effect on low-cycle fatigue behavior,
199

V

Video image correlation, 285

W

Walker equation, 199
Wear, titanium matrix composites, 55
Weibull statistics, 145
Wire winding, 199