

# Subject Index

## A

- Air phase, 109, 157
- Alidrain drain, 652, 655, 658–659
  - compression versus time, 656–657
  - equivalent diameters, 660
  - repeatability, 661
  - technical specifications, 653
- Andreasen method, 491
- Anteus apparatus, 119, 694, 697
  - Leda clay, 702–704, 706
- Anteus back-pressure consolidometer, 109
- Anteus consolidometer, 437
- Anteus oedometers, modified, 158
- As-compacted prestress, 111, 184, 191–193
  - determination, 188–191
  - effect of water content, 191–193
  - equation, 193
- ASTM D 653: 86, 88
- ASTM D 698: 186
- ASTM D 1557: 186
- ASTM D 2435: 11, 87, 241, 244, 651, 654, 713–714
- ASTM D 4186: 171, 173–174, 176, 182–183, 443, 713–714
- Atterberg limits, profiles, 611–613
- Automated system, 217
- Automation, 112
  - adaptability of constant rate of strain consolidation test, 174

## B

- Bäckebol clay, stress-strain curves, 311
- Backpressure
  - cell, 283–284
  - consolidometer, 109
  - specimen saturation, 45–46
- Band-shaped prefabricated drains, 642–661
  - compression versus time
    - Alidrain wicks, 655–656
    - consolidation test with no wick, 655
    - wick drain testing program, 655, 657
  - consolidation, 648–650
  - drains, 651–653
  - equivalent diameters, 648, 660
  - loosely fitted filter jacket, 659
  - rate of consolidation, no wick test, 654
  - repeatability, 659, 661
  - results, 654–658
  - settlement, 657, 661
  - soil, 650–651
  - technical specifications, 653
  - testing sequence, 652
  - water release, 656–659, 661
  - wick drain consolidometer (*see* Wick drain consolidometer)
- Batiscan clay
  - creep and oedometer tests, 387
  - rheological behavior, 381
  - rheological model, 383
  - simulated MSL test, 396
  - soil parameters, 384
  - strain rate-strain relations, 390–391
  - strain rate-time relations, 388–389
  - stress-strain relations, 390–391
- Bemben method, maximum past pressure, 622–624
- Bentonite-sand mixtures, 627–640

- Bentonite-sand mixtures (*continued*)  
 classification diagram, 636  
 compression index, 639–640  
 consolidometer, 630  
 effect of salt infiltration, 636–638, 640  
 four-phase soil model, 629–630  
 fundamentals of study, 628–629  
 physical properties of specimens, 631  
 procedure and materials, 629–631  
 relationships between clay content and dry density, 635–636  
 specimen description, 632  
 structural model, 628  
 threshold nonclay void ratio, 634–635  
 void ratio and effective pressure relationships, 631, 633–636
- Bessel's function, successive roots, 28–29
- Biaxial consolidation test, 476–477  
 anisotropic properties, measurement, 465–467  
 anisotropic soils, 465–484  
 average consolidation, 472  
 comparison of permeabilities, 481  
 elastic constant determination, 473, 476  
 normalized flow through specimen end, 473  
 procedure, 469  
 results, 478–480  
 stiffness constants, 470, 479  
 test device, 468  
 test equipment, 468–469  
 tests on pepper shale, 480–484  
 theoretical behavior, 469–473  
 theoretical consolidation curves, 473  
 theoretical relationship for  $V_a$  versus  $V_r$  during consolidation, 474–475
- Biaxial consolidometer test, 120
- Biot's coupled consolidation theory, 583
- Bjerrum's model, 287
- Bjerrum's procedure, 435
- Boston Blue Clay, consolidation, 91
- Boundary conditions, 471
- Bounding surface, 593, 599, 608  
 invariant stress space, 600  
 parameters, 602
- Bourdon pressure gage, 221
- Breakpoint method, maximum past pressure, 620–622
- Brittle behavior, 610–625  
 breaking of cement bonds, 615  
 correlation to field undrained shear strength, 624  
 log plot construction, 615, 617  
 one-dimensional test curves, 613–618  
*See also* Vertical stress
- BS 1377, 209
- Bulk modulus, 588
- C**
- Cam Clay  
 elastic component of strain, 382  
 models, 118  
 modified, 583, 585
- Canadian clays, preconsolidation pressure, 310
- Cardboard strip-type drain, 644
- Casagrande construction, 222–223
- Casagrande logarithm, 194
- Casagrande's fitting method, 529
- Casagrande's logarithm of time fitting method, 225–226
- Casagrande's log  $t$  method, 127
- Casagrande's method, 613, 625  
 maximum past pressure, 618  
 replacement by curve rule method, 543–545
- Castleboard drain, 652, 660  
 technical specifications, 653  
 water release, 658
- Castor oil, 490  
 density-temperature characteristics, 495

- viscosity-temperature relationship, 494
- Cementation, post-depositional, 611, 625
- Cemented soil, 129–130
  - disturbance, 55
- Centrifuge
  - curved vertical stress distribution, 590
  - effect of friction and adhesion, 590
  - limitations, 589–591
  - radial acceleration field, 589
  - University of California at Davis, 570–571
  - See also* Selfweight consolidation test
- Centrifuge model, 125, 548, 593–608
  - bounding surface in invariant stress space, 600
  - bounding surface plasticity theory, 599
  - comparison with numerical model, 124–126
  - effective stress distribution, 598
  - finite-element analysis, 604–607
  - incrementalization of rate equations, 602
  - instrumentation and data acquisition, 596
  - isotropic consolidation results, 601
  - model package, 594–595, 597
  - pore pressure
    - dissipation during initialization, 604
    - response to loading and unloading, 605
  - results and comparison, 603–607
  - settlement during loading and unloading, 606
  - specimen preparation, 594–596
  - surface settlement during initialization, 603
  - testing program, 596–598
  - testing sequence, 597
  - undrained stress paths under triaxial conditions, 600–601
- Centrifuge test, 125–126, 716
  - advantages, 568
  - soft clay deformation (*see* Time-dependent numerical model, soft clay deformation)
- Champlain clay, 119, 719–720
  - preconsolidation pressure, 722
  - variation of  $\alpha_2$  coefficient with strain rate, 722
- Champlain Sea clay (*see* Leda clay)
- CHG test (*see* Controlled-hydraulic gradient test)
- Clay, 684
  - behavior and consolidation, 379–383
  - bulk density determination using gamma radiation, 123–124
  - characteristics, presenting strain rate effects, 720
  - consolidation strain, 85
  - content and dry density, 635–636
  - deposit, consolidation under load, 73
  - geological history and compressibility, 74–75
  - highly structured, preconsolidation pressure, 81
  - k*-line, 347–348
  - medium-to-stiff, trimming, 333
  - model specimen, 550
  - overconsolidation, 75–76
  - physical properties, 554
  - preconsolidation pressure, 309
  - remolded, 82
  - rheological behavior, 380
  - sensitive, 118
  - skeleton, deformation behavior, 118
  - soft plastic, constant-rate-of-strain test, 343
  - stiff, incremental loading oedometer test, 334
  - strain rate, 719
  - See also* specific clays
- Clayey gytja, properties, 311
- Clayey soil, 684, 717
  - classification diagram, 636

- Clay-kaolinite mixture, coefficient of consolidation, determination, 539–540
- Clay shale, 465
- Clay suspension concentration profile, 490–498
  - castor oil
    - density-temperature characteristics, 495
    - viscosity-temperature relationship, 494
  - concentration profiles with time, 497
  - destructive testing, 491
  - materials and experimental procedures, 492–495
  - non-destructive testing, 491
  - results, 496–498
  - sampling apparatus, 493
  - specific surface area of sediment specimens, 498
  - velocity of droplet and clay concentration, 495–496
- Coefficient of compressibility, nonlinear, 139
- Coefficient of consolidation, 11, 25, 69, 87, 170, 172, 274–275, 307, 329, 351, 437, 439, 663
  - air phase, 157
  - brittle behavior, 617
  - calculated values, 27
  - computation, 126–127
  - constant
    - assumption, 419, 424–430
    - finite strain on, 532–534
  - constant rate of deformation tests, 48
  - continuous loading tests, 51–52
  - corrected starting point, 13
    - alternative methods, 15–17
    - comparison of square root and logarithmic methods, 14
  - correction by primary consolidation ratio, 126
  - CRS test, 619
  - curve fitting, 12–18
    - determination, 526–546
      - clay-kaolinite mixture, 539–540
      - correction by primary consolidation ratio, 530–531
      - curve rule method, 528–530
      - graphic analysis of time-compression curve, 546
      - from intercept with primary compression curve, 272
      - peat, 539, 541
      - research, 543
      - routine, 543–544
      - settlement-time factors, relations, 533, 535
        - from time factor, 328
        - variable, 526
    - effect of decomposition, 133
    - effect of disturbance, 56
    - field and laboratory results, 61
    - function of modulus and permeability, 320
    - function of permeability, 303, 306
    - functions of modulus, 303, 306
    - heat-accelerated test, 292
    - histograms, one-dimensional tests, 466–467
    - horizontal flow, 646, 668–670
    - incremental compressibility test, 290
    - incremental loading oedometer test, 336
    - versus log effective stress plots, 245, 250–251
  - oedometer test, 346–349
    - plasticity index and, 430
  - selfweight consolidation test, 562, 564–565
  - soil with occluded air bubbles, 45
  - standard methods, 12–15
  - time factor for consolidation of finite strain, 534
  - variable, 526
    - finite strain and, 534–543
  - variable strain and
    - examples, 539–543

- final consolidation ratio, 536
  - time-consolidation relation, 535–539
  - variation with  $\sigma'_v$ , 290–292
- Coefficient of lateral earth pressure, 704–705, 707
- Coefficient of permeability, 118, 168, 351
  - continuous test, 348
  - heat-accelerated test, 292
  - incremental compressibility test, 290
  - incremental loading oedometer test, 337
  - incremental loading test, 347–348
  - variation with  $\sigma'$ , 290–291
- Coefficient of secondary compression, 690
  - and compression index, 692
  - effect of disturbance, 57
- Coefficient of secondary consolidation
  - as percentage of primary consolidation, 91
  - relationship to consolidation pressure, 91
  - relationship to rate, 96
- Cohesive soils, 405
- Combwich mud, 209
- Compacted fills
  - as-compacted prestress, 191–193
    - water content relationships, 191
  - compressibility, 186–197
  - confining pressure effect, 195
  - experimental apparatus and procedure, 186–188
  - saturated prestress, 194, 196–197
  - settlement, 197–201
  - volume change, 194–196
- Compaction energy, 111, 189
  - versus plastic deformation, 190
- Compaction prestress, 111
- Compressibility, 139–140, 299, 466, 627
  - as-compacted, 187–188
  - compacted fills (*see* Compacted fills)
  - continuity and, 139
  - curve, 287–288
    - conventional and CRS tests, 720
  - law, 378
  - Mexico City clay, 258
  - moduli, 109–110
  - parameters, 287–289
  - relationships, unsaturated soil, 156
  - selfweight consolidation test, 559–562
  - unsaturated soil, 160, 162–163
  - variation, 107
- Compression, 642
  - behavior, 129–131
    - demarcation between rebound and virgin segments, 129
    - industrial sludge, 130
    - influence of coarse fraction, 130
    - inorganic and organic soils, 133
    - kaolin, 709
  - calculations, 9–11
  - comparison of field and theory, 59–60
  - curve, 425, 610
    - Leda clay, 698, 701
  - line, virgin, 117
  - resistance of soil structure, 99
  - secondary
    - following primary consolidation, 32–33
    - influence on subsequent time-settlement response, 34–35
    - influence on subsequent void ratios, 33–34
    - settlement versus log of time, 33
  - strain, 408
- Compression index, 86, 245, 252
  - bentonite-sand mixtures, 639–640
  - coefficient of secondary compression and, 692
  - constant assumption, 419, 424–430
  - virgin, natural water content relation, 624

- CON2D, 125–126, 567, 568, 583, 585, 586–588, 591  
 overprediction of immediate deformation, 587–588
- CONMULT, 297
- CONMULT model, 118, 390, 398
- Consolidation  
 average, 472  
 behavior, 119, 610  
 cell, 116  
 characteristics variation, 77  
 clay behavior, 379–383  
 coefficient, radial, 29  
 curves, 148–150  
 finite difference equation, 407  
 governing equations, 469–470  
 law, 354  
 seepage-induced, 503  
 self-weight consolidation testing, 501–503  
 Terzaghi's coefficient, 140–141  
   constant, 145–146, 151  
   time rate, 663  
   effects of disturbance, 57  
*See also* Primary consolidation; Secondary consolidation
- Consolidation line, virgin, 455–456, 458  
 isotropic, 569
- Consolidation parameters, 279, 548  
 constant rate of strain test, 312  
 continuous loading tests, 325
- Consolidation pressure  
 effect of nonclay content, 630  
 void ratio relations, 631, 633–636
- Consolidation ratio  
 at bottom of specimen, 415  
 at top of specimen, 414  
 versus secondary consolidation rate, 90
- Consolidation strain, clay layer, 85
- Consolidation tests, 7–63  
 anisotropically prepared specimens, 453  
 associated techniques, 715–716  
 boundary impedance, 19–21  
 case histories, 58–59  
 coefficient of consolidation (*see* Coefficient of consolidation)  
 comparative study, 694–710  
   Anteus apparatus, 697  
   comparison of test results, 706  
   kaolin clay, 705–709  
   Leda clay, test results, 698–705  
   oedometer, 696  
   Rowe cell, 697  
   triaxial cell, 697–698  
 comparison of field observations and laboratory results, 58–61, 91–98  
   coefficient of consolidation, 61  
   compressions, 59–60  
   long-term observations, 95  
   Nottaway, Broadback, and Rupert River region, 93  
   pressure/void curve, Olga clay, 93–94  
   secondary consolidation effects, 92  
   settlement, 59–60  
     embankments, 92  
     rate, 94–95  
   stress-strain, 59–60  
 consolidometer, 453–454  
 constant rate of deformation tests, 47–49, 117  
 constant rate of strain, 79  
 defined, 7  
 different methods of data scrutiny, 717  
 disturbance, 54–57  
   cemented soils, 55  
   consolidation time rates, 57  
   effect on coefficient of consolidation, 56  
   effect on coefficient of secondary compression, 57  
   effect on reduction in void ratio, 54–55  
   thin-walled, fixed piston sampler, 55  
 early history, 8

- effective vertical stress-void ratio behavior, 455–459  
 fibrous peat, 485–489  
 incremental loading, 78  
 instrumentation, 454  
 isotropically prepared specimens, 452–453  
 large diameter (*see* Large diameter consolidation tests)  
 materials, 452  
 method influence, 77–78, 115  
   on time-deformation curves, 87–88  
 methods, 83  
 microcomputer (*see* Microcomputer applications)  
 modified, 116  
 new equipment, 715–716  
 normalized pressure-void ratio relationships, 460–462  
 partial saturation, 41–46, 63  
   backpressure, specimen saturation, 45–46  
   Henry's law, 42–43  
   interconnected air voids, 41–42  
   occluded air bubbles, 42–45  
   volumetric strain, 41  
 pore water pressure, 459–460  
   dissipation rates, 23–24  
 problems and issues, 718  
 rapid loading, 18–19  
 ring friction, 21–23  
 sample size, 62  
 sample size effects, 52–54  
 standard technique, 714  
   one-dimensional vertical-flow tests, 11–12  
 storage effects, 58  
 stress-strain (*see* Stress-strain relationship)  
 stress surface, 18  
 temperature effects, 23  
 testing procedure, 455  
 time-compression curves, 89  
 time rate estimation, 10  
 time-settlement curve  
   influence of drainage distance, 53  
    $\sqrt{t}$  method, 62  
   *T-U* relationship, 18  
   variables used in one-dimensional analyses, 8–11  
   *See also* Kaolin; Leda clay; specific tests  
 Consolidometer, 437, 453–454  
   bentonite-sand mixtures, 630  
   Rowe type, 120  
   slurry, 503–504  
   wick drain, 132, 642, 651–652, 654, 666  
 Constant gradient test, 321–322  
   strain rate, 326  
 Constant-head permeability tests, 337–338  
 Constant rate consolidation test, 565  
 Constant rate of deformation tests, 47–49  
   automatic, 117  
 Constant-rate-of-loading consolidation test, 49, 112–113, 236–256  
   analysis, 237–239  
   apparatus, 239–241  
   development, 236–237  
   average pore pressure ratio, 252–253  
   average time, 252  
   coefficient of consolidation versus log effective stress plots, 245, 250–251  
   comparison of range of results, 253–254  
   completion time, 255  
   compression index, 245, 252  
   cross section of specimen container, 241  
   loading rate  
     versus liquid limit, 256  
     selection, 255  
   microcomputer applications, 242  
   procedure, 242, 244  
   rebound index, 245, 252  
   soil description, 241–243

- Constant-rate-of-loading consolidation test (*continued*)  
 test conditions, 245  
 time consolidation curves, 245–249
- Constant-rate-of-strain test, 79, 110, 119, 170–183, 203, 236, 299–327, 338–341, 610, 625  
 adaptability to automation, 174  
 apparatus, 174–175, 300–301, 338–340  
 assumed stress distribution, 308  
 coefficient of consolidation, 320  
 comparison with  
   controlled-hydraulic gradient tests, 442–446  
   conventional incremental tests, 320–323, 442–446  
   real field behavior, 320–323  
 compressibility curves, 720  
 constant modulus  $M_L$ , 313–314  
 data acquisition and regulation system, 174, 340–341  
 development, 435  
 disadvantages, 170–171  
 history, 170  
 interpretation, 306  
 limiting pressure, 315–316  
 microcomputer applications, 340–341  
 modulus number  $M'$ , 314–315  
 parameter  $a$ , 314–316  
 permeability (*see* Permeability)  
 preconsolidation pressure (*see* Preconsolidation pressure)  
 procedure, 174, 176–177, 301–302  
   loading, 341  
 results, 181, 302–305, 342–344  
 soft plastic clay, 343  
 sources of error, 307–309  
 specimen trimming process, 174, 176  
 strain rate, 326  
   selection criteria, 171–174  
   stress-strain curves, 311, 400
- Constitutive model, 568, 583
- Continuous loading test, 46–52, 63, 79–80, 82, 203, 322–326, 329  
 coefficient of consolidation, 51–52  
 coefficients, 50  
 consolidation parameters, 325  
 correlation with constant rate of strain test, 325  
 general case, 49–50  
 maximum previous consolidation pressure, 50–51  
 property measurement, 50  
 rate-dependent parameters, 324–325  
 solutions, 49  
*See also* specific tests
- Controlled gradient test, 79, 203, 297, 396–398, 433, 694, 707  
 Leda clay, 703, 705
- Controlled-hydraulic gradient test, 433  
 comparison with incremental loading and CRS tests, 442–446  
 development, 435–436  
 results, 441–442  
 soft clays, 437–438
- Controlled rate of strain tests, 297
- Controlled strain rate, 433
- Conventional-incremental-loading test, 236  
 apparatus, 241, 243  
 comparison of range of results, 253–254  
 comparison with constant rate of strain test, 320–323  
 preconsolidation pressure, correlation with constant rate of strain test, 310  
 procedure, 244
- Cordemais clay, permeability, 361, 364
- Cour inflection point method, 226–227
- Creep, 297, 465  
 Singh-Mitchell parameters, 569
- Creep law, 119
- Creep test, 116  
 Batiscan clay, 387–389  
 long term, 296–297  
 natural clays, 387–392

- strain rate-time relations, Batiscan clay, 388–389
  - ultrasonic method, 521–524
  - Crimp tests, 673–675, 679
  - Critical gradient, influence on consolidation of clays, 354–376
    - degree of consolidation, 371–372
    - equipment, 355–356
    - interpretation of tests, 369–370, 375
    - pore pressure evolution, 367, 369
    - test principle, 355, 357–358
    - See also* Permeability law; Saint Herblain clay
  - Critical stress, 258–261
  - CRS test (*see* Constant rate of strain test)
  - Cumberland River silty clay, constant-rate-of strain consolidation, 178–180
  - Curing, specimen conditions before and after, 562
  - Curve fitting, 526, 528–530
    - clay, 541
    - clay-kaolinite mixture, 540
    - remolded peat, 541–542
    - See also* specific methods
  - Curve rule method, 126, 526, 528–530
    - replacement of Casagrande's method, 543–545
- D**
- Darcy's law, 354, 551
  - Dashpot, 39–40
  - Decomposition, 133
  - Deformation
    - Casagrande construction, 223
    - condition, 408
    - effect on
      - modulus  $M_L$ , 314
      - permeability parameters, 318
      - preconsolidation pressure, 312
      - stress, 316
    - false, correction for, incremental loading test, 336
    - natural, 152
    - rate, 47–48
    - soft clay (*see* Time-dependent numerical model, soft clay deformation)
  - Degree of consolidation, 131, 153, 366
    - average, 18, 20, 26–27, 238, 265, 647
    - effect of boundary impedance, 20
    - equal strain inflow and outflow, 29
    - free strain inflow and outflow, 28–29
    - radical flow consolidation testing, 28–29
    - secondary effects, 36
    - dependence on ratio of final to initial thickness, 109
    - influence of critical gradient, 371–372
    - influence of length of drainage path, 373
    - sludge, 512
    - time relations, 688
    - versus time for Drammen clay, 39
  - Desol wick drains, 681–683
  - Differential equation, 471
  - Dilatibility, sand, 520–521
  - Drammen clay
    - degree of secondary consolidation versus time, 39
    - time-settlement curve, secondary consolidation, 38
  - Dundas soil, 451
    - effective vertical stress-void ratio relationship, 457
    - physical properties, 452
- E**
- Elastic constants, 465
    - determination, 473, 476
  - Electrolyte solution, 627

- Embankment, 567  
 deformation due to overburden stresses, 198  
 pressure, 198  
 section, 198  
 settlement, 197–201, 262  
 and piezometric levels, 92  
 unit weight, 200  
 vertical stress exceeding preconsolidation stress, 97
- EngCon, Desk Top Computer Analysis of Consolidation Data, 222
- Engineering index properties, lacustrine clay deposit, 186
- Experimental methods and techniques, 122–128, 715–716  
 bulk density determination by gamma radiation, 123  
 centrifuge and numerical modeling comparisons, 124–126  
 oedometer tests, 714–715  
 solids content determination, 122–123  
 ultrasonic device, 124
- Extended consolidation theory, 406
- ### F
- $f$ -log  $\sigma'$ , 418–419, 423–427
- Fall-drop technique, clay suspension concentration profile (*see* Clay suspension concentration profile)
- FEADAM, 585
- FEM, 583, 585
- Finite-difference model, grid system, 386
- Finite-element analysis, 125, 593, 604–605  
 grid, 607  
 solution steps, 607  
*See also* FEM
- Finite strain  
 consolidation program, 126  
 consolidation theory, 500, 503  
 constant coefficient of consolidation, 532–534  
 variable coefficient of consolidation, 534–543
- Floating ring consolidometer, 239–240
- Franki-Kjellman drain, 652, 656  
 technical specifications, 653
- ### G
- Gamma radiation, bulk density of clay, determination, 123–124
- Gas formation, 113
- Gault clay, consolidation characteristics, 77
- Geocomposites, 642
- Geodrain drain, 652, 658, 660  
 technical specifications, 653
- Geomechanics, 593
- Geotextiles, 663–664
- Gloucester clay, preconsolidation pressure-strain rate relationship, 447–448
- Graphic method, 225–226
- ### H
- Heat-accelerated test, 117, 291–293  
 equipment, 292  
 interpretation, 293  
 principle, 291  
 procedure, 293  
 saturation, 292–293
- Henry's law, 42–43
- High-air-entry ceramic disk, 158, 168
- Highly compressible soils, intergranular viscosity, 257–280  
 fitting methods, 268, 271–276  
 curves Type I, 268, 271–272  
 curves Type II, 272–279  
 theoretical considerations, 263–268  
 clay structure, 263  
 consolidation curves, 268–269  
 Kelvin unit, 264–266  
 rheological model, 264  
 Terzaghi's primary time factor, 267

volumetric strain, 264  
 Z-unit, 266–268  
*See also* Mexico City clay; Oedometer test

Historical developments, 74–77  
 Bjerrum's interpretation, 73–76  
 Terzaghi, 72  
 young and aged clays, 73–74

Honmoku clay, 418–419  
 selfweight consolidation process, 425

Hvorslev's constants, 637

Hydraulic conductivity  
 comparison of measured and computed values, 15  
 smear zone, 30

Hydraulic consolidation cell, 53

Hyperbolic elastic model, 521

## I

Illicon computer program, 94

Impact-type compaction test, 189

Incremental compressibility test  
 compressibility parameters, 287–289  
 equipment, 285–286  
 increment duration, 287  
 loading law, 286  
 procedure, 286–287  
 remolding criterion, 289  
 saturation, 286  
 settlement versus time, 289–290  
 $\sigma'$ , variation of coefficients of consolidation and permeability, 290–292  
 Taylor's method, 290  
 unloading-reloading cycle, 288

Incremental loading oedometer test, 99, 334–338  
 apparatus, 334–335  
 coefficient of consolidation, 336  
 coefficient of permeability, 337  
 constant-head permeability tests, 337–338  
 correction for false deformation, 336

loading procedure, 334–336  
 results, 342  
 soft clays, test results, 438–439  
 stiff clay, 334  
 time-compression curve, 337

Incremental loading test, 78, 117, 433–434, 610, 615  
 comparison with CRS and CHG tests, 442–446  
 compression-log pressure curves, 81  
 determination of rate of consolidation parameters, 614–616  
 soft clays, 436–437  
 stress-strain curve, 435  
 vertical stress and strain, 615

Inflection point method, 226

Initial conditions, 471

Interconnected air voids, 41–42

Intergranular viscosity (*see* Secondary consolidation)

Ishii's consolidation method, 545

Isochrones, 378

Isotropic compression tests, 124

## J

Japan Industrial Standard code, 531–532

Japan Society of Soil Mechanics and Foundation Engineering, 531–532

Joliette clay, MSL tests, 395

## K

Kaolin, 154, 451, 594, 642, 694  
 band-shaped prefabricated drains, 650–651  
 centrifuge tests, 569  
 classification properties, 569  
 compacted, 109  
 compression behavior, 709  
 consolidation testing results, 705–709  
 effective vertical stress-void ratio relationship, 455–457, 459

- Kaolin** (*continued*)  
 geotechnical properties, 452, 696  
 material properties, 570  
 permeability tests, 477  
 stiffness constant, 479  
 testing program summary, 708  
 time-versus pressure ratio, 459  
 $V_a$  versus  $V_r$ , 478–480  
*See also* Unsaturated soil
- Kaolinite Flat D**, index properties, 492
- Karol-Warner dual range consolidometer**, 218–219
- Karol-Warner fixed ring oedometer**, 187–188
- Kavazanjian, Mitchell, and Bonaparte**, 125
- Kelvin unit**, 264–266
- $k$ -line method**, 346–349  
 continuous tests, 348  
 incremental tests, 347–349  
 tangent modulus, 348–349
- $K_0$ -triaxial test**, 119
- L**
- Laboratoires des Ponts et Chaussées**, 282
- Laboratory tests**, 107–114  
 equipment, 282  
 summary of papers, 108
- Lacustrine clay deposit**  
 dry unit weight versus moisture content curves, 187  
 index properties, 186  
*See also* Compacted fills
- Landfill, model, initial state**, 431
- Large diameter consolidation tests**, 664–672  
 apparatus, 664, 666  
 coefficient of consolidation, horizontal flow, 668–670  
 equivalent drain diameters, 670, 672  
 implications, 671  
 procedure, 667–668  
 results, 667–671
- Lateral drainage**, 663
- Lateral pressure tests**, 676–680
- Lateral strain measurement**  
 geotechnical characteristics of tested soils, 523  
 ultrasonic method, 516–524  
 capabilities, 520  
 clay testing, 520–522  
 consolidation and creep tests, 521–524  
 determining measurement precision, 518–520  
 indicator, 516–518  
 interpretation of measurement, 519  
 principle of operation, 518–519  
 strain-time relationship for peat, 523  
 strength and dilatability characteristics, 520–521  
 ultrasonic device, 517
- Leda clay**, 694, 709  
 Anteus apparatus, 702–704, 706  
 compression curve, 698, 701  
 controlled gradient test results, 703, 705  
 effect of membrane stiffness on load-deformation response, 704  
 effect of specimen size on preconsolidation pressure, 698, 702  
 normalized pressure-void ratio relationship, 461  
 oedometer test results, 698, 700–702  
 properties, 695–696  
 Rowe cell, 700–704  
 strain versus log effective pressure relationships, 698, 700  
 testing program summary, 699  
 time-compression curves, 89  
 triaxial cell, 704–705, 707
- Linear variable differential transformer**, 217–219, 221
- Liquidity index**, 170  
 versus soil index property dependent coefficient, 182

Load increment ratio, 434  
 effect on shape of dial reading-time curves, 87–88  
 influence on subsequent time-settlement response, 34–35

Loading  
 history, 451  
 law, 286  
 rate  
 constant-rate-of-loading consolidation test, 255–256  
 versus liquid limit, 256

Logarithm of time fitting method, 225–226

Log  $C_v$ -log  $\sigma'_{av}$ , 418, 423, 425, 428–429

Log  $t$  method, 225–226, 528–529

Long-term creep test, 296–297

Louisville clay  
 consolidation curve, 438  
 geotechnical properties, 436

LVDT, 217–219, 221

## M

Mark IV centrifuge, 555

Mebradrain drain, 652, 655, 658  
 equivalent diameters, 660  
 technical specifications, 653

Mexico City clay  
 compensated foundation settlement, 261–262  
 compressibility curve, 258  
 embankment settlement, 262  
 structure, 263  
 Type I consolidation, 259  
 Type II consolidation, 259–260  
 Type III consolidation, 259–260  
 Type IV consolidation, 259, 261

Microcomputer applications, 217–235  
 concept, 218  
 constant-rate-of-loading consolidation test, 242  
 constant-rate-of-strain loading test, 340–341

deformation versus square root of time, 232

hardware, 218–221  
 configurations, 220  
 programming, 219

one-dimensional consolidation, 231, 233–234

software, 222–228  
 assumptions, 222  
 Casagrande construction, 222–223  
 Casagrande's logarithm of time fitting method, 225–226  
 inflection point method, 226–227  
 preconsolidation stress, 222–223  
 printed output, 227–228  
 Schmertmann procedure, 223–224  
 soil phase relationship conditions, 226–227  
 time-dependent analysis, 224–225, 231–232, 235  
 system calibration, 221  
 testing, 221–222

Mikasa's consolidation theory, 119, 127–128

Mikasa's method, 526–527

Model tests, 405

Modulus  $M_L$ , 313–314

Modulus number  $M'$ , 314–315

Modulus of compressibility, 351

Modulus-stress plot, 303, 306

Mono 90, 594

Monterey #0 sand, properties, 570

Multiple-stage loading test, 393–396

## N

Nanko Clay, 554, 556  
 effect of curing time on  $f$ -log  $p$  relation, 561  
 $f$ -log  $c_v$  relations, 562  
 $f$ -log  $p$  relations, 561, 563  
 relation of permeability and volume ratio, 559  
 time-consolidation curves, 558

- Natural clays, consolidation, 378–403  
 clay behavior during testing, 386–387  
 controlled gradient test, 396–398, 400  
 creep test, 387–392  
 multiple-stage loading test, 393–396  
 numerical treatment, 383, 385–386  
 single-stage loading test, 392–394, 401
- North Sea clay, incremental loading oedometer test, 342
- Norton-Hoff law, 443, 449
- Norwegian Geotechnical Institute, 329–352
- Nottaway, Broadback, and Rupert River region, 93
- No wick test, rate of consolidation, 654
- Numerical model, 118  
 comparison with centrifuge model, 124–126  
 soft clay deformations (*see* Time-dependent numerical model, soft clay deformation)
- O**
- Occluded air bubbles  
 coefficient of consolidation, 45  
 flow rate, 44  
 Henry's law, 42–43  
 initial compressive strain, 44  
 time rates of compression, 43
- Oedometer test, 137, 282–297, 329–352, 378, 451, 694, 696, 707  
 back-pressure cell, 283–284  
 back-pressure chamber, 331–332  
 cells, 330–332  
 clay, consolidation theory application, 141–149, 151  
 boundary-value problems, 143–145  
 consolidation curves, 148–150  
 $C_v$  constant case, 145–146  
 degree of settlement, 146–148  
 coefficient of consolidation, 346–349  
 determination (*see* Coefficient of consolidation, determination)  
 consolidation curves, 277–278  
 consolidation equation, 527–528  
 creep, Batiscan clay, 387  
 curves exhibiting brittle behavior, 611  
 entrapped gas influence, 276–278  
 evolution, 283  
 falling head tests, 319  
 gas expansion, 276  
 highly compressible soils (*see* Highly compressible soils)  
 improving, recommendations, 279–280  
 incremental loading (*see* Incremental loading oedometer test)  
 increment of stresses, 279  
 interpretation, 350–351  
 Leda clay, 698, 700–702  
 new techniques and procedures, 714–715  
 primary consolidation errors, 276  
 problems, 276, 279–280  
 specimen  
 saturation, 284–285, 300–301  
 stress distribution, 350  
 trimming equipment and procedure, 331–334  
 medium-to-stiff clay, 383  
 mounting with dry filter stones, 333–334  
 very soft clay, 332–333  
 undisturbed specimens, 95, 97  
 with and without back pressure, 348–349  
*See also* specific types of tests
- Oil sands sludge, 500  
 degree of consolidation, 512  
 flow chart for sampling analysis, 509  
 pore pressure dissipation with depth, 512  
 solid content with depth, 513
- Oil sand waste slurry, 126

- Olga clay  
 pressure/void ratio curve, 93–94  
 secondary consolidation, relationship of rate to coefficient, 96  
 settlement rate, 93, 95
- One-dimensional consolidation test, 107, 130, 137, 451, 610  
 brittle behavior, 613–618  
 equation, 364–366, 549–550  
 assumptions, 549  
 governing equation, 385  
 incremental loading, 615  
 microcomputer applications, 231, 233–234  
 theory, 645
- Osaka Bay mud, 430
- Overburden stress, 198–199, 258–259
- Overconsolidation, 71, 82  
 clay, 75–76  
 idealized modulus-effective stress curve, 83
- Oxford cell, 206–207, 212  
 pneumatic loading system, 208
- P**
- Parameter  $a$ , 314–316
- Partial saturation, 7
- Particle segregation, 548, 565–566
- Peat  
 coefficient of consolidation, determination, 539, 541  
 fibrous, side friction (*see* Side friction, fibrous peat)  
 saturated, isotropic compression tests, 124  
 strain-time relationship, 523
- Pepper shale, pore pressure versus time, 482–484
- Permeability, 140, 173, 203, 205, 307, 315–320, 354, 465, 548  
 calculation, 302  
 change index, 318–319  
 compression and, 303  
 constant-head tests, 337–338  
 correlation with special oedometer results, 319  
 deformation effect, 318  
 evolution during loading, 365  
 parameters, 402  
 selfweight consolidation test, 556–559  
 sources of errors, 317  
 strain-rate as function of, 170  
 test, 110  
 transversely isotropic soil, 466  
 variation, 107  
 homogeneous soil, 317  
 void ratio relations, 303, 378, 380  
 volume ratio relation, 559–560
- Permeability law  
 bilinear, 369  
 comparison, 368  
 evolution of consolidation, 369, 371–374  
 nonlinear, 354, 375  
 parameters  
 choice, 367  
 definition, 364  
 schematic, 365
- Plastic deformation, 188  
 versus compaction energy, 190
- Plasticity index, coefficient of consolidation, 430
- Plasticity model, 125
- Plasticity theory, validation (*see* Centrifuge model)
- Plastic resistance, time-dependence, 72, 74
- Plastic soils, saturated, 137
- Poisson's ratio, 521, 600, 605  
 between axial and radial direction, 476
- Pore pressure, 236, 378, 405, 459–460, 465, 500, 567, 591  
 base versus log of time, 26  
 centrifuge tests, 576–578, 581–583  
 dissipation, 37, 587

- Pore pressure (*continued*)
- with depth, 512
  - during initialization, 604
  - rates, 23–24
  - distribution in model landfill, 431
  - effect on preconsolidation pressure,
    - Leda clay, 700–701, 703
  - evolution, 375
  - excess, 585
  - foundation, 125
  - generation, 98
  - high shear strength delay in increase, 97
  - influence of critical gradient, 367, 369
  - influence of drainage path length, 369–370
  - isochrones, 374, 388, 390, 393
    - CGT test, 398
    - selfweight consolidation, 551–552
    - vicinity of preconsolidation pressure, 390, 394
  - logarithm of time curves, 390, 392
  - measurements, self-weight consolidation testing, 509–511
  - negative, 236–237
  - nonuniform distribution, 204
  - ratio, 172, 459
    - average, constant-rate-of-loading consolidation test, 252–253
    - equation, 238
    - maximum, 173–174
  - response to loading and unloading, 605
  - versus time, pepper shale, 482–484
- Pore water, flow velocity, 551–552
- Preconsolidation pressure, 71, 80–85, 286, 289, 299, 303, 309–313, 694
- apparent, 451, 460
  - Champlain clays, 722
  - comparison of studies showing dependence on strain rate, 447–449
  - compression-log pressure curves, 81
  - constant-rate-of-strain test, 401
  - correlation between constant rate of strain test and
    - conventional incremental tests, 310
    - field tests, 309
  - correlation between different oedometer tests, 401
  - definition, 460
  - effect of base pore water pressure, 700–701, 703
  - effect of deformation rate, 312
  - effect of specimen size, Leda clay, 698, 702
  - highly structured clays, 81
  - idealized modulus-effective stress curve, overconsolidated clay, 83
  - influence of test procedure, 100
  - in situ* values, 83–84
  - normalized-void ratio relationship, 460–462
  - oedometer test, 82
  - overburden pressure ratio, 74–75
  - versus parameter  $a$ , 316
  - remolded clays, 82
  - settlement rate near, 93, 95
  - strain rate relations, 83–85, 313, 399, 443–446, 721, 722
  - stresses close to, 302
  - time dependence, 82
  - void ratio curve, Olga clay, 93–94
- Preconsolidation stress
- derived, 345
  - determination from plasticity index and undrained shear strength, 351–352
  - maximum possible, 223
  - vertical stress exceeding, 97
- Prefabricated drains (*see* Bentonite-sand mixtures; Remolded soils, prefabricated drains; Wick drains; specific drains)
- Preloading, 684
- CRS tests on very soft soils, 412–415
  - as soft ground stabilizer, 131

Pressure transducer, 206  
 calibration and stability, 210–211  
 differential, 215  
 Prestress, saturated (*see* Saturated prestress)  
 Primary consolidation  
 defined, 86  
 errors in oedometer test, 276  
 rate, 87  
 ratio, 526  
 correction of coefficient of consolidation, 530–531  
 self-induced, 97

## Q

Quasi-static loading, 451

## R

Radial drainage test, 116, 294–296  
 Radial flow consolidation testing, 7, 27–31, 62–63  
 average degree of consolidation, 28–29  
 factors recommended for use with, 30  
 smear zone, 30  
 Rapid loading test, 18–19  
 Rate process theory, 523  
 Rebound index, 245, 252  
 Recompression  
 curve, 455–456, 459  
 index, 80  
 Regression equations, 184  
 Reloading, 335  
 Remolded soils, prefabricated drains, 663–683  
 average soil parameters, 665  
 crimp tests, 673–675, 679  
 further research needs, 681  
 laboratory tests, 664  
 large diameter consolidation tests (*see* Large diameter consolidation tests)

lateral pressure tests, 676–680  
 load transfer before buckling, 682–683  
 Remolding criterion, 289  
 Restricted flow consolidation test, 111–112, 203–216  
 behavior during consolidation stage, 212–213  
 cell requirements, 205–208  
 comparative results, 214  
 development, 210–213  
 errors, 210  
 experimental details, 208–210  
 flow restrictor, 205–206  
 Oxford cell, 206–208, 212  
 potential, 215  
 principle, 204–205  
 results, 213–215  
 Rowe cell, 206, 208–209, 212  
 soft sample results, 214  
 swell-back stage, 212  
 test arrangement, 209  
 undrained incremental loading for partly saturated soil, 211  
 Rheologic model, 36, 113  
 Ring friction, 21–23  
 Rope drains, 684  
 pore water pressure distribution, 692  
 relations of time versus degree of consolidation, 688  
 settlement strain distribution, 691  
 Rowe cell, 206, 437, 694, 697  
 Leda clay, 700–704  
 modified, 119  
 restricted flow consolidation test, 208–209, 212

## S

Saint-Cesaire clay, SSL test, 394  
 Saint Herblain clay, 354  
 characteristics, 357  
 compression and permeability curve, 357, 361–363  
 physicochemical characteristics, 380

- Salt infiltration, 627
  - effects, 636–638, 640
- Sample disturbance, 329, 343–347
- Sand-clay mixtures
  - advantages, 627–628
  - compressibility, 130
  - See also* Bentonite-sand mixtures
- Sand drains, 684
  - relations of time versus degree of consolidation, 688
  - settlement strain distribution, 691
  - vertical, 643
- Sand, shear and dilatancy characteristics, 520–521
- Sandy clay, deformation characteristics, 522
- Sandy soil, classification diagram, 636
- Saturated prestress, 111, 184
  - embankment, 202
  - prediction equation, 196
- Saturation
  - by back pressure, 285
  - compacted kaolin, 109
  - degree, 109
  - oedometer test, 284
    - heat-accelerated test, 292
    - incremental compressibility test, 286
    - radial drainage test, 294–295
  - partial, 190
- Scaling relationships, 127
- Schmertmann procedure, 223–224
- Secondary compression, 257, 617, 684
  - displacement-time curves, 113
- Secondary consolidation, 31–41, 63, 87–91, 100, 257
  - average degree of consolidation, 36
  - compression following primary consolidation, 32–33
  - dashpots, 39–40
  - defined, 31, 88
  - degree of consolidation versus time for Drammen clay, 39
    - effects of nonlinearity, 39
    - incremental loading, 40
    - influence of compression on subsequent void ratios, 33–34
    - mechanism, 544–545
    - phenomenon, 268–270
    - rate, 88
      - versus consolidation ratio, 90
    - relationship to coefficient, 96
    - remolded peat, 34
    - rheologic model, 36–37
    - secondary curve slope, 35
    - settlement
      - embankments, 92
      - versus log of time, 32
    - subsequent time-settlement response, 34–35
    - theories, 35–41
    - time-settlement curve for Drammen clay, 38
    - See also* Highly compressible soils, inter-granular viscosity
- Sedimentation, 490, 500
  - self-weight consolidation testing, 501–503
- Sedimentation test
  - apparatus, 424
  - $f$ -log  $\sigma'$ , 424–427
  - log  $C_v$ -log  $\sigma'_{av}$ , 425, 428–429
- Sediment waste, nonconventional tests, 134
- Seepage consolidation test, 565
- Selfweight consolidation test, 126, 128, 425, 430, 500–514
  - in centrifuge, 548–566
    - coefficient of consolidation, 562, 564–565
    - compressibility, 559–562
    - disadvantage, 565
    - general consolidation equation, 549–550
    - initial settlement rate, 551–553
    - Mark IV centrifuge, 555
    - permeability, 556–559

- purpose, materials, and procedures, 553–556
- similarity law, 549–550, 553
- specimen conditions before and after curing, 562
- under single drainage condition, 551–552
- velocity of pore water flow, 551–552
- comparison of predicted and experimental consolidation, 513
- flow chart for sludge sample analysis, 509
- large-strain slurry consolidometers, 503–504
- pore pressure
  - dissipation with depth, 512
  - measurement, 509–511
- sampling mechanism, 506, 508
- sedimentation and consolidation states determination, 501–503
- solids content with depth, 513
- ten-metre selfweight consolidation cylinder, 507
- ten-metre tests, 506–514
- two-metre slurry consolidation cylinders, 585–586
- Sensitive clays (*see* Soft clays)
- Settlement, 100, 299, 591
  - calculation, 307
  - compacted fills, 111, 197–200
  - comparison of field and theory, 59–60
  - compensated foundation, 261
  - compensated friction pile foundation, 262
  - degree, 146–148
  - differential, 684, 690
  - due to selfweight, 198
  - during loading and unloading, 606
  - embankment, 92, 262
  - fill due to saturation, 199
  - fill over soft ground, 684–693
    - construction procedure, 689
    - design conditions, 686
    - design method, 686
    - model of ground, 686
    - pore water pressure distribution, 692
    - profile of differential settlement, 690
    - profile of filling procedure and slip failure, 685
    - relation between coefficient of secondary compression, 692
    - relations of time versus degree of consolidation, 688
    - residual settlement, 687
    - settlement strain distribution, 691
    - settlement versus time curves, 689–690
    - soil conditions and estimation of settlement, 686–687
    - soil profile and properties, 685
    - surcharge versus consolidation settlement, 687
    - time of surcharge and design of vertical drains, 688
- Illicon computer program, 94
- model landfill, 431
- natural degree, 152–153
- Olga clay, 93, 95
- overestimation, 99
- prediction of rates, 76–77
- prefabricated drains, 681
- rate, selfweight consolidation, 551–553
- ratio of ultimate to primary, 37
- residual, 132, 687
- secondary, 617
- selfweight consolidation, 430–432
- storage tank, 124–125
- surface, during initialization, 603
- ultimate, 97–98
- versus time curves, 289–290, 295–296
- time factor relations, 533, 535
- total final, 147

Settlement (*continued*)

- vertical, centrifuge tests, 583–584
- Shear, sand, 520–521
- Shearing stress, local side, 21
- Shear strength, undrained, as function of preconsolidation stress ratio and plasticity index, 353
- Side friction, fibrous peat, 485–489
  - effective stress distribution on base, 487–488
  - test data, 486–489
  - variation of strain and stresses with time, 487
- Silts, *k*-line, 347–348
- Silty clay, deformation characteristics, 522
- Similarity Law, 549–550, 553
- Simulated CGT tests, Batiscan clay, 397
- Singh-Mitchell creep parameters, 569
- Single-stage loading test, 392–394
- Slip failure, 685
- Sludge, compressibility, 130
- Slurry, 548
- Smear zone, hydraulic conductivity, 30
- Snow-Cal 50, 594
- Soft clay, 433, 548, 694
  - CRS consolidation test, 405–432, 437
    - application to settlement analysis, 430–432
    - calculation procedure, 422
    - coefficient of primary consolidation, 439
    - consolidation constant determination, 416–418, 420–422
    - constant compression index and coefficient of consolidation assumption, 419, 424–430
    - curve-fitting on selfweight consolidation process, 425
    - equipment, 410–411
    - $f$ -log  $\sigma'$ , 418–419, 423–427
    - graphic representation, 408, 410

- log  $C_v$ -log  $\sigma'_{av}$ , 418, 423, 425, 428–429
- original data, 420–421
- physical properties of samples, 412
- pore pressure, 440
- preloading, 412–415
- record of experiments, 416
- sample specimen preparation, 410, 412
- test results, 439–441
- theoretical basis, 406–408
  - volume ratio versus log effective stress, 423
- See also* Sedimentation test
- deformation (*see* Time-dependent numerical model, soft clay deformation)
- incremental loading oedometer test, test results, 438–439
- trimming, 332–333

## Soil

- anisotropic properties, measurement, 465–467
- anisotropic soils, biaxial consolidation test (*see* Biaxial consolidation test)
- characterization, 593
- critical state parameters, 599
- gaseous, 717
- improvement, 663
- mechanics, 71
- model, four-phase, 629–630
  - definitions of physical properties, 630
- homogeneous, natural variation in permeability, 317
- with occluded air bubbles, coefficient of consolidation, 45
- parameters, 665
- partially saturated, 109
- phase diagram, 188
- phase relationship conditions, 226–227
- plastic, saturated, 137
- problem soils, 716–717

- profile, 685
- properties, 8, 71, 177, 203, 243, 595, 685
- remolded, 100
- stratification and properties, 52
- structure, 71, 100, 610
  - bentonite-sand mixtures, 628–629
  - resistance to compression, 99
- tests, 71, 516
- unsaturated (*see* Unsaturated soil)
- unsaturated (*see* Unsaturated soil)
- very soft, 405
- volume change, 133
- volumetric flow rate, 675
- Soil index property dependent coefficient, 178–179
  - versus liquidity index, 182
- Solids content
  - determination to dilute suspension, 122–123
  - measurements, 500
- Specimen preparation
  - anisotropic, 453
  - centrifuge model, 594–596
  - isotropic, 452–453
  - soft clay, 410, 412
  - trimming, 331–334
- Stabilization, 663
- Standard incremental test (*see* Conventional-incremental-loading test)
- Stiffness constants, 470, 479
- Strain
  - definition, 8–9
  - distribution
    - fill settlement, 691
    - within specimen, 409
  - equal, 645
  - finite (*see* Finite strain)
  - free, 645
  - initial compressive, 44
  - lateral (*see* Lateral strain measurement, ultrasonic method)
  - versus log effective pressure, Leda clay, 698, 700
  - natural, 532
  - nominal, 532
  - ratio of bottom to top strain, 408, 410, 413, 417–418
  - time relationship for peat, 523
  - total, increment, 385
  - vertical (*see* Vertical strain)
  - volumetric, 41, 264–267
- Strain rate, 117–118, 170–174, 378
  - comparison of test methods, 442–443
  - comparisons of rates, 183
  - constant gradient test, 326
  - constant rate of strain test, 326
  - effect on preconsolidation pressure, 83–85, 399
  - elastic components, 382
  - equation, 171–173, 179
    - governing, 379
  - natural clay, 719
  - parameter determination, 173–174
  - plastic strains, 382
  - preconsolidation and, 313
  - pressure relations, 443–446, 721, 722
  - previous work, 171
  - relationship to controlling parameters, 171–172
  - shear stress relationship, 523–524
  - strain relations, Batican clay, 390–391
  - variation of  $\alpha_2$  coefficient, 722
- Stress
  - effective, 173
    - average, 47, 301, 308
    - distribution in centrifuge, 598
    - mean, 48
    - parabolic isochrone, 388
    - in terms of volumetric strains, 470
    - vertical, 123
  - undrained paths under triaxial conditions, 600–601
  - vertical (*see* Vertical stress)
  - volume change relationship, 129
- Stress-compression, 97–98
- Stress-strain relationship, 8–9, 118, 302, 399, 402
  - Acthafalaya clay, 19

Stress-strain relationship (*continued*)

- Batiscan clay, 390–391
  - clay from Hammond, Indiana, 10
  - curve, correction, 345–346
  - field and laboratory curves, 59–60
  - nonlinear, 7, 9, 410
    - average degree of consolidation, 26–27
    - base bore pressures versus log of time, 26
    - coefficient of consolidation, 25–27
    - curves, 25
    - primary effects, 25–27
  - samples taken using thin-walled, fixed piston samplers, 55
  - secant parameter, 267
- Suction, 236–237
- Suspension density, 490
- Swelling, 194, 197
- Swell potential, influences on, 133
- Syndrude Canada Ltd., 500

## T

- $\sqrt{t}$  method, 528–529
- Tangent modulus, 348
- Taylor's  $\sqrt{t}$ , 127
- Terzaghi's consolidation theory, 7, 99, 137–151, 217, 645
  - application to oedometer test (*see* Oedometer test, clay, consolidation theory application)
  - assumptions, 222
  - coefficient of consolidation, 140–141
  - compressibility, 139–140
  - consolidation equation, 369
  - continuity and compressibility, 139
  - differential equation, 44, 69, 140–141
    - significance, 152
  - linear coefficient of volume decrease, 139–140
  - modified, 118
  - permeability, 140
    - primary time factor, 267
    - See also* Microcomputer applications
- Three-dimensional consolidation, 645–647
- Time-compression curves, Leda clay, 89
- Time-consolidation relation, 134, 526
- Time-dependent numerical model, soft clay deformation, 567–591
  - analysis and comparison, 583, 585–589
  - apparatus, 571
  - instrumentation, 572
  - material, 569–570
  - model preparation, 572
  - Series I results, 574–580
    - analysis and comparison, 586–588
    - deformations, 579
    - finite element mesh and boundary conditions, 587
    - pore pressure response, 576
    - transducer locations, 576
    - vertical deformations, 579–580
  - Series II results, 574, 579, 581–584
    - analysis and comparison, 588–589
    - finite element mesh and dimensions, 588
    - pore pressure response, 576–578
    - vertical settlements, 583–584
- testing procedures, 573
- test listing, 575
- University of California at Davis Schaevitz centrifuge, 570–571
- Time factor
  - consolidation of finite strain, 534
  - settlement relations, 533, 535
  - values associated with midphase excess pore pressure ratio, 24
  - wick drains, 670
- Time-scaling factor, 589
- Tokuyama Clay, 554, 556
  - $f$ -log  $p$  relations, 563
  - relation of permeability and volume ratio, 560
  - time-consolidation curves, 557–558

Triaxial cell, 110, 694, 697–698  
     kaolin, 709  
     Leda clay, 704–705, 707  
 Two-dimensional consolidation, 567,  
     645–647  
 Two-phase flow, 154

## U

Ultrasonic device, 124  
 Ultrasonic method, lateral strain mea-  
     surement (*see* Lateral strain  
     measurement, ultrasonic method)  
 Unsaturated soil, 717  
     comparisons between theoretical  
     analysis and laboratory results,  
     167  
     consolidation theory, 154–157  
     constitutive equations, 155  
     continuity requirement, 155  
     laboratory tests, 157–161  
     change of stress-state variable  
     components, 159  
     equipment, 158  
     soil structure and water phase vol-  
     ume changes, 159–161  
     volume-mass relations, 158  
     theoretical analyses, 160, 162–167  
     two-phase flow, 154–155

## V

Varved clay, 610  
     geotechnical aspects, 611–613  
 Vertical drainage system, 642  
 Vertical drains, 684  
     design, 688  
 Vertical pressure, 141  
 Vertical strain, 406  
     CRS test, 618  
     due to saturation, 198–199, 202  
     one-dimensional consolidation test,  
     614–615  
 Vertical stress, 437  
     Bemben method, 622–624

breakpoint method, 620–622  
 CRS test, 618  
 distribution in centrifuge model, 590  
 limiting pressure, 315–316  
 one-dimensional consolidation test,  
     614–615  
 previous, 618  
     maximum, 621  
 void ratio behavior, 204  
     anisotropically and isotropically  
     prepared specimens, 456–459  
     isotropically prepared specimens,  
     455–456  
 Viscoplastic constitutive equation, 382–  
     383  
 Void ratio, 10, 48, 123, 627  
     clay component, 637  
     effective consolidation pressure re-  
     lations, 631, 633–636  
     effective vertical stress (*see* Vertical  
     stress, void ratio behavior)  
     effect of nonclay content, 630  
     effect on percent volume change, 194,  
     196  
     elastic volume change, 620  
     normalized, preconsolidation pres-  
     sure relationship, 460–462  
     sand-clay mixture, 130  
     threshold nonclay, 634–635, 640  
     vertical effective stress and, 204  
 Volume change, 154  
     one-dimensional percent change,  
     194  
     void ratio effects, 194, 196  
     water content effects, 196  
 Volume compressibility, 548  
 Volumetric field flow rate, 678

## W

Waste slurry, 500  
 Water, flow through clay soils, critical  
     gradients, 118  
 Water content, 617  
     compacted fills, 191

Water content (*continued*)  
 virgin compression index relation, 624  
 Water phase, 109  
 partial differential equation, 156  
 Water release, 642, 656–657, 659, 661  
 Wick drain consolidometer, 132, 642,  
 651–652, 654, 666  
 Wick drains, 644, 663, 717  
 equivalent diameter, 132  
 flow within zone of influence, 646  
 performance, 131–132  
 percent consolidation, 131  
 rigid-core wick, 132

time factor, 670  
 use to speed up consolidation, 132  
*See also* specific types of drains  
 Wykeham Farrance triaxial cells, mod-  
 ified, 158

**Y**

Young's modulus, 588

**Z**

Z-Unit, 266–268