

Subject Index

β -quenching, 529-38

A

anisotropy, 3-18, 583-93, 776-95
annealed, 699-722
annealing, 674-94

B

barrier layer, 384-400
BWR, 303-24

C

CANDU reactor, 507-23
cavities, 19-26
channeling, 583-93
cladding, 119-37, 635-49
cladding mechanical properties, 205-25
climb, 19-26, 541-9
cold-worked, 699-722
corrosion, 269-81, 303-24, 384-400, 471-83, 486-505
corrosion behavior, 430-56
corrosion modeling, 405-27
corrosion resistance, 360-80
crack propagation, 205-25
creep, 541-9, 674-94
crystallographic texture, 529-38
cyclic behavior, 405-27

D

defective fuel rods, 193-203
deformation, 529-38, 541-9
delayed hydride cracking, 244-62
deuterium ingress, 507-23
dislocation loops, 19-26, 541-9, 674-94
dislocations, 3-18, 583-93, 724-41
dpa, 19-26
dry storage, 651-71
ductile-to-brittle transition, 91-118
ductility, 119-37, 141-60

E

EIS, 326-57
element partitioning, 71-90
embrittlement, 119-37

F

fast neutron flux 19-26, 541-9
fatigue cracking, 205-25
finite element modeling, 119-37
fission fragments, 193-203
fluence 141-60
fractography, 53-68
fracture properties, 699-722
fracture toughness, 163-77, 205-25, 796-813
fuel, 635-49
fuel cladding tube, 651-71

G

gamma radiation, 326-57

H

heat flux 405-27
heat-treated, 699-722
heterogeneous radiolysis, 326-57
high burnup, 119-37, 651-71
high temperature oxidation, 71-90, 91-118
hydride, 29-48
hydride reorientation, 651-71
hydride rim, 119-37
hydrides, 119-37, 163-77, 405-27, 594-609, 635-49
hydriding, 141-60
hydrogen effect, 91-118
hydrogen pick-up, 384-400, 430-56

I

impedance spectroscopy, 303-24
impurities, 53-68
in-reactor deformation, 699-722
interaction distance, 181-91
interface layer, 384-400

intergranular constraints, 776-95
 intergranular strain, 550-63
 interphase constraints, 776-95
 interstitial, 19-26, 541-9
 irradiated corrosion, 326-57
 irradiation, 19-26, 193-203, 541-9, 583-93
 irradiation creep, 3-18, 529-38
 irradiation growth, 3-18, 430-56, 594-609, 724-41
 irradiation-induced damage, 724-41
 irradiation-induced growth, 564-82

J

J-integral, 205-25
 J-R curve, 796-813

L

length changes, 594-609
 LOCA, 53-68, 71-90, 91-118
 low-tin Zircaloy-4, 71-90, 91-118, 405-27, 430-56

M

M5, 71-90, 91-118, 430-56
 massive hydriding, 193-203
 MDA, 651-71
 mechanical tests, 141-60
 microhardness, 564-82, 674-94
 microscopic full-field measurements, 181-91
 microstructural evolution, 360-80
 microstructure, 3-18, 53-68, 244-62, 269-81, 430-56, 471-83, 550-63, 564-82, 594-609, 699-722, 724-41
 multilayered samples, 71-90

N

neutron flux, 405-27
 Noble Metal Chemical Application (NMCA), 285-300

O

oxidation, 507-23, 594-609
 oxide, 119-37, 269-81, 471-83
 oxide films, 360-80
 oxide growth, 285-300, 303-24
 oxide phases, 486-505

oxide stratification, 405-27

P

phase, 724-41
 phase compositions, 724-41
 phase field, 29-48
 phase identification, 29-48
 phase transformation, 71-90
 plastic behavior, 181-91
 plastic deformation, 776-95
 plasticity modelling, 550-63
 point defects, 19-26, 541-9
 post-quench ductility, 71-90
 post-quench mechanical properties, 91-118
 precipitate, 471-83
 precipitation process, 29-48
 pressure tube, 507-23, 796-813
 prior- β microstructure, 91-118
 Pt particle coverage, 285-300

R

radial hydride, 119-37, 651-71
 radiation damage, 19-26, 541-9, 583-93
 radiation damages and phase composition, 564-82
 radiation-induced defects, 193-203
 radiolysis, 193-203
 reorientation, 119-37, 635-49
 residual ductility, 53-68
 ring compression, 119-37
 round-robin, 205-25

S

scanning electron microscopy, 360-80
 scanning probe microscopy, 360-80
 secondary failures, 193-203
 segregation, 796-813
 SEM/EDX, 507-23
 SIMS, 507-23
 spillover, 285-300
 standard method, 244-62
 steam-hydrogen mixtures, 193-203
 stoichiometry, 269-81
 strain, 541-9
 strength, 244-62, 699-722
 sub-oxide, 384-400

T

tearing instability, 796-813
 TEM, 674-94
 tensile tests, 583-93
 texture, 3-18, 244-62, 550-63, 699-722
 thermal, 541-9
 Thermo-calc, 754-74
 transition, 384-400
 transmission electron microscopy, 360-80

V

vacancy, 19-26, 541-9

X

x-ray diffraction, 486-505
 XPS, 507-23

Y

yielding, 583-93

Z

Zircaloy, 163-77, 303-24
 Zircaloy-2, 269-81, 285-300, 635-49, 651-71
 Zircaloy-4, 29-48, 119-37, 141-60,
 326-57, 594-609, 651-71
 Zircobase, 754-74
 zirconium, 19-26, 529-38, 541-9, 583-93
 zirconium alloys, 53-68, 71-90,
 181-91, 193-203, 360-80, 384-400, 430-56,
 471-83, 486-505, 564-82, 674-94,
 724-41, 776-95
 ZIRLO, 550-63, 651-71
 Zr alloys, 405-27
 Zr(Nb,Fe)₂ intermetallic phase, 754-74
 (Zr,Nb)₄Fe₂ intermetallic phase, 754-74
 Zr-2.5Nb, 244-62, 699-722, 796-813
 Zr-Fe-Cr, 754-74
 Zr-Fe-Ni, 754-74
 Zr-Nb-Fe, 754-74
 Zr-Sn, 754-74