

STP 1456

***Advances in Geosynthetic  
Clay Liner Technology:  
2<sup>nd</sup> Symposium***

*Robert E. Mackey and Kent von Maubeuge, Editors*

ASTM Stock Number: STP1456



ASTM International  
100 Barr Harbor Drive  
PO Box C700  
West Conshohocken, PA 19428-2959

Printed in the U.S.A.

# Contents

## Overview

vii

### ASSESSMENT OF CLAY COMPONENT

**Various Aspects of Sodium Bentonite Testing**—J. T. OLSTA, J. H. CHUNG, AND  
D. E. DANIEL

3

**Quality Requirements for Bentonite in Geosynthetic Clay Liners and the  
Validity of Test Methods**—K. VON MAUBEUGE AND T. EGLOFFSTEIN

11

### DURABILITY OF CLAY COMPONENT

**A Simple Compatibility Testing Protocol for Bentonite-Based Barrier  
Systems**—R. S. OSICKI, I. R. FLEMING, AND M. D. HAUG

31

**Evolution of GCL Hydraulic Performance During Contact with Landfill  
Leachate**—V. NOROTTE, G. DIDIER, D. GUYONNET, AND E. GAUCHER

41

**Performance of Geosynthetic Clay Liners Used in Two Landfill Closures in a  
Coastal Area of Florida**—R. E. MACKEY AND J. T. OLSTA

53

### EVALUATION OF CURRENT AND PROPOSED GCL STANDARDS

**An Assessment of Current GCL Manufacturing Quality Control and On-Site  
Acceptance Testing Standard of Practice**—R. B. ERICKSON AND  
K. S. JESIONEK

75

**Laboratory Measurement of GCL Shear Strength**—P. J. FOX, T. D. STARK, AND  
R. H. SWAN, JR.

92

**Comparing GCL Performance Using Rigid Versus Flexible Wall  
Permeameters**—G. KOERNER

110

MOVEMENTS OF COMPOUNDS THROUGH THE GCL

|   |     |
|---|-----|
| <b>Investigation of the Behavior of Geosynthetic Clay Liners Subjected to Thermal Gradients in Basal Liner Applications</b> —J. M. SOUTHEN AND R. K. ROWE | 121 |
| <b>Effect of Freeze-Thaw on the Permeation of Arctic Diesel Through a GCL</b> —R. K. ROWE, T. MUKUNOKI, M. H. LI, AND R. J. BATHURST                      | 134 |
| <b>Experimental and Numerical Study of Oxygen Diffusion Through a Partially Hydrated Needle-Punched Geosynthetic Clay Liner</b> —A. BOUAZZA AND F. RAHMAN | 147 |