

# Manual of Petroleum Measurement Standards Chapter 11—Physical Properties Data

Section 2, Part 5—A Simplified Vapor Pressure  
Correlation for Commercial NGLs

ASTM Technical Publication [Stock No. PETROLTBL-TP15]  
GPA Technical Publication TP-15

SEPTEMBER 2007





# Manual of Petroleum Measurement Standards Chapter 11—Physical Properties Data

Section 2, Part 5—A Simplified Vapor Pressure  
Correlation for Commercial NGLs

ASTM Technical Publication [Stock No. PETROLTBL-TP15]  
GPA Technical Publication TP-15

Measurement Coordination

SEPTEMBER 2007

Prepared for

American Petroleum Institute  
1220 L Street, NW  
Washington, D.C. 20005

ASTM International  
100 Barr Harbor Drive  
West Conshohocken, PA 19428

Gas Processors Association  
6526 E. 60th Street  
Tulsa, OK 74145



## Foreword

The purpose of this procedure is to provide a simplified means of estimating equilibrium vapor pressures of various natural gas liquids (NGLs) from a knowledge of the fluid's relative density (60°F/60°F) and process temperature. The intended application of this procedure is to provide the values of  $P_e$  (equilibrium vapor pressure) required to determine the pressure effect contributions to volume correction factors as specified in the American Petroleum Institute *Manual of Petroleum Measurement Standards (MPMS)* Chapter 11.1-2004<sup>[1]</sup> (which superseded Chapter 11.2.1-1984<sup>[2]</sup>) and Chapter 11.2.2<sup>[3]</sup>. It is realized that other equations of state are currently in use for specific custody transfer applications and that such methods will continue to be used as acceptable for both buyer and seller.

This procedure is applicable to four major classifications of petroleum fluid mixtures: commercial propanes, commercial butanes, natural gasolines, and light end fluids. The latter consists of EP mixes and high ethane content fluids. It covers the relative density range of 0.350 to 0.675 over a temperature range of -50°F through 140°F. This procedure is an extension of GPA Technical Publication TP-15 (1988)<sup>[9]</sup>/API *MPMS* Addendum to Chapter 11.2.2-1994<sup>[4]</sup> to include light end fluids in the relative density range of 0.350 to 0.490.

Variations from the computed vapor pressures to the actual values are to be expected because of the infinite number of possible compositions that can result in the same relative density product. Representative and extreme compositions were selected to develop the correlations, but it is realized that additional streams with compositions from among the infinite potential may well behave differently. This potential for variation is especially true at relative densities in the neighborhood of 0.500. For example, at a relative density of 0.505 the fluid could be propane or Y-grade mix, each having significantly different compositions and vapor pressure behaviors.

As is always the case in correlations published for custody transfer and settlement purposes, additional accuracy may be obtained by developing a modified correlation for certain specific applications if agreed to by all contracting parties. An equation to improve the accuracy of the generalized correlation at 100°F is also included.

It is important to note that the application of the correlations presented in this document to conditions or fluids not specified, will result in untested and unknown results which could contain significant errors.

Nothing contained in any API publication is to be construed as granting any right, by implication or otherwise, for the manufacture, sale, or use of any method, apparatus, or product covered by letters patent. Neither should anything contained in the publication be construed as insuring anyone against liability for infringement of letters patent.

This document was produced under API standardization procedures that ensure appropriate notification and participation in the developmental process and is

designated as an API standard. Questions concerning the interpretation of the content of this publication or comments and questions concerning the procedures under which this publication was developed should be directed in writing to the Director of Standards, American Petroleum Institute, 1220 L Street, N.W., Washington, D.C. 20005. Requests for permission to reproduce or translate all or any part of the material published herein should also be addressed to the director.

Generally, API standards are reviewed and revised, reaffirmed, or withdrawn at least every five years. A one-time extension of up to two years may be added to this review cycle. Status of the publication can be ascertained from the API Standards Department, telephone (202) 682-8000. A catalog of API publications and materials is published annually and updated quarterly by API, 1220 L Street, N.W., Washington, D.C. 20005.

Suggested revisions are invited and should be submitted to the Standards and Publications Department, API, 1220 L Street, NW, Washington, D.C. 20005, [standards@api.org](mailto:standards@api.org).

## API Special Notes

API publications necessarily address problems of a general nature. With respect to particular circumstances, local, state, and federal laws and regulations should be reviewed.

Neither API nor any of API's employees, subcontractors, consultants, committees, or other assignees make any warranty or representation, either express or implied, with respect to the accuracy, completeness, or usefulness of the information contained herein, or assume any liability or responsibility for any use, or the results of such use, of any information or process disclosed in this publication. Neither API nor any of API's employees, subcontractors, consultants, or other assignees represent that use of this publication would not infringe upon privately owned rights.

API publications may be used by anyone desiring to do so. This publication is an updated version of *MPMS* Addendum to Chapter 11.2.2. Previous editions of this publication were numbered *MPMS* Addendum to Chapter 11.2.2. Users of this standard should take efforts to ensure they are using the most current version of this publication. Every effort has been made by the Institute to assure the accuracy and reliability of the data contained in them; however, the Institute makes no representation, warranty, or guarantee in connection with this publication and hereby expressly disclaims any liability or responsibility for loss or damage resulting from its use or for the violation of any authorities having jurisdiction with which this publication may conflict.

API publications are published to facilitate the broad availability of proven, sound engineering and operating practices. These publications are not intended to obviate the need for applying sound engineering judgment regarding when and where these publications should be utilized. The formulation and publication of API publications is not intended in any way to inhibit anyone from using any other practices.

Any manufacturer marking equipment or materials in conformance with the marking requirements of an API standard is solely responsible for complying with all the applicable requirements of that standard. API does not represent, warrant, or guarantee that such products do in fact conform to the applicable API standard.

*All rights reserved. No part of this work may be reproduced, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher.*

### **ASTM Note**

This publication does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this publication to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.

## **GPA Disclaimer**

Neither the GPA nor any person acting on behalf of the GPA makes any warranty, guarantee, or representation, express or implied, with respect to the accuracy, completeness, or usefulness of the information contained in this report. The GPA hereby expressly disclaims any liability or responsibility for loss or damage resulting from the use of any apparatus, method, or process disclosed in this report; and for the infringement of any patent or the violation of any federal, state, or municipal law or regulation arising from the use of, any information, apparatus, method, or process disclosed in this report.

*All rights reserved. No part of this work may be reproduced, stored in a retrieval system, or transmitted by any means, electronic, mechanical, photocopying, recording, or otherwise, without prior written permission from the publisher.*

Copyright © 2007 American Petroleum Institute, Gas Processors Association

# Table of Contents

<i>Foreword</i>	<i>ii</i>
<i>API Special Notes</i>	<i>iii</i>
<i>ASTM Note</i>	<i>v</i>
<i>GPA Disclaimer</i>	<i>vi</i>
<i>Table of Contents</i>	<i>vii</i>
<i>List of Tables</i>	<i>viii</i>
<i>List of Figures</i>	<i>viii</i>
<b>0 Implementation Guidelines</b>	<b>1</b>
<b>1 Background</b>	<b>1</b>
<b>2 Vapor Pressure Correlation for Commercial NGLs</b>	<b>2</b>
<b>3 Correlation Development</b>	<b>3</b>
<b>3.1 Propanes</b>	<b>7</b>
3.1.1 Product Specifications	7
3.1.2 Data Collection	8
3.1.3 Data Regression	8
3.1.4 Error Analysis	8
<b>3.2 Butanes</b>	<b>11</b>
3.2.1 Product Specifications	11
3.2.2 Data Collection	11
3.2.3 Data Regression	12
3.2.4 Error Analysis	12
<b>3.3 Natural Gasolines</b>	<b>15</b>
3.3.1 Product Specifications	15
3.3.2 Data Collection	15
3.3.3 Data Regression	17
3.3.4 Error Analysis	17
<b>3.4 Light Ends</b>	<b>19</b>
3.4.1 Product Specifications	19
3.4.2 Data Collection and Validation	20
3.4.3 Data Regression	22
3.4.4 Error Analysis	25
<b>4 Ad Hoc Improvement of the Correlation For Specific Situations</b>	<b>25</b>
<b>5 List of References</b>	<b>26</b>

## List of Tables

Table 1: Parameters for Vapor Pressure Correlation (Use in Equation 2) .....	3
Table 2: GPA Liquefied Petroleum Gas Specifications: GPA Standard 2140-88 <sup>[7]</sup> .....	7
Table 3: Correlation Parameters for Propanes and Butanes .....	9
Table 4: SRK Interaction Parameters for Propanes and Butanes .....	9
Table 5: Compositions and Relative Densities of Propane Samples .....	9
Table 6: Comparison of Vapor Pressure Correlations for Commercial Propanes .....	10
Table 7: Compositions and Relative Densities of Butane Samples Data Regression .....	12
Table 8: Comparison of Vapor Pressure Correlations for Commercial Butanes .....	13
Table 9: GPA Standard 3132-84, “Natural Gasoline Specifications and Test Methods” .....	15
Table 10: Grades of Natural Gasoline as specified by the GPA .....	15
Table 11: Correlation Constants for Natural Gasolines .....	16
Table 12: SRK Interaction Parameters for Natural Gasolines .....	16
Table 13: Compositions and Relative Densities of Natural Gasolines .....	17
Table 14: Comparison of Vapor Pressure Correlations for Natural Gasolines .....	18
Table 15: Compositions of Components Used to Generate Data for Light Ends Correlation .....	21
Table 16: Representative Comparison of Vapor Pressures Obtained from HYSYS with those from NGLCALC .....	22
Table 17: Representative Comparison Between HYSYS SRK Vapor Pressures and Vapor Pressures from the Correlation for Light End Fluids .....	23

## List of Figures

Figure 1: Vapor Pressures from Correlations .....	5
Figure 2: “A” Parameter (Equation 2 & Table 1) .....	6
Figure 3: “B” Parameter (Equation 2 & Table 1) .....	6
Figure 4: Maximum Temperature vs Relative Density .....	21



1220 L Street, NW  
Washington, DC 20005-4070  
USA

202.682.8000

**Additional copies are available through IHS**

Phone Orders: 1-800-854-7179 (Toll-free in the U.S. and Canada)  
303-397-7956 (Local and International)

Fax Orders: 303-397-2740

Online Orders: [global.ihs.com](http://global.ihs.com)

Information about API Publications, Programs and Services  
is available on the web at [www.api.org](http://www.api.org)

Product No. H1102051