

Author Index

A

Abeln, B., 26-46

B

Bergers, M., 205-242
 Besserud, K., 205-242
 Black, A. J., 205-242
 Brasseur, M. J., 86-123
 Broker, K. A., 473-504, 505-528
 Bull, E., 529-564

C

Carbary, L. D., 86-123, 205-242
 Chen, D., 3-25
 Cholaky, J., 529-564

D

Dieterich, O., 286-307

E

El-Hacha, R., 3-25
 Enomoto, N., 47-69, 343-360, 385-403

F

Feldmann, M., 26-46
 Filliben, J. J., 177-201
 Fisher, S., 473-504, 505-528

G

Gutowski, W. S., 243-265

H

Hagl, A., 266-285, 286-307
 Hahn, K., 370-384
 Hailesilassie, B. W., 308-330
 Hopps, E. R., 447-455
 Huff, D. N., 361-369
 Hunston, D. L., 70-85, 177-201,
 432-443
 Hunt, C. G., 70-85

I

Ito, A., 343-360

J

Jung, J., 370-384

K

Krumenacker, C., 505-528

L

Lacasse, M. A., 47-69, 385-403
 Lacher, S., 70-85
 Lee, H., 370-384
 Li, S., 243-265

M

Maton, I., 331-340
 Mazurek, A., 205-242
 Memari, A. M., 473-504, 505-528
 Misson, D., 205-242
 Miyauchi, H., 47-69, 385-403
 Modrich, R.-U., 505-528
 Murata, S., 47-69, 385-403

N

Nelson, P. E., 447-455
Nicklisch, F., 152-176

P

Partl, M. N., 308-330
Pintar, A. L., 177-201
Piteo, N. A., 456-470
Prautzsch, V., 152-176
Preckwinkel, E., 26-46

R

Recknagel, C., 404-431
Rubis, K., 205-242
Rutila, D. A., 456-470

S

Schueneman, G. T., 70-85

Sitte, S., 86-123
Slick, D. S., 456-470

T

Tanaka, K., 47-69, 343-360,
385-403
Tan, K. T., 177-201, 432-443
Toikka, G., 243-265

V

Vandereecken, P., 331-340
Vogt, I., 124-151, 152-176

W

Weller, B., 124-151, 152-176
White, C. C., 70-85, 177-201,
432-443
Wolf, A. T., 86-123

Subject Index

A

*ABAQUS*TM, 308-330
 accelerated exposure, 343-360
 accelerated weathering, 370-384
 acrylate, 124-151
 adhesion, 243-265, 331-340
 adhesive, 124-151, 447-455, 456-470
 adhesive failure, 370-384
 adhesive technology, 26-46
 apparent modulus, 70-85
 architectural design feature, 205-242
 argon retention, 205-242
 ASTM C719, 432-443
 ASTM C1519, 432-443
 ASTM C1736, 361-369
 ASTM E2188, 205-242
 ASTM E2190, 205-242
 autoclaved lightweight concrete,
 47-69, 385-403

B

bent glass, 205-242
 blister growth, 308-330
 bond, 3-25
 bonding design, 266-285
 Building sealant, 70-85

C

capability evaluation, 404-431
 closed-form solution, 308-330
 cold bent glass, 205-242, 286-307
 compression set, 70-85
 concrete, 447-455
 construction, 177-201
 continuous sealant evaluation,
 361-369

corner load, 286-307
 creep, 308-330
 cured, 361-369
 curtain wall systems, 529-564
 curtain walls, 473-504
 cyclic loading, 266-285

D

degradation, 266-285
 doubly curved glass, 205-242
 durability, 47-69, 70-85, 243-265,
 331-340, 343-360, 432-443
 durability evaluation, 404-431
 dynamic-mechanical testing, 404-431

E

earthquake, 529-564
 epoxy, 3-25
 exposure testing, 47-69

F

fibre reinforced polymers, 3-25
 film adhesive, 86-123
 finite-element method, 308-330
 Finite Element Modeling, 473-504
 floor, 447-455
 foamed, 456-470
 fracture, 385-403

G

glass, 3-25, 124-151
 glass fin, 124-151
 glass frame, 124-151
 glazing, 86-123

H

high strain rate behavior of structural silicone, 529-564
 hybrid beam, 124-151
 hybrid steel-glass beams, 26-46

I

indirect tensile test, 308-330
 insulating-glass durability, 205-242
 insulation, 456-470
 interstory drift, 529-564

J

joint, 361-369

K

Korea, 370-384

M

master curve, 308-330
 material characterization, 404-431
 mechanical characteristics, 404-431
 metallic substrate, 243-265
 mixing ratio, 266-285
 model, 177-201
 modulus, 177-201, 385-403, 432-443
 moisture, 447-455, 456-470
 molecular brushes, 243-265

N

non-destructive evaluation, 361-369

O

one part, 370-384
 organic substrate, 243-265

outdoor aging, 70-85
 outdoor exposure, 343-360

P

performance assessment, 404-431
 photovoltaic facade, 124-151
 PIB durability, 205-242
 point fixing, 86-123
 polyethyleneimines, 243-265
 primers, 331-340
 Prony series, 308-330

R

racking test, 473-504
 relaxation, 308-330
 rolling device, 361-369
 roofing, 456-470

S

Sealant, 47-69, 177-201, 343-360, 385-403, 404-431, 432-443
 sealant failure in adhesion, 361-369
 seismic evaluation, 473-504
 Service Life Prediction, 177-201
 shear, 3-25
 sigmoidal function, 308-330
 silica sand, 3-25
 silicone, 86-123, 370-384, 473-504
 silicone adhesion, 243-265
 silicone adhesive, 266-285, 286-307
 silicones, 243-265, 331-340
 small- and large-scale tests, 26-46
 SPHERE, 177-201
 SSG, 529-564
 Statistics, 177-201
 strain cycling, 70-85
 stress relaxation, 432-443
 structural, 86-123

structural behavior, 26-46
structural glazing, 26-46, 266-285,
286-307, 370-384, 404-431
structural sealant glazing, 473-504
structural silicone, 205-242
structural silicone glazing, 529-564
superimposed loading, 404-431
surface degradation, 343-360
surface engineering, 243-265
system test method, 404-431

T

tensile strength, 370-384
tension, 3-25
two part, 370-384

U

Ultra-High-Performance- Concrete,
3-25

V

VOCs, 447-455

W

wall panel, 47-69, 385-403
warped glass, 205-242,
286-307
weatherability, 343-360