

Index

- A**
- Acoustic emission
 - Correlation with microdamage, 60, 67-69, 72
- B**
- Boron-aluminum (see Fabrication of)
 - Boron-epoxy (see Fabrication of)
 - Buckling, 14
 - Buckling restraint, 9, 75, 126, 234
- C**
- Clip gage, 154
 - Cold-curing, 207
 - Compression
 - Effects of, 3-25, 43-46, 130, 145-147
 - Test data
 - Cyclic, 78-88
 - Cyclic stress-strain test, 215-216, 238
 - Static, 11-12, 30, 31, 233-237
 - Conditioning
 - Creep, 89-103
 - Moisture, 103-122
 - Constant life diagram, 31-32, 44
 - Core-shell stacking, 104
 - Crack
 - Growth mechanisms, 48
 - Growth rate versus stress intensity amplitude data, 50
 - Initiation, 217, 224-225
 - Length versus stress intensity data, 49
 - Propagation, 48, 50-56, 57-72, 217, 224-225
 - Stabilized length, 66
 - Crack opening displacement, 28, 29, 40, 42, 46, 154, 167
- Creep**
- Alteration of residual stresses by, 89-102
 - Calculation of strain due to, 92-93, 100-102
 - Strain as a function of time, 94
- Critical stress intensity factor, 55
- Cryogenic temperatures (effect on response), 141-151
- D**
- Damage development, 162-167
 - Damage tolerance, 123
 - Data
 - Acquisition systems, 29, 59, 125, 172
 - Analysis, 9-10, 188-190, 203-204
 - Scatter, 3, 9, 10, 15-18, 51, 146, 190
 - Defects, 152-170
 - Defect structure, 213-225
 - Delamination, 13, 33, 38, 39, 60, 63, 110, 127, 128, 134-136, 162, 232, 244
 - Design
 - Applications to, 25, 228-247
 - Dynamic modulus
 - Data, 145-150, 179-184
 - Determination of, 143, 172-173
- E**
- Electron microscope
 - Fractography, 54, 79-80, 83-84, 215-225

Endurance limit, 18, 31, 43, 44
 Environmental effects (see specific types)
 Etching, 48, 51-53, 55

F

Fabrication of
 Boron-aluminum, 48, 142
 Boron-epoxy, 75, 91-92, 142
 Carbon fiber reinforced poly-methylmethacrylate, 209-210
 Effect of, 25, 30
 Glass-epoxy, 186-188
 Graphite-epoxy, 4-6, 28-29, 58-59, 124, 153, 186-188, 231, 250
 S-glass-graphite-epoxy hybrid, 103-105
 Failure mechanisms, 44, 60, 81-82, 85, 88, 112-113, 127-128, 131-139, 214-225
 Failure modes, 11, 12, 22, 33, 35, 39, 60, 63, 65, 97, 181-182, 161-165, 229, 232-236, 243-247, 253-255
 Comparison of static and cyclic, 60, 65
 Fatigue effect (see Fatigue sensitivity)
 Fatigue failure theories, 190-191, 198-202
 Fatigue limit (see Endurance limit)
 Fatigue sensitivity, 43, 46
 Fiber breaks, 78, 79, 82, 94-97, 136, 253
 Flaws, 152-170
 Fractography, 52-54, 215-225
 Fracture mechanics, 48, 55, 232, 253-254, 260
 Fracture toughness
 Boron-aluminum, 51
 Graphite-epoxy, 231-237
 Frequency
 Effect of, 171-184

Of load oscillation, 9, 29, 48, 59, 75, 92, 110, 143, 154, 187, 210, 211, 236, 251

G

Goodman diagram 31-32
 Graphite-epoxy (see Fabrication of)
 Guide plates (see Buckling constraints)
 Gumbel, 10

H

Heat emission (see Temperature increase during testing)
 Heat treatment
 Effect on static strength, 94-95
 Of boron-epoxy laminates, 89-102
 Procedure for boron-epoxy, 91-92
 Holes (see Notched response)
 Hybrid composites (see Fabrication of)
 S-glass/graphite/epoxy, 103-122

I

Impact
 Influence on fatigue response, 238-240
 Influence on static strength, 233-237
 Inherent flaw model, 157-158
 Initial defects
 Effect on fatigue and fracture response, 152-170
 Interlaminar shear test data, 195, 199
 Interlaminar stress, 192
 Internal friction, 142

L

Linear elastic fracture mechanics (see Fracture mechanics)
 Loading modes
 Effect of, 185-205
 Low cycle fatigue, 145-151

M

- Manufactured defects, 153
- Matrix creep, 89-94, 96-97
- Matrix damage, 79-81, 82-85, 134, 225, 239
- Mechanical resonances
 - Test for, 144
- Mechanics of materials analysis, 128-130
- Micrographs, 163-164, 219-225
- Minimum life, 260-266
- Modulus measurements (see Stiffness measurements or other specific types)
- Moisture
 - Absorption, 107-110
 - Conditioning, 106-107
 - Effect on residual mechanical properties, 103-122
 - Weight gain versus time data, 108-109

N

- Nondestructive testing, 57-72, 126
 - Acoustic emission, 60, 252, 254-256, 262, 266
 - C-scan, 5, 10, 136-137, 155, 156
 - Thermography, 96-98
 - X-ray, 29, 33-34, 36, 39, 43, 58, 61, 62, 64-65, 67-68, 76, 94-95, 135-138
- Notched response
 - Holes, 27-28, 30, 32-36, 46, 78-88, 100, 155-156, 171-184, 231-247
- Sharp notches
 - Center notch, 57-72
 - Double edge notch, 27-28, 30, 36-46
 - Single edge notch, 48-56
 - Surface notches, 123-140, 153
- Notch sensitivity
 - Compared to aluminum, 241-243

P

- Part-through slit, 153
- Piezoelectric transducers, 144
- Poisson's ratio, 13
 - Variation during fatigue loading, 111-122
- Polymethylmethacrylate
 - Carbon fiber reinforced, 206-227
 - Plexiglas, 210-227
- Preloads
 - Effect on response, 152-170
- Proof testing, 168-169, 248-266
 - Levels, 152, 251, 260
 - Life after, 260-262
 - Residual strength after, 262-264
- Properties (data)
 - Glass-epoxy, 192
 - Graphite-epoxy, 192
 - Polymethylmethacrylate, 214
- Prosthesis, 206-227
- Pullout, 51

R

- Real-time monitoring, 57, 96-98
- Regression curve fitting to $S-N$ data, 190-197, 252-266
- Reliability analysis, 190
- Residual strength, 18-22, 33, 38, 87, 111-122, 136-140, 155-156, 175-176, 241, 257-259
 - Correlation with microdamage, 140
 - Increase during fatigue loading, 158-161, 175-176
 - Scatter as a function of cycles of loading, 259
- Residual stress
 - Alteration by heat treatment, 89-102
 - Calculation of, 93-94
- Resonance
 - Method of modulus determination, 147, 150
- Root diameter, 29, 48

S

- Sample size, 22-25
- Scaling, 25, 26
- Scanning electron microscope (see Electron microscope)
- Shadowing technique, 134
- Short beam shear tests, 188, 229, 230
- Spectrum loading, 58, 60, 125
- Stacking sequence
 - Effect on
 - Cyclic response, 44-45, 162
 - Static response, 239-247
 - Selection of, 4
- Static strength-fatigue life relationships, 258-266
- Statistical representations, 9, 10, 16, 19, 21-24, 26, 252-266
- Stiffness
 - Change as a failure criterion, 171-184
 - Changes, 11, 25, 33, 37, 38, 85-87, 111-122, 145-150, 167, 171-184, 264-265
 - Changes correlated with matrix degradation, 87
 - Dynamic measurement of, 145-160
 - Measurement of, 10, 76-77, 143, 145-160, 214
- Strain gage
 - Measurements of residual stiffness, 116, 143
- Strain rate
 - Effect on response, 211-214, 217-218
- Stress concentrations (see Notches, Holes, etc.)
- Stress intensity factor, 49, 53-56
- Striations, 215
- Surgical implants, 206-227

T

- Temperature
 - Effect of on response, 123-140

Cryogenic levels, 141-151

Increase during testing, 13, 96-99, 252, 257

Tensile data

Cyclic, 14, 17-19, 21-23, 31, 33, 37, 38, 59-70, 78-88, 111-122, 158-161, 167, 190-196, 217-218

Cyclic stress-strain test, 215-216

Static, 10-11, 30, 95, 125, 155-156, 158, 187, 211-214, 233-237, 238, 252

Static at 300°F (boron-epoxy), 91

Tension-compression data

Cyclic, 15-18, 20-23, 40-43, 130, 131, 193, 238

Testing procedures

Compression-compression fatigue, 29-30, 75, 142-144, 236

Interlaminar shear, 188

Static compression, 8, 29, 30, 142-144, 234

Static tension, 8, 29-30, 124-125, 142-144, 154, 187, 210, 251

Tension-compression fatigue, 8, 9, 29-30, 125, 126, 210, 237-238

Tension-tension fatigue, 8, 29-30, 59, 75, 92, 142, 144, 154, 173-174, 187-188, 236, 251

Tetrabromoethane (TBE), 29, 58, 135-138

Thermographic monitoring, 96-99

Time-at-load effects, 182

U

Ultrasonic attenuation (see Non-destructive testing, C-scan)

V

Video monitoring, 127

Voids as defects, 214-225

Void contents, 10, 186

W**Waddoups model**, 232–237**Wearin**, 174–183**Wear-out**, 19, 141, 142, 149, 174–183**Weibull distributions**, 9, 16, 19, 21–24, 26, 190, 198, 252–266