

# Index

- A**
- Absorbed moisture, 19  
 Adhesive, 163  
 Aircraft, 118–134, 161  
 AS carbon fibers, 120, 138, 154  
 Autoclave, 29
- B**
- Beams (*See* Sandwich beams)
- C**
- Celion carbon fibers, 6, 22, 34, 74, 91  
 Compression, 96, 120–134, 142, 147  
 CPI-2237 resin, 34  
 Crack, 11, 25, 56, 143  
 Crack density, 144, 146  
 Cryogenic properties, 83, 90, 95–109  
 C-scan, 8
- D**
- Damping, 149–160  
 Degradation, 11  
 Delamination, 163, 171  
 Diffusion, 114, 123, 130  
 Dynamic properties, 113, 115, 148–160
- E**
- Elastic properties, 77, 90  
 Emittance, 59, 70, 72, 111
- F**
- Fabrication of composites, 6, 22, 36, 119, 162
- Failure, 85  
 Fatigue, 107  
 Fiber-matrix adhesion, 42  
 Fickian diffusion, 129, 133  
 Filament wound composite, 95–109  
 Flaw, 85, 171  
 Flexure properties, 8, 10, 38, 52, 141, 147  
 Fortafil fiber, 34  
 Fracture, 43, 74, 87
- G**
- Gamma ( $\gamma$ ) radiation, 100, 111, 116  
 Glass fiber, 96, 103, 138  
 Glass transition temperature (*See* T<sub>g</sub>)  
 GY70 carbon fiber, 34
- H**
- Heat capacity, 111  
 Heat conductivity, 96  
 HTS carbon fibers, 6, 55, 71  
 Hybrid, 137, 146  
 Hydrothermal, 13  
   Exposure, 8, 148–160
- I**
- Infra-red, 97  
 Interlaminar shear strength, 8–19, 39, 52, 113, 116
- L**
- Long term exposure, 6
- M**
- Mechanical properties, 11, 24, 96, 148

- Microcracks, 56  
 Modulus, 13, 24, 37, 78, 105, 144, 153-160, 167  
 Moisture  
   Absorption, 52, 114, 148, 153  
   Concentration, 18  
   Content, 150, 164, 166, 169  
   Diffusion, 113  
   Gain, 122-134
- N**
- Net resin, 29  
 Nondestructive testing (*See* C-scan)  
 Notched strength, 83, 90  
 NR-150B2 resin, 34, 55, 71
- O**
- Outgassing, 106  
 Oxidation resistance, 40, 52
- P**
- Photomicrograph, 11  
 PMR-15 polyimide, 6-19, 33, 55, 71, 74, 91  
 Poisson's ratio, 77, 168
- Q**
- Quality control, 161-171
- R**
- Radiative degradation, 111  
 Real time, 119, 124, 132  
 Relative humidity, 150  
 Residual stress, 137, 145  
 Resin  
   934, 112  
   3501, 120, 138, 154  
   5208, 149, 162
- S**
- Sandwich beam, 150-160
- Scanning electron microscope, 50, 165, 169, 170  
 SCI REZ080 resin, 103  
 Shear modulus (*See* Modulus)  
 Short beam shear (*See* Interlaminar shear strength)  
 Space environments, 110-117  
 Space shuttle, 96  
 Specific heat, 59, 69, 71  
 Stacking sequence, 138  
 Stiffness (*See* Modulus)  
 Strain-energy, 25, 27  
 Strain gage, 75, 104, 120, 164  
 Structural dynamics, 148-160  
 Swelling, 152
- T**
- Tensile properties, 26, 74, 76, 86, 124, 133, 168, 170  
 Tg, 15, 21, 33, 36, 115, 119, 129, 133, 141, 159  
 Thermal aging, 23  
   Conductivity, 56, 60, 71, 105  
   Cycle, 138-147  
   Degradation, 40  
   Expansion, 59, 63, 71, 137, 145  
   Gravimetric analysis (TGA), 162  
   Isolate, 96, 102, 109  
   Spike, 8-19, 23-32, 126, 129, 131  
   Stress, 138, 146  
 Thermomechanical properties, 25, 33-53  
 Thermooxidative exposure, 6  
   Stability, 10, 40, 42  
 Thermophysical, 54-72, 96  
 Thick laminate processing, 27  
 Transverse cracking, 141, 146  
 T 300 carbon fibers, 8-19, 22, 112, 149, 162
- U**
- Unnotched specimens, 74  
 Strength, 90

**V**

Vacuum, 111, 150, 163  
Vibration test, 97, 151-160  
Void content, 29, 45, 52, 63, 103, 112  
V378A polyimide, 20-32

**W**

Weight loss, 9, 40

**Y**

Young's modulus (*See* Modulus)