

Index

A

- Abcite coating, wear of, 28-69
- Abrasive wear, 10, 11
 - Equation for, 11
 - Influence of hardness on, 11
 - Tests for, 11, 16-27, 71-91, 123-125, 161-162
- Absorbance measurements in erosion, 35-37
- Adhesion tests, 5
- Adhesive wear, 8-10
 - Equation for, 9
 - Tests for, 8-10, 92-117, 122, 123, 136, 137
- Air-blast and sand erosion rig, 30, 31
- Aluminum, wear of, 71-91
- Anodize coatings
 - Type of, 120, 121
 - Wear of, 118-133
- Application tests, 26, 27
- ASTM wear tests
 - D 673, 19, 20
 - D 1044, 17
 - D 3363, 23, 24
 - G 65, 72, 73

B

- Bend strength, 8
- Block-on-ring test, 122, 123, 136, 137
- Borided coatings, wear of, 71-91
- Break-away friction, for ice, 165

C

- Cadmium, wear of, 118-133
- Chromium platings
 - Types of, 119, 120
 - Wear of, 71-91, 118-156

Coatings

- Characterization of, 4-8
- Properties of, 3
- Types of, 3
- Composites, wear of, 28-69, 92-117
- Contact stress, concentrated loading of coating, 98

D

- Dry sand-rubber wheel test, 72, 73, 123-125
 - Use of, 126, 129-133

E

- Elastic modulus for coatings, 95-98
- Elastomer coatings, wear of, 28-69
- Erosion/abrasion test, with ice, 161, 162
- Erosive wear, 4, 11, 12, 28-70
 - Damage by, 39, 51-54
 - Equation for, 12
 - Tests for, 12, 13, 29, 30, 161, 162

F

- Falling silicon carbide test, 19-21
- Fargo abrasion testing machine, 72
- Fatigue wear, 13
- Fiber, influence on the wear of composites, 109, 110
- Fluorocarbons, wear of, 28-69
- Fracture toughness, 8
- Friction, for ice, 163-165
 - Measurement of, 10, 163-165

G

- GE brush abrasion test, 26

H

- Hardness
 Determination of, 7, 23, 24
 Influence on wear of coated plastics, 19-23
 Haze, as wear measure, 17, 18

I

- Ice-crushing test, 159, 160
 Impact angle, effect on erosion, 33, 34, 40-42
 Indentation tests, 6

J

- Jaw-crusher test rig, 159, 160

L

- Laboratory wear tests, uses of, 16, 17
 Low stress abrasion, 71-91, 124, 126, 129-133
 Wear tests for, 72, 124, 125

M

- Metal coatings, wear of, 71-91, 118-156

N

- Nickel platings
 Types of, 120, 138, 139
 Wear of, 118-156
 Nonmetallic coatings, wear of, 16-69, 71-117, 157-176

O

- Optical characteristics, 17, 18, 32, 35-37
 Oscillating sand technique for surface abrasion, 27
 Osmium, wear of, 118-133

P

- Pencil hardness test, 23, 24
 Pin-on-disk tester, 9
 Platings, wear of, 118-156
 Polycarbonate, wear of, 21, 28-69
 Polymer coatings, wear of, 16-69, 92-117, 157-176
 Polyurethane coatings, wear of, 28-69
 PTFE, influence in composite wear, 110, 111
 Pull test, 7

R

- Reciprocating line contact apparatus (RLC), 94, 95
 Uses of, 92-117
 Reinforced composite, wear of, 28-69, 92-117
 Resin, influence in composite wear, 110
 Rhodium, wear of, 118-133
 RLC (*see* Reciprocating line contact apparatus)
 Roughness, influence in erosion test, 35

S

- SAE abrasion test method, 72-75
 Extension to thin coatings, 71-91
 Sand weight impacted, influence on erosion testing, 34, 35
 Scratch test, 6
 Silver, wear of, 118-133
 Static friction of ice, 165
 Steel wool rotary test, 22, 23
 Substrate, effect on composite wear, 109
 Surface roughness, influence on erosion, 35

T

Taber abraser test, 17-19
 Thin metallic coatings, wear of, 71-91
 Time-of-flight device in erosion testing, 31
 Transfer film, 112, 113
 Transmittance measurement, in erosion, 35-37
 Transparent coatings, wear of, 16-69
 Tribotester, 9

W

Wear tests/testers

Abrasive wear, 11, 16-27, 71-91, 123-125, 161, 162
 Adhesive wear, 8-10, 92-117, 122, 123, 136, 137
 Air blast-sand erosion, 30, 31
 ASTM
 D 673, 19, 20

D 1044, 17
 D 3363, 23, 24
 G 65, 72, 73
 Block-on-ring, 122, 123, 136, 137
 Dry sand-rubber wheel, 72, 73, 123-125
 Erosion, 12, 13, 29, 30, 161, 162
 Erosion/abrasion, 161, 162
 Falling silicon carbide, 19-21
 Fargo abrasion, 72
 GE brush abrasion, 26
 Ice-crushing, 159, 160
 Jaw-crusher, 159, 160
 Low stress abrasion, 72, 124, 125
 Oscillating sand, 27
 Pin-on-disk, 9
 Reciprocating line contact, 94, 95
 SAE abrasion, 72-75
 Steel wool rotary, 22, 23
 Taber abraser, 17-19
 Tribotester, 9
 Wet sand-rubber wheel, 71-91
 Windshield-wiper test, 26, 27