

Index

- A**
- ASTM C 613, 120
 ASTM D 256, 154
 ASTM D 638, 4, 30, 37
 ASTM D 638M, 5
 ASTM D 790, 4, 5
 ASTM D 3029, 154
 ASTM D 3039, 75
 ASTM D 3410, 75
 ASTM D 3763, 144, 154, 158, 161
 ASTM D 4065, 144–161, 165
 ASTM D 4092, 145
 ASTM D 4092, 145
 ASTM E 399, 41
- B**
- Bolted Joint, 74
 Failure mode, 74
 Strength, 73
 Boundary layer thickness, 89
- C**
- Clamping pressure (bolt torque), 76
 Cleavage failure, 81
 Complex viscosity, 150
 Compression test, 75
 Crack density, 58
 Crack growth rate, 65
 Crack propagation mode, 38
 Creep, 134
 Cure behavior, 151
 Cylindrically orthotropic disk, 89
- D**
- Delamination, 58, 62, 68
 Denton, Douglas L., 23–35
 Driscoll, Stephen Burke, 144–161
 Dynamic mechanical testing, 144
- E**
- Edge cracking, 71
 Environmental degradation, 104
- F**
- Failure, 8, 45
 Interlaminar, 45
 Flexural, 8
 Matrix, 47
 Transfiber cracking, 45
 Fatigue, 42, 47, 51, 52, 54
 Axial, 65
 Crack growth, 42
 Deflection controlled, 52, 54
 Flexural, 51
 Life, 47
 Load controlled, 54
 Fiber avoidance mode, 38
 Fiber avoidance model, 36
 Fiber length distributions, 37
 Fiber orientation, 3, 24
 Fiber orientation distribution, 86, 90
 Findley equation, 132
 Flexure testing, 4
 Fracture toughness, 41
 Fraunhofer diffractometer, 27
 Freeman, William T., Jr., 119–130

G

Gillespie, John W., Jr., 86–102

H

Hahn, Hong Thomas, 103–118
 HCl spray mist treatment, 14
 Hermann's orientation parameter, 25,
 93
 Hiel, Clement, 131–143
 Hoa, Suong V., 65–72
 Hosangadi, Ashok B., 103–118
 Hygrothermal, 103

I

Inherent flaw size, 85
 Instrumented impact testing, 154
 Interlaminar cracking, 45

L

Lead glass fibers, 25
 Li, Chia-Geng, 36–50
 Linear elastic fracture mechanics, 41
 Liquid environment, 65
 Loos, Alfred C., 119–130

M

McGarry, Frederick J., 36–50
 Mandell, John F., 36–50
 Matrix cracks, 40
 Matrix crazing, 40, 46
 Mechanical property variability, 5
 Microhardness measurements, 67
 Modulus,
 Degradation, 55
 Tension, of R25 SMC, 9
 Flexural, of E-glass/epoxy, 57
 Moisture, 104, 105
 Absorption, 104
 Desorption, 104
 Diffusion, 105
 Mold coverage, 30
 Morris, Donald H., 131–143

Munson-McGee, Stuart H., 23–35

N

Net tension failure, 83
 Newaz, Golam M., 51–64
 Ngo, Ahn-Dung, 65–72

P

Pipes, R. Byron, 86–102
 Pseudo-stiffness ratio, 56
 Pyrolysis, 14

R

Resin content, 120
 Resin flow, 119
 Rheology, 145

S

Sankar, Thiagas S., 65–72
 Shear yield zone, 40, 46
 Shirrell, C. David, 3–22
 Short beam shear, 105
 SMC R25, 3
 SMC R50, 74
 SMC R65, 65
 S-N curve, 46, 61
 Stiffness degradation, 55
 Strength, 5, 8, 75
 Flexural, 5, 8
 SMC R25, 8
 Tension, 75
 SMC R50, 75
 Surface fiber veil, 14
 Swelling coefficient, 115
 Longitudinal, 115
 Transverse, 115

T

Tension test, 4, 30, 37
 Thermoelastic response, 86
 Time-dependent behavior, 132

U

Ultrasonic attenuation, 105

V

Viscoelasticity, 131, 145, 146

W

Weibull strength distribution, 6

Wilson, Dale W., 1, 73–85, 163–165

X

X-radiographic tracer fibers, 24

X-radiography, 24

Y

Yen, Shing-Chung, 131–143