

Subject Index

A

Accelerated testing, 89
 Aging
 accelerated, 113
 chemical and functional tests, 142
 elastomers, 142
 simulation, 76, 319
 Alkali metal silicates, 327
 Aluminum
 corrosion inhibitors, 7
 critical pitting potential, 133
 fully formulated coolants, 361
 heat-rejecting, 52, 327
 incipient passivating layers, 23
 Antifreeze
 manufacturing and quality control, 352
 recycling, 251, 292
 by vacuum distillation, 231
 ASTM D 1384, 113, 133
 ASTM D 2809, 319
 ASTM D 3147, 319
 ASTM D 4340, 23, 113, 319
 ASTM D 4985, 43
 ASTM D 5752, 43

B

Beaker tests, 210
 Brass, corrosion inhibitors, 7
 Bulk fluid temperatures, 210

C

Carboxylates, 23
 electrochemical degradation of elastomers, 183
 Cast iron, corrosion inhibitors, 7
 Cavitation, 392
 Chloride, recycled coolant, 270
 Compatibility, with nonmetals, 168
 Conductivity, as estimate of total dissolved solids,
 199
 Contract blender/packages, 352
 Copper, corrosion inhibitors, 7
 Copper-triazole interaction, 76

Corrosion

 carboxylate- and silicate-inhibited coolants, 23
 inhibitors, 7
 additives, 89
 copper-triazole interaction, 76
 light-duty applications, 52
 recycled coolant, 270
 Corrosion-fatigue, 89
 Critical pitting potential, 133

D

Delayed-release, 361, 409
 Depletion, 76, 113
 fully formulated coolants, 361
 recycled coolant, 270
 Deposits, 319
 high-heat-rejection engines, 210
 silicate stabilization, 327

E

Elastomers
 aging, 142
 effect of propylene and ethylene glycol base,
 168
 electrochemical degradation behavior, 183
 Electrochemical degradation, ethylene-propylene
 rubber, 183
 Electrochemical potentiometric measurements,
 133
 Electrochemical testing, 133
 Electrochemistry, organic acids, 7
 Ethylene glycol, 168
 collant base, 43
 manufacturing of final product, 352
 recycling, 251
 by vacuum distillation, 231
 Ethylene-propylene rubber, electrochemical
 degradation behavior, 183
 Extended life coolants, 113
 Extended service interval, 43, 142
 filter, 409
 fully formulated coolants, 361
 total dissolved solids, 199

F

Filter
 delayed-release, 43
 extended service, 409
 fleet testing, 370
 Filter/conditioner, 370
 Fleet testing, 43
 coolant filter, 370
 fully formulated coolant, 361
 modeling, 113
 recycled coolant, 270, 292
 Flow rate, 210
 Fully formulated coolants
 extended service, 361
 recycling, 251
 total dissolved solids, 43, 199
 FVV Test R443/1986, 392

G

Galvanic corrosion, 89
 Germany, testing methods, 392
 Glassware corrosion test, 133
 inhibitors, 7
 Glycol
 concentration and conductivity, 199
 degradation, 113
 Glycol degradation acids, recycled coolant, 270

H

Hardness, 210
 Hard water stability, 327
 Heat flux, 210
 Heat transfer, 210, 392
 Heavy-duty coolants
 extended service, 361
 recycled, fleet testing, 270
 scale and deposits, 210
 total dissolved solids, 199
 Hot surface temperature, 210

I

Immersion testing, 168
 Inorganic inhibitors, 142
 Inverse solubility, 210
 ISO 9002, 352

L

Laboratory testing, fully formulated coolant, 361
 Lead, corrosion inhibitors, 7
 Long-life coolants, 319

N

Nitrited organic acid, 43
 Nitrite inhibited coolants, electrochemical
 degradation of elastomers, 183
 Nonmetals, coolant compatibility, 168

O

Open circuit potential, 133
 Organic acids, 7, 23
 chemical and physical properties, 113
 electrochemical degradation of elastomers, 183
 fleet test evaluation, 43
 as inhibitor, 142
 light-duty applications, 52
 nitrited, 43
 nonmetal compatibility, 168
 Organosilicon stabilization, 327

P

Passive layer, heat-rejecting aluminum, 23
 Performance tests, 53, 113
 Phosphate based coolant, deposits, 210
 Phosphate-free low-silicate coolants, 361
 Pitting, 89
 Polymer, water-soluble, 210
 Polymer coating, coolant filter, 409
 Propylene glycol, 168
 coolant base, 43
 electrochemical degradation of elastomers, 183
 recycling, 251
 silicate stabilization studies, 327

Q

Quality control, 352

R

Recycling, 89
 evaluation of processes, 292
 high-volume, stationary, multiple technology
 equipment, 251
 by vacuum distillation, 231
 Rubber compounds
 coolant compatibility, 168
 electrochemical degradation, 183

S

Scale, 319
 high-heat-rejection engines, 210
 silicate stabilization, 327

Silicate, 23
 filtering, 251
 fully formulated coolants, 361
 light-duty applications, 52
 low, 43
 nonmetal compatibility, 168
 stabilization studies, in propylene glycol, 327

Solution analysis, 270

Steel, corrosion inhibitors, 7

Stress/strain relaxation, 142

Sulfate, recycled coolant, 270

Supplemental coolant additive, 199

 filtration, 370, 409

 in recycled coolant, 270

 scale and deposits, 210

T

Testing equipment, 319

Testing methods, 89, 319

 European, 392

Thermoplastics, effect of propylene and ethylene
 glycol base, 168

TMC RP 329 and 330, 361

Total dissolved solids

 conductivity as estimate of, 199

 low, 43, 361

V

Vacuum distillation, recycling by, 231

W

Water pumps, fully formulated coolants, 361

X

X-ray photoelectron spectroscopy, passivating
 layers, 23