

Subject Index

A

Acoustic pulses, 642
 Adhesive fatigue, 764
 Adhesive fracture, 764
 Adhesives, structural, 764
 Adjusted compliance ratio, 674
 Aircraft
 aging, 97
 high speed civil, 713
 Aluminum
 2024-T3, 815
 2324-T39, 674
 6013-T651, 674
 7075-T6, 552
 7075-T7751, 674
 alloy, 407, 426, 727, 815
 plates, 97
 specimens, 453
 ASTM standards
 A 508, C113, 284
 A 533, Grade B, 17, 341
 A 723, 897
 E 647, 674
 opening load method, 674
 Autofrettage, 565, 584

B

Bauschinger effect, 565
 Bending loads, 552
 Beremin model, 284
 Bicycle components, off-road,
 743
 Blunting model, crack tip, 552
 Bridge specimens, 696
 Brittle fracture, 40, 154
 Buckling, 114

C

Calibration, 862
 Calibration function, 248
 Cannon components, high
 strength steel, 897

Carbon precipitate/nickel grain
 boundary interfaces, 384
 Carrier cloth, 764
 Cell models, 9
 Center-cracked plate specimen,
 9, 82
 Charpy specimens
 precracked, 55
 precracked Charpy v-notch,
 135
 sub-Charpy-size, 40
 Cladding, 284
 Cleavage fracture, 135, 284, 341
 Coarsening, heterogeneous, 786
 Compact tension specimens,
 284, 674, 815, 851
 Compact toughness specimen,
 830, 862
 Composite materials
 carbon fiber-reinforced
 polymer, 713
 Compression, 474
 Computational cell
 methodology, 9, 135
 Constant amplitude fatigue
 cycling, 642
 Constant amplitude loading,
 uniform, 453
 Constitutive model, 264
 Constraint, 40, 55, 135
 evaluation, 830
 Contact geometry, 696
 Continuum damage models, 851
 Cracks and cracking
 axial, through wall, 215,
 830
 closure, 426, 496, 674, 727
 closure, resulting growth
 rates, 407
 closure, fatigue, 438
 closure, plasticity-induced,
 453, 516
 closure, roughness-induced,
 535
 closure technique, virtual, 176
 Configuration, 114
 development, 599

916 FATIGUE AND FRACTURE MECHANICS

- engineering size, failure definition, 599
 - extension, 884
 - extension, 82, 264
 - extension, ductile, 135
 - fatigue, 786
 - fatigue, nucleation process, 614
 - fatigue, propagation, 474, 552
 - fields, asymptotic, 233
 - front, 658, 862
 - front mesh normality, 176
 - growth, 565
 - growth behavior, 516
 - growth, ductile, 851, 862
 - growth, fatigue, 407, 426, 552, 658, 713
 - growth, fatigue, measurement, ASTM E 647, 674
 - growth, fatigue, theory, 496
 - growth, increment, 438
 - growth, mixed mode, 658
 - growth, plastic, 233
 - growth, plasticity-induced, 535
 - growth rate, 438, 897
 - growth, stable, 97, 341, 815
 - initiation, 642
 - length, critical, 830
 - length, relation to displacement and load, 82
 - length to specimen width ratio, 114
 - multiple site damage, 114
 - oblique, 658
 - opening angle, 884
 - opening displacement, 764
 - opening displacement method, 176
 - propagation, 453, 674
 - propagation stress intensity factor, 474
 - size, 496
 - small, 426, 496
 - specimens, surface, 55
 - surface, 453
 - tension specimens, surface, 55
 - threshold, environmental cracking, 897
 - tip blunting, 552
 - tip constraint, 284
 - tip cyclic strain, 674
 - tip displacement field, 438
 - tip loading rates, 17
 - tip opening angle, 97, 114, 815
 - tip opening displacement, 315, 552
 - tip plasticity, 438
 - tip stress intensity factor, 696
 - Creep, 384
 - Creep/fatigue crack growth, 215
 - Critical planes, 599
 - Crossbore intersections, 584
 - Cylinders, 215
 - thick-walled, 565
- ### D
- Damage mechanics, 201, 364
 - Damage models, 851
 - Damage, multiple site, 815
 - Damage tolerance, 713, 727
 - Defects, butt welds, 862
 - Deformation, 82, 384
 - factor, 248
 - fields, 233
 - plastic, 264, 552
 - Dispersion strengthening, 786
 - Displacement, relation to load and crack length, 82
 - Driving force, 496
 - mechanical, 474
 - Ductile-brittle regime, 9
 - Ductile-brittle transition, 17, 55
 - Ductile crack extension, 135
 - Ductile crack growth, 851, 862
 - Ductile damage, 201, 341
 - Ductile fracture, 248, 364
 - Ductile tearing, 40, 82, 341, 884
 - prediction, 201
 - resistance, 135
 - stable, 851
 - Ductility, residual, 884
 - Durability, 713
 - Dynamometers, 743
- ### E
- Elastic-plastic, 97
 - fracture, 264
 - Elastoplastic stress, 233
 - Energy absorption rate, 496
 - Equivalent domain integral method, 176
 - Exclusion region theory, 264
 - Extraction methods, 176

F

Failure assessment, 248
 Failure loads, buckling influence
 on, 114
 Failure model, micromechanical,
 341
 Failure stresses, 815
 Fasteners, 384
 Fatigue, adhesive, 764
 Fatigue analysis, multiaxial,
 614, 599
 Fatigue crack growth, 407, 426,
 552, 658, 713
 analysis, 215
 measurement, ASTM E 647,
 674
 theory, energy consideration
 basis, 496
 Fatigue crack nucleation
 process, 614
 Fatigue crack propagation, 474
 Fatigue cracks, 565
 Fatigue damage, ultrasonics
 for, 642
 Fatigue durability
 enhancement, 584
 Fatigue failure, 743, 764
 Fatigue, high cycle, 626
 Fatigue life estimation, 584, 802
 Fatigue lifetime, 565
 Fatigue limit, 626
 Fatigue, low cycle, 626
 Fatigue, railroad, 614
 Fatigue strength, 764
 Fatigue test, 802
 Fatigue, thermomechanical, 786
 Fatigue threshold, 674
 Fatigue, variable amplitude, 727
 Ferritic structural steel, 40
 Fiber bridging, 713
 Fiber diameter, 393
 Finite element analysis, 9, 176,
 201, 284, 802
 curved specimen cracks, 658
 ductile crack growth, 851
 nonlinear, 135
 plane strain, 135, 552
 predicting ductile tearing, 82
 shell, 97
 three-dimensional, 135, 215,
 815, 830

Finite element code,
 two-dimensional, 264
 Finite element mesh, 201
 Flat plate specimen, 658
 Four point bend fatigue tests, 438
 Fracture, adhesive, 764
 Fracture resistance, 233, 315
 Fracture toughness, 154, 315, 393
 crack tip constraint influence
 on, 284
 dynamic, 17
 predictions, 341
 transition region, 40
 Fretting fatigue tests, 696
 Fuselage panel test, 713

G

Geometric constraint, 658
 Gradient effect, 364
 Grain boundary precipitates, 384
 Grain size, 535
 Gurson model, 201, 341, 364
 Gurson-Tvergaard dilatant
 plasticity formulation, 862

H

Haigh diagram, 626
 Handlebar forces, 743
 Heat affected zone, 315
 Helicopter loading spectra, 727
 High-speed civil transport, 713
 Homogenization, 154
 Honeycomb sandwich, 713
 Hoop stress, residual
 compressive, 565
 Hydrogen cracking, 897
 Hydrogen laden propellant
 environments, 897

I

I-beam specimen, 82
 Impact loading, 135
 Impact specimens, 40
 Intergranular failure, 384

J

J-integral, 55, 215, 830, 884
 Joints, solder, 786

918 FATIGUE AND FRACTURE MECHANICS

Joints, welded, 315
J-Q approach, 9
J-R curve, 884
J-T approach, 9

L

Laminate sandwich fuselage
 panel test, 713
Lead-tin eutectic solders, 786
Length scale, 201
Life prediction, 474
Linear damage rule, 743
Load, applied, 642, 658
Load, crack opening, 407
Load factor, 248
Loading, biaxial, 764
Loading, constant amplitude, 453
Loading, cyclic, 453
Loading, elastic, 426
Loading, high amplitude, 743
Loading, impact, 135
Loading, multiaxial, 599
Loading, proof, 584
Loading rates, crack tip, 17
Loading, service, 584
Loading spectra, 727
Loading, structural, 743
Loading, tensile shear, 802
Loading, uniaxial, 599
Loading/unloading, 496
 deformation, 552
Load interaction effect, 474
Load, limit, 884
Load method, opening, 674
Load ratio, 516
Load ratio effects, 802
Load, relationship to
 displacement and crack
 length, 82
Load reversal, 438
Load, shear, 764
Loads, variable amplitude, 802
Local approach, 284, 315
Local compression, 154

M

Master curve, 55
Mechanical driving force, 474
Mesh size effect, 201

Micromechanical failure
 model, 154
Micromechanical parameters,
 Gurson, 364
Microscopy, high resolution,
 384
Microstructure, 535
Microstructure evolution, solder
 joints, 786
Microvoid density, 407
Middle crack tension specimens,
 674, 815
Miner's linear damage rule, 743
Mixed mode specimens,
 independently loaded, 764
Mohr-Coulomb yield condition,
 233
Moiré interferometry, 438
Multiaxial fatigue analysis, 599,
 614
Multiple-site damage
 specimens, 815

N

Nicalon, 393
Nickel-copper alloys, 384
Nickel-iron base alloys,
 austenitic, 897
Nil-ductility temperature, 17
Notch plasticity, 516
Notch strain analysis, 584

O

Oscilloscope, digitizing, 642
Overload effect, 474
Overloading, controlled,
 techniques, 584

P

Palmgren-Miner's rule, 803
Pedal forces, 743
Piezoelectric transducers, 642
Pipes, pressurized, 215
Plane strain three point bend
 specimen, 201
Plastic constraint, 496
Plastic crack growth, 233

Plasticity, 438, 535
 crack tip, 552
 criterion, reverse, 584
 Plasticity-induced closure, 453
 Plastic strain, 565
 Plastic strain energy, 496
 Porosities, initial material, 862
 Precleavage tearing, 851
 Pressure sensitivity, 233
 Pressure tube, 830
 Pressure vessel shell weld, 851
 Pressure vessel steel, 17, 40
 Pressure vessel structural integrity, 284
 Proof loading, 584
 Propellant environments, hydrogen laden, 897

R

Rail grinding, 614
 Railroad rails, 614
 R-curves, 862
 Reduced strain technique, 407
 Residual compressive hoop stress, 565
 Residual compressive stress, 584
 Residual strength, 82, 97
 prediction, 815
 Residual stress, 154, 516
 Bauschinger effect on, 565
 compressive, 474, 584
 railroad rail fatigue, 614
 Reverse plasticity criterion, 584
 Reverse yielding, 552, 565
 Rolling contact, 614
 Roughness, 535
 R ratio effect, 496

S

Shearing force, 696
 Silicon carbide, 393
 Single lap shear, 786
 Size effects, 40, 233
 Slip contact, partial, 696
 S-N interpolation approach, 626
 S-N method, 743
 Solder microstructures, 786
 Stable crack growth, 97, 341, 815

Stable tearing, 884
 behavior, 114
 STAGS shell code, 114
 Steel, 40
 18G2AV, 516
 A 508 C13, 284
 A 533, Grade B, 17, 341
 A 723, 897
 EH-36, 884
 ferritic structural, 40, 341
 high strength, cannon components, 897
 high strength low alloy, 82, 642, 884
 pressure vessel, 17, 341
 railroad rails, 614
 Strain amplitude, 599
 Strain, cyclic, 674
 Strain energy, stored, 215
 Strain hardening, 642
 Strain saturation, 642
 Stress amplitude, 599
 Stress analysis, 453
 finite element, 897
 Stress, applied, 496
 Stress effect, mean, 802
 Stress effects, residual, 614
 Stress field, residual, 516
 Stress incursion, plastic zone, 474
 Stress intensity factor, 176, 565, 897
 correlation with crack growth increment, 438
 crack propagation, 474
 crack tip, 696
 effective, 674
 Weibull stress and, 284
 Stress intensity range, 426
 Stress, maximum principal, 658
 Stress ratio, 407, 426, 626
 Stress/rupture specimens, 384
 Stress-strain curve, 82
 Stress-strain technique, 830
 Stress-zone volume, 830
 Stretch zone, 496
 Strain incursion, plastic zone, 474
 Strip-yield model, 453, 516
 Structural calibration function, 248
 Structural components, 743, 884

920 FATIGUE AND FRACTURE MECHANICS

Structural constraint, 341
Structural stress method, 802
Subclad flaw, 284
Superposition method, 154
Surface closure measurements, 407
Surface cracks, 453
Surface flaws, 393
Surface roughness, 535

T

Tearing, stable, prediction, 815
Tensile behavior, 393
Tensile residual stress, subsurface, 614
Tensile shear loading, 802
Tensile stress, 393
Thermomechanical fatigue, 786
Three-dimensional computational fracture mechanics, 176
Three-point bend, 9, 315
 plane strain specimen, 201
 specimens, 154
Tin enrichment, 786
Titanium
 alloy, 727
 foils, 713
 Ti-6Al-4V, 626
Train derailment, 614
Transferability, 315
Transformation procedure, simplified, 248
Transition region
 ductile-brittle, 55
 temperature, 40
T-stress, 341
Tube, autofretted, 565
Tube, high strength cannon, 897
Tube, pressure, through-wall crack, 830
Two-dimensional finite element code, 264
Two-parameter approach, 9

U

Ultrasonic pulse transmit-receiver method, 642
Upper shelf energy
 Charpy, 40
Upper shelf temperature, 341

V

Variable amplitude fatigue crack growth, 727
Void nucleation law, 364
Void volume fraction, 201, 364

W

Waves
 amplitude, 642
 longitudinal, 642
Weibull stress, 135, 284, 315
Welded joints, 315
Weld fracture, 154
Weld material, ductile crack growth in, 851
Welds, resistance spot, 802
Weld strength mismatch, 315
Weld tests, multi-specimen, 862

Y

Yielding
 localized, 584
 reverse, 552, 565
Yield strength, 862
Yield stress, 426
Young's modulus, 393

Z

Zirconium, 830