

Subject Index

A

Adhesive, 62
 Aerospace applications
 high temperature, 172, 216
 Alumina, 118
 alumina-silica, 172
 ASTM standards
 C 1275, 15, 48, 86
 C 1292, 15
 C 1341, 15
 development, 3

B

Beam test, double cantilever, 31
 Boron nitride-containing
 interphase, 48, 86, 229,
 306

C

Calibration, compliance, 31
 Coating techniques, 276
 Combustor liner, high
 temperature, 3, 201
 Conductivity, thermal, 185
 Cracks and cracking, 245, 262
 growth, 229
 matrix, 134, 306
 stress, matrix, 148
 Creep, 172
 creep-rupture, 245, 290

D

Damage, 185
 accumulation, 306
 Debonding, 185
 Deformation, 134
 tensile, 262
 time-dependent, 216
 Degradation, 229, 290
 high temperature, 118
 modulus, 245
 Delamination toughness, 31

Density, bulk, 86
 Double cantilever beam, 31
 Double notch compression, 15
 Durability, high temperature,
 107

E

Elastic modulus, 86
 Embrittlement, temperature, 306
 End-notched flexure, 31
 Engine, turbine, 3, 62

F

Fatigue, 262
 testing, 245
 Fiber bridging, 229
 Fiber creep, 262
 Fiber waviness, effect on tensile
 response, 148
 Finite element calculations, 185
 Fixturing, 62
 Flexural properties
 C 1341, 15
 Flexural strength, 160
 Flexure test, 31, 86
 Fracture, 172
 Fracture properties, reinforcing
 fibers, 134
 Fracture stress, fiber, 148

G

Gas turbine, 201
 engine, 3
 Graphite/bismaleimide
 laminates, 160
 Gripping, 62

H

Hoop testing, 3
 Hysteresis, 118

I

Interfacial bonding, 276
 Interfacial conductance, 185
 Interfacial shear stress, 118
 Interphase, 306
 boron nitride, 48, 86, 229, 306
 carbon, 229, 306
 fiber/matrix, 118
 oxidation, 229

L

Laminate
 delamination, 15, 31
 graphite/bismaleimide, 160
 Larson-Miller, 134
 Loading, 107, 118, 216
 constant, 290
 mechanical, 185, 245
 mode, effect on tensile
 deformation, 262
 sustained, 172
 tensile, 148, 172

M

Mastercurve, 148
 Melt infiltration, 216
 Microstructure, 62
 analysis, 201
 assessment, 276
 damage, 185
 Mixed mode single leg bending
 test, 31
 Mode I double cantilever beam
 test, 31
 Mode II end-notched flexure
 test, 31
 Models and modeling, 3
 component lifetimes, 229
 micromechanics-based, 185
 notch effect, 160
 oxidation, 290
 oxidation/volatilization, 201
 rupture, 134
 Monkman-Grant, 134

N

Nextel720/AS, 172

Nicalon, 15, 86, 107, 262
 Hi-Nicalon, 306
 Nicalon-LAS II, 185
 Nicalon/MAS-5, 31
 Nicalon/Sylramic, 48
 Notch effect model, 160
 Notch strength, 172

O

Overstressing, 107
 Oxidation, 185, 290, 306
 damage, 245
 degradation, 229
 fiber coating, 216
 interphase, 229
 paralinear, 201
 protection, 276
 Oxide/oxide, 62, 172

P

Paralinear oxidation, 201
 Plain weave, 148
 Polysilazane, 15, 48

R

Ring burst, 3
 Rupture modeling, 134

S

Satin weave, 148
 Scale formation, 201
 Shear strength
 C 1292, 15
 Shear stress, 118
 Silicon carbide
 creep rupture, 245
 damage accumulation, 306
 degradation, 290
 durability, 107
 interface oxidation, 229
 loading mode effects, 262
 oxidation behavior, 201
 stress rupture, 216
 Silicon nitride, 210
 Silicon nitrocarbide, 48

Single leg bending, 31
 Steam environment, high
 pressure, high
 temperature, 201
 Strain accumulation, 262
 Strength predictions, 160
 Stress concentration, 160
 Stress-relaxation, 216
 Stress, residual, 118, 148
 Stress-rupture, 107, 216
 Stress-strain, 306
 curves, tensile, 276
 Stress, time-averaged, 245
 Surface roughness, 160
 Sylramic, 15, 48, 86, 306

T

Temperature effects on
 delamination toughness,
 31
 Temperature embrittlement, 306
 Tensile behavior, 148
 Tensile deformation, 262
 Tensile loading, 148, 172
 Tensile properties, 134
 Tensile strength testing
 C 1275, 15, 48, 86
 transthickness, 62

Tensile stress-strain, 306
 curves, 276
 Tensile testing, 262
 Tension testing, 86, 118
 Thermal conductivity, 185
 Thermal diffusivity, 185
 Thermal expansion, 216
 Thermal exposure, 118
 Thermogravimetric analysis, 290
 Thermomechanical properties,
 134
 Toughening mechanism, 276
 Toughness, delamination, 31
 Transmission electron
 microscopy, 276
 Transthickness tension, 62
 Turbine engines, 62
 Turbine, gas, 201
 Tyranno-Hex, 276

U

U.S. Air Force, 172

W

Waviness, fiber, effect on tensile
 response, 148