

# Subject Index

## A

- Abbey School Sports Hall, 279
- Acetone, chromatographic scan, 239
- Acute respiratory health monitoring, 134–135
- Aerosol, 9
- Air
  - distribution system, 54
  - movement pathways, ventilation efficiency, 114–115
  - sampling rates, 12
- Airborne particles, 9
- Air-conditioning system. *See* HVAC
- Air exchange, 287
  - parameters, 152
- Air exchange rate, 121, 185
  - factors, 150
  - house, 173
  - measurement, 137
  - tracer gas decay method, 288
  - versus temperature difference, 45–46
- Airflows, interzonal, 288, 291–294
- Air handling units, 36
- Airtightness, 185
- Air-to-air heat exchanger, 148–149, 151, 159, 161
- ASHRAE Dust Spot rating, 13, 20, 26
- ASHRAE Standard 55-1981, 72, 87–88
- ASHRAE Standard 62-1981, 72, 87–88
- ASTM E 741-83, 44, 123, 257–258, 288
- Atomic absorption analysis, 29–30
- Aureobasidium*, 95–96

## B

- Benzene, chromatographic scan, 238–239
- Benzo (*a*) pyrene, 178–184
  - activity questionnaire, 182
  - food, 182
  - home selection, 180
  - indoor/outdoor air sampling, 180
  - methods validation, 180–182
  - seasonal variation, 183
  - soils, 182
  - study area selection, 180
  - study design, 182–183
  - water, 181
- Bioaerosols, 48–49, 116, 125, 129, 141–142
  - data collection, 119–120
  - monitoring, 231
- Breakthrough volume
  - defined, 246
  - low boiling compounds, 247
- British Gas Maintenance Depot, 283
- Building illness syndrome. *See* Sick building syndrome
- Buildings, 2–3, 35–49
  - air distribution system, 36–38
  - air handling units, 36
  - air quality and ventilation rates, 58–59
  - bake out, 107–108
  - carbon monoxide, levels, 40
  - characteristics, 121–122
  - closeout procedure, 107–109
  - contractors, 76
  - construction closeout procedure, 99
  - current investigation, 42–49
    - bioaerosols, 48–49
    - indoor pollutant measurements, 47–48
    - inspection, 42–43
    - system airflows and ventilation effectiveness, 46–47
    - tracer gas decay tests, 43–46
  - description, 36–38
  - design professionals, 76
  - draft, 59, 61
  - envelope, 204–205
  - factors affecting air quality studies, 51–61
  - health and ventilation reduction, 57
  - health and temperature, 58
  - history of complaints, 35
  - indoor climate, 56–57
    - measurements, 55–56
  - investigation, 73, 203, 209
    - factors influencing, 74
    - see also* NIOSH investigations

Buildings—*Continued*

- maintenance problems, 43
- major findings, 38–39
- materials contamination, 70
- mechanical system, contaminant source, 118
- mechanisms for introduction of contaminants, 77–78
- microbiological contaminants, 41
- organizational interests, 75–77
- owners and managers, 76
- past investigations, 38–41
- performance, 35
- pre-occupancy evaluations, 107
- project and problem definition, 73–79
- recommendations, 40
- relief air system, 42–43
- sources of difficulty, 74
- statistical methods, 55–56
- study design, 53–55
- technical causes of problems, 73
- technical systems, 58–60
- time variation of air contamination, 78–79
- single cell, 266
  - multipoint sampling, 267
- see also* Diagnostics; specific buildings or types

## C

- Calcium, 9
- California state office buildings, 99–109
  - air sampling data, 101
  - Bateson building, Sacramento, 100–102
  - California Energy Commission Building, Sacramento, 104–105
  - design flaws, 106
  - recommendations, 107
  - State Office Building, Long Beach, 102–104
- Canister collection systems, VOC, 266–227
- Carbon dioxide, 63
  - concentration, 48, 67, 88, 113–114
  - monitoring, 262–263
- Carbon monoxide, 219
  - concentration, 40, 48
  - GEOMET test houses, 155
  - electrochemical personal exposure monitors, 221
  - monitoring, 172, 221
- Carrier gas flow rate, electron capture detector, 271–272
- Chemical reactivity, 188
  - equivalent volumetric flow rate, 192

- Chemiluminescence, NO<sub>2</sub> monitoring, 222
- Coarse particles, 9
  - indoor and outdoor concentrations, 21–22
- Combustion-related sources, 115, 166–177, 205
  - broad, low-intensity field studies, 171
  - cross-sectional studies, 171, 177
  - emission rates, source strengths, and venting factors, 173–174
  - factors affecting usage patterns, 169–170
  - measurement techniques and protocols, 171–175
  - modeling, 168–171
  - reactivity rates and penetration factors, 174–175
  - samplers, 172–173
  - short-term concentrations, 175
  - source strength, 169, 171
  - source usage parameters, 173
  - types, 167–168
  - venting factor, 169
- Commercial buildings. *See* Buildings
- Consultation, 80, 82–83
  - flowchart, 84
- Consumer products, 234, 237
- Contaminant, 35, 99
  - assessment, 47–48, 55, 115
  - concentration, 185, 196
    - attenuation of differences, 196
    - change in, 251
    - factors affecting, 169–170
    - spatial average, 168–169
  - evaluations, 111
  - exposure-response relationship, 205
  - mechanisms for introduction, 77–78
  - sources, 115–116
    - outside, 116–117
    - time variation, 78–79
  - source strength. *See* Source strength
  - storage and release, 188
- Control strategies, 90
- Cooling towers, contaminant source, 117
- Courtaulds Engineering Workshop, 280
- Courtaulds Pattern Making Shop, 281
- Coventry Airport, 282

## D

- Data
  - analysis, 214
  - evaluation, 213–215
  - flow and tracking, 213
  - quality, 18–19, 179

- Data collection, 19, 111–125  
 air movement pathways, 114–115  
 assessing ventilation rates, 113–114  
 bioaerosols, 119–120  
 building height, 118  
 building mechanical system, contaminant source, 118  
 computer-controlled, 264  
 contaminant assessment, 115  
 history of occupant complaints and building operation, 112–113  
 HVAC, preventive maintenance, 118  
 indoor contaminant sources, 115–116  
 mechanical systems, 114  
 outside contaminant sources, 116–117  
 tracer gas decay measurement, 120–124
- Deposition velocity, 9
- Design, 99  
 definition, 1  
 flaws, 106  
 original intent, 113
- Diagnostics  
 consultation, 82–83  
 data acquisition, 84  
 determining appropriate instrumentation, 82  
 hypotheses, 85  
 interpreting results of measurements, 83  
 knowing what to measure, 82  
 predicting building performance, 83  
 protocols, 81–83  
 qualitative, 82, 85–91  
   chemical and physical agents, 86–88  
   control strategy analysis, 90  
   flowchart, 86  
   load analysis, 90  
   performance criteria, 85–89  
   problem and complaint characterization, 89  
   report, 90–91  
   simulation, 90–91  
   system boundaries, 89  
 quantitative, 82, 91–97  
   analysis, interpretation, and report, 95–97  
   flowchart, 92  
   human resource questionnaire, 93–95  
   informed consent notice, 94, 96  
   objective measures, 93  
   quality assurance and control, 93  
   site selection, 91–93  
   subjective measures, 93–95
- Diffusive sampling, VOC, 29
- Draft, 51  
 commercial and office buildings, 59, 61
- Dust, monitoring, 231–232
- ## E
- Electrochemical CO personal exposure monitors, 221
- Electron capture detector  
 amplifier, 268–269  
 block diagram, 259–261  
 carrier gas flow rate, 271–272  
 column dimensions, 269, 271  
 current, 269–270  
 performance, 271  
 sample loop volume, 271  
 sampling and calibration valves, 259  
 six-channel design, 271, 273–274  
 system optimization, 269
- EI  
 ventilation rates, 259–261
- Emission rate, 234  
 combustion-related sources, 173–174
- Energy conservation, 9, 99
- Energy consumption, 148, 287  
 factors, 150  
 parameters, 152
- Engineering analysis, 80
- Environmental chamber, 234
- Environmental chamber/gas chromatographic instrumental system, 235–236
- Environmental inventories, 203
- Environmental Inventory Questionnaire. *See* Questionnaires
- Environmental parameters, 152
- Epidemiology, 206–207
- Evaluation criteria, 68
- Exfiltration, 121
- Exhaust systems, localized, contaminant source, 117
- Exposure, 185  
 factors, current levels of knowledge, 206  
 multiple vector assessment, 179
- ## F
- Fibers, 116
- Field tests, 185  
 protocol, 194–195
- Filters, preparation and weighing, 11
- Filtration, 9  
 household, 187
- Fine particles, 9  
 indoor and outdoor concentrations, 21–22  
 sources, 26

Food, benzo(*a*)pyrene. 182  
 Formaldehyde, 129, 219  
   concentrations. 103, 164  
   measurements. 138–140  
   monitoring. 224–225  
   regression model. 164

## G

Gas analyzer  
   block diagram. 273  
   calibration. 271, 275  
 Gas chromatography. 219, 269, 289  
   ventilation rates. 258  
 Gaseous-pollutant concentration. 168  
 Gaseous sample introduction system. 235–237  
 GEOMET test houses. 148–165, 289  
   closed-wall construction. 152  
   critique and recommendations. 161–162  
   data analysis and interpretation. 157–161  
   data flow and use. 157  
   experimental design. 149–151  
   floor plans. 153, 290  
   house model. 152–153  
   models. 158  
   objectives. 148  
   occupancy simulations. 151  
   post-retrofit monitoring. 149  
   retrofit effect. 158–159  
   semicontinuous measurements. 156  
 Governmental agencies. 77

## H

Halocarbon tracers. 291–294  
 Harvard Six-Cities Study. 130  
 Heating. *See* HVAC  
 Hot water heating system. 54  
 Human resource questionnaire. 93–95  
 Humidity. 63, 68  
   control, contaminant source. 118  
 HVAC. 9, 51, 63, 111  
   boundaries. 89–90  
   capacities. 90  
   evaluation. 65–68, 100  
   malfunctions. 102  
   mechanical systems. 114  
   operation  
     changes. 32  
     indoor air effect. 13  
     procedure implementation. 15  
   parameters. 16–17  
   status. 21

  variable air volume multizone. 99  
 Hypersensitivity pneumonitis. 49, 69

## I

Ill buildings. 51  
 Indoor climate  
   attributes. 94  
   commercial and office buildings. 56–57  
   identification. 204  
   measurements. 55–56  
 Indoor concentration. 21  
   average. 20  
   inorganic gases. 24–25, 27  
   ionic species. 22, 26  
   nonpolar organic compounds. 24, 27  
   trace elements. 22–23, 27  
   VOC. 22, 24–25, 27  
 Infiltration. 81, 121, 148, 266, 287  
   instrumentation. 257  
   measurement. 257  
   prediction model. 191  
   rate. 279–283, 293  
     seasonal frequency distribution. 158–159  
     whole building. 282–283  
 Informed consent notice. 94, 96  
 Infra-red gas analysers. 267  
 Inhaled particle monitors. 223  
 Inorganic gases. 9  
   indoor and outdoor concentrations. 24–25, 27  
 Inspection, office building. 42–43  
 Instrumentation. 4, 166, 219–232  
   bioaerosol monitoring. 231  
   CO monitoring. 221  
   CO<sub>2</sub> monitoring. 262–263  
   failures. 16  
   formaldehyde monitoring. 224–225  
   house dust monitoring. 231–232  
   integration, survey studies. 212–213  
   monitor development. 220  
   NO<sub>2</sub> monitoring. 221–223  
   PAH monitoring. 228  
   pesticides and related SVOCs. 227–228  
   positioning. 18  
   radon monitoring. 230–231  
   respirable particles. 223–224  
   selection. 17–18, 82  
   surveys. 211–213  
   survey studies. 200  
   ventilation. 257  
   ventilation rates. 262–264  
   VOC monitoring. 225–227  
   *see also* specific devices

Integrative passive sampling devices, 221–223  
 Interest groups, 75–77  
 Interzone flows, 279–283  
 Ionic compounds, 9  
 Ionic species, indoor and outdoor concentrations, 22, 26

## K

Kerosene heaters, 143–144  
 Kingston-Harriman, Tennessee, multipollutant study, 129

## L

*Legionella*, 141–142  
 Loading docks, contaminant source, 117  
 Long-term exposure prediction, 185–197  
   analysis methodology, 193–194  
   concentrations, 196  
   equivalent ventilation, 196  
   factors affecting modeling, 186–187  
   field testing protocol, 194–195  
   future work, 197  
   hourly average concentration, 195  
   model development, 188  
     parametric forms, 189–191  
     ventilation models, 191–193  
   Wadden and Scheff single-cell model, 189  
   removal mechanisms, 187–188  
   sources, 195–196

## M

Mass balance model, 9, 19–20, 28–30, 158, 166, 244  
   systematic identification, 204  
   two-zone case, 291–292  
   VOC, 251, 253  
 Mass spectrometry, 219  
 Material suppliers, 76  
 Measurement methods, 219  
 Methodology, 4, 73  
 Methods validation, 178  
   multisorbent sampling technique, 246–248  
 Methylene chloride, chromatographic scan, 239  
 Microbiological agents, 88–89  
 Microbiological contamination, 41, 70–71  
 Microbiology, 111  
 Microenvironmental survey, 178, 182  
 Microorganisms, 129  
 Mixing factor, 185, 191  
   calculation, 194–195

Modeling, 148, 166, 185  
   combustion-related sources, 168–171  
   conceptual, 204  
   GEOMET test houses, 158  
   long-term exposure prediction, factors affecting, 186–187  
   *see also* Mass-balance model  
 Monitoring, 73  
 Multiple exposures vector assessment, 179  
 Multipollutant study, 129–147  
   acute respiratory health monitoring, 134–135  
   air exchange rate, measurement, 137  
   bioaerosols, 141–142  
   core air quality monitoring, 135–137  
   energy use and weatherization characterization, 142–145  
   formaldehyde, measurements, 138–140  
   group classification code, 131  
   Harvard Six-Cities Study, 130  
   house construction and retrofit, 154  
   kerosene heater, 143–144  
   monitoring strategy, 154–156  
   nitrogen dioxide, monitoring, 135–136  
   PAHs, monitoring, 139–141  
   parameters, 152, 162  
   phases, 153–154  
   post-study evaluation survey, 145–146  
   protocols, 133–134, 154–156  
   radon, measurements, 137–139  
   respirable particles, monitoring, 136–137  
   study design, 130–133  
   supplemental air quality monitoring, 137–142  
   water vapor, monitoring, 136–138  
   weekly initial setups, 132  
 Multisorbent sampling technique, 244–255  
   application, 248–255  
   laboratory and field evaluation, 246  
   materials and methods, 245–246  
   method validation, 246–248

## N

National Ambient Air Quality Standards, 87–88, 198  
 NIOSH investigations, 41  
   building materials contamination, 70  
   by building type, 69–70  
   common health complaints, 70  
   inadequate ventilation, 71–72  
   indoor air quality questionnaire, 66–67  
   inside contamination, 71  
   methodology, 64–69

- NIOSH investigations—*Continued*  
 additional site assessments, 68–69  
 background assessments, 64–65  
 evaluation criteria, 68  
 initial site assessment, 65–68  
 microbiological contamination, 70–71  
 outside contamination, 71  
 by problem type, 70–71  
 by year, 69
- Nitrogen dioxide, 129, 219  
 monitoring, 135–136, 221–223
- Nitrous oxide, as tracer gas, 266
- Non-dispersive infrared spectroscopic detection, 221
- Non-Occupational Pesticides Exposure Study, 227–228
- Nonpolar organic compounds, indoor and outdoor concentrations, 24, 27
- O**
- Objective measures, 93
- Odor recognition thresholds, 87, 98
- Office buildings. *See* Buildings
- Operating room, model for contaminant balance, 91
- Optical particle counters, 31–32
- Organic chemicals, 116
- Organizational interests, 75–77
- Outdoor concentrations, 21, 71  
 inorganic gases, 24–25, 27  
 ionic species, 22, 26  
 nonpolar organic compounds, 24, 27  
 trace elements, 22–23, 27  
 VOC, 22, 24–25, 27
- Ozone, 115
- P**
- Palmes tube, 222
- Parametric forms, 189–191
- Parametrics, 185
- Parking lots, contaminant source, 117
- Particles  
 fractionating, 29  
 optical counters, 31–32  
 source, 115
- Particulate organics, 9
- Particulate samples, characteristics, 12
- Pasila Office Center, 52–53  
 air distribution system, 54  
 hot water heating system, 54  
 indoor climate measurements, 55–56  
 protocols  
 sampling, 199–200  
 statistical, 199
- Passive badges, 219
- Passive bubbler monitor, 224
- Passive sampling, 19, 133  
 formaldehyde, 224–225  
 NO<sub>2</sub>, 221–223  
 VOCs, 17, 226–227
- PCP, levels, 103, 106
- Penetration factor, 175
- Perfluorocarbon tracers, 288–289, 294–296
- Performance criteria, 80, 85–89
- Personal exposure monitors  
 CO, 221  
 respirable particles, 223–224
- Personal interviews, 65
- Personal monitors, 219
- Pesticides, 219  
 monitoring, 227–228
- Phillipsburg, New Jersey, 180–181
- Pneumonitis, hypersensitivity, 49, 69
- Polyaromatic hydrocarbons, 219
- Polynuclear aromatic hydrocarbons, 129  
 denuder-based samplers, 229–230  
 monitoring, 139–141, 228–230  
 sources, 228
- Polyurethane foam, 219, 227–228  
 adsorbent cartridge, PAH monitoring, 228–229
- Power availability, sampling equipment, 16
- Prediction, 185
- Pre-occupancy evaluations, 107
- Probability distributions, 184
- Professional services, 76–77
- Protocol, 73, 80–83, 99  
 combustion-related sources, 171–175  
 definition, 1  
 field tests, 194–195  
 long-term exposure prediction, 194–195  
 multipollutant study, 133–134, 154–156  
 sampling, 199–200  
 statistical, 199  
 telephone office buildings, 16–19
- Proton-induced X-ray emission, 27, 30–31
- Q**
- Quality  
 assurance, 93  
 control, 93
- Questionnaires, 66–67, 203–210  
 administration issues, 210–211  
 assessment, 211  
 comfort and psycho-social considerations, 209

design, 210–211  
 development, 209–210  
 effectiveness, 206  
 logic of conceptualization, 210  
 necessary information, 207–209  
 reliability and validity, 207  
 significant questions, 207–209  
 standard, 209–210  
 survey role, 206–207  
 techniques of operationalization, 210

## R

Radon, 116–117, 129, 219  
 concentrations, 48  
 measurements, 137–139  
 monitoring, 230–231  
 Reactivity, 185  
 Reactivity rate, 174  
 Regression model, formaldehyde, 164  
 Relief air system, 42–43  
 Removal mechanisms, 205  
 Residential buildings, 3–4  
 field studies, 129  
 Respirable particles, 129  
 monitoring, 136–137, 223–224  
 sampling, 172  
 Retrofit, 148  
 effect, 158–159  
 monitoring after, 149  
 procedure, 154  
 Roadways, contaminant source, 117  
 Room temperature, 51, 63, 68  
 distribution, 56–57  
 draft sensation and, 61  
 health and, 58  
 performance criteria, 87–88

## S

Sampling  
 combustion-related sources, 172–173  
 periods, 18  
 program, California state office buildings,  
 103  
 protocols, 199–200  
 site selection, 91–93  
 sufficient material, 17  
 Scandium-titride source, 259  
 Semivolatile organic chemicals, monitoring,  
 227–228  
 Sick building syndrome, 51, 219  
*Aureobasidium*, 95–96  
 SBS-score, 55–57  
 symptoms, 51–52, 69–70, 244, 246  
 adjusted summation score, 58–60  
 correlation with room temperature, 61  
 passive smoking and, 61  
 Simulation, 90–91  
 Single-cell model, 187, 189  
 Site assessment, 65–69  
 Smoking  
 environmental smoke, 208  
 particle source, 115  
 passive, SBS symptoms and, 61  
 Soils, benzo(*a*)pyrene, 182  
 Sorbents, 219  
 Sorbent sampler, 244  
 Sorbent tube samplers, VOC, 246  
 Sources, 185  
 inventories, 107  
 Source strength, 169, 185, 244  
 apparent specific, 251–253  
 combustion-related sources, 171–174  
 parametric response to step change, 190  
 VOC, 249–250, 254  
 Space heater  
 source strengths, 171  
 usage, 208  
 Stack effect parameters, 192  
 Standardization, 203  
 State Office Building, Long Beach, 102–104  
 Statistical protocols, 199  
 Stuffly offices, 51  
 Subjective measures, 93–95  
 Sulfate, 9  
 Sulfur hexafluoride  
 calibration curve, 262–263  
 concentrations, 155–156  
 decay method, 293  
 electron capture detector, 259–261, 268  
 peaks  
 height and base line, 269–270, 272  
 various concentrations, 259, 261  
 as tracer gas, 257–264, 266, 289  
 tygon tubing, 262  
 Surface sampling, 11–12  
 Survey studies, 198–201, 203  
 design considerations, 199  
 evaluation, 213–215  
 identification of factors, 203–207  
 integration of instruments, 212–213  
 issues, 200–201  
 measurement methods and instruments,  
 200  
 microenvironmental, 178, 182  
 monitoring instrument selection, 211–213  
 post-study evaluation, 145–146  
 recommendations, 201  
 role of questionnaires, 206–207

Survey studies—*Continued*  
 sampling protocols, 199–200  
 statistical protocols, 199  
 walk-through, 65

Suspended particles, indoor and outdoor concentrations, 21–22

## T

Telephone office buildings, 9–33  
 air sampling rates, 12  
 data collection and management procedures, 19  
 design variables affecting accuracy, 13  
 goal of study, 10, 28  
 implementation and protocols  
 adequate samples, 17  
 data quality assurance, 18–19  
 HVAC parameters, 16–17  
 instrument failure, 16  
 instrument positioning, 18  
 instrument selection, 17–18  
 power availability, 16  
 procedure development, 14  
 procedure implementation, 14–16  
 sampling periods, 18  
 unusual activities at sites, 17  
 weather effects, 16  
 indoor and outdoor concentrations  
 fine, coarse and total suspended particles, 21  
 inorganic gases, 24–25, 27  
 ionic species, 22, 26  
 nonpolar organic compounds, 24, 27  
 trace elements, 22–23, 27  
 VOC, 22, 24–25, 27  
 interpretation of results, 25–28  
 leakage rate, 30  
 model 30–31  
 development, 19–21  
 origin of study, 9–10  
 particulate samples, characteristics, 12  
 preparation and weighing of filters, 11  
 recommendations, 31–32  
 retrospective analysis, 28–31  
 sampling duration, 10  
 site selection, 13  
 study design, 10–13, 28–30  
 surface sampling, 11–12  
 volatile organic sampling, 12–13  
 Tenants, 76  
 Tenax-GC sorbent tubes, 219, 225–226  
 Thermosorb cartridge, 222–223  
 Threshold limit values, 87  
 Tight office building syndrome, 51

Toluene, chromatographic scan, 239  
 Total exposure assessment methodology study, 198  
 Total human environmental exposure study, 178  
 Trace contaminants, exposure vectors, 179  
 Trace elements, 9  
 indoor and outdoor concentrations, 22–23, 27  
 Tracer gas decay method, 43–46, 111, 114, 120–124, 266–285  
 air exchange  
 evaluation, 121–124  
 rates, 45–46, 288  
 airflows, 46–47, 124  
 air sampling, 44–45  
 automated measurement system, 44  
 block diagram, 274  
 building characteristics, 121–122  
 calibration, 271, 275–276  
 constant concentration, 287  
 data analysis, 277–278  
 effective volume, 123–124  
 future developments, 285  
 halocarbons, 291  
 infiltration rates, 279–283  
 injection system, 123, 277  
 constant injection, 287, 289  
 instrumentation, 122–123  
 interzone flows, 279–283  
 multiple, 287–296  
 calculations, 291–292  
 interzonal airflows, 288, 291–294  
 results, 292–296  
 multipoint, 267  
 oscillation due to time lags, 284–285  
 percent recirculation, 124  
 perfluorocarbon tracers, 288–289, 294–296  
 quantities of outside air delivered, 123  
 setup, 277  
 site calibration, 277  
 specification, 267–268  
 Tracer gas dilution, 257, 275–276  
 1,1,1-Trichloroethane, 105

## V

Ventilation, 35, 63, 121, 185  
 assessment, 111  
 effective, 185  
 effectiveness, 47, 187  
 efficiency, air movement pathways, 114–115  
 equivalent, 196



- inadequate, 71–72
  - instrumentation, 257
  - measurement, 257
  - mechanical, 121
  - models, 191–193
  - natural, 81, 121
  - reduction and health, 57
  - testing, 104
  - Ventilation rate, 51, 244, 257–264
    - across-the-envelope, 187
    - air quality and, 58–59
    - assessment, 113–114
    - calibration system, 262–263
    - codes and standards, 81
    - computer-controlled data acquisition system and driving software, 264
    - effective, 113–114, 191
    - electron capture detector, 259–261
    - equivalent, 185, 188
    - gas chromatograph, 258
    - instrumentation, 262–264
    - sampling system, 262
  - Venting factors, 174
  - Volatile organic chemicals, 4, 9, 219
    - adhesive, 243
      - chromatographic scan, 239, 241
      - source strength, 254–255
    - carpet, chromatographic scan, 239–240
    - collection on solid sorbents, 234
    - concentrations, 48, 105, 250–252
      - as function of ventilation rate, 250, 252–253
    - consumer product testing, 237
    - diffusive sampling, 29
    - environmental chamber/gas chromatographic instrumental system, 235–236
      - experimental procedure, 236–238
      - gaseous sample introduction system, 235–237
      - indoor and outdoor concentrations, 22, 24–25, 27, 248–250
      - low-boiling compounds
        - breakthrough volumes, 247
        - precision and accuracy, 247–248
      - mass-balance model, 251, 253
      - monitoring, 225–227
      - multisorbent sampling technique. *See* Multisorbent sampling technique
      - paint, chromatographic scan, 239, 242
      - passive sampling, 17, 226–227
      - retention times, 237–238
      - sampling, 12–13
        - valving diagram, 236–237
      - source strengths, 254
- W**
- Wadden and Scheff single-cell model, 189
  - Walk-through survey, 65
  - Water
    - benzo(a)pyrene, 181
    - vapor, monitoring, 136–138
  - Weather, effects on procedure implementation, 16
  - Weatherization, 142
  - Wind effect parameter, 192
- X**
- XAD-2 resin, 229