

Subject Index

A

Adhesion, 113, 252, 335
 silicone sealants, 65, 97
 Adhesion failure, 37, 280
 Adhesion rate, 303
 Ageing, 372
 Airport, 346
 Alkoxy-cure system, 97
 Antifungal, 228
 Antimicrobial, 228
 Asphalt, modified, 262
 ASTM C24 standards, 355
 ASTM C 836, 88
 ASTM C 920, 143
 ASTM C 1135, 303
 ASTM C 1184, 45, 56
 ASTM C 1401, 45
 ASTM C 1521, 335
 ASTM D 1002, 3
 ASTM G 21, 228

B

Backing foam, 171, 184
 Backing material, 280
 Biocide, 228
 Biodeterioration, 228
 Bond durability, 143
 Bond strength, 113
 Braining, 88
 Building, 385
 Butyl, 262

C

CAN2-19.0-M77, 228
 CAN/CGSB-37-58, 88
 Carbon arcs, 355
 China, curtain walls, 56
 Cladding systems, 171, 184
 Closed-cell, 171
 Cohesive failure, 280
 Cold application, 346
 Cold liquid-applied waterproofing, 88
 Compression, 372
 Concrete pavement, 346
 Construction joints, 385
 Control joint, 280
 Curtain wall, 37, 45, 56, 171, 303

D

Degradation, 206
 Drainage system, secondary, 3
 DSC, 310
 Duct leakage, 213
 Duct tape, 213
 Durability, 3, 65, 97, 113, 303, 325, 355
 Durability design, 24
 Durability test method, 206

E

Elastomeric sealants, 171, 325, 372
 Expansion joint, 280
 Exterior cladding, 3

F

Factory applied glazing, 45
 Fatigue, 184
 cycling, 206
 resistance, 156
 Field testing, 335
 Finite element analysis, 24, 156, 372
 Flashing, 262
 Flex duct, 213
 Float glass, 97, 252
 Fluorescent UV lamps, 355

G

GB 16776, 56
 Glass curtain wall, 56
 Glass-transition temperature, 143

H

Harmonization, 355
 Horizontal sealant joint, 280

I

Image analysis, 310
 Infiltration, 3
 Insulating glazing, 372
 Intersection, 156
 ISO 846, 228
 ISO standards, 355

J

Joint design, 156
 Joint geometry, 24
 Joint sealing, 346

K

Kraton, 310

L

Leaching, 228
 Lock-strip gaskets, 14

M

Maintenance, 346
 Mechanical performance, 171, 184
 Mechanical property, 325
 Microscopy, 310
 Modulus, 280
 Moisture, 113
 Morphology, 310
 Movement during cure, 171, 184
 Mullins effect, 325

N

NFX 41-514, 228
 Nondestructive testing, 335

O

Open-cell, 171

P

Peel adhesion, 143
 Penetration resistance, 280
 Percolation, 3
 Personal injury, 280
 Physical-chemical characteristics, 310
 Point supports, 24
 Polyester powder coating, 65
 Polyether, 206
 Polysulfide, 206, 310
 Polyurethane, 171, 206, 310
 Portland cement concrete, 346
 Preformed silicone, 14
 Primer, 113

Q

Quality assurance, 45

R

Remedial glazing, 45, 303
 Remedial weathersealing, 303
 Rheology, 143, 325
 RILEM TC139-DBS, 206
 Rocking movement, 156

S

Sealant failure, 310
 Sealant joints, 3, 156, 184, 280, 335, 385
 Sealant longevity, 213
 Self-leveling sealant, 280
 Service life prediction, 385
 Shear movement, 156
 Silicone, 206, 228, 310
 Silicone adhesive, 14
 Silicone extrusion, 3
 Silicone rubber extrusions, 303
 Silicone rubber molded parts, 303
 Silicone sealants, 65, 97, 252
 Silicone structural glazing, 37, 45, 372
 Silyl-terminated polyether, 143
 Silyl-terminated polyurethane, 143
 Sizing articles, 14
 Spalling, 280
 Specification, 346
 Stress-extension, 325
 Stress relaxation, 372
 Stress-strain curve, 372
 Structural glazing, 24, 37, 45
 Structural sealant glazing, 97
 Structural silicone sealant, 45, 56
 Surface composition, 252

T

Tension, 372
 Testing, 45
 TGA, 310
 Toxic mold, 335
 Triglycidyl isocyanurate, 65

U

UL 181B, 213
 Uniaxial load, 372
 UV exposure, 252

V

Viscoelasticity, 325

W

Water absorption, 88
 Water immersion, 113, 252
 Water management, 262
 Waterproofing, 88
 Wax, 65
 Weathering, 228, 310, 355
 artificial, 206
 Weatherproofing, 97, 303, 335, 372

Window flashing, 262

X

Xenon arc, 355
 Xenon-light, 206

Z

Zipper gaskets, 14