

Subject Index

A

- Absorptance, surface, thermal effect, 457-458
- Absorption, water, 717
- Active measurement strategy, thermal performance of walls, 92-93, 94(table), 96-97(tables)
- Adsorption, water, 717
- Aerial thermography, 176, 178, 181-185
- Air barrier, discussion, 625
- Air change rates, Corry Field units, 386(tables)
- Air conditioning, 14-20, 560
- Air exchange rates, domestic houses, 606(table)
- Air film resistance, 570
- Air flow, 154, 158, 171
- Air flow requirements for energy efficiency, 12, 545
- Air flow visualization, 171
- Air gap systems, 46
- Air handler installations, 14, 15(fig.)
- Air infiltration (*see also* Air leakage)
 - measurement by tracer gas, 175-176
 - of building envelope, 124, 125(fig.)
- Air infiltration tests, 377
- Air layer, 283-286
 - thermal conductivity versus thickness, 290(fig.), 291
- Air leakage
 - building envelope, 34, 36, 38
 - field tests, 644
 - infiltration tests by tracer gas, sulfur hexafluoride, 377
 - R* value accuracy limitations, 213
 - simulated
 - experimental procedure, 642
 - test apparatus, 640, 641(fig.)
- Air leakage reduction (*see also* Insulating materials)
 - cellulose wall insulation, 639
 - insulating materials, flow rate, 643(table)
 - modular retrofit experiment, 647
 - retrofit, 645(table), 648
 - standards development
 - control requirements, 34, 36-37
 - infiltration, 32-33, 124
 - thermal transmittance, 683(fig.)
 - thermographic inspections, 180
 - wood frame walls, 405
- Air movements, thermal performance of building envelope, 124
- Air permeability, 125
- Air pressure changes, face wall, 127
- Air space *R* values for Hi-Hat wall system, 727(table)
- Air temperature, 573
- Air thermal conductivity, 287
- Airtightness, 679, 680(fig.)
 - building envelope, 124-125(fig.), 128-129, 616
 - heat loss reduction, 647
 - pressure versus air flow measurements, 644
- Alarm systems, pressurized monitoring of conduit, 47
- Alkalinity, underground pipe systems, 44-45
- Aluminosilicate fibers, test specimens for radiation heat transfer, 687
- Aluminum jacketing
 - corrugated, vapor barrier design, 74
 - engineered specifications, 84
 - on foamed polyurethane insulation, 74, 77-79
- Ammonia storage tanks, foam insulation systems, 80
- Annual energy budget and usage, 16-18, 19(table), 20
- Antifreeze protection, heat-traced systems, 85
- Apparent thermal conductivity, 518, 522-523(table), 533(table)
- Application procedure checklist, thermal insulation materials, 87-88
- Army buildings, energy conservation, 214-216
- Ash, thermal conductivity, 271(table)
- ASHRAE handbook procedure, heat loss factor, 134-135
- Asphalts
 - application to foam test specimens, 438
 - roofing insulation, 434

- ASTM Committee C-16 on thermal insulation, summary of approach on standards for burn hazard potential, 705
- ASTM standardization work
 proposed standard test method for thermal performance of building components, 718-719
 standards development, uniform definition of human burn hazard, 709
- ASTM standards (*see also* Standards)
 C 76-82: 508
 C 177-76: 108, 494, 588, 651, 656, 686
 C 201-68: 68
 C 202-71(1977): 687
 C 236-80: 297, 310, 311, 326, 346, 508, 509, 567, 652, 724, 728
 C 518-64T: 653
 C 518-70: 651
 C 518-76: 423, 478, 494, 521, 527, 656
 C 518-80: 311
 C 578-83: 520
 C 653-70: 655
 C 653-83: 652
 C 680-82: 709, 710
 C 755-73(1979): 75
 C 976-82: 323, 346, 508, 567, 583, 586
 C 1055-86: 709, 710
 C 1057-86: 709, 711
 D 9-81: 251
 D 95-83: 436
 D 226-82: 434
 D 245-81: 251
 D 250-84: 434
 D 312-78: 434
 D 1079-83a: 432
 D 1165-80: 251
 D 2126-75: 524
 D 2395-83: 251
 D 2555-781: 247, 251
 E 84-84: 73
 E 96-80: 74-75, 464, 716
 E 230-83: 319
 E 331-83: 378, 389
 E 398-83: 463
 E 741-83: 377
 E 799-81: 644
- ASTM Subcommittee C08.05, round robin analysis for ceramic fiber insulation, 686
- Attic air humidity ratios, 631, 632(fig.), 636(fig.)
 measured and predicted, 634, 635(fig.)
- Attic insulation, 210-213, 213-215(figs.)
 field tests, 217-218, 494-500
 standard deviations and means, 502, 503-504(tables)
- impact on indoor formaldehyde concentrations, 231-232, 235
 loose-fill, densities, 495
 low levels, 637
 test module, 716, 717(fig.)
- Attic ventilation, 635
 guidelines, 637
- Average computed conductivity, comparison of mean data, 248(table)
- ## B
- Backfilling, 46
 Balance point temperature, 554
 Balloon frame construction, air leakage reduction after wall insulation retrofit, 644
 Basement air leakage, 644
 Basement wall/floor heat loss, 132
 climatic sensitivity, 142(fig.)
 Washington, DC, 136-138(figs.), 144-151(appendix tables)
- Beadboard insulation (expanded polystyrene, EPS), 422, 518
- Biguarded thermal hot plate, 286
- Birch, thermal conductivity, 268-269(table)
- BLAST (*see* Building Loads Analysis and System Thermodynamics)
- Blistering, built up roofing membranes, 432-433, 447
- Block-molded polystyrene insulation, exposure studies, 524-529, 534, 582, 588, 589
- Blower-cyclone-shaker (BSC) test, 500, 501(table, fig.)
- Blown-in loose-fill insulation, 199
- BOCA (*see* Building codes)
- Bubbling phenomenon
 application of hot asphalt, 438
 roof insulation, 433, 440, 443, 446
- Building codes, 721
 Florida model energy efficiency code for building construction, 9, 12, 14-15, 20
- Building component characteristics, ASTM test methods for evaluation, 713
- Building component performance, domestic houses, 607
- Building components, test development simulators, 717
- Building component thermal, resistances, 179
- Building design for energy efficiency, 14, 15(table)
- Building design requirements and trade-off approaches, 29

- Building design thermal insulation, 679
 - Building diagnostics, 179
 - Building energy requirements, 341
 - Building envelope, 29, 639
 - air infiltration, 124, 125(fig.)
 - air leakage control, 34, 36-38
 - air movements, 124
 - air permeability, 125
 - BLAST program, 544
 - defects, 310, 680
 - openings for electrical installations, windows, doors, ventilation, etc., 682
 - design, 238
 - energy requirements, 341
 - exterior of office buildings, thermal resistance, 107
 - heat flow test procedures, 110-113
 - heat loads/gains, 203
 - heat loss, 179, 317
 - high-solar-gain house, 545
 - office buildings, 107
 - pressurization tests for measuring tightness, 175
 - thermal performance, 107-108, 124-131, 616, 679
 - use of thermal insulating materials, 477
 - Building heat transfer, 154, 156, 169
 - Building Loads Analysis and System Thermodynamics (BLAST), 542, 544
 - Building materials, moisture performance, 616
 - Building performance optimization, 21-22
 - code compliance, 9, 29-34
 - energy analysis procedure, 27-28, 35-36, 341
 - parameter selection and analysis, heating and cooling, 28
 - Building Research Association of New Zealand, 94
 - Buildings
 - heat transfer characteristics, masonry cavity wall, 319
 - moisture problems, 371
 - U.S. Army, *R* values, field investigations, 203
 - use of thermography to rank heat loss characteristics, 178
 - Building thermal analysis, 203-210
 - heat loss calculations, 132
 - Building types
 - army, 205

	(tables)
--	----------
 - for energy calculations, 12, 13

	(table)
--	---------
 - Built-up roofing/insulation specimens, delamination, 437, 443, 444
 - Built-up roofing membranes, 432
 - Burn hazard evaluation, 704-711
 - design conditions, 710
 - potential, 705
 - Burn potential for heated surfaces, 711
 - Burn protection, 704
- C**
- Calcium carbonate fill, treated in insulating envelope system, 48
 - Calcium silicate pipe insulation, 46
 - Calibrated hot box (*see also* Hot box), 163, 319-325, 346
 - design considerations, effect of environment, 358
 - testing, 582, 584(fig.)
 - test apparatus, 585(fig.)
 - vapor barrier, 615
 - Calibration, 576, 653-654, 658
 - instrumentation development, 659
 - Calibration constant versus thickness, R-Matic instrument, 660(fig.)
 - Calibration specimen, 577(fig.)
 - Calorimeter analysis, comparison between four and twelve data points, 694
 - Calorimeters, 175, 567, 569(fig.), 572
 - air temperature, 573
 - design, 573-575
 - heat flux, 119-120
 - portable, 108, 109(fig.)
 - water, 686
 - Calorimeter test data
 - ceramic fiber round robin, 690
 - thermal conductivity versus mean temperature, 698(fig.)
 - Carrier pipes, cement, 47
 - Cavity walls, 319
 - heat transmission characteristics, 339
 - Cedar, thermal conductivity, 249

	(table), 268-269(table)
--	-------------------------
 - Ceilings
 - air leakage, 213
 - Ceilings (*cont.*)
 - code requirements, 23(fig.)
 - heat loss due to missing insulation, 120, 180
 - insulation, 610, 644
 - retrofit, 646
 - resistance variations, cause of differences in surface temperatures, 178
 - standards development, 29, 36
 - Cellular glass insulation, 48
 - Cellular plastic insulation, 421, 422-423, 432, 582, 720
 - Cellular polyurethane, 71
 - Cellulose insulation
 - air leakage reduction, 643

- Cellulose insulation (*cont.*)
 density test, 495-498
 new construction applications, 642
 settling test (BSC test), 500
 spray-applied laboratory/field tests, 362-366, 367(table)
- Cellulose wall insulation
 effect on leakage, 644, 646(table)
 retrofit reducing air leakage, 647
- Cementitious coatings, vapor barrier design, polyurethane foam insulation, 74
- Centre de Recherches Industrielles de Rangigny (CRIR), 161, 284
 heat flux transducer, 656
- Ceramic fiber insulations, heat transfer, 689
- Ceramic fiber round robin, test results, 687, 690
- Chlorosulfonated polyethylene (CSPE) mastic, 464
- CH₂O (*see* Formaldehyde)
- Climate-heating-cost (CHC) parameters, U.S. Army energy savings program, 218
- Climatic conditions
 cold climate studies, 406
 effects on heat loss, Mitalas systems for calculating, 134-135, 144-151(tables)
 influence of airtightness and thermal insulation, 679
- Climatic sensitivity, basement wall/floor heat loss, 142(fig.)
- Closed-cell cellular glass (Foamglas) insulated heat distribution systems, 43-44, 48
- Coatings
 cementitious, 74
 for insulated concrete, 45-46, 48
- Code compliance procedures, 9, 29-34
- Code requirements, comparative assessment, 23-24(figs.)
- Cold climate studies, 406
 moisture levels
 in test wall panels, 415(fig.)
 in wood frame walls, 411, 413(table)
- Cold Regions Research and Engineering Laboratory (CRREL), 422, 428
- Cold weather condensation hazard, 615, 625
- Combustible cellular plastic thermal insulation, 720
- Commercial construction, model energy code compliance procedures, 9, 29-34
- Computer model description, TARP program, 542, 550, 565
- Concrete
 cavity walls, 319
 temperature and relative humidity, 379, 390
 in insulating envelope system, 48
- Concrete block cavities, influence on moisture movement, 379, 382, 383(table), 390
- Concrete block wall, uninsulated, thermal resistance, 594-596(table)
- Concrete block wall with drywall laminate system, thermal resistances, 594-595(fig.)
- Concrete block wall with exterior, insulated finishing system, thermal resistances, 589, 593-594, 596(table), 597
- Concrete masonry walls, 582
- Concrete sewer tile for pipe conduits, 48
- Condensation, 371, 395, 397
 attics, 633
 wood-frame walls, 405, 406
- Condensation hazard, 615
 decay, 406
 discussion, 625
- Condensation potential, metal window frames, 572
- Condensation studies
 conclusions, 416
 data acquisition/recording, 410-411
 moisture levels, 407, 411, 412, 413(table)
 results, 411
 test methods/structures, 407
 experimental structure, 408(fig.)
 R values, wall panels, 409(fig.)
- Conductance, 284-285, 290, 567
 reduction after wall insulation retrofit, 646
- Conduction losses, efficiency measurements, 169-171
- Conductive/radiative heat transfer, 210, 284-285, 290, 639
- Conductivity of wood, North America, major research, 280
- Conduit systems
 alarm systems, 47
 factory fabricated, 47-48
 field fabricated, 47-48
 pressurized monitoring, 47
 underground pipe insulation, 46
- Consensus standard test methods, 713
- Conservation of energy
 army buildings, 214-216
 energy efficiency, 639
 engineered specifications, 82
- Construction materials (*see also* Wall system installation), 588
- Construction specifications, federal agencies, underground heat distribution systems, 43
- Contact burn potential, from heated surfaces, 711
- Convection, 284, 570, 572

- cold air in attics, 210-211, 213, 214-215(fig.), 219
- from solar wall ducts, 606
- natural, 205, 209-210
- Convection heat transfer
 - forced convection, 572
 - hot box measurement, 347-349, 395
 - formulas, 349-354
 - wet mineral wool insulation, 399
- Cooling (*see* Heating and cooling)
- Cooling load, 14-18
 - comparison of measured/predicted, 548-549(figs.)
- Copper pipes, 47
- Corrosion cracking, insulated stainless piping, engineered specifications, 86
- Corrosivity, soil criteria for design of underground pipe systems, 44-45
- Corrugated aluminum jacketing, vapor barrier design, polyurethane foam insulation, 74
- Corry Field housing units
 - air change rates, 386(table)
 - moisture problems, 372
- Cost-effectiveness, 599
- Counterflow insulation systems (*see also* Dynamic insulation applications)
 - France, residential houses, 153
 - Scandinavia, industrial building roofs, 153
 - efficiency, 153, 154
 - testing experiments, temperature measurement, 165-168(figs.)
- Cracking, corrosion, 86
- CRIR (*see* Centre de Recherches Industrielles de Rantigny)
- CRREL (U.S. Army Cold Regions Research and Engineering Laboratory), 422, 428
- CSPE (chlorosulfonated polyethylene) vapor retarder mastic, 464
- Cypress, 268-269(table)
 - thermal properties, 238-252, 252-253(table)

D

- Data acquisition, condensation, 410-411
- Data base design methodology, 239, 277-282
 - thermal properties of wood
 - data analysis, 277-278
 - experimental data, 240
- DBR (Canadian Division of Building Research) calorimeter design, 573-574, 575(fig.)
- DBR wall calorimeter, comparison with window calorimeter, 576
- Decay, condensation in wood frame walls, 406
- Delamination
 - built-up roofing/insulation specimens, 437, 443, 444
 - roofing membranes, 432
- Delsante solution, slab-on-grade heat loss calculations, 132, 134
- Density
 - ceramic fiber round robin, 689(table)
 - conductivity correlation, 251, 277
 - loose-fill attic insulation
 - measurement *in situ*, 496, 497-499(tables)
 - variations with time, 497
 - thermal properties of wood, standard deviation of mean, 243(table)
- Department of Defense (DOD), energy conservation investment program (ECIP), 214
- Design criteria, underground piping systems, 44-45
- Dew point/dry bulb temperatures, 379
- Domestic dwellings
 - air exchange rates, 606(table)
 - building component performance, 607
 - design, 599-600
 - energy requirements, 607
- Doors, standards development, 29, 36
- Double glazing, 610
- Double vapor barrier, 615
- Douglas fir, thermal conductivity, 262(table)
- Draft barriers, 86
- Drainage patterns, underground pipe systems, 44-45
- Drainage tests, 377, 386, 387(table)
- Drywall installation, 588
 - TGIF and Z-furring, 720
- Drywall laminate system, 589, 594-595, 597
- Durability, insulating mineral fibers, 477
- Dynamic flow of moisture, equation, 633
- Dynamic insulation (*see also* Counterflow insulation systems)
 - experiments
 - test apparatus, 161-162
 - test wall, 162-163
 - measurements, 163
 - parietodynamic insulation, air circulating along wall, 154, 155(fig.)
 - permeodynamic insulation, air circulating through mineral wool as a heat exchanger, 154, 160
 - temperature measurement, 166-169
 - theoretical efficiency, equations, 154, 156-161

- Dynamic insulation (*cont.*)
 - thermodynamic insulation, air circulating independent of ventilation system, 154-156
 - Dynamic performance, 449
 - Dynamic response
 - behavior, long-term monitoring, 607
 - wall thermal performance, 91-92, 94-98, 99(table), 100
 - Dynamic tests
 - test procedures, temperature cycles, 328
 - test results, 329
 - Dynamic thermal performance, 94-100
 - Dynatech R/D Co., R-Matic heat flow meter, 659
- E**
- Earth contact systems
 - heat loss factor, 134-135
 - Mitalas heat loss calculations, 132-134 applied to U.S. climate, 143
 - Earth temperature, climatic conditions in U.S., 134-135
 - ECIP (*see* Energy conservation investment Program)
 - Economic analysis, 214-216, 216(table)
 - procedures, modeling parameters, 34
 - EERS (*see* Equipment energy efficiency ratios)
 - Elastomeric coatings, polyurethane foam, vapor barrier design, 74
 - Elastomeric membrane, 422
 - Electrical installations, cause of building envelope penetrations, 682
 - Electrical resistance of wood, 617
 - Electric resistance heating, heat tracing medium, 85
 - Elm, thermal conductivity, 267(table)
 - Emission rates, formaldehyde, 224
 - Emissivity, 284, 287, 291
 - effect on heat loss, 84
 - EMTL (*see* Energy Materials Testing Laboratory)
 - Energy analysis calculations
 - building types, 12-13
 - parameter selection and analysis, heating and cooling, 28
 - Energy analysis/performance criteria, 27-28, 30-36, 341
 - Energy audits, 179, 339
 - Energy balance equation, 323-324
 - Energy code compliance procedures for determining efficiency
 - building performance, 9
 - design standards, 9
 - point value system, 9
 - Energy codes, resulting in wide use of energy analysis methods, 31
 - point system approach, 31
 - systems analysis approach, 31-32
 - Energy conservation, 582, 639
 - analysis procedure, 34
 - army buildings, 214
 - consumption reduction, 713
 - control of air leakage, 32(fig.)
 - cost savings, 652
 - counterflow insulation systems, 154-172
 - engineered specifications, 82
 - removable covers, 84
 - goals, 519, 541
 - use of thermal insulating materials, 477
 - Energy conservation investment program (ECIP)
 - impact on mortgage costs, 26
 - U.S. Army, 202, 214, 216
 - Energy conservation standards, 25-26, 565
 - Energy conserving materials
 - building applications, 662
 - test apparatus and test methods, 662
 - Energy consumption reduction, 713
 - Energy costs, 16-18, 20, 26-27
 - Energy efficiency
 - air flow requirements, 12, 545
 - building codes, 9
 - design, 6, 14, 15(tables), 615
 - glazing, 14
 - improvement, U.S. Army, 214
 - optimization parameters, 26-28, 35
 - roofing systems, 431, 432, 449
 - thermal insulation, 69
 - Energy efficiency ratios, equipment, 20
 - Energy Materials Testing Laboratory (EMTL), 535
 - Energy performance standards, prescriptive approach, 29
 - Energy requirements, 21, 338-339
 - building envelope, 341
 - domestic houses, 607
 - Energy savings
 - extra insulation, 610
 - solar house versus typical house, 607
 - solar wall, 608
 - thermal insulation, 69
 - Trombe-type solar wall, 608, 611
 - U.S. Army, 218
 - Energy savings measures
 - cost effectiveness, 610
 - domestic dwellings, 599

Energy Technology Support Unit (ETSU), U.K. Department of Energy, 600

Energy transfer processes, modeling parameters, 34

Energy usage calculations, 10-11

Engineered specifications, 84-88
 applications procedures, checklist, 87-88
 corrosion cracking, 86
 energy conservation, 82
 expansion and contraction, 84-85

Envelope systems, insulating underground pipe, 46, 48

Envelope thermal test unit (ETTU), 92, 93(fig.), 94-97

Environmental chamber tests, 224, 225-229

Environmental criteria, temperature and humidity, 535

Epoxy-lined cement carrier pipes, 47

EPS (expanded polystyrene) foam sheathing insulation, 422-423, 582, 588, 589

Equipment energy efficiency ratios (EERS), 20

Equivalent leakage area (ELA), increased after ceiling insulation retrofit, 646

Equivalent radiative thermal conductivity, 667, 668

Error analysis, heat transfer measuring techniques, 355-357

ETSU (*see* Energy Technical Support Unit)

ETTU (*see* Envelope thermal test unit)

Evaluation procedure, building components, 713

Evaporation, 397

Expanded polystyrene (EPS) insulation, 422, 518

Expansion and contraction, engineered specifications, 84-85

Expansion chambers, 45

Expansion of piping, design considerations for underground systems, 44-49

Experimental error, air flow measurement, 545

Exposure study, EPS materials, 582, 588-589
 experimental details, winter temperature/humidity conditions, 524-529
 roof insulation tests, 428

Exterior envelope, 107

Exterior insulated finishing system, 592

External relative humidity, 616

Extinction coefficient, 665, 670(fig.), 671

Extruded EPS sheathing, 588, 590, 592

Extruded polystyrene sheathing, 518, 615
 exposure study, winter conditions, 528, 534
 moisture control performance, 625

F

Face wall, air pressure changes, 127

Family housing, moisture problems, 371

FCC (*see* Federal Construction Council)

FCC guide specification, Section 15705, underground heat distribution systems, prefabricated/preengineered type, 44

FCGS (*see* Federal construction guide system)

Federal Construction Council (FCC) (*see also* National Academy of Sciences/National Research Council, FCC technical reports), 43

Federal construction guide system (FCGS), 43-44

Federal Interagency Group, 44

Felt, built-up roofing insulation, 443

Fenestration
 annual energy usage, 18(table)
 solar, energy calculations, 11

Fiber batt insulation, new construction applications, 642

Fiberboard sheathing, 412

Fiberglass blowing wool, new construction applications, 642

Fiberglass insulation
 spray-applied, 360
 effect of moisture, 362-364
 unbonded loose-fill, 310

Fiberglass reinforced plastic pipe, 47

Fiberglass wall insulation, 197

Fibrous glass insulation, 223-224
 ceiling insulation, 236(table)
 formaldehyde emissions, 224-227, 236
 impact on indoor formaldehyde concentrations, 230-231

Fiber insulation
 heat transfer, 689
 mass scattering coefficient versus temperature, 672(fig.)

Fibrous insulation material, 394, 665, 674(fig.)
 equations derived from radiation-conduction heat transfer, 666-668
 mass scattering coefficient, 671
 model, equation, 668
 optical behavior model, 669

Fibrous loose-fill insulation, quality control instrument for determining thermal resistance, 655

Fick's law to describe formaldehyde transport, 233

Field-fabricated systems, not pressure testable, 48

- Field experiments, effect of moisture in spray-applied fiberglass insulation, 363-366
- Field measurement
attic insulation retrofit, 217-218
heat loss in underground systems, 63, 66
- Field studies, 615
space heating/cooling loads, effect of wall mass, 541
- Field tests, 108
attic insulation, 210-213, 213-215(figs.)
heat flow through building envelopes, test procedures, 110-113
- Fills for insulating concretes, 49
- Filter coefficients, wall surfaces, 95
- FIP polyurethane foam (see Polyurethane foam insulation)
- Fire protection, polyurethane insulation systems, 73
- Fireplaces, air leakage standards development, 7
- Fir, thermal conductivity, 259(table)
- Floors
basement heat loss calculations, 132, 142
comparative assessment of code requirements, 24(fig.)
insulation, 610
- Florida model energy efficiency code for building construction, 9, 12, 14-15(table), 20
- Flow for retrofit, insulating materials, 644(table)
- Flow of water into wood, model, 633
- Fluid mechanics of air leakage, 639
equation, 640
- Foamed polyurethane insulation, 47
- Foamed-in-place (FIP) polyurethane insulation, 71-73
- Foamglas, 43-44
- Foam insulation, 432
storage tanks, 80
- Foam service life, 463
- Foam sheathing, 405, 422-428, 582, 588-589
test methods/structures, 407
- Foam test specimens, application of asphalt, 438
- Footing, water leakage, 387, 390
- Forced convection (see Convection heat transfer)
- Forest Products Laboratory, Madison, Wisconsin
research on condensation in walls, 406
- Formaldehyde (CH₂O)-based resins, 223-227
- Formaldehyde concentrations, indoor
attic insulation model, 235
diffusion model, 230-231
impact of fibrous glass insulation, 230
- Formaldehyde emission measurements, 225-236
- Formaldehyde surface emission monitor (FSEM), 224-225, 236
- Formaldehyde transport model, equations, 233-235
- Formaldehyde vapor permeability data, 232(table)
- Fourier transforms, passive and active wall fluxes, 100-104(figs.)
- Frothing, polyurethane foam, 72, 434, 440
- FSEM (see Formaldehyde surface emission monitor)
- Fuel consumption, annual, computer program, 8
- Fuel energy program, calculation procedures, 12
- Full-scale thermal testing, 161-171, 583-586
- Furring wall system installation, 588

G

- Gases, analysis of, in roofing blisters, 437, 444
- Glass fiber insulation, 223-224
cellular, 48
conductivity increased with moisture, 361-362
correlation between thickness, density, and temperature, 674(fig.)
laboratory/field experiments, 362-366
reinforced polyisocyanate test construction, 721-722
- Glass fibers, 154, 163, 477
- Glazing
considerations for energy efficiency, 9, 14
double, 610
standards development, 29
- Ground-based infrared thermography, 176-177, 180
- Ground drainage tests, Corry Field housing units, 377, 386, 387(table)
- Groundwater conditions
Corry Field housing units, 377
soil criteria for design of underground pipe systems, 44-45, 52
- Guarded hot box, 506, 567, 571-572
design considerations, effect of environment, 358
imbalance analysis, 357(fig.)
principles of operation, 299
test measurements, 305, 311
test results for wall systems, 724-725(table)

- tests of thermal resistance, wall construction components, 720-721
 verification for thermal properties measurement, 297, 346
- Guarded hot plate, 286(table), 287
 apparatus, 288(fig.), 292
 ceramic fiber round robin test data, 691(table)
 evaluating thermal performance of insulations, 652, 686
 heat transfer testing, 395
 measurements on wet material, 397-398
 performance, 302-303
 thermal conductivity versus mean temperature, 697, 698(fig.)
- Gypsum wallboard, 582
- H**
- Hardwoods, thermal conductivity, 240-241
- Hazard potential
 from heated surfaces, 705
 human exposure limits, 705
- Heat and humidity, effect on inorganic insulating fibers, 477
- Heat distribution systems, manholes, 45, 50
- Heated surfaces, hazard potential, 704
- Heat exchange, between test specimen and guarded hot box, equations, 571-572
- Heat exchange coefficients, 307
- Heat flow, 108
 mineral fiber insulation, 394, 399
 surface to surface temperature difference, 402(fig.)
 versus temperature difference, glass fiber, 403(fig.)
- Heat flow meter, 175, 652-653, 654(fig.)
 future needs, 662-663
 historical development, 659
 instrumentation, Dynatech R/D Co., 659
 schematic, 658(fig.)
 standards, 656
- Heat flow meter apparatus, product performance, 661
- Heat flow resistance
in situ measurement, 120
 insulation air space leak testing, 48
- Heat flow test procedure, 110-113
- Heat flux
 density, 668
 dynamic performance of wall, 92
 measurement, 94
 dynamic test results, 332-334(figs.)
- thermal resistance of office building walls, 112-120
 versus temperature difference, 289(fig.)
- Heat flux calorimeter, 108, 119-120
- Heat flux sensors, 203, 207-208
 calibration, 205-208
 conversion factors, 208
- Heat flux transducers, 108, 110, 119-120, 652-653, 656-657
- Heating and cooling, energy analysis, 28
- Heating and cooling equipment, 28
- Heating and ventilation systems, solar houses, 604(fig.)
- Heating load correlations
 comparison of predicted/measured, 546-547(figs.)
 masonry walls, 556(table)
 wood frame walls, 554, 555(table)
- Heat load, 11, 14-15, 203
 roof *U* values, 17(table)
 wall *U* values, 16(table)
- Heat loss, 679
 basement walls and floors, 132
 building envelope, 179, 317
 heat loss eliminated from, 317
 calculations, Mitalas system, 132-134, 134-135
 design characteristics, 600
 due to missing insulation, 120
 effect of emissivity, 84
in situ measurement, 52, 63, 108
 insulation, permeodynamic systems versus conventional insulation systems, 171
 office buildings, 108
 reduction by airtightness, 647
 scale model test results, pipe systems, 64-65(tables)
 thermal analysis, 132
 thermography, 178
 underground heat distribution systems, *in situ* measurement, 52-53, 63
 Washington, DC, Mitalas system, basement walls/floors, 136-138(figs.), 144-151(tables)
- Heat loss coefficients, domestic houses, 604, 605(table)
- Heat loss factors
 earth contact systems, 134-135
 Mitalas system, full basement, Washington, DC, 144-151(appendix table)
- Heat pump
 roof systems, 450
 versus electric strip heating, 28
- Heat sink, 397
- Heat storage capacities, cavity walls, 341

- Heat tracing mediums, 85
- Heat transfer
- characteristics, 319
 - conductive/radiative, 169-171, 210, 284, 639
 - convection, 572
 - infrared inspection techniques, 178-179
 - masonry cavity wall, 319
 - measurement, 94-105, 169, 355-357
 - mineral fiber insulation, 399
 - model, 94, 156
 - radiative, 208-209, 219, 284, 292
 - wall thermal performance, 92-98, 129
- Heat transfer behavior, low-density thermal insulation, instrument design, 656
- Heat transfer calculations, 597
- Heat transfer coefficients, 307(table), 570
- Heat transfer energy, 666
- Heat transfer factors, basement and slab floors, 143
- Heat transfer from phase changes, 395-396
- Heat transfer model, 666
- Heat transfer properties
- BLAST program, 544
 - high-solar-gain house, 545
 - typical house, 545(table)
- Heat transfer reaction, source of high energy, 707
- Heat transfer through fiber insulation, 689
- Heat transfer U values
- equations, 569-572
 - windows, 567
- Heat transmission, 160-162, 311, 582
- characteristics, cavity walls, 339
 - coefficients, 325-326
 - mechanisms, 652
 - windows, 568
- Hemlock, thermal properties, 260-261(table)
- High-solar-gain house, 542, 545
- heat transfer properties, 545
 - reduction in space cooling loads, 562(table)
 - reduction in space heating loads, 560, 561(table)
- High-temperature optical parameters, 665
- High temperature tests, 685
- Hi-Hat system
- air space R value, 727(table)
 - R value comparisons, 726(table)
 - test constructions, 722(fig.)
- Hot box method (*see also* Calibrated hot box) measuring technique, 346
- Hot box tests, 507
- measured thermal performance, 514(table)
- Hot, humid climates
- moisture levels in test wall panels, 412, 415(fig.)
 - moisture problems in family housing, 371-393
- Hot plate and heat flow meter, 654
- Hot plate, thermal biguarded, 286
- House heat loss coefficients, 604
- Housing construction details
- London, Ontario, 619(table)
 - Regina, Saskatchewan, 619(table)
 - St. John's, Newfoundland, 620(table)
 - Winnipeg, Manitoba, 618(table)
- Housing units, field studies of moisture, 372
- Human burn protection standards, 704
- Human skin burns, contact resistance, 708
- Humidity
- effects on inorganic insulating fibers, 477
 - effects on mineral fibers, 477
 - environmental criteria, 535
 - testing for moisture problems, 375, 379, 381(table)
- Humidity ratios, 630, 632(fig.)
- Hydrocarbon fill, granulated, insulating envelope systems, 48-49
- Hygric experiments, 449, 458
- Hyperthermia, 705
- effects on human skin, 706

I

ICBO (*see* Building codes)

Imbalance detection, heat transfer measurement, 354-357

Indoor air quality, 223

Indoor concentrations of formaldehyde, 223-237

Industrial roof insulation, Sweden, 153

Infiltration

- air, in building envelope, 124, 176

- cause of air leakage, 32

- standards development for energy efficiency, 29, 34

- tests, 377

Inframetrics infrared unit, 197

Infrared imaging system, 177

Infrared inspection techniques, 178-179

Infrared scans, walls, 197

Infrared surveys, 175, 180-185

Infrared thermography

- applications, 176-177, 203

- field investigations, army buildings, 205

- review of insulated surfaces, 88

- wall inspection, 197

Infrared thermometer (*see* Spot radiometer)

Inorganic mineral fibers, durable for insulating applications, 477

- Inside surface temperatures, 572
- In situ* insulation thickness and density, 495-496, 497-499(tables), 500
- In situ* measurement
 - heat flow through composite walls, 120
 - heat loss, 52, 63, 108
 - R value measurement, 203, 209
 - thermal performance
 - building envelope, 107-108
 - walls, 91-105,
- Inspection procedures, exterior envelopes of office buildings, 177
- Inspection program, wall insulation, installation, 200
- Installation and backfill, underground piping, 45-46
- Installation problems, workmanship, 680
- Instruments development, calibration, 659
- Insulated concrete, 45-46
- Insulated heat distribution systems, field investigations, 43
- Insulated stainless steel piping, 86
- Insulated underground piping systems, 45-49
- Insulated wall systems, measured thermal resistance, 592, 593(table)
- Insulating concretes, 49
- Insulating envelope systems, 48
- Insulating materials and systems
 - air leakage properties, laboratory measurements, 639
 - pressure drop versus air flow, 642(fig.)
 - thermal resistances, 582
- Insulating mineral fibers, 477
- Insulation (*see also* Counterflow insulation, Dynamic insulation), 679, 685
 - air leakage reduction, 639
 - attics, 637
 - building envelope, 680
 - ceilings, 610
 - cellular glass, 48
 - cellular polyurethane, 71
 - cellulose, 362-367
 - density, 495-498
 - settling tests, 500
 - density, 495-498
 - effect of moisture, laboratory experiments, 362-363
 - gaps, 313-314
 - heat transfer reduction, 639
 - impact on thermal resistances, 597
 - wall systems, 588
 - moisture trapped in vapor barrier, 401
 - polyurethane foam, 71, 74, 431
 - protected membrane roofs
 - laboratory tests, 423-425
 - wetting behavior, 428, 429
 - quality control instrument design, 655
 - quality of installation, 196, 314
 - standards development, 29, 36
 - retrofit, 202-220, 643, 646
 - thermal performance measurement, 652
 - ceilings, 644
 - wet mineral wool, 399
- Insulation configurations, basement wall/floor heat loss, Mitalas system, 144-151(appendix tables)
- Insulation densities, 495
- Insulation efficiency, of polyurethane foam, 71, 73
- Insulation for energy efficiency, 9-16
- Insulation for stainless steel surfaces, engineered specifications, 86
- Insulation materials
 - ceramic fiber round robin, 686
 - fiberglass, 197
 - new products, laboratory testing, 316
 - protective finish, 83-84
 - retrofit, 643(table)
 - selection criteria, 70-71, 83, 87-88
 - testing for new construction
 - cellulose, 642
 - fiberglass batt, 642
 - vermiculite, 642
- Insulation panels, engineered specifications, 86
- Insulation retrofit, 218
- Insulation R values, 515(table)
- Insulation specifications, 82
- Insulation specimens, roofing, 437, 443-444
- Insulation systems
 - application method, polyurethane-banded aluminum jacket, 78
 - banded tanks, 78
 - design objectives, 70, 73, 87
 - energy-saving thermal insulation, 70
 - ceilings, walls, floors, double glazing, 610
 - parietodynamic, 154-155
 - permeodynamic, 154, 160
 - polyurethane foam coatings/coverings, 73
 - fire protection, 73
 - shortcomings, 73
 - spray-applied fiberglass, 310, 360, 367-369
 - thermodynamic, 154-156
 - unbonded loose-fill fiberglass, 310
- Insulation thickness, 45, 652
 - primary means of energy conservation, 83
- Interior insulation system, 593
- Interlaboratory comparison, 685
- Interlaboratory reproducibility
 - mean temperature versus thermal conductivity, 699(table)

- Interlaboratory reproducibility (*cont.*)
 - thermal conductivity versus mean temperature, 700(fig.)
- International Refrigeration Institute, round robin test, 654

J

- Jacketing, aluminum (*see* Aluminum jacketing)
- Jacket seam
 - bonded aluminum jacket on foamed insulation, 80
 - design testing, 74
 - permeability, 74
 - polyurethane insulation, 74, 78-79
- Joints, 679

L

- Laboratory experiments, spray-applied fiberglass insulation, effect of moisture, 362-363
- Laboratory measurement, 567
- Laboratory tests, protected membrane roof, 425
- Larch, thermal conductivity, 263(table)
- Leakage flow rate, insulation materials, 643(table)
- Leak testing, insulation air space, 48
- Life cycle cost (LCC) principles, energy efficiency, 202, 214-215
- Lighting loads, for energy calculations, 12
- Loose-fill attic insulation, 493, 495
- Loose-fill cellulose
 - blower-cyclone-shaker (BSC) test, 500
 - wall insulation, 197, 199
- Loose-fill thermal insulation, 494
- Low-energy dwellings, design, 599
- Low-frequency weather fluctuations, 103
- Low-permeance foam sheathing
 - moisture content, discussion, 625
 - versus other types of sheathing, 615
- Low temperature
 - design objectives for insulation systems, 70, 78-80
 - storage tanks, thermal insulation, 70, 76, 79

M

- Maintenance, design criteria for tank insulation systems, 70
- Manholes
 - design and maintenance, 50
 - pumping facilities and venting, 45
- Maple, thermal conductivity, 270(table)
- Masonry, moisture problems in family housing, 371-372
- Masonry cavity walls, 319
 - thermal response, 341
- Masonry securement systems, test constructions, 721-724
- Masonry wall constructions, 582
 - heating load correlations, typical house, 554
- Mass absorption coefficient (*see* Absorption coefficient)
- Mass scattering coefficient (*see* Scattering coefficient)
- Material degradation, thermal insulating mineral fibers, 477
- Materials
 - factors affecting choice, 83
 - insulation systems, 71
 - application procedure checklist, 88
 - types of materials, 83
- Mathematical models
 - data reduction, ceramic fiber round robin, 702(appendix)
 - roof thermal performance, 449
- Mean temperature
 - comparison of averages of all water calorimeter and guarded hot plate tests, 702(table)
 - versus thermal conductivity calorimeter tests, 698(fig.)
 - guarded hot plate tests, 697(fig.)
- Mean values
 - thermal properties of wood
 - density, 243, 247(tables)
 - moisture content, 244(table)
 - thermal conductivity, 240-242(tables)
 - use increasing design reliability, 280
- Measuring techniques (*see also* Active measuring strategy)
 - heat transfer, 355-357
 - hot box method, 349-354
 - tracer gas, 175, 176
- Measurement/error analysis, 209
- Mechanical properties of EPS materials, exposure study, winter conditions, 524-529, 531(table)
- Mechanical stress, in foam insulation systems, 75
 - equations, 76
- Membrane blistering, roofing systems, 432
- Metal jackets, securement, 84
- Metallic jacketing, 84

- Metal window frames, condensation, 572
- Metal Z-furring channel system, 590, 591(fig.)
- Metering box
 - heat transfer coefficients, 307
 - space temperature difference behavior, 304(fig.)
- Metering chamber calibration, 584
- temperature ranges, 586, 594
- Mildew, on walls and furnishings, 371, 379
- Mineral fiber bats, quality control instrument for thermal resistance, 655
- Mineral fibers, 154
 - material disintegration, 480(table), 482-484
 - thermogravimetric analysis, 477
- Mineral wool
 - insulation, 399
 - material degradation, 477
 - wet thermal resistance, 396
- Mitalas equations
 - basement model, 133(fig.)
 - climatic conditions, U.S. weather stations, heat loss calculations, 132-134
 - Washington, DC, 144-151(appendix tables)
- Model building codes, 720
- Model energy code compliance, 9, 29-34
- Model, flow of water into wood, 633, 637
- Modeling, 630
- Modeling parameters
 - development of energy transfer processes, 34
 - dynamic performance of a wall, 92
- Modular retrofit experiment, 647
- Module simulator, 713, 714(fig.)
- Module testing, 713, 715(figs.), 716
 - versus ASTM proposed standard test method for thermal performance of building components, 718-719
- Moisture
 - concrete block cavities, 379, 382, 383(table), 390
 - condensation studies, test methods/structures, 407
 - desorbed
 - from roof sheathing, 632
 - from wood, 633
 - dynamic flow, 633
 - effect on family housing, 371-372
 - effect on loose-fill cellulose, laboratory experiments, 362, 368-369
 - effect on roofing, 432-434
 - effect on spray-applied fiberglass insulation, 360
 - effect on thermal insulation properties, 519
 - effect on thermal resistance, 360
 - literature survey, 361
 - effect on wood and wood products, 406
 - exposure studies, EPS materials, winter conditions, 528
 - main cause of insulation and pipe failure, 46
 - metal window frames, condensation, 572
 - polyurethane foam insulation, 431
 - protected membrane roof
 - reducing thermal resistance of wood and wood products, 406
- Moisture content
 - foam insulation, 436
 - insulation board facings, 436
 - thermal insulation, 394, 399, 405
 - wall materials, 382, 385(table), 390, 405
 - wood, 634
 - data analysis, 277-278
 - standard deviation of mean, 244(table)
 - test panels, 415
 - used for residential construction, 251, 252-273(tables)
 - wood frame walls, 411, 413(table), 417
 - wood studs, 616
- Moisture control, 405, 406
 - performance of extruded polystyrene, 625
- Moisture detection, RTRA/ORNL roof systems, 452
- Moisture gain, exposure study, EPS material, 524-528, 529(table), 530(table)
- Moisture migration, 395
- Moisture monitoring, instrumentation, Delmhorst moisture elements, 616
- Moisture performance of building materials, 616
- Moisture permeance, urethane foam, 469
- Moisture problems
 - family housing, Corry Field units, 371-372, 378-379, 390-392
 - masonry cavity walls, 319
 - mineral fibers, 477
- Moisture research, 618-620
- Moisture resistance, 48
- Moisture retarder paint, evaluated by module testing, 716
- Moisture storage and release, 637
- Moisture tests, 716
- Moisture thermal performance, cellular plastic insulation, 518
- Molded EPS materials, 521, 527
 - R values, 524
 - thermal conductivity, 524
- Monitoring, long-term, domestic houses, 607

Multilayer reflective insulation, 506, 511
heat flow, 515-516

N

National Academy of Sciences/National Research Council, Federal Construction Council (NAS/NRC/FCC)

technical reports

No. 30: Underground heat distribution systems, 43

No. 39: Evaluation of components for underground heat distribution systems

No. 47: Field investigation of underground heat systems, 43

No. 66: Criteria for underground heat distribution systems, 44

National Bureau of Standards (NBS)

effects of thermal mass, 238

design of thermesthesiometer, 709

National Program Plan

energy programs, 26

insulation performance, 519

thermal properties of wood, 238

National Research Council of Canada, 108

environmental test facility, 568

National Roofing Contractors Association (NRCA), 432-433

National Voluntary Laboratory Accreditation Program (NVLAP), 509

proficiency testing on thermal insulation, 659

Natural convection, 209-210

New insulation products, laboratory testing, 316

New Mexico Energy Research and Development Institute (NMERDI), 238-239

New Zealand Building Research Association, 94

Nonpressure testable systems, underground pipe installation, 47

NRCA (National Roofing Contractors Association), 432, 447

O

Oak Ridge National Laboratory (ORNL), 239, 449, 458

Oak, thermal conductivity, 272-273(table)

Occupant surveys, moisture and mildew, Corry Field units, 378-379, 389, 390, 391(table)

Off-gassing, 432-433, 444

Office buildings

building envelope, thermal resistance, 107
calculation procedures for energy efficiency, 10

construction details, 121-123

description of test buildings, 181(table)

thermal bridges, 182(figs.)

thermal resistance of exterior wall, 107-123

thermographic inspections, 180-181

anomalies, 182(table)

On-site review, 87

Opacity criteria, 674, 676

Openings, air leakage

building envelope penetration caused by windows, doors, ventilation, etc., 682

standards development, 36

Optical behavior, fibrous material, 669, 675

Optical measurements, 671

Optical thickness, 665-666, 669, 673

reference materials, 672, 676

Optimization parameters for energy efficiency, 27-28, 35-36

Outdoor storage tanks, behavior of water vapor retarders, 464-465

Outside air film, 572

Outside air humidity ratios, 632(fig.), 635

P

Parietodynamic insulation, 154, 155(fig.)

Passive measurement, building walls, dynamic thermal performance, 94-97, 98, 99(table), 100

Passive solar construction, 30-31

Passive solar system evaluation with module testing, 715, 716(fig.)

Peak energy load, building envelope, 336

Penetrations of building envelope, 682

Periodic heat flux, wall thermal performance, 92, 94

Perlite fill, granular

in cavity walls, 319, 320

in insulating envelope systems, 49

Permeability

air, 125

building envelope, 125-127

foamed polyurethane insulation aluminum jacket seam, 74-75

Permeance values, exterior sheathing materials, 615, 616(table)

Permeodynamic insulation systems, 154, 160, 171

Personnel protection, 704

Phase change, 395, 399

- Phenolic foam, exposure study, winter conditions, 528, 534
 - Physical properties, exposure study, EPS materials, winter conditions, 528-529
 - Physical testing versus theoretical modeling, 713, 716
 - Pilkington Brothers, Research and Development Laboratories, U.K., guarded hot box facility, 297, 299(table), 301, 303, 307
 - Pipe conduit, 46
 - Pipe expansion, 45
 - Pipe heat loss, 52-53, 63-65
 - Pipe insulation, calcium silicate, 46
 - Pipes, copper, 47
 - Piping
 - fiberglass reinforced plastic, 47
 - insulated stainless steel, engineered specifications, 86
 - Piping, underground
 - design and installation criteria, 43
 - system failures, 43-51
 - Plastic and metal jacketing materials, vapor barrier design, polyurethane foam insulation, 74
 - Plastic insulation, cellular, 71
 - Point system approach to energy analysis for standards development, 31-33, 38
 - Polyethylene mastic, 464
 - Polyisocyanurate foam insulation, 432
 - test construction, 721, 722
 - Polystyrene beads, insulating concrete aggregate, 49
 - Polystyrene insulation
 - exposure study, 525-527
 - moisture distribution, 530(table)
 - moisture resistance, 421, 422
 - roofing, 432
 - Polystyrene sheathing, 412, 589
 - Polyurethane foam
 - bubbling, 440
 - elastomeric coatings, 74
 - field-installed (FIP) design, 71-73, 78-80
 - froth systems, 72
 - insulating efficiency, 73
 - insulating envelope systems, 49
 - pour system, 72
 - resistivity, 71(fig.)
 - spray system, 72
 - thermogravimetric analysis, 437
 - vapor barrier design, 74
 - water vapor retarders, 463-474
 - Polyurethane foam specimens, thermogravimetric analysis, 437
 - Polyurethane insulation, 47, 74, 77-79, 432-434
 - bubbling, with hot asphalt applications, 444
 - fire protection, 73
 - Porous material, 665-668
 - Portable calorimeter, 108, 109-110(figs.)
 - Pouring, polyurethane foam, 72
 - Predicted and measured attic air humidity ratios, 635(fig.), 636(fig.)
 - Prefabricated pipe construction, underground heat distribution systems, 48
 - Prescriptive approach, standards development for energy efficiency, 33
 - Pressure differences, 679
 - Pressure piping code, 46
 - Pressure-testable systems, underground piping installation, 46
 - Pressurization data, 642(fig.), 644, 647
 - Pressurization tests, building envelopes, measuring tightness, 175
 - Product variability, 651
 - Project Pinpoint surveys, National Roofing Contractors Association, 432
 - Propane tank shell, foam insulation, 76
 - Protected membrane roof, 421, 422(figs.)
 - exposure tests, 425, 426-427(figs.)
 - Protected membranes, 422
 - Protective coatings, insulated pipe, 46
 - Protective finishes, insulation materials, 83-84
- Q**
- Quality assurance, 655
 - Quality control
 - infrared scans, 197
 - installation problems, 196, 199-200
 - instrument design, 655-659
- R**
- Radiant transfer, reduced by reflective insulations, 507
 - Radiation absorption, thickness dependent, 65
 - Radiation-conduction heat transfer, 666
 - Radiation heat flux density, 666-667
 - Radiation heat transfer, 208-209, 284-285, 354, 675-676
 - ceramic fiber insulations, 689
 - test materials for round robin, 687
 - thermal conductivity, 666
 - Radiation reference materials,
 - Radiometer inspections, 176

- Redwood, thermal conductivity, 254(table)
- Reference material, 674-676
 thermal conductivity measurements, 283, 666
- Reflectance, solar, 457-458
- Reflective insulation, 506
 data from hot box tests, 511, 512(table)
- Reinforced plastic pipe, 47
- Relative humidities
 cavity walls, 379, 390
 low-permeance sheathing walls, 620
 maritime regions, 618-620
 measurement for moisture problems, 375, 379, 381(table)
- thermal resistance of insulation, 394
- Reproducibility (*see also* Interlaboratory reproducibility)
 interlaboratory, 699(table)
 mandate for standardization, 656
- Residential building envelopes, 34, 36-38
- Residential construction, model energy code compliance procedures, 9
- Residential energy standard, ASHRAE 90A-80 versus new standard
 analytical tool selection, 26
 basis for new standard, 22-25
 economic approach, 25-26
 economic parameters, 26
 technical approach, energy analysis program criteria, 25
- Residential housing insulation, France, 153
- Residential insulation, 639
- Residential space heating, 153-172
- Residential walls, 615
- Resistance, thermal insulation, 652
- Resistance variations
- Resistivity (*R* values)
 of thermal insulating materials, 71(fig.)
 wall thermal performance, 91
- Retrofit, 639, 643
 army buildings, 218
 effect of insulation on air leakage, 644
 leakage data, 646(table)
 modular retrofit experiment, 647
 return on investment (ROI), 317
 spray-applied insulation, 360
 wall insulation, 196-201, 316
 reduction in air leakage heat loss, 645(table)
- RIC/TIMA (Roof Insulation Committee of the Thermal Insulation Manufacturers Association), 447
- Ringwall-supported tanks, foam insulation systems, 79
- R-matic instrument for calibration, 660(fig.)
- wall securement systems, test results, 726(table)
- Rockwall wall insulation, 197
- Rock wool, 477
- Roof blisters, composition of gas, 446(table)
- Roofing blisters, 432-433, 447
 analysis of gases, 437
- Roofing/insulation specimens, 438, 443-444
- Roofing membranes, delamination, 432
- Roofing systems, 432
- Roof insulation
 bubbling, 433, 438-440, 443
 exposure tests, 428
 heat storage effects, 453
- Roof reflectance, 457-458
- Roofs
 exterior membrane, 178
 protected membranes, 421
 reflectance, 449
R values, 213, 449
 thermal efficiency of insulation systems, 172, 178
 thermal performance, 449
U values, 17(table)
- Roof sheathing and trusses
 flow of water, 637
 temperature, 632(fig.)
 wood moisture content, 631(figs.)
- Roof surface temperature, 452
- Roof systems
 counterflow insulation, Scandinavia, 153
 evaluation by aerial thermography, 181-182, 185, 186-187(figs.)
 moisture detection, 452
 surface temperatures, 452, 454-455(figs.)
 thermal performance, 449
 thermographic inspections, 178
- Roof thermal research apparatus (RTRA), 449, 458
 controlled by heat pump, 450
 test panel construction, 450
- Round-robin test, 283
 ceramic fiber thermal conductivity, 685-696
 expanded polystyrene specimens, 535
 hot plate and heat flow meter, 654
- RTRA (Roof thermal research apparatus), 449, 450
- R* values (resistivity), 506, 515(table), 570
 air leakage, 213, 377
 army buildings, measurement, 205, 209(table), 210
 earth contact systems, 135
 loose-fill attic insulation, 494, 495(table), 500

- measurement by spot radiometer, 187, 189, 190
 - roofs, 449
 - test panels with foam sheathing, 407, 409(fig.)
 - thermal insulation materials, 71(fig.)
 - walls, 91, 219-220, 314
 - wall securement systems, test results, 726
- S**
- Sandbox, 53-54, 66
 - test results, 64-65
 - Savings to investment ratio (SIR), life cycle costing, energy efficiency program, 214-215, 218
 - SBCC (*see* Building codes)
 - Scale model, 55, 66
 - test results, 64-65
 - Scanning electron microscopy, test data for insulating mineral fibers, 477-479(fig.), 482-485
 - Scattering coefficient, 665, 669, 671(fig.), 674, 676
 - correlation between density and thickness, 675(fig.)
 - versus temperature, 672
 - Service life, design criteria for tank insulation system, 70
 - Settling, 494, 500
 - Shading of solar walls, 606
 - Sheathing, 412
 - Sheathing, low-permeance, 615
 - Sheathing, roof, 616
 - Silicate-coated perlite module, 717
 - Simplified thermal parameter (STP), 94
 - Simulated pipe system, small-scale test, 55, 56(fig.)
 - sand temperatures, 57-62(figs.)
 - Single-wall insulation systems, 70
 - Skylights, air leakage control, standards development, 36
 - Slab-on-grade-floor heat loss
 - basement heat loss factor, 140-141, 143, 144-151
 - Delsante solution, 132, 134
 - Slabs
 - comparative assessment of code requirements, 24(fig.)
 - standards development for energy efficiency, 29
 - Slag rock wool fibers, 477
 - material degradation, 482-491
 - Smoke test, air flow visualization, 171
 - Society of the Plastics Industry
 - expanded/extruded polystyrene, 519
 - round robin study, EPS materials, 535
 - test materials
 - black molded polystyrene, 520
 - extruded polystyrene, 520
 - phenolic foam, 520-521
 - Softwoods, thermal conductivity, 240-241
 - Soil condition criteria, design of underground pipe systems, 44-48
 - Soil corrosivity determination, by soil resistivity test, 45
 - Soil moisture content, 65
 - Soil thermal conductivity, 65-66, 135
 - Mitalas system, 144-151
 - Solar fenestration, energy calculations, 11
 - Solar heating and ventilation systems, 604(fig.)
 - Solar houses, 600
 - Solar insulation, domestic houses, 607
 - Solar reflectance, on thermal performance of roof systems, 457
 - Solar wall ducts, convective contribution, 606-607
 - Solar walls, 599
 - shading, 606
 - Southern pine, thermal conductivity, 264-266
 - Space conditioning loads, predicted and measured, 550
 - 551-552
 - Space cooling load comparisons, masonry/wood frame, 559
 - Space heating, 153-172
 - Space heating/cooling loads
 - computer program (TARP) for predicting, 542
 - high-solar-gain house, annual reductions, 561
 - results of comparisons, 544
 - Space heating load comparisons, masonry/wood frame, 558
 - Space heating, savings in energy consumption, 607
 - SPI (*see* Society of the Plastics Industry)
 - Spot radiometer
 - inspections, 176
 - thermal resistance measurement, 187, 189
 - used to measure interior surfaces, 178-179
 - Spray-applied fiberglass insulation, 310

- Spray-applied insulation systems, 360, 367-369
 polyurethane foam, water vapor retarders, 463-474
 thermal effects of moisture, field experiments, 363-366
- Spraying polyurethane foam, 72
- Spruce, thermal conductivity, 250(table)
- Stainless steel surfaces, insulation, engineered specifications, 86
- Standardization, 656
- Standards (*see also* ASTM standards)
 API 620: 76
 ASHRAE *Ad Hoc* Standard 90-R: 29
 ASHRAE cooling and heating load calculation manual, 10
 ASHRAE *Handbook of Fundamentals*, 10, 721
 ASHRAE SPC 119P: 34
 ASHRAE Standard 62-81: 34
 ASHRAE Standard 90: 21-22
 ASHRAE Standard 90A-80: 22, 26-31
 ASHRAE Standard 90B, Section 10-11: 29
 ASME B31.1, Code for Pressure Piping, 46
 British Standard 874: 346
 California Energy Code, Title 24 (CEC), 22
 Farmers Home Administration (FmHA), 22
 French Standard, NFX 10-022, 346
 German Standard DIN 52611: 346
 Housing and Urban Development Minimum Property Standards (HUD-MPS), 22
 housing industry dynamics (HID) survey, 22
 International Organization for Standardization, Committee 163 on thermal insulation, 346
 International Organization for Standardization, heat flow meter standards, 656
 Pennsylvania Energy Code (PENN), 22
 Swedish Standard (SS) 02 42 12: 346
- Standards assessment, 22, 31-34
- Standards development
 air leakage, 32-33, 124
 ASTM Committee C-16, human burn protection, 704
 ceilings, 29, 36
 energy analysis methods, 31
 point system approach to energy analysis, 31-33, 38
- Standards methodology, 22, 25-35
- Standard test method, ASTM proposed, thermal performance of building components, 718
- Standing water during rain, 386-387
- State energy programs, 26
- Steam, heat tracing medium, 85
- Steel pipe, for hot water and steam installations, 47
- Still air layer, 283-286, 666
- Storage tanks, 69-70, 76-80
- STP analysis (*see* Simplified thermal parameter)
- Stress corrosion cracking, of insulated stainless steel piping, engineered specifications, 86
- Stress, thermal and mechanical equations, 75-76
 in foam insulation systems, 75-76
- Stud moisture content, 622-624
- Styrene insulation, 421
 laboratory tests, 423
- Sulfur hexafluoride tracer gas, 377
- Superinsulated buildings, 153, 216
- Surface absorptance, thermal effect, 457
- Surface heat transfer coefficients, 308
- Surface humidity ratio, 634
- Surface temperatures
 hermetically sealed glazing unit, 568(fig.)
 hot box design, 356
- Sweden, National Testing Institute, classifying insulating materials, 395
- Systems analysis approach for energy conserving design, 31-33

T

- Tanks, 78-80
 outdoor storage, water vapor retarders, 464-466
 thermal insulation, 70, 76
- TARP (*see* Thermal Analysis Research Program)
- Temperature
 batt/sheathing interface, 627(fig.)
 dynamic performance of wall, 92
 office building walls, field tests, 111(fig.), 112
 mass scattering coefficient, 672(fig.)
 moisture problems in family housing, Corry Field units, 375, 379, 380(table)
 roof sheathing and trusses, 632(fig.)
- Temperature and heat flux, dynamic test results, 329-334(figs.)
- Temperature baffle, 574(fig.), 577
- Temperature measurement
 cavity walls, 379, 390
 counterflow insulation systems, 165-168
 dynamic insulation, 166-169

- dynamic temperature cycles, 329-331(figs.)
- for moisture problems, 375, 379, 380(table)
- glass, 567
- guarded hot box facility, 302-303
- roof thermal research apparatus (RTRA), 450
 - versus moisture capacity, 628(fig.)
- Temperature/moisture profiles
 - roof sheathing and trusses, 632(fig.)
 - urethane foam in tanks, 469(fig.)
- Temperature profiles, 65, 67(fig.)
- Temperature/time relationship, human skin burns, 706-707(fig.)
- Temperature uniformity, 354-355
- Temp Guard insulation furring (TGIF) system, 590, 591(fig.), 597
- Test apparatus
 - instrumentation and control, 583-585, 686
 - temperature sensing, 583
- Test constructions for masonry securement systems, 721-724
- Testing for air leakage, 377, 641-642
- Testing insulation, 642-643
- Test method and apparatus, 567
 - model parameters determined by least squares, ceramic fiber round robin, 693(table)
 - round robins, 699
 - thermal conductivities, ceramic fiber round robin, 691
- Tests for thermal resistance of wall constructions, 720-721
- TGIF system (*see* Temp Guard insulation furring system)
 - test construction, 721-722(fig.)
- Thermal analysis, heat loss calculations, 132
- Thermal Analysis Research Program (TARP), 542, 565
- Thermal and hygric measurements, roof systems, 449
- Thermal barrier, interior surface finish, 720
- Thermal bridges, 180, 182-185(figs.), 311, 592, 593, 602, 721
- Thermal capacity, walls, 11
- Thermal conductances (*C* value), 306, 506, 567
- Thermal conductivity (*U* value) (*see also* Average computed conductivity), 65, 66(table), 160, 169, 394
 - air, 287
 - ASHRAE recommendations, 570
 - building envelope, 127-129(fig.)
 - ceramic fiber insulation, round robin, 686
 - correlated with density, 251
 - decrease caused by convective heat transfer, 369
 - exposure studies, expanded polystyrene materials, winter conditions, 524-530, 531(table)
 - glass-fiber insulation materials, 368
 - guarded hot box facility, 299, 306
 - loose-fill insulations, 494(table)
 - mean temperature
 - calorimeter tests, 698(fig.)
 - guarded hot plate tests, 697(fig.)
 - of wet material, 395, 400
 - polyurethane foam, 73
 - exposed to moisture, 75
 - protected membrane roof, 421
 - results, laboratory averages, 709(table)
 - round robin analysis for ceramic fiber insulation, 686
 - spray-applied insulation, 362-364, 365(table)
 - standard deviation of mean, 242(table)
 - versus moisture content, 361
 - walls, 91, 94
 - wood, selected species, data analysis, 249, 268, 269(table)
- Thermal conductivity measurement, 668, 671, 675
 - mineral fibers, 485
- Thermal conductivity tests, 695(table)
- Thermal conductivity versus density, 669(fig.), 670(fig.)
- Thermal effects of surface absorptance, 457
- Thermal efficiency
 - insulation materials, 720
 - measured by wet/dry thermal resistance, 424
 - roof insulation, 172, 178, 431
- Thermal environment in buildings, module test used to evaluate, moisture retarder paint, 716
- Thermal experiments, 450
- Thermal hot plate, biguarded, 286
- Thermal insulating materials, 477
- Thermal insulation, 506, 541, 567, 582, 599
 - airtightness, 680(fig.)
 - army buildings, 203, 207
 - ASTM Committee C-16, 705
 - basement heat loss factors, 144-151(tables)
 - building envelope air movements, 124
 - cavity wall, 319, 338
 - cellular plastic, 518
 - combustible cellular plastic, 720
 - counterflow systems, 154-162
 - deterioration, due to groundwater ingress, 52
 - earth contact systems, 135
 - energy efficiency, 69
 - engineered specifications, 82-88

Thermal insulation (*cont.*)

- exterior envelopes of office buildings, 175-195
 - formaldehyde emissions, 223-237
 - heat loss factors, 144-151(tables), 286-287
 - hot box method for testing, 297-299, 303, 307, 346-347
 - installation, workmanship, 679, 680, 681(fig.)
 - loose-fill attic insulation, 493
 - materials
 - application procedures, 87-88
 - degradation, 477
 - thermal resistance values, 652
 - measuring techniques, hot box method, 345-359
 - metal furred wall systems, 720
 - mineral fiber, 394-395
 - module tests, 716
 - moisture problems in family housing, 371-372
 - new products, 310
 - office buildings, field measurement, 107-123
 - polyurethane foam insulation system, 69-81, 431
 - reference materials, 666
 - residential energy standards, 32-34
 - resistance, 652
 - basement heat loss factors, 144-151(appendix tables)
 - retrofitted walls, 196-201
 - roof systems, 172, 178, 449
 - protected membranes, 421
 - slab-on-grade floor heat loss, 144-151(tables)
 - spray-applied, 360, 367-369
 - stress, 75
 - equations, 75-76
 - underground heat distribution systems, 46, 49, 52
 - wall thermal performance, 92-98, 198-200
 - wall U values, 11-15, 92, 94
 - water vapor retarders, 463
 - wood data base 238-282
 - wood frame walls, 405
- Thermal Insulation Manufacturers Association (RIC/TIMA), 447
- Thermal mass effect 541, 542
- dependent on internal heat gains, 563, 565
- Thermal parameter theory, 92
- Thermal performance, 567
- army buildings, field investigations, 203
 - building components, ASTM proposed Standard test method, 718
 - building envelope, 107-108, 124-131, 616
 - guarded hot box facility, 297
 - conductance/transmittance, 301
 - energy measurement, 300(fig.), 301
 - in situ* measurements of roof systems, 449
 - monitoring, 599
 - of insulation, heat flow meter technique, 652
 - reflective insulations, 506
 - related to poor application procedures, 314
 - roofs, 449
 - solar reflectance, 457
 - spray-applied insulation systems, 360, 367-369
 - walls
 - active measurement strategy, 91-92
 - passive measurement strategy, 91-92, 94, 98-100
- Thermal properties
- exposure studies, expanded polystyrene materials, winter conditions, 528, 531(tables), 532-534
 - measurement/verification, 297
 - of wood, data base, 238-282
- Thermal resistance measurement
- future needs
 - high-temperature heat flux transducers, 662
 - high-temperature reference materials of different thicknesses, 663
 - stability over a high-temperature range, 663
 - instruments
 - calibrated hot box, 327(table)
 - guarded hot box, 175-176, 311-313, 314(table)
 - spot radiometer, 187, 189, 190(tables), 192, 193(figs.)
- Thermal resistances (R values)
- building envelope, 131, 310
 - concrete block wall, 593(table), 594, 596(table)
 - decreasing with increasing moisture, 424
 - discussion, 592
 - hermetically sealed glazing, 568(fig.), 570(table)
 - insulation materials, 71(fig.), 160, 310, 394-395
 - mean temperature for concrete block with wall laminate, 595
 - office buildings, 107
 - protected membrane roof, 421
 - quality control instrument, 655
 - reductions, 564(fig.), 565(table)
 - reflective insulations, 506

- test results, 592
 - walls, 91, 112-113(fig.), 326
 - wet mineral wool, 396-397
 - Thermal response dynamic tests, test procedures/results, 328-329
 - Thermal sensations, range of temperatures compatible with tissue life, 708(table)
 - Thermal shorts, 316-317
 - Thermal testing, 92-97, 161-171
 - calculation techniques, 511
 - reflective insulations
 - apparatus and test panels, 509
 - laboratory test plans, 508
 - test results and discussion, 511
 - test specimens, 510
 - Thermal transfer test facility, 298(fig.)
 - Thermal transmission data, 597
 - Thermal transmission properties, test wall, 584
 - Thermal transmittance
 - air flow along insulation, 682(fig.)
 - air leakage around electrical outlet, 683(fig.)
 - guarded hot box, 299
 - increase due to pressure and air flow, 130(fig.)
 - Thermesthesiometer, new NBS tool for evaluation of hazardous conditions, 709
 - Thermistors, 110
 - Thermodynamic insulation, 164
 - Thermographic inspections, 176-177, 180-182, 194, 196-201, 207
 - Thermographic survey of solar houses, 602
 - Thermography, infrared
 - aerial and ground-based, 176
 - review of insulated surfaces, 88
 - Thermography scans, wall insulation, cost effectiveness, 200
 - Thermogravimetric analysis
 - insulating mineral fibers, 478-479, 482-485(figs.), 488-489(figs.)
 - polyurethane foam specimens, 437, 441, 442(fig.)
 - Thermometer, infrared (*see* Spot radiometer)
 - Thermophysical properties of wood, data base, 238-282
 - Thermo-Stud system, 589-590, 597
 - Thickness effect, 671, 675
 - cellular plastic insulation, 518
 - heat flow meter use for quality control, 661-662(table)
 - Thickness, loose-fill attic insulation
 - measurement *in situ*, 496, 497-499(tables)
 - variations with time, 497
 - Thickness measurements, before/after round robin testing
 - by calorimeter, 688(table)
 - by guarded hot plate, 688(table)
 - Thickness versus calibration constant, R-Matic instrument, 660(fig.)
 - Time constant, wall thermal performance, 91, 96-99(tables)
 - Tissue life, after hazard exposure, 708(table)
 - Tools for evaluation of hazardous conditions, thermesthesiometer, testing the thermophysical reaction of human skin to a heated surface, 709
 - Tracer gas, air infiltration measurement, 175-176, 377
 - Transducers, heat flux, 108, 110, 119-120
 - Transducer signals, 583
 - Transfer standards, 651
 - Trench systems, insulated underground pipe, 46
 - Trombe-type solar wall (U.K.), substantial energy saving, 608
 - Trusses, roof, 631-632, 637
 - Tunnel systems, buried, for housing underground piping, 50
- U
- Ultraviolet light, vapor barrier design, aluminum jacketing, 74
 - Unbonded loose-fill fiberglass insulation, 310
 - Underground heat distribution systems, 43
 - Underground insulated piping systems
 - alkalinity, 44-45
 - conduit systems, 46
 - design and installation criteria, 43
 - drainage, 44-45
 - failures, 43-44
 - maintenance and performance, 50
 - Underground water conditions, classification, 44(table)
 - Uniform temperature convection heater, 575(fig.), 577
 - Urea-formaldehyde foam insulation (UFFI) walls, 199
 - Urethane foam insulation, 421
 - laboratory tests, 423
 - temperature/moisture profiles, 469(fig.)
 - U* value (*see* Thermal conductivity)
- V
- Vapor barrier, 615, 679, 682
 - coating, 74, 423
 - design, 74

- Vapor barrier (*cont.*)
 - effect on airtightness, 133
 - effect on pressure drop, 129
 - efficiency, 75
 - polyurethane foamed insulation, 47
 - design, 74, 79, 80
 - trapped moisture, 401
 - Vapor compression air conditioning, 560
 - Vapor movement
 - effect on conductivities, 369
 - effect on heat transfer, 361
 - Vapor pressure gradients, laboratory wetting test, 428
 - Vapor proofing, engineered specifications, 84
 - Vapor retarder, 406, 412, 464, 466-467
 - Vapor retarder coatings, 463
 - Vapor retarder paint tests, 716-717(fig.)
 - Vapor sealing membranes, 46
 - Ventilation
 - attic, 635
 - new rationale required, 637
 - building envelope, 125
 - exchanges, 605
 - fresh air, 18, 19(table)
 - insulation efficiency, 154-156, 160-171
 - load, energy efficiency, 9, 12, 14
 - whole-house, versus vapor-compression air conditioning, 560
 - Ventilation systems, solar houses, 604(fig.)
 - Verification procedures
 - guarded hot box facility performance, 308
 - measurement/verification, 302-304
 - thermal properties, 297
 - Vermiculite
 - insulating concrete aggregate, 49
 - new construction applications, 642
 - Vitrified clay, for pipe conduits, 48
 - Voids
 - roofing insulation, 434, 444, 445(fig.), 446(fig.)
 - wall insulation, 198-199, 314
- W**
- Wall cavities, excessive moisture, 405
 - Wall conductance, reduction after wall insulation retrofit, 646
 - Wall constructions
 - discussion of test results, 592
 - interior insulation systems, 587
 - St. John's, Newfoundland, 621(fig.)
 - surface-to-surface R values, measured concrete block wall, 592, 593(table)
 - Wall dynamic thermal performance, 335
 - Wall fluxes, Fourier transforms, 100-104
 - Wall heat loss, 108
 - Wall heat transfer, measurement strategies, 94-100
 - Wall insulation, 14-17, 197, 610
 - fiberglass, 197
 - installation problems, 197-200
 - quality control, 199-200
 - on-site inspection program, thermography scans, 200
 - retrofit, reduction in air leakage heat loss, 644-645(table)
 - void areas, 198-199
 - Wall materials, moisture content, 375
 - Wall orientations, 10(table)
 - Wall relative humidity, 626(fig.)
 - Walls
 - air leakage, 213
 - basement heat loss calculations, 132, 142
 - code requirements, 23(fig.)
 - convection, army housing units, 209
 - dynamic thermal response, 92-98
 - heat flow, 120
 - inside surface temperature, 571
 - insulation efficiency, 171, 196
 - infrared thermography scans, 197
 - residential, 615
 - R values, 213, 219-220(table)
 - standards development, 29
 - thermal performance, measurement strategies
 - active, 92-94, 96-98
 - passive, 94-96
 - thermal resistances, 112, 114-116(table), 117, 120
 - measurement period, 119
 - tests, 721
 - U values, 16(table)
 - water vapor permeance, 616
 - Wall surface temperatures, hot box measurement, 355
 - Wall systems, 311, 312-313(figs.)
 - cavity walls, 319
 - comparison of measured and calculated R values, 728(table)
 - discussion, test results, 592-597
 - drywall laminate system, 589
 - exterior insulated finishing system, 592
 - guarded hot box test results, 725(table)
 - installation, 588
 - metal Z-furring channel system, 590
 - R values, 313
 - Temp Guard insulation furring (TGIF) system, 590
 - test results of R values, 726(table)
 - Thermo-Stud system, 589-590
 - Washington, DC, basement wall/floor heat loss, 144-151(appendix tables)

- Water absorption of foam, 467-468(tables)
 Water calorimeter, 686
 Water flow rate inside attic, 633, 637
 Water leakage
 at footing, 387
 in family housing, 377, 390
 Waterproof coatings, underground pipe systems, 45-46
 Water spray tests, moisture problems, 378, 388-389
 Water table, ground drainage tests, 377
 Water vapor diffusion, 463
 Water vapor movement rate, 405
 Water vapor permeability, 232
 of wall materials, 372
 vapor barrier design, aluminum jacketing, 74
 Water vapor permeance of walls, 616
 Water vapor pressure, in insulation systems, 73, 390
 Water vapor retarders, chlorosulfonated polyethylene mastic, 464, 466-468
 Water vapor transport, preventive use of vapor retarders, 716
 Weather fluctuations, 103
 Weatherization, walls, 196-201
 Weather side air film, 572
 Wet bulb temperature, 12
 Wet insulation in walls, after condensation, 406
 Wetting
 behavior of insulations, 428-429, 456(fig.)
 protected membrane roofs, 424, 428
 exposure tests, 425-427(figs.)
 White pine, thermal conductivity, 251, 255-258(tables)
 Wind flow around tanks, 77
 Wind loading, estimations of pressure differences, 127
 Wind loads and pressure, 679
 Wind machine, Canadian Division of Building Research, 572, 573(fig.)
 Window frames, metal condensation, 572
 Windows
 evaluation program, 578
 heat transfer equations, 569-572
 standards development, 36
 surface temperature, hermetically sealed glazing unit, 568(fig.)
 tests using DBR wall calorimeter apparatus and test setup, 578-581
 thermal performance, 567
 Wind protection, 679, 681
 building envelope, 124-125, 127-128
 Wind resistance, design criteria for tank insulation systems, 70, 76-77(fig.)
 Wind speed, 636(fig.)
 Winter temperatures, humidity conditions, 524-529
 Wood
 data analysis
 electrical resistance, 617
 moisture content, 634-635, 636(fig.)
 specimen preparation/test conditions, 274-275(table), 277
 surface film humidity ratio, 634-635
 thermal conductivity, 277-278, 280
 used for domestic residential construction
 mean density compared with mechanical property data, 247(table)
 thermal properties, 251, 252-273(tables)
 Wood frame walls
 condensation, 405, 410-416
 decay, 406
 Workmanship, deficiencies in installation, 679-680

Y

 Yellow pine, mechanical/thermal properties, 251

Z

 Z-furring test construction, 724(fig.)