

Subject Index

A

adiabatic compression, 337-61,
362-88
adsorbent, 322-36
advanced crew escape suit (ACES),
246-65
air separation, 303-21
air separation unit, 49-67
aluminum, 49-67, 204-18
aluminum anodization, 246-65
aluminum combustion, 303-21
aluminum foil, 322-36
applications, 468-94
argon, 49-67
ASU, 303-21
autogenous ignition temperature,
195-203
autoignition temperature, 124-32

B

BAHX, 303-21
batch testing, 133-43
bellows, 322-36
brazed aluminum heat exchanger,
303-21
burn criteria, 21-37
burn length, 21-37
burning, 80-95, 450-67

C

cavity, 303-21
cavity incident, 303-21
CGA 870 seals, 429-49
chlorine trifluoride, 468-94
combustion, 144-74
compatibility, 322-36

components, 133-43
computational fluid dynamics, 429-
49
contamination, 322-36, 322-36
copper, 49-67
crew escape suit, 175-94
cryogenic, 49-67, 322-36
cutting torch, 266-84
CW6M, 10-20
cylinder valves, 429-49

D

Dalton, 68-79
design, 266-84
diffusion, 175-94, 175-94
dust layer, 389-428

E

electrical arc ignition, 219-26
Elgiloy, 10-20
exchanger, 49-67
Extravehicular Mobility Unit, 175-94

F

filling process, 124-32
fire hazard, 124-32
fire risk, 285-302
fires, 266-84
flammability, 1-9, 10-20, 21-37,
49-67, 80-95, 124-32, 133-43, 175-94
flammability materials testing,
219-26
flow friction ignition, 429-49
fluorinated polymers, 109-23
foil, 49-67

G

gas analysis, 144-74
 gaseous fluid impact, 337-61, 362-88
 gaseous oxygen enrichment,
 175-94
 getter, 322-36
 glass fiber, 322-36
 good practices, 266-84

H

handheld electrical devices, 219-26
 handling, 468-94
 Hastelloy B-3, 10-20
 Hastelloy W, 10-20
 hazards, 468-94
 hazards analysis, 285-302
 heat affected, 80-95
 heat affected zone, 21-37
 heat conduction, 21-37
 heat transfer, 38-48, 450-67
 heterogeneous burning, 38-48
 hexadecane, 49-67
 high pressure, 227-45
 high purity oxygen atmosphere, 68-79
 hydrocarbon, 49-67

I

igniter effects, 21-37
 ignition, 49-67, 80-95, 285-302,
 389-428
 impact, 49-67, 322-36
 impact test, 322-36
 insulation material, 322-36
 intermediate layers, 322-36
 interspace, 322-36
 iron, 450-67

isentropic compression, 337-61,
 362-88

L

layer, 49-67
 liquid, 49-67
 liquid oxygen, 322-36
 liquid oxygen environment, 204-18

M

maintenance, 133-43
 manufacturing, 322-36
 MAPTIS, 109-23
 maximum oxygen concentration
 (MOC), 175-94
 medical oxygen, 285-302
 melting, 38-48, 450-67
 metal combustion, 21-37
 metallic contaminant particles, 204-18
 metals, 10-20
 microchannel flow, 429-49
 microgravity, 450-67
 model, 38-48
 MP35N, 10-20
 MSDS, 468-94

N

nitrogen, 49-67
 NITROX, 124-32
 non-metallic materials, 144-74
 nonmetallic materials,
 124-32, 133-43, 195-203
 nonmetals, 175-94
 nonorganic, 322-36

O

organic, 322-36
 oxidizer, 1-9
 oxygen, 1-9, 49-67
 Oxygen, 80-95
 oxygen, 144-74, 219-26, 266-84,
 337-61, 362-88, 389-428
 oxygen cleaning, 266-84
 oxygen compatibility, 1-9, 133-43
 oxygen concentration, 68-79,
 195-203
 oxygen enrichment, 124-32
 oxygen fires, 429-49
 oxygen hazards, 285-302
 oxygen lance, 266-84
 oxygen mixtures, 124-32
 oxygen percentage, 68-79
 oxygen systems, 109-23

P

partial pressures, 68-79
 particle impact ignition testing, 246-
 65
 particle impact testing, 227-45
 PCTFE, 144-74
 permeation, 175-94
 PICT behavior, 10-20
 pneumatic impact, 124-32, 133-43,
 195-203, 337-61, 362-88
 polyester, 322-36
 polytetrafluoroethylene, 109-23
 PPE, 468-94
 promoted combustion, 21-37, 80-95
 promoted combustion chamber,
 68-79
 promoted ignition, 21-37
 promoted ignition-combustion, 10-
 20
 promoter, 80-95

propagating brush discharge, 389-
 428
 properties, 468-94
 PTFE, 144-74
 purge cycles, 68-79
 purge equation, 68-79
 purity, 49-67

Q

quality assurance, 133-43
 quick disconnect, 227-45

R

RA 330, 10-20
 rate-limiting mechanism, 38-48,
 450-67
 reboiler, 49-67, 303-21
 release, 468-94
 rods, 80-95
 rotating friction ignition testing, 204-
 18

S

SCUBA diving, 124-32
 sealed cavity, 303-21
 severity index, 362-88
 shock-wave heating, 337-61, 362-88
 solid/liquid interface, 450-67
 stagnation heating, 429-49
 stainless steel, 227-45
 steel mill, 266-84
 Stellite 6, 10-20
 superinsulation, 322-36

T

temperature, 80-95
 testing, 468-94
 textiles, 175-94