

# Subject Index

## A

*ABAQUS*<sup>TM</sup>, 308-330  
 accelerated exposure, 343-360  
 accelerated weathering, 370-384  
 acrylate, 124-151  
 adhesion, 243-265, 331-340  
 adhesive, 124-151, 447-455, 456-470  
 adhesive failure, 370-384  
 adhesive technology, 26-46  
 apparent modulus, 70-85  
 architectural design feature, 205-242  
 argon retention, 205-242  
 ASTM C719, 432-443  
 ASTM C1519, 432-443  
 ASTM C1736, 361-369  
 ASTM E2188, 205-242  
 ASTM E2190, 205-242  
 autoclaved lightweight concrete,  
 47-69, 385-403

## B

bent glass, 205-242  
 blister growth, 308-330  
 bond, 3-25  
 bonding design, 266-285  
 Building sealant, 70-85

## C

capability evaluation, 404-431  
 closed-form solution, 308-330  
 cold bent glass, 205-242, 286-307  
 compression set, 70-85  
 concrete, 447-455  
 construction, 177-201  
 continuous sealant evaluation,  
 361-369

corner load, 286-307  
 creep, 308-330  
 cured, 361-369  
 curtain wall systems, 529-564  
 curtain walls, 473-504  
 cyclic loading, 266-285

## D

degradation, 266-285  
 doubly curved glass, 205-242  
 durability, 47-69, 70-85, 243-265,  
 331-340, 343-360, 432-443  
 durability evaluation, 404-431  
 dynamic-mechanical testing, 404-431

## E

earthquake, 529-564  
 epoxy, 3-25  
 exposure testing, 47-69

## F

fibre reinforced polymers, 3-25  
 film adhesive, 86-123  
 finite-element method, 308-330  
 Finite Element Modeling, 473-504  
 floor, 447-455  
 foamed, 456-470  
 fracture, 385-403

## G

glass, 3-25, 124-151  
 glass fin, 124-151  
 glass frame, 124-151  
 glazing, 86-123

**H**

high strain rate behavior of structural silicone, 529-564  
 hybrid beam, 124-151  
 hybrid steel-glass beams, 26-46

**I**

indirect tensile test, 308-330  
 insulating-glass durability, 205-242  
 insulation, 456-470  
 interstory drift, 529-564

**J**

joint, 361-369

**K**

Korea, 370-384

**M**

master curve, 308-330  
 material characterization, 404-431  
 mechanical characteristics, 404-431  
 metallic substrate, 243-265  
 mixing ratio, 266-285  
 model, 177-201  
 modulus, 177-201, 385-403, 432-443  
 moisture, 447-455, 456-470  
 molecular brushes, 243-265

**N**

non-destructive evaluation, 361-369

**O**

one part, 370-384  
 organic substrate, 243-265

outdoor aging, 70-85  
 outdoor exposure, 343-360

**P**

performance assessment, 404-431  
 photovoltaic facade, 124-151  
 PIB durability, 205-242  
 point fixing, 86-123  
 polyethyleneimines, 243-265  
 primers, 331-340  
 Prony series, 308-330

**R**

racking test, 473-504  
 relaxation, 308-330  
 rolling device, 361-369  
 roofing, 456-470

**S**

Sealant, 47-69, 177-201, 343-360, 385-403, 404-431, 432-443  
 sealant failure in adhesion, 361-369  
 seismic evaluation, 473-504  
 Service Life Prediction, 177-201  
 shear, 3-25  
 sigmoidal function, 308-330  
 silica sand, 3-25  
 silicone, 86-123, 370-384, 473-504  
 silicone adhesion, 243-265  
 silicone adhesive, 266-285, 286-307  
 silicones, 243-265, 331-340  
 small- and large-scale tests, 26-46  
 SPHERE, 177-201  
 SSG, 529-564  
 Statistics, 177-201  
 strain cycling, 70-85  
 stress relaxation, 432-443  
 structural, 86-123

structural behavior, 26-46  
 structural glazing, 26-46, 266-285,  
 286-307, 370-384, 404-431  
 structural sealant glazing, 473-504  
 structural silicone, 205-242  
 structural silicone glazing, 529-564  
 superimposed loading, 404-431  
 surface degradation, 343-360  
 surface engineering, 243-265  
 system test method, 404-431

### **T**

tensile strength, 370-384  
 tension, 3-25  
 two part, 370-384

### **U**

Ultra-High-Performance- Concrete,  
 3-25

### **V**

VOCs, 447-455

### **W**

wall panel, 47-69, 385-403  
 warped glass, 205-242,  
 286-307  
 weatherability, 343-360