

Journal of Testing and Evaluation

Author Index to Volume 6

1978

Number	Month of Issue	Pages
1	January	1-80
2	March	81-156
3	May	157-240
4	July	241-288
5	September	289-324
6	November	325-380

A

- Aleszka, J.C.: Low energy impact behavior of composite panels, May, 202
 Andrews, C.W.: Volume fraction determination in cast superalloys and directionally solidified eutectic alloys by a new manual point count practice, Jan., 20
 Arnon, U.: *see* Ishai, O. and Arnon, U.

B

- Barbato, G., Desogus, S., and Levi, R.: Design and performance of a deadweight standard Rockwell hardness testing machine, July, 276
 Beese, J.G.: Some parameters influencing the release pressure of reverse-buckling safety disks, Sept., 315
 Borchelt, J.G. and Brown, R.H.: Indirect tensile test for masonry units, March, 134
 Brown, R.H.: *see* Borchelt, J.G. and Brown, R.H.
 Buzzard, R.J. and Fisher, D.M.: Load-displacement measurement and work determination in three-point bend tests of notched or precracked specimens, Jan., 35

C

- Cairns, J., Jr. and Dickson, K.L.: Field and laboratory protocols for evaluating the effects of chemical substances on aquatic life, March, 81
 Chipperfield, C.G.: Summary and comparison of *J* estimation procedures, July, 253
 Chirigos, J.N. and Meyer, T.A.: Influence of material property variations on the assessment of structural integrity of nuclear components, Sept., 289
 Chopra, K.S.: Interlaboratory measurements of amphibole and chrysotile fiber concentration in water, July, 241
 Cohen, J.B.: *see* James, M. and Cohen, J.B.
 Cotsworth, R.P.: Use of pelletized slag in concrete masonry units, March, 156

D

- Dahir, S.H. and Meyer, W.E.: Polishing characteristics of common rock types used as aggregate in bituminous pavement surfaces, Jan., 52

Davison, J.I. and Sereda, P.J.: Measurement of linear expansion in bricks due to freezing, March, 144

de Malherbe, R.: *see* Tomlinson, P.N., Venter, R.D., de Malherbe, R., and Lees, L.

Desogus, S.: *see* Barbato, G., Desogus, S., and Levi, R.

Diaz, E.S.: *see* Lange, F.F. and Diaz, E.S.

Dickson, K.L.: *see* Cairns, J., Jr. and Dickson, K.L.

Dilipkumar, D.D.: *see* Wood, W.E. and Dilipkumar, D.D.

Donachie, M.J., Jr.: Phase extraction and analysis in superalloys—second summary of investigations by ASTM Subcommittee E04.91, May, 189

Donald, J.K.: *see* Saxena, A., Hudak, S.J., Jr., Donald, J.K., and Schmidt, D.W.

Dorward, R.C., Hasse, K.R., and Helfrich, W.J.: Marine atmosphere stress corrosion tests on precracked specimens from high-strength aluminum alloys: effect of corrosion-product wedging, July, 268

F

Fisher, D.M.: *see* Buzzard, R.J. and Fisher, D.M.

Fox, A. and Fuchs, E.O.: Mechanical properties in bending at elevated temperature of high strength copper alloy flat spring materials, May, 211

Frenkel, H. and Rhoades, J.D.: Effects of dispersion and swelling on soil hydraulic conductivity, Jan., 60

Fricke, W.G.: *see* Nordmark, G.E. and Fricke, W.G.

Fuchs, E.O.: *see* Fox, A. and Fuchs, E.O.

G

Gauvin, R. and Trotignon, J.P.: New method of test for flexural fatigue of plastics, Jan., 48

Gross, B.: Displacement coefficients along the inner boundaries of radially cracked ring segments subject to forces and couples, May, 196

H

Hasse, K.R.: *see* Dorward, R.C., Hasse, K.R., and Helfrich, W.J.

Helfrich, W.J.: *see* Dorward, R.C., Hasse, K.R., and Helfrich, W.J.

Hoeppner, D.W.: *see* Ryder, J.T., Krupp, W.E., Pettit, D.E., and Hoeppner, D.W.

Hsu, T.R.: *see* Trasi, S.R. and Hsu, T.R.

Hudak, S.J., Jr.: *see* Saxena, A., Hudak, S.J., Jr., Donald, J.K., and Schmidt, D.W.

I

Ishai, O. and Arnon, U.: "Instantaneous" effect of internal moisture conditions on the strength of glass-fiber-reinforced plastics, Nov., 364

J

James, M. and Cohen, J.B.: "PARS"—a portable X-ray analyzer for residual stresses, March, 91

Janakiram, K.S.: *see* Syamala Rao, B.C. and Janakiram, K.S.

Johnston, P.R.: Determining filtration efficiency by comparing the particle-size distribution in the feed stream to that in the filtrate, Sept., 311

Particle-size distribution in AC fine test dust, March, 103

Jonas, O.: Tapered tensile specimen for stress corrosion threshold stress testing, Jan., 40

Jordan, E.H. and Sandor, B.I.: Stress analysis from temperature data, Nov., 325

K

Kendall, D.P.: *see* Underwood, J.H. and Kendall, D.P.

Kesterson, K.F.: *see* Poore, M.W. and Kesterson, K.F.

Krupp, W.E.: *see* Ryder, J.T., Krupp, W.E., Pettit, D.E., and Hoeppner, D.W.

Kuc, A.P. and Shewchuk, J.: Effect of interference on the dimpled, loaded-hole fatigue strength of 2024-T3 Alclad® aluminum alloy, May, 157

L

Lamba, H.S. and Sidebottom, O.M.: Proportional biaxial cyclic hardening of annealed oxygen-free high-conductivity copper, July, 260

Lange, F.F. and Diaz, E.S.: Powder-cushion gripping to promote good alignment in tensile testing, Sept., 320

Lawson, R. and Ramey, H.H., Jr.: Comparison of cotton fiber fineness and maturity on air-flow instruments, July, 248

Lees, L.: *see* Tomlinson, P.N., Venter, R.D., de Malherbe, R., and Lees, L.

LeFort, P. and Mowbray, D.F.: Calibration of the side-grooved modified wedge-opening-load specimen, March, 114

Levi, R.: *see* Barbato, G., Desogus, S., and Levi, R.

M

- Mai, Y.W.: Fracture toughness evaluation of polymers with surface-crack specimens, Nov., 347
 Marion, R.H.: Short-time, high temperature mechanical testing facility, Jan., 3
 Marston, T.U.: *see* Stahlkopf, K.E. and Marston, T.U.
 Mehta, S.D.: *see* Nathan, S.S., Mehta, S.D., and Selvarajan, A.
 Mercer, T.T.: Respirable fraction of airborne dust: quantitative descriptions, formal definitions, and performance characteristics of samplers matched to them, Jan., 9
 Meyer, T.A.: *see* Chirigos, J.N. and Meyer, T.A.
 Meyer, W.E.: *see* Dahir, S.H. and Meyer, W.E.
 Mowbray, D.D.: *see* LeFort, P. and Mowbray, D.F.

N

- Nassar, E.M.: Evaluation of cushion dynamic properties by impedance measurements, May, 231
 Nathan, S.S., Mehta, S.D., and Selvarajan, A.: Holographic interferometry study of chemical bond of concrete to smooth steel rods, July, 284
 Nordmark, G.E. and Fricke, W.G.: Fatigue crack arrest at low stress intensities in a corrosive environment, Sept., 301

P

- Pettit, D.E.: *see* Ryder, J.T., Krupp, W.E., Pettit, D.E., and Hoepplner, D.W.
 Pickel, F.M.: *see* Ryder, J.T. and Pickel, F.M.
 Pierce, W.S. and Shannon, J.L., Jr.: Surface-crack shape change in bending fatigue using an inexpensive resonant fatiguing apparatus, May, 183
 Poore, M.W. and Kesterson, K.F.: Measuring the thermal expansion of solids with strain gages, March, 98

R

- Ramey, H.H., Jr.: *see* Lawson, R. and Ramey, H.H., Jr.
 Rhee, S.K.: *see* Young, C.T. and Rhee, S.K.
 Rhoades, J.D.: *see* Frenkel, H. and Rhoades, J.D.
 Ryder, J.T.: and Krupp, W.E., Pettit, D.E., and Hoepplner, D.W.: Comparison of stress corrosion cracking properties of several aircraft structural alloys, March, 120
 and Pickel, F.M.: Effect of temperature on stress corrosion cracking of 300M steel, March, 129

S

- Sandor, B.I.: *see* Jordan, E.H. and Sandor, B.I.
 Saxena, A., Hudak, S.J. Jr., Donald, J.K., and Schmidt, D.W.: Computer-controlled decreasing stress intensity technique for low rate fatigue crack growth testing, May, 167
 Schmidt, D.W.: *see* Saxena, A., Hudak, S.J., Jr., Donald, J.K., and Schmidt, D.W.
 Selvarajan, A.: *see* Nathan, S.S., Mehta, S.D., and Selvarajan, A.
 Sereda, P.J.: *see* Davison, J.I. and Sereda, P.J.
 Server, W.L.: Impact three-point bend testing for notched and precracked specimens, Jan., 29
 Seth, B.B.: *see* Tu, L.K.L. and Seth, B.B.
 Shannon, J.L., Jr.: *see* Pierce, W.S. and Shannon, J.L., Jr.
 Shannon, J.L., Jr.: *see* Pierce, W.S. and Shannon, J.L., Jr.
 Shewchuk, J.: *see* Kuc, A.P. and Shewchuk, J.
 Sidebottom, O.M.: *see* Lamba, H.S. and Sidebottom, O.M.
 Stahlkopf, K.E. and Marston, T.U.: Assessment of reactor pressure vessel irradiated materials considerations, March, 108
 Stephens, J.R.: *see* Witzke, W.R. and Stephens, J.R.
 Suga, S.: Development of light- and water-exposure apparatus, Nov., 341

T

- Tomlinson, P.N., Venter, R.D., de Malherbe, R., and Lees, L.: Mathematical model for the determination of the breakage distribution in batch grinding, Sept., 304
 Trasi, S. R. and Hsu, T. R.: Improvement of sheet metal strength by localized thermal shocks, July, 280
 Trotignon, J.P.: *see* Gauvin, R. and Trotignon, J.P.
 Tu, L.K.L. and Seth, B.B.: Threshold corrosion fatigue crack growth in steels, Jan., 66

U

- Underwood, J.H. and Kendall, D.P.: Cooperative plane strain fracture toughness tests with C-shaped specimens, Sept., 296

V

- Venter, R.D.: *see* Tomlinson, P.N., Venter, R.D., de Malherbe, R., and Lees, L.
 Vosikovsky, O.: Frequency, stress ratio, and potential effects on fatigue crack growth of HY130 steel in salt water, May, 175

W

- Witzke, W.R. and Stephens, J.R.: Comparison of equivalent energy and energy per unit area (\overline{W}/A) data with valid fracture toughness data for iron, aluminum, and titanium alloys, Jan., 75
 Wood, W.E. and Dilipkumar, D.D.: Composite grip design for elimination of extraneous noise during acoustic emission testing, Nov., 369

Y

- Young, C.T. and Rhee, S.K.: Evaluation of correction methods for determining load-independent Knoop microhardness, May, 221