

Journal of Testing and Evaluation

Author Index to Volume 13

1985

Number	Month of Issue	Pages
1	January	1-88
2	March	89-180
3	May	181-244
4	July	245-328
5	September	329-392
6	November	393-460

A-B

- Abrams, M. S., D'Souza, M. V., Higginson, P., Metes, W. S., Quintiere, J. G., Parker, W. J., Robins, R. F., and White, J. A., Jr.:** Review of ASTM test for surface burning characteristics of building materials (E 84) (an ASTM white paper), March, 89
- Balbás, M.:** *see* Gascón, F. and Balbás, M.
- Baratta, F. I.:** Stress intensity factors for notched configurations, July, 275
- Baxter, W. J.:** Optimization of the gel electrode for repeatable imaging of fatigue cracks in aluminum alloys, July, 245
- Berke, N. S. and Townsend, H. E.:** Comparison of the Kesternich sulfur dioxide test with industrial atmospheric corrosion tests of zinc-, aluminum-, and Al-Zn-coated steel sheet, Jan., 74
- Beynon, J. H. and Sellars, C. M.:** Strain distribution patterns during plane strain compression, Jan., 28
- Brahma, K. K.:** *see* Murthy, C. R. L. and Brahma, K. K.
- Brose, W. R.:** *see* Leax, T. R., Dowling, N. E., Brose, W. R., and Peck, M. G.
- Brown, P. W.:** *see* Grimes, J. W., II, Brown, P. W., and Kaetzel, L.
- Brown, W. F., Jr.:** *see* Lemon, D. D. and Brown, W. F., Jr.
- Bush, R. W. and Quesnel, D. J.:** Effect of dither on strain-controlled fatigue and tensile results obtained with a closed-loop servo-hydraulic testing machine, Nov., 405

C-F

- Cairns, J., Jr., Pratt, J. R., and Niederlehner, B. R.:** Provisional multispecies toxicity test using indigenous organisms, July, 316
- Campbell, D. N.:** *see* Spangler, G. E., Carrico, J. P., and Campbell, D. N.
- Carrico, J. P.:** *see* Spangler, G. E., Carrico, J. P., and Campbell, D. N.
- Ceschini, L. J.:** *see* James, L. A. and Ceschini, L. J.
- Cheng, S.:** Test method for evaluation of shear modulus and modulus of elasticity of laminated anisotropic composite materials, Sept., 387
- Cook, T. S.:** Effect of R_e on cyclic stress-strain behavior of Inconel 718, Nov., 434
- Corten, H. T.:** *see* Putatunda, S. K., Rigsbee, J. M., and Corten, H. T.

- Coulon, A., Knosp, B., and Saisse, H.:** Plastic strain arising from fatigue crack initiation, July, 265
- Cropper, W. V.:** Review of *From the American System to Mass Production, 1800-1932: The Development of Manufacturing Technology in the United States* by Hounshell, July, 323
- Dowling, N. E.:** *see* Leax, T. R., Dowling, N. E., Brose, W. R., and Peck, M. G.
- Drefahl, K., Kleinau, M., and Steinkamp, W.:** Creep behavior of copper and copper alloys as design criteria in pressure vessel manufacture, Sept., 329
- D'Souza, M. V.:** *see* Abrams, M. S., D'Souza, M. V., Higginson, P., Metes, W. S., Quintiere, J. G., Parker, W. J., Robins, R. F., and White, J. A., Jr.
- During, M.:** *see* Havelaar, A. H., van Breemen, L. W. C. A., Vaessen, H. A. M. G., During, M., van der List, C., and van Erne, E. H. W.
- Eisele, U., Roos, E., Silcher, H., and Zimmerman, C.:** Method for the defined fatigue pre-cracking of round notched bars, Jan., 46
- El-Zoghby, A.:** *see* Ragab, A-R. and El-Zoghby, A.
- Evans, E. G.:** *see* Rhodes, R. C., Mitchell, W. J., Puzak, J. C., and Evans, E. G.
- Fett, T. and Munz, D.:** Determination of crack growth parameter N in ceramics under creep conditions, March, 143

G-H

- Gascón, F. and Balbás, M.:** Optical measurement of granite surface polish, Sept., 367
- Ghorehy, M., Mackay, W. B. F., and Smith, R. W.:** Preparation of impact specimens from cast austenitic manganese steels, March, 176
- Gibson, M. W.:** *see* Shimizu, H. and Gibbon, M. W.
- Grimes, J. W., II, Brown, P. W., and Kaetzel, L.:** Methodology for the evaluation of the thermal performance of phase-change storage materials, Nov., 429
- Gromala, D. S.:** Determination of modulus of rigidity by ASTM D 198 flexural methods, Sept., 352
- Harmathy, T. Z.:**
Correction of the results of standard fire resistance tests, July, 303
Temperature of the unexposed surface of fire resistance test specimens, March, 127
- Harmouche, M. R. and Wolfenden, A.:** Modulus measurements in ordered Co-Al, Fe-Al, and Ni-Al alloys, Nov., 424
- Harris, E. S.:** *see* Lazaridis, N. A., Heberling, T. G., Harris, E. S., Lange, E. A., and Wilson, A. D.
- Hart, R. R.:** Improving bend and tensile yield strengths of metallic strip by reducing the effects of residual stresses, July, 320
- Hartman, G. A., III:** Thermal control system for thermal cycling, Sept., 363

- Hashida, T. and Takahashi, H.:** Simple determination of the effective Young's modulus of rock by the compliance method, Jan., 77
- Havelaar, A. H., van Breeman, L. W. C. A., Vaessen, H. A. M. G., During, M., van der List, C., and van Erne, E. H. W.:** Poor selectivity of certain lots of commercially available KF-streptococcus agar, May, 206
- Heberling, T. G.:** *see* Lazaridis, N. A., Heberling, T. G., Harris, E. S., Lange, E. A., and Wilson, A. D.
- Heger, J. J.:** Austenitic iron-aluminum-manganese alloys as possible substitutes for austenitic stainless steel, Nov., 446
- Higginson, P.:** *see* Abrams, M. S., D'Souza, M. V., Higginson, P., Metes, W. S., Quintiere, J. G., Parker, W. J., Robins, R. F., and White, J. A.
- Hirano, K., Ishizaki, S., Kobayashi, H., and Nakazawa, H.:** Determination of threshold stress corrosion cracking characteristics using rising load K_{Isc} testing based on ultrasonic method, March, 162
- Kobayashi, H. and Nakazawa, H.:** Single-specimen determination of J_{Ic} by the ultrasonic method and analysis of its statistical distribution characteristics, Sept., 356
- Hobbs, J.:** Introduction to symposium on explosives detection for security applications, May, 210
- Huang, F.-H.:** J_{Ic} measurements on single sub-sized specimens of ferritic alloys, July, 257
- Huber, G.:** *see* Mott, R., Huber, G., and Lee-wood, A.
- Hudson, C. M.:** Review of *Fracture Mechanics Technology Applied to Material Evaluation and Structure Design* by Sih, Ryan, and Jones, Sept., 390

I-L

- Ishizaki, S.:** *see* Hirano, K., Ishizaki, S., Kobayashi, H., and Nakazawa, H.
- James, L. A. and Ceschini, L. J.:** New method for *in situ* compliance measurements for fatigue crack growth testing in autoclaves, Nov., 409
- Johnston, P. R.:** Fluid filter media: measuring the average pore size and the pore-size distribution, and correlation with results of filtration tests, July, 308
- Jones, P. L.:** *see* Moore, K. D. and Jones, P. L.
- Kaetzel, L.:** *see* Grimes, J. W., II, Brown, P. W., and Kaetzel, L.
- Kleinau, M.:** *see* Drefahl, K., Kleinau, M., and Steinkamp, W.
- Klepaczko, J. R.:** Determination of the critical value of the J -integral at high loading rates using the wedge-loaded specimen, Nov., 441
- Knosp, B.:** *see* Coulon, A., Knosp, B., and Saisse, H.
- Kobayashi, H.:**
see Hirano, K., Ishizaki, S., Kobayashi, H., and Nakazawa, H.

see also Hirano, K., Kobayashi, H., and Nakazawa, H.

Lange, E.: see Lazaridis, N. A., Heberling, T. G., Harris, E. S., Lange, E. A., and Wilson, A. D.

Lazaridis, N. A., Heberling, T. G., Harris, E. S., Lange, E. A., and Wilson, A. D.: Task group report: results of the interlaboratory test program to determine percent shear of dynamic tear test specimens, Jan., 17

Leax, T. R., Dowling, N. E., Brose, W. R., and Peck, M. G.: Methodology for correlating fatigue data obtained under different test conditions, Nov., 393

Leewood, A.: see Mott, R., Huber, G., and Leewood, A.

Lemon, D. D. and Brown, W. F., Jr.: Fracture toughness of hot-pressed beryllium, March, 152

Lucero, D. P.: User requirements and performance specifications for explosive vapor detection systems, May, 222

M-N

Mackay, W. B. F.: see Ghoresly, M., Mackay, W. B. F., and Smith, R. W.

Mamlouk, M. S.: Evaluation of *in situ* pavement moduli from deflection measurements, Jan., 60

Mannan, S. L.: see Mathew, M. D., Mannan, S. L., and Rodriguez, P.

Mathew, M. D., Mannan, S. L., and Rodriguez, P.: Influence of gage dimensions of elongation values for Type 316 stainless steel, May, 191

Metal Properties Council, Inc.: Creep and rupture tests of Alloy A-286 at elevated temperatures, July, 285

Metes, W. S.: see Abrams, M. S., D'Souza, M. V., Higginson, P., Metes, W. S., Quintiere, J. G., Parker, W. J., Robins, R. F., and White, J. A., Jr.

Miller, G. A.: Interlaboratory study of strain-cycle fatigue of 1.2-mm-thick sheet specimens, Sept., 344

Mitchell, W. J.: see Rhodes, R. C., Mitchell, W. J., Puzak, J. C., and Evans, E. G.

Moore, K. D. and Jones, P. L.: Positron study of the quench and tempering process in AISI 4340 steel, May, 196

Mott, R., Huber, G., and Leewood, A.: Biaxial test method for characterization of fabric materials used in permanent fabric roof structures, Jan., 9

Munz, D.: see Fett, T. and Munz, D.

Murthy, C. R. L. and Brahma, K. K.: Nondestructive evaluation of bond quality of bimetallic strips using acoustic emission, Sept., 371

Naga, S. A. R.: Effect of fire fighting media on the mechanical properties of steel bars, March, 132

Nakazawa, H.

see Hirano, K., Ishizaki, S., Kobayashi, H., and Nakazawa, H.

see also Hirano, K., Kobayashi, H., and Nakazawa, H.

Niederlehner, B. R.: see Cairns, J., Jr., Pratt, J. R., and Niederlehner, B. R.

O-R

Owerbach, D.: Discussion of the method for the determination of free cyanide in water and wastewater by microdiffusion, March, 123

Papirno, R.: Algebraic approximations of stress-strain curves for Kevlar-reinforced composites, March, 115

Parker, W. J.: see Abrams, M. S., D'Souza, M. V., Higginson, P., Metes, W. S., Quintiere, J. G., Parker, W. J., Robins, R. F., and White, J. A., Jr.

Peck, M. G.: see Leax, T. R., Dowling, N. E., Brose, W. R., and Peck, M. G.

Perl, M.: see Sides, A., Uzan, J., and Perl, M.

Plaut, R. L. and Sellars, C. M.: Analysis of hot tension test data to obtain stress-strain curves to high strains, Jan., 29

Polvani, R. S., Reeve, C. P., and Veale, R. C.: Optical test method for measuring biaxial deformations, Jan., 69

Pratt, J. R.: see Cairns, J., Jr., Pratt, J. R., and Niederlehner, B. R.

Putatunda, S. K., Rigsbee, J. M., and Corten, H. T.: Effect of size on elastic-plastic fracture toughness parameters, May, 181

Puzak, J. C.: see Rhodes, R. C., Mitchell, W. J., Puzak, J. C., and Evans, E. G.

Quesnel, D. J.: see Bush, R. W. and Quesnel, D. J.

Quintiere, J. G.: see Abrams, M. S., D'Souza, M. V., Higginson, P., Metes, W. S., Quintiere, J. G., Parker, W. J., Robins, R. F., and White, J. A., Jr.

Ragab, A. R. and El-Zoghby, A.: Evaluation of the mechanical behavior of plain and spirally stiffened polyvinyl chloride pipes, March, 137

Reeve, C. P.: see Polvani, R. S., Reeve, C. P., and Veale, R. C.

Rhodes, R. C., Mitchell, W. J., Puzak, J. C., and Evans, E. G.: Comparison of precision and accuracy estimates from state and local agency air monitoring stations with results of EPA's national performance audit program, Sept., 374

Rigsbee, J. M.: see Putatunda, S. K., Rigsbee, J. M., and Corten, H. T.

Robins, R. F.: see Abrams, M. S., D'Souza, M. V., Higginson, P., Metes, W. S., Quintiere, J. G., Parker, W. J., Robins, R. F., and White, J. A., Jr.

Roder, F. L.: Principles, history, and status of dual-energy computerized tomographic explosives detection, May, 211

Rodriguez, P.: see Mathew, M. D., Mannan, S. L., and Rodriguez, P.

Roman, I.: Effect of acoustic impedance on the apparent impact fracture energy of a tungsten base sintered alloy, May, 199

Roos, E.: see Eisele, U., Roos, E., Silcher, H., and Zimmermann, C.

Rosenfield, A. R.: Effect of crack-tip morphology on cleavage-crack extension, May, 202

S-T

Saisse, H.: see Coulon, A., Knosp, B., and Saisse, H.

Schmieder, A. K.: Effect of misalignment on the time to rupture, July, 292

Seher, C. C.: Development program for radiation contrast baggage inspection system, May, 217

Sellars, C. M.

see Beynon, J. H. and Sellars, C. M.

see also Plaut, R. L. and Sellars, C. M.

Shaw, B. J.: Design and use of load monitoring environmental test chamber for stress corrosion testing, Nov., 416

Shepic, J. A.: see Tobler, R. L. and Shepic, J. A.

Shimizu, H. and Gibbon, M. W.: Instrumented impact testing of steel plate, March, 169

Sides, A., Uzan, J., and Perl, M.: Comprehensive viscoelasto-plastic characterization of sand-asphalt compressive and tensile cyclic loading, Jan., 49

Silcher, H.: see Eisele, U., Roos, E., Silcher, H., and Zimmermann, C.

Smith, R. W.: see Ghoresly, M., Mackay, W. B. F., and Smith, R. W.

Spangler, G. E., Carrico, J. P., and Campbell, D. N.: Recent advances in ion mobility spectrometry for explosives vapor detection, May, 234

Steinkamp, W.: see Drefahl, K., Kleinau, M., and Steinkamp, W.

Takahashi, H.: see Hashida, T. and Takahashi, H.

Tobler, R. L. and Shepic, J. A.: Design and performance of a ring-shaped clip gage for fracture mechanics testing, July, 299

Townsend, H. E.: see Berke, N. S. and Townsend, H. E.

U-Z

Urbanik, T. J.:

Deckboard bending theory for three-stringer wood pallets in drive-in racks, Jan., 3

Method for determining the effect of fasteners on the stiffness and strength of wood drive-in-rack pallets, Sept., 379

Uzan, J.: see Sides, A., Uzan, J., and Perl, M.

Vaessen, H. A. M. G.: see Havelaar, A. H., van Breemen, L. W. C. A., Vaessen, H. A. M. G., During, M., van der List, C., and van Erne, E. H. W.

van Breemen, L. W. C. A.: see Havelaar, A. H., van Breemen, L. W. C. A., Vaessen, H. A. M. G., During, M., van der List, C., and van Erne, E. H. W.

van der List, C.: see Havelaar, A. H., van Breemen, L. W. C. A., Vaessen, H. A. M. G., During, M., van der List, C., and van Erne, E. H. W.

van Erne, E. H.: see Havelaar, A. H., van Breemen, L. W. C. A., Vaessen, H. A. M. G., During, M., van der List, C., and van Erne, E. H. W.

Veale, R. C.: see Polvani, R. S., Reeve, C. P., and Veale, R. C.

White, J. A., Jr.: see Abrams, M. S., D'Souza, M. V., Higginson, P., Metes, W. S., Quintiere, J. G., Parker, W. J., Robins, R. F., and White, J. A., Jr.

Wilson, A. D.: see Lazaridis, N. A., Heberling, T. G., Harris, E. S., Lange, E. A., and Wilson, A. D.

Wolfenden, A.: see Harmouche, M. R. and Wolfenden, A.

Zimmermann, C.: see Eisele, U., Roos, E., Silcher, H., and Zimmermann, C.