

Journal of Testing and Evaluation

Subject Index to Volume 21

1993

A

Abrasion resistance

Compressibility analysis of wet abraded woven fabrics (Ukponmwan), July, 312

Effect of wet abrasive wear on the tensile properties of cotton and polyester-cotton fabrics (Ukponmwan), Jan., 84

Absorbed energy

Introduction of new dynamic fracture toughness evaluation system (Kobayashi, Yamamoto, and Niinomi), May, 145

Accelerated testing

ASCOR test: a simple automated method for stress corrosion testing of aluminum alloys (Schra and Groep), Jan., 44

Accelerator abrasion tester

Effect of wet abrasive wear on the tensile properties of cotton and polyester-cotton fabrics (Ukponmwan), Jan., 84

Accuracy

Introduction to workshop on accuracy of load and strain measurement of testing machines (Perlov), Nov., 504

What's new in traceability (Garner and Raspberry), Nov., 505

Acoustic impact technique

Characterization of defects in graphite fiber based composite structures using the acoustic impact technique (AIT) (Rajun, Patel, and Vaidya), Sept., 377

Adhesion

Determining paint adhesion to wood using a uniform double-cantilever beam technique (Knaebe and Williams), July, 272

Adhesives

Contoured wood double cantilever beam specimen for adhesive joint fracture tests (River and Okkonen), Jan., 21

Aggregate source

Effect of moisture on laboratory-prepared asphalt mixtures (Akili), Jan., 73

Allowable stress diagrams

Mean stress diagrams for composites generated using a modified up-and-down test methodology: Part I—Extensive preliminary data (Little), Sept., 366

Alumina

Techniques for the determination of the static and dynamic internal friction coefficients of ceramic powder (Martinez, Cortés, Sánchez-Gálvez, and Navarro), Nov., 494

Aluminum alloys

ASCOR test: a simple automated method for stress corrosion testing of aluminum alloys (Schra and Groep), Jan., 44

Testing the superplastic flow characteristics of advanced aluminum alloys (Goforth and Srinivasan), Jan., 36

Analog-to-digital converter

Automated data acquisition and load and strain measurement resolution (Lehman), Nov., 510

API X70 steel

Initiation and stable crack growth behavior of API X70 steel at low temperatures ($25^{\circ}\text{C} \geq T \geq -95^{\circ}\text{C}$) (Romilly), July, 239

Armor

Novel method for imaging the damage pattern in laminated plastic materials subjected to ballistic impact (Sivakumar, Ramakrishna, Ramanjaneyulu, and Balakrishna Bhat), July, 280

Asbestos

Asbestos-free gasket materials for turbines (Jones and Seth), Jan., 94

Asphalt concrete

Analysis of Marshall test behavior with triaxial test determined material properties (Low, Tan, and Fwa), May, 192

Asphalt mixtures

Compaction of asphalt mixtures for laboratory testing: evaluation based on density profile (Fwa, Low, and Tan), Sept., 414

Attrition test

Laboratory testing procedure for evaluation of moving bed catalyst attrition (Doolin, Gainer, and Hoffman), Nov., 481

Automatic control

Design of a control system for a superimposed frequency fatigue test machine (Stoten and Smith), May, 154

B

Bacillus thuringiensis var. *kurstaki*

Formulation and application technologies for microbial pesticides: review of progress and future trends (Cibulsky, Devisetty, Melchior, and Melin), Nov., 500

Back face strain

Monitoring fatigue crack propagation in compact tension specimens via remote sensing of back face strain (Simha, Hande, and Arora), Jan., 3

Bacterial survival

Effects of wash temperature on bacterial survival and strength retention of cotton fabrics (Perenich and Moore), May, 211

Beryllium-copper alloys

Fatigue and corrosion fatigue of beryllium-copper spring materials (Bagheri and Miller), March, 101

Beverage containers

Effect of internal gas pressure on the compression strength of beverage cans and plastic bottles (Singh and Burgess), March, 129

Bituminous concrete

Flow and stability limits for six-inch-diameter Marshall specimens (Newton, Turner, and Schmidt), March, 114

Bituminous mixtures

Effect of moisture on laboratory-prepared asphalt mixtures (Akili), Jan., 73

Book reviews

Advanced Technologies in Failure Prevention: Proceedings of the 43rd Meeting of the Mechanical Failures Prevention Group by Shives (Scott and Riga), Jan., 97

ANSI/ASQC Q900/ISO 9000 Guidelines for Use by the Chemical and Process Industries (Belfit), March, 139

Electrochemical and Optical Techniques for the Study and Monitoring of Metallic Corrosion by Ferreira and Melendres (Burnell) March, 140

Fracture Mechanics: Fundamentals and Applications by Anderson (Shehata), Nov., 539

The Govmark Book on Flammability Standards and Flammability Test Methods of Textiles, Plastics and Other Materials Used in Home and Contract Furnishings, Book I, Analyses of Codes (Third Edition) by Messina (Hirschler), July, 326

Inspection Errors for Attributes in Quality Control by Johnson et al. (Riga and Scott), Jan., 97

Modern Ceramic Engineering: Properties, Processing, and Use in Design, Second Edition by Richerson (Eppler), Nov., 540

Quality in America: How to Implement a Competitive Quality Program by Hunt (Riga), Nov., 539

Brass wire

Discussion on "characterization of early and modern wire for an Italian harpsichord" by J. H. Underwood et al. (Goodway), March, 136

British standards

Dynamic testing of the strength of helmet chin straps (Gilchrist and Mills), Nov., 488

Building assemblies

Resonance monitoring of building assemblies for durability tests (Hearn and Testa), July, 285

C

Calculation

Calculation for rolling contact fatigue life and strength of case-hardened gear materials by computer (Jiang, Zheng, and Wang), Jan., 9

Calibration

Calibration techniques for extensometry: possible standards of strain measurement (Watson), Nov., 515

Density measurement of cylindrical specimens within a mold by gamma-rays (Tan and Fwa), July, 296

Carbonation

Effect of internal gas pressure on the compression strength of beverage cans and plastic bottles (Singh and Burgess), March, 129

Case-hardened gear materials

Calculation for rolling contact fatigue life and strength of case-hardened gear materials by computer (Jiang, Zheng, and Wang), Jan., 9

Catalyst attrition

Laboratory testing procedure for evaluation of moving bed catalyst attrition (Doolin, Gainer, and Hoffman), Nov., 481

Catalyst particles

Laboratory testing procedure for evaluation of moving bed catalyst attrition (Doolin, Gainer, and Hoffman), Nov., 481

Ceramic powder

Techniques for the determination of the static and dynamic internal friction coefficients of ceramic powder (Martínez, Cortés, Sánchez-Gálvez, and Navarro), Nov., 494

Characterization

Characterization of hypervelocity impact debris: Naval Research Laboratory tests (Fortson and Winter), Sept., 438

Charpy impact

Embrittlement of an AISI 8640 lower bainite steel (Rinnovatore, Lukens, Reinhold, and Mahon), Sept., 329

Chemical compatibility

Enhancing thermal hazard awareness with compatibility charts (Gay and Leggett), Nov., 470

Chin strap failure

Dynamic testing of the strength of helmet chin straps (Gilchrist and Mills), Nov., 488

Closed-loop response

Design of a control system for a superimposed frequency fatigue test machine (Stoten and Smith), May, 154

Compact tension

Monitoring fatigue crack propagation in compact tension specimens via remote sensing of back face strain (Simha, Hande, and Arora), Jan., 3

Compaction methods

Compaction of asphalt mixtures for laboratory testing: evaluation based on density profile (Fwa, Low, and Tan), Sept., 414

Composite materials

Metallized microballoon filled composite EMI shielding materials (Radford and Cheng), Sept., 396

Novel method for imaging the damage pattern in laminated plastic materials subjected to ballistic impact (Sivakumar, Ramakrishna, Ramanjaneyulu, and Balakrishna Bhat), July, 280

Compressibility

Compressibility analysis of wet abraded woven fabrics (Ukponnwan), July, 312

Compressive strength

Effect of internal gas pressure on the compression strength of beverage cans and plastic bottles (Singh and Burgess), March, 129

Condoms

Cutting apparatus to aid in the preparation of ring specimens for tensile testing of latex condoms and other thin elastic films (Lennon and Srisamang), July, 309

Sensitivity of water leak tests for latex condoms (Herman, Carey, and Rinaldi), March, 124

Constant load

ASCOR test: a simple automated method for stress corrosion testing of aluminum alloys (Schra and Groep), Jan., 44

Contact stress

Evaluation of static and dynamic contact stresses in simulated granular particles using strain gages (Xu and Shukla), May, 178

Contoured double cantilever beam (CDCB)

Contoured wood double cantilever beam specimen for adhesive joint fracture tests (Rüger and Okkonen), Jan., 21

Control concept and algorithm

Advanced control concept and algorithm for long-term data acquisition in high-temperature fracture mechanics tests (Liu and Dogan), Sept., 351

Corrosion fatigue

Fatigue and corrosion fatigue of beryllium-copper spring materials (Bagheri and Miller), March, 101

Corrugated containers

More rapid edgewise crush test methods (Urbanik, Catlin, Friedman, and Lund), Jan., 62

Crack extension

Maximum-load predictions in the Dugdale model using a critical CTOA criterion (Gu), Nov., 461

Crack growth rate

Minimization and quantification of error associated with the K gradient and the interval of crack length measurement in fatigue crack growth testing (Oore), March, 101

Crack-tip opening displacement

Initiation and stable crack growth behavior of API X70 steel at low temperatures ($25^{\circ}\text{C} \geq T \geq -95^{\circ}\text{C}$) (Romilly), July, 239

J and CTOD estimation equations for shallow cracks in single edge notch bend specimens (Kirk and Dodds), July, 228

Crimp strain

Mechanical extensometer for high-temperature tensile testing of ceramics (Liu and Ding), Sept., 406

Cutting device

Cutting apparatus to aid in the preparation of ring specimens for tensile testing of latex condoms and other thin elastic films (Lennon and Srisamang), July, 309

Cyclic loading

Fatigue and corrosion fatigue of beryllium-copper spring materials (Bagheri and Miller), March, 101

Cylindrical molds

Density measurement of cylindrical specimens within a mold by gamma-rays (Tan and Fwa), July, 296

Cylindrical specimens

Density measurement of cylindrical specimens within a mold by gamma-rays (Tan and Fwa), July, 296

D**Data acquisition**

Advanced control concept and algorithm for long-term data acquisition in high-temperature fracture mechanics tests (Liu and Dogan), Sept., 351

Automated data acquisition and load and strain measurement resolution (Lehman), Nov., 510

Database management

Static structural integrity monitoring system (Mo), Sept., 453

Debris

Characterization of hypervelocity impact debris: Naval Research Laboratory tests (Fortson and Winter), Sept., 438

Defect characterization

Characterization of defects in graphite fiber based composite structures using the acoustic impact technique (AIT) (Rajun, Patel, and Vaidya), Sept., 377

Density measurement

Compaction of asphalt mixtures for laboratory testing: evaluation based on density profile (Fwa, Low, and Tan), Sept., 414

Design considerations

Future of water treatment (Puckorius), March, 118

Detection method

Detection method of fatigue crack initiation by analyzing strain waveform (Makabe, Nishida, and Kaneshiro), Sept., 339

Detergents

Effects of wash temperature on bacterial survival and strength retention of cotton fabrics (Perenich and Moore), May, 211

Diffusion

Improved moisture permeability measurement method (Douglas, Kuehn, and Ramsey), July, 302

DiPel²

Formulation and application technologies for microbial pesticides: review of progress and future trends (Cibulsky, Devisetty, Melchior, and Melin), Nov., 500

Displacement

Calibration techniques for extensometry: possible standards of strain measurement (Watson), Nov., 515

Dry cup method

Infrared technique as a research tool for measuring water vapor transmission of roofing membranes (Dutt, Lavallée, and Ashton), May, 199

Dugdale model

Maximum-load predictions in the Dugdale model using a critical CTOA criterion (Gu), Nov., 461

Durability

Resonance monitoring of building assemblies for durability tests (Hearn and Testa), July, 285

Dynamic strength test

Dynamic testing of the strength of helmet chin straps (Gilchrist and Mills), Nov., 488

E**Elastic constants**

Assessment of the piezoelectric ultrasonic composite oscillator technique (PUCOT) for measuring the elastic and technical constants of solids (Wolfenden and Harmouche), Nov., 470

Elastic-plastic fracture

Initiation and stable crack growth behavior of API X70 steel at low temperatures ($25^{\circ}\text{C} \geq T \geq -95^{\circ}\text{C}$) (Romilly), July, 239

Maximum-load predictions in the Dugdale model using a critical CTOA criterion (Gu), Nov., 461

Elasticity

Assessment of the piezoelectric ultrasonic composite oscillator technique (PUCOT) for measuring the elastic and technical constants of solids (Wolfenden and Harmouche), Nov., 470

Electromagnetic interference

Metallized microballoon filled composite EMI shielding materials (Radford and Cheng), Sept., 396

Electrostatic discharge (ESD)

Use of a proposed test procedure for quantifying the triboelectric charging propensity of packaging films (Hall, Singh, and Burgess), Jan., 57

Embedded crack

Slice synthesis technique for an embedded crack in residual stress fields (Nishimura), July, 256

Embrittlement

Embrittlement of an AISI 8640 lower bainite steel (Rinnovatore, Lukens, Reinhold, and Mahon), Sept., 329

Endurance limit estimation

Up-and-down methodology applied to statistically planned experiments (Little and Thomas), Jan., 14

Engineering crack size

Detection method of fatigue crack initiation by analyzing strain waveform (Makabe, Nishida, and Kaneshiro), Sept., 339

Environmental chambers

Fiber optic chemical sensor for measurement of groundwater pH (Maher and Shahriari), Sept., 448

Experimental methods

Accurate and precise fabrication of Iosipescu shear test specimens (Blacketter and Odom), July, 322

Extensometer

Calibration techniques for extensometry: possible standards of strain measurement (Watson), Nov., 515

Mechanical extensometer for high-temperature tensile testing of ceramics (Liu and Ding), Sept., 406

F

Fatigue

Axial-torsional fatigue: a study of tubular specimen thickness effects (Bonacuse and Kalluri), May, 160

Fatigue crack initiation in nonferrous materials: a model assessment (Azimi and Miller), July, 221

Mean stress diagrams for composites generated using a modified up-and-down test methodology: Part I—Extensive preliminary data (Little), Sept., 366

Fatigue crack detection

Gel electrode revisited: fatigue crack detection with a polymer film (Baxter), May, 169

Fatigue crack growth

Minimization and quantification of error associated with the K gradient and the interval of crack length measurement in fatigue crack growth testing (Oore), March, 101

Fatigue crack initiation

Detection method of fatigue crack initiation by analyzing strain waveform (Makabe, Nishida, and Kaneshiro), Sept., 339

Fatigue crack initiation in nonferrous materials: a model assessment (Azimi and Miller), July, 221

Fatigue crack propagation

Monitoring fatigue crack propagation in compact tension specimens via remote sensing

of back face strain (Simha, Hande, and Arora), Jan., 3

Fatigue limit estimation

Up-and-down methodology applied to statistically planned experiments (Little and Thomas), Jan., 14

Fiber optic chemical sensor

Fiber optic chemical sensor for measurement of groundwater pH (Maher and Shahriari), Sept., 448

Flaws

Lifetime predictions of uPVC pipes from short time tests (Seldén and Gradin), Sept., 402

Flex resistance

Vibration-flex test method to determine the susceptibility of plastic films to pinhole formation due to flexing (Varughese and Gyeszly), May, 188

Flexible graphite

Asbestos-free gasket materials for turbines (Jones and Seth), Jan., 94

Flexural testing

Use of robotics to eliminate testing variability in the evaluation of polymeric matrix composites subjected to three-point flexure (Croman and Jefferis), Nov., 522

Flexural yield strength

Quality assessment tests for nails (Chiang and Chu), Jan., 51

Flow

Flow and stability limits for six-inch-diameter Marshall specimens (Newton, Turner, and Schmidt), March, 114

Formulation

Formulation and application technologies for microbial pesticides: review of progress and future trends (Cibulsky, Devisetty, Melchior, and Melin), Nov., 500

Fracture mechanics tests

Advanced control concept and algorithm for long-term data acquisition in high-temperature fracture mechanics tests (Lin and Dogan), Sept., 351

Fracture toughness

Contoured wood double cantilever beam specimen for adhesive joint fracture tests (River and Okkonen), Jan., 21

Determining paint adhesion to wood using a uniform double-cantilever beam technique (Knaebe and Williams), July, 272

Embrittlement of an AISI 8640 lower bainite steel (Rinnovatore, Lukens, Reinhold, and Mahon), Sept., 329

Introduction of new dynamic fracture toughness evaluation system (Kobayashi, Yamamoto, and Niinomi), May, 145

J and CTOD estimation equations for shallow cracks in single edge notch bend specimens (Kirk and Dodds), July, 228

Some microstructural conditions for evaluating fracture toughness and R -curve behavior in platelet-reinforced composites (Pezzotti, Niihara, and Nishida), Sept., 358

G

Gamma-ray density gage

Density measurement of cylindrical specimens within a mold by gamma-rays (Tan and Fwa), July, 296

Gel electrode imaging

Gel electrode revisited: fatigue crack detection with a polymer film (Baxter), May, 169

Graphical user interface

Static structural integrity monitoring system (Mo), Sept., 453

Graphite fiber composites

Characterization of defects in graphite fiber based composite structures using the acoustic impact technique (AIT) (Rajun, Patel, and Vaidya), Sept., 377

Groundwater monitoring

Fiber optic chemical sensor for measurement of groundwater pH (Maher and Shahriari), Sept., 448

H

Hardness

Discussion on "characterization of early and modern wire for an Italian harpsichord" by J. H. Underwood et al. (Goodway), March, 136

Harpsichord

Discussion on "characterization of early and modern wire for an Italian harpsichord" by J. H. Underwood et al. (Goodway), March, 136

Helmets

Dynamic testing of the strength of helmet chin straps (Gilchrist and Mills), Nov., 488

Hydraulic machines

Design of a control system for a superimposed frequency fatigue test machine (Stoten and Smith), May, 154

Hypervelocity impact

Characterization of hypervelocity impact debris: Naval Research Laboratory tests (Fortson and Winter), Sept., 438

I

Impact bend angle

Quality assessment tests for nails (Chiang and Chu), Jan., 51

In-phase

Axial-torsional fatigue: a study of tubular specimen thickness effects (Bonacuse and Kalluri), May, 160

Infiltration radiography

Novel method for imaging the damage pattern in laminated plastic materials subjected to ballistic impact (Sivakumar, Ramakrishna, Ramanjaneyulu, and Balakrishna Bhat), July, 280

Infrared sensor

Infrared technique as a research tool for measuring water vapor transmission of roofing membranes (Dutt, Lavallée, and Ashton), May, 199

Instrumented Charpy impact test

Introduction of new dynamic fracture toughness evaluation system (Kobayashi, Yamamoto, and Niinomi), May, 145

Inter-reactivity

Enhancing thermal hazard awareness with compatibility charts (Gay and Leggett), Nov., 470

Interlaboratory testing

Outliers in interlaboratory testing (Mandel), March, 132

Internal friction

Techniques for the determination of the static and dynamic internal friction coefficients of ceramic powder (Martínez, Cortés, Sánchez-Gálvez, and Navarro), Nov., 494

Internal pressure

Effect of internal gas pressure on the

compression strength of beverage cans and plastic bottles (Singh and Burgess), March, 129

Iosipescu shear test

Accurate and precise fabrication of Iosipescu shear test specimens (Blackletter and Odom), July, 322

J-K

J-integral

Initiation and stable crack growth behavior of API X70 steel at low temperatures ($25^{\circ}\text{C} \geq T \geq -95^{\circ}\text{C}$) (Romilly), July, 239

Jacket effects

Pressure and flexible membrane effects on direct-contact extensometer measurements in axisymmetric compression tests (Mellegard, Pfeifle, Fossum, and Senseny), Nov., 530

Jet fuel thermal oxidation test

Analysis of jet fuel thermal oxidation deposits by spectral fluorometric technique (Brice), Sept., 422

Jet fuels

Analysis of jet fuel thermal oxidation deposits by spectral fluorometric technique (Brice), Sept., 422

K gradient

Minimization and quantification of error associated with the K gradient and the interval of crack length measurement in fatigue crack growth testing (Oore), March, 101

L

Laser-induced spectral fluorometry

Analysis of jet fuel thermal oxidation deposits by spectral fluorometric technique (Brice), Sept., 422

Latex

Cutting apparatus to aid in the preparation of ring specimens for tensile testing of latex condoms and other thin elastic films (Lennon and Srisumang), July, 309

Sensitivity of water leak tests for latex condoms (Herman, Carey, and Rinaldi), March, 124

Laundering temperature

Effects of wash temperature on bacterial survival and strength retention of cotton fabrics (Perenich and Moore), May, 211

Leakage tests

Sensitivity of water leak tests for latex condoms (Herman, Carey, and Rinaldi), March, 124

Life expectancy

Future of water treatment (Puckorius), March, 118

Lifetime prediction

Influence of substrate deformations on the thermal fatigue life of SMT solder joints (Zafran and Sendor), Sept., 346

Lifetime predictions of uPVC pipes from short time tests (Seldén and Gradin), Sept., 402

Load

Introduction to workshop on accuracy of load and strain measurement of testing machines (Perlov), Nov., 504

Novel stage for ultrasonic measurement of real contact area between rough and flat parts under quasi-static load (Polijaniuk and Kaczmarek), May, 174

Load monitoring

Static structural integrity monitoring system (Mo), Sept., 453

M

Major-minor cycling

Design of a control system for a superimposed frequency fatigue test machine (Stotten and Smith), May, 154

Marshall test

Analysis of Marshall test behavior with triaxial test determined material properties (Low, Tan, and Fwa), May, 192

Flow and stability limits for six-inch-diameter Marshall specimens (Newton, Turner, and Schmidt), March, 114

Mass transfer

Improved moisture permeability measurement method (Douglas, Kuehn, and Ramsey), July, 302

Minimum load

Minimum-load predictions in the Dugdale model using a critical CTOA criterion (Gu), Nov., 461

Moist load

Monitoring fatigue crack propagation in compact tension specimens via remote sensing of back face strain (Simha, Hande, and Asora), Jan., 3

Moist stress diagrams

Moist stress diagrams for composites generated using a modified up-and-down test methodology: Part I—Extensive preliminary data (Little), Sept., 366

Measurement

Improved moisture permeability measurement method (Douglas, Kuehn, and Ramsey), July, 302

Measurement comparisons

What's new in traceability (Garner and Raspberry), Nov., 505

Minimizing properties

Optimization of test parameters for quantitative stress measurements using the miniaturized disk-bend test (Meyers, Chen, Zhang, and Ardell), July, 263

Miles

Performance of hybrid reinforcements in PVC composites: Part I—Use of surface-modified mica and wood pulp as reinforcements (Maldas and Kokta), Jan., 68

Microballoons

Metalized microballoon filled composite EMI shielding materials (Radford and Cheng), Sept., 396

Microbial pesticides

Formulation and application technologies for microbial pesticides: review of progress and future trends (Cibulsky, Devisetty, Melchior, and Melin), Nov., 500

Miniaturized disk-bend test

Optimization of test parameters for quantitative stress measurements using the miniaturized disk-bend test (Meyers, Chen, Zhang, and Ardell), July, 263

Moisture

Effect of moisture on laboratory-prepared asphalt mixtures (Akili), Jan., 73

Improved moisture permeability measurement method (Douglas, Kuehn, and Ramsey), July, 302

Multiaxial

Axial-torsional fatigue: a study of tubular

specimen thickness effects (Bonacuse and Kalluri), May, 160

N-O

Nails

Quality assessment tests for nails (Chiang and Chu), Jan., 51

Nondestructive evaluation

Characterization of defects in graphite fiber based composite structures using the acoustic impact technique (AIT) (Rajun, Patel, and Vaidya), Sept., 377

Nondestructive inspection

Gel electrode revisited: fatigue crack detection with a polymer film (Baxter), May, 169

Nonferrous materials

Fatigue crack initiation in nonferrous materials: a model assessment (Azimi and Miller), July, 221

Outliers

Outliers in interlaboratory testing (Mandel), March, 132

Out-of-phase

Axial-torsional fatigue: a study of tubular specimen thickness effects (Bonacuse and Kalluri), May, 160

P

Packaging compression

More rapid edgewise crush test methods (Urbanik, Catlin, Friedman, and Lund), Jan., 62

Packaging films

Use of a proposed test procedure for quantifying the triboelectric charging propensity of packaging films (Hall, Singh, and Burgess), Jan., 57

Paint

Determining paint adhesion to wood using a uniform double-cantilever beam technique (Knaebe and Williams), July, 272

Paper testing

More rapid edgewise crush test methods (Urbanik, Catlin, Friedman, and Lund), Jan., 62

Penetration

Novel method for imaging the damage pattern in laminated plastic materials subjected to ballistic impact (Sivakumar, Ramakrishna, Ramanjaneyulu, and Balakrishna Bhat), July, 280

Permeance

Infrared technique as a research tool for measuring water vapor transmission of roofing membranes (Dutt, Lavallée, and Ashton) May, 199

pH sensor

Fiber optic chemical sensor for measurement of groundwater pH (Maher and Shahriari), Sept., 448

Photoelasticity

Evaluation of static and dynamic contact stresses in simulated granular particles using strain gages (Xu and Shukla), May, 178

Piezoelectric ultrasonic composite oscillator technique

Assessment of the piezoelectric ultrasonic composite oscillator technique (PUCOT) for measuring the elastic and technical constants of solids (Wolfenden and Har-mouche), Nov., 470

Plastic films

Vibration-flex test method to determine the susceptibility of plastic films to pinhole formation due to flexing (Varughese and Gyeszly), May, 188

Plastic piles

Lifetime predictions of uPVC pipes from short time tests (Seldén and Gradin), Sept., 402

Plasticity model

Analysis of Marshall test behavior with triaxial test determined material properties (Low, Tan, and Fwa), May, 192

Platelet composites

Some microstructural conditions for evaluating fracture toughness and *R*-curve behavior in platelet-reinforced composites (Pezzotti, Niihara, and Nishida), Sept., 358

Polymeric composites

Use of robotics to eliminate testing variability in the evaluation of polymeric matrix composites subjected to three-point flexure (Croman and Jeferis), Nov., 522

Pressure effects

Pressure and flexible membrane effects on direct-contact extensometer measurements in axisymmetric compression tests (Mellegard, Pfeifle, Fossum, and Senseny), Nov., 530

PVC

Performance of hybrid reinforcements in PVC composites: Part I—Use of surface-modified mica and wood pulp as reinforcements (Maldas and Kokta), Jan., 68

R**Reactive chemicals**

Enhancing thermal hazard awareness with compatibility charts (Gay and Leggett), Nov., 470

Real contact area (RCA)

Novel stage for ultrasonic measurement of real contact area between rough and flat parts under quasi-static load (Poljaniuk and Kaczmarek), May, 174

Rejection

Outliers in interlaboratory testing (Mandel), March, 132

Repeatability

Outliers in interlaboratory testing (Mandel), March, 132

Reproducibility

Outliers in interlaboratory testing (Mandel), March, 132

Residual stress

Slice synthesis technique for an embedded crack in residual stress fields (Nishimura), July, 256

Resolution

Automated data acquisition and load and strain measurement resolution (Lehman), Nov., 510

Resonance testing

Resonance monitoring of building assemblies for durability tests (Hearn and Testa), July, 285

Robotic testing

Use of robotics to eliminate testing variability in the evaluation of polymeric matrix composites subjected to three-point flexure (Croman and Jeferis), Nov., 522

Rolling contact fatigue life and strength

Calculation for rolling contact fatigue life and strength of case-hardened gear materials

by computer (Jiang, Zheng, and Wang), Jan., 9

S**Safety**

Enhancing thermal hazard awareness with compatibility charts (Gay and Leggett), Nov., 470

Sheet gaskets

Asbestos-free gasket materials for turbines (Jones and Seth), Jan., 94

Silicon carbide

Some microstructural conditions for evaluating fracture toughness and *R*-curve behavior in platelet-reinforced composites (Pezzotti, Niihara, and Nishida), Sept., 358

Techniques for the determination of the static and dynamic internal friction coefficients of ceramic powder (Martinez, Cortés, Sánchez-Gálvez, and Navarro), Nov., 494

Silicon nitride

Some microstructural conditions for evaluating fracture toughness and *R*-curve behavior in platelet-reinforced composites (Pezzotti, Niihara, and Nishida), Sept., 358

Single-edge notch bend specimens

J and CTOD estimation equations for shallow cracks in single edge notch bend specimens (Kirk and Dodds), July, 228

Small sample up-and-down tests

Up-and-down methodology applied to statistically planned experiments (Little and Thomas), Jan., 14

Solder joints

Influence of substrate deformations on the thermal fatigue life of SMT solder joints (Zafran and Sandor), Sept., 346

Specimen fabrication

Accurate and precise fabrication of Iosipescu shear test specimens (Blackketter and Odom), July, 322

Split-plot designs

Up-and-down methodology applied to statistically planned experiments (Little and Thomas), Jan., 14

Spring materials

Fatigue and corrosion fatigue of beryllium-copper spring materials (Bagheri and Miller), March, 101

Stability

Flow and stability limits for six-inch-diameter Marshall specimens (Newton, Turner, and Schmidt), March, 114

Static charge

Use of a proposed test procedure for quantifying the triboelectric charging propensity of packaging films (Hall, Singh, and Burgess), Jan., 57

Statistics

Characterization of hypervelocity impact debris: Naval Research Laboratory tests (Fortson and Winter), Sept., 438

Strain

Calibration techniques for extensometry: possible standards of strain measurement (Watson), Nov., 515

Introduction to workshop on accuracy of load and strain measurement of testing machines (Perlov), Nov., 504

Strain gage

Evaluation of static and dynamic contact stresses in simulated granular particles using strain gages (Xu and Shukla), May, 178

Strain interference method

Detection method of fatigue crack initiation by analyzing strain waveform (Makabe, Nishida, and Kaneshiro), Sept., 339

Strain measurement

Mechanical extensometer for high-temperature tensile testing of ceramics (Liu and Ding), Sept., 406

Strain rate sensitivity

Testing the superplastic flow characteristics of advanced aluminum alloys (Goforth and Srinivasan), Jan., 36

Stress corrosion

ASCOR test: a simple automated method for stress corrosion testing of aluminum alloys (Schra and Groep), Jan., 44

Stress intensity factor

Minimization and quantification of error associated with the *K* gradient and the interval of crack length measurement in fatigue crack growth testing (Oore), March, 101

Slice synthesis technique for an embedded crack in residual stress fields (Nishimura), July, 256

Stress wave

Evaluation of static and dynamic contact stresses in simulated granular particles using strain gages (Xu and Shukla), May, 178

Structural integrity

Static structural integrity monitoring system (Mo), Sept., 453

Substrate deformations

Influence of substrate deformations on the thermal fatigue life of SMT solder joints (Zafran and Sandor), Sept., 346

Superplastic deformation

Testing the superplastic flow characteristics of advanced aluminum alloys (Goforth and Srinivasan), Jan., 36

Surface mount technology

Influence of substrate deformations on the thermal fatigue life of SMT solder joints (Zafran and Sandor), Sept., 346

T**Technological surface layer**

Novel stage for ultrasonic measurement of real contact area between rough and flat parts under quasi-static load (Poljaniuk and Kaczmarek), May, 174

Tensile properties

Effect of wet abrasive wear on the tensile properties of cotton and polyester-cotton fabrics (Ukponmwan), Jan., 84

Tensile strength

Discussion on "characterization of early and modern wire for an Italian harpsichord" by J. H. Underwood et al. (Goodway), March, 136

Tension testing

Cutting apparatus to aid in the preparation of ring specimens for tensile testing of latex condoms and other thin elastic films (Lennon and Srisamang), July, 309

Mechanical extensometer for high-temperature tensile testing of ceramics (Liu and Ding), Sept., 406

Thermoplastic composites

Performance of hybrid reinforcements in PVC composites: Part I—Use of surface-modified mica and wood pulp as reinforcements (Maldas and Kokta), Jan., 68

Traceability

What's new in traceability (Garner and Rasberry), Nov., 505

Transition temperature

Embrittlement of an AISI 8640 lower bainite steel (Rinnovaipre, Lukens, Reinhold, and Mahon), Sept., 329

Triaxial compression

Pressure and flexible membrane effects on direct-contact extensometer measurements in axisymmetric compression tests (Mellegard, Pfeifle, Fossum, and Sensen), Nov., 530

Triaxial test

Analysis of Marshall test behavior with triaxial test determined material properties (Low, Tan, and Fwa), May, 192

Triboelectric charging

Use of a proposed test procedure for quantifying the triboelectric charging propensity of packaging films (Hall, Singh, and Burgess), Jan., 57

Tubular specimens

Axial-torsional fatigue: a study of tubular specimen thickness effects (Bonacuse and Kalluri), May, 160

Turbines

Asbestos-free gasket materials for turbines (Jones and Seth), Jan., 94

U-V**Ultrasonic measurement**

Novel stage for ultrasonic measurement of real contact area between rough and flat parts under quasi-static load (Polijaniuk and Kaczmarek), May, 174

Ultrasonic NDE

Time-domain ultrasonic NDE of the wave velocity of a sub-half-wavelength elastic layer (Kinra and Zhu), Jan., 29

Uniaxial strain

Pressure and flexible membrane effects on direct-contact extensometer measurements in axisymmetric compression tests (Mellegard, Pfeifle, Fossum, and Sensen), Nov., 530

Uniform double-cantilever beam

Determining paint adhesion to wood using a uniform double-cantilever beam technique (Kanebe and Williams), July, 272

Unplasticized polyvinyl chloride

Lifetime predictions of uPVC pipes from short time tests (Seldén and Gradin), Sept., 402

Vibration

Vibration-flex test method to determine the susceptibility of plastic films to pinhole formation due to flexing (Varughese and Gyeczly), May, 188

Vickers hardness

Quality assessment tests for nails (Chiang and Chu), Jan., 51

W**Water management**

Future of water treatment (Puckorius), March, 118

Water quality

Future of water treatment (Puckorius), March, 118

Water vapor transmission

Infrared technique as a research tool for measuring water vapor transmission of roofing membranes (Dugg, Lavallée, and Ashton), May, 199

Wavelength

Time-domain ultrasonic NDE of the wave velocity of a sub-half-wavelength elastic layer (Kinra and Zhu), Jan., 29

Wave speed

Time-domain ultrasonic NDE of the wave

velocity of a sub-half-wavelength elastic layer (Kinra and Zhu), Jan., 29

Wave velocity

Time-domain ultrasonic NDE of the wave velocity of a sub-half-wavelength elastic layer (Kinra and Zhu), Jan., 29

Wood

Contoured wood double cantilever beam specimen for adhesive joint fracture tests (River and Okkonen), Jan., 21

Wood fiber

Performance of hybrid reinforcements in PVC composites: Part I—Use of surface-modified mica and wood pulp as reinforcements (Maldas and Kokta), Jan., 68

Working stress diagrams

Mean stress diagrams for composites generated using a modified up-and-down test methodology: Part I—Extensive preliminary data (Little), Sept., 366

Woven fabrics

Effect of wet abrasive wear on the tensile properties of cotton and polyester-cotton fabrics (Ukponmwan), Jan., 84

Woven textile fabrics

Compressibility analysis of wet abraded woven fabrics (Ukponmwan), July, 312

Y**Yield stress**

Optimization of test parameters for quantitative stress measurements using the miniaturized disk-bend test (Meyers, Chen, Zhang, and Ardell), July, 263

Young's modulus

Assessment of the piezoelectric ultrasonic composite oscillator technique (PUCOT) for measuring the elastic and technical constants of solids (Wolfenden and Har-mouche), Nov., 470