

Journal of Testing and Evaluation

Author Index to Volume 18

1990

Number	Month of Issue	Pages
1	January	1-86
2	March	87-140
3	May	141-228
4	July	229-308
5	September	309-372
6	November	373-466

A-B

- Addassi, E: *see* Ragab, AR, Alawi, H and Addassi, E
- Al-Otaibi, K. M.: *see* Mahmood, S. T., Al-Otaibi, K. M., Jung, Y. H., and Murty, K. L.
- Alawi, H: *see* Ragab, AR, Alawi, H and Addassi, E
- Banerjee, G: *see* Das, SK, Ghosh, A, Das, PK and Banerjee, G
- Barker, L. M.: *see* Munz, D. and Barker, L. M.
- Bashu, SA:** Impact energy/specimen thickness relationship for two turbine steels, Sept., 363
- Baxter, WJ:** Imaging short fatigue cracks with the gel electrode, Nov., 430
- Berens, AP and Watanabe, RT:** Introduction to symposium on quantitative methods in the assessment of structural defects, Nov., 420
- Biron, A: *see* Bui-Quoc, Gomuc, R, Biron, A, Nguyen, HL and Tadros, RN
- Brinkley, JW: *see* Sulowski, AC and Brinkley, JW
- Bucci, RJ: *see* Magnusen, PE, Hinkle, AJ, Kaiser, WT, Bucci, RJ, and Rolf, RL
- Buck, O: *see* Rehbein, DK, Thompson, RB, and Buck, O
- Bui-Quoc, T, Gomuc, R, Biron, A, Nguyen, HL and Tadros, RN:** Cyclic stress-strain behavior and low cycle fatigue of Ti6242, May, 160

C-D

- Clark, T. R., Hertzberg, R. W., and Manson, J. A.:** Influence of test methodology on fatigue crack propagation in engineering plastics, Sept., 319
- Crosley, PB and Ripling, EJ:** A quality control test for selecting materials to arrest fast-running, full-thickness cracks, Nov., 396
- Dally, JW and Sanford, RJ:** Measuring the stress intensity factor for propagating cracks with strain gages, July, 240
- Das, PK: *see* Das, SK, Ghosh, A, Das, PK and Banerjee, G

- Das, SK: *see* Parida, N, Das, SK, Gope, PC, and Mohanty, ON
- Das, SK, Ghosh, A, Das, PK and Banerjee, G: An appraisal of hydration characteristics of dead burnt dolomite grains, Jan., 76
- Davis, G. B. and Schroeder, L. W.:** Influence of contact angles on the leakage of latex condoms, Sept., 352
- Davis, DC:** An approach to predicting long-term toughness, strength, and ductility of a Cr-Mo-V steel alloy using short-term tests, July, 286
- DuQuesnay, DL: *see* Pompetzki, MA, Topper, TH, DuQuesnay, DL and Yu, MT
- see* Yu, MT, DuQuesnay, DL and Topper, TH

E-G

- Ernst, HA: *see* Wert, MJ, Saxena, A and Ernst, HA
- Ghosh, A: *see* Das, SK, Ghosh, A, Das, PK and Banerjee, G
- Goddard, MJ: *see* Malaiyandi, M and Goddard, MJ
- Gomuc, R: *see* Bui-Quoc, Gomuc, R, Biron, A, Nguyen, HL and Tadros, RN
- Gope, PC: *see* Parida, N, Das, SK, Gope, PC, and Mohanty, ON
- Gordon, JR: *see* Smith, DJ and Gordon, JR
- Grabovac, I: *see* Wycherley, GW, Mestan, SA and Grabovac, I
- Groth, HL and Zenkert, D:** Fracture of defect foam core sandwich beams, Nov., 390

H-J

- Haggag, FM, Server, WL, Lucas, GE, Odette, GR and Shekherd, JW:** The use of miniaturized tests to predict flow properties and estimate fracture toughness in deformed steel plates, Jan., 62
- Hartwig, KT, Jr.: *see* Richards, GL and Hartwig, KT, Jr.
- Hellmann, JR: *see* Segall, AE, Hellmann, JR and Strzepa, P
- Hertzberg, RW: *see* Clark, T. R., Hertzberg, R. W., and Manson, J. A.
- Hinkle, AJ: *see* Magnusen, PE, Hinkle, AJ, Kaiser, WT, Bucci, RJ, and Rolf, RL
- Hirth, JP: *see* Manoharan, M, Hirth, JP and Rosenfield, AR
- Inukai, T: *see* Kimura, K, Inukai, T, Saito, K and Kashiwaya, H
- Jhansale, HR and McCann, DR:** Bore inspection and life evaluation of vintage steam turbine/generator rotors, Nov., 446
- Jiang, B. and Shao, E.:** A rapid method for measurement of rolling contact fatigue limit of case-hardened gear materials, Sept., 328
- Joyce, JA:** Characterization of the effects of

- large unloading cycles on the ductile tearing toughness of HSLA steel, Nov., 373
- Jung, Y.: *see* Mahmood, S. T., Al-Otaibi, K. M., Jung, Y. H., and Murty, K. L.

K-L

- Kain, R. M.:** Crevice corrosion testing in natural seawater: significance and use of multiple crevice assemblies, Sept., 309
- Kaiser, WT: *see* Magnusen, PE, Hinkle, AJ, Kaiser, WT, Bucci, RJ, and Rolf, RL
- Kasal, D: *see* White, MS, McLain, TE, Padla, D and Kasal, B
- Kashiwaya, H: *see* Kimura, K, Inukai, T, Saito, K and Kashiwaya, H
- Kimura, K, Inukai, T, Saito, K and Kashiwaya, H:** Nondestructive evaluation of in-service toughness degradation for Cr-Mo-V steam turbine rotor steel, May, 172
- Kirk, M. T. and Sanford, R. J.:** A K_I calibration for a modified single edge notched tension specimen, Sept., 344
- Lau, PWC and Tardif, Y.:** A computer-aided image system for analyzing cracks created by nailing in wood, March, 131
- Leon-Salamanca, T.:** Review of *Nondestructive Testing (Metallurgy and Materials Science)*, July, 305
- Leung, C-P, McDowell, DL and Saxena, A.:** Estimation of the C_I parameter: experimental implications, Jan., 25
- Liao, K. C.:** Use of X-ray diffraction for measuring recrystallization of low carbon steels for tin plate application, Sept., 338
- Little, RE:** Optimal stress amplitude selection in estimating median fatigue limits using small samples, March, 115
- Lucas, GE: *see* Haggag, FM, Server, WL, Lucas, GE, Odette, GR and Shekherd, JW

M

- Macdonald, BD and Pajot, JJ:** Stress intensity factors for side-grooved fracture specimens, July, 281
- Magnusen, PE, Hinkle, AJ, Kaiser, WT, Bucci, RJ, and Rolf, RL:** Durability assessment based on initial material quality, Nov. 439
- Mahboub, K:** Elasto-plastic fracture characterization of paving materials at low temperatures, May, 210
- Mahmood, S. T., Al-Otaibi, K. M., Jung, Y. H., and Murty, K. L.:** Dynamic strain-aging and neutron irradiation effects on mechanical and fracture properties of A533B class 1 PV steel and 2.25Cr-1Mo steel, Sept., 332
- Malaiyandi, M and Goddard, MJ:** Development of analytical methodology and a

- report on collaborative study on the determination of morpholine, cyclohexylamine, and diethylaminoethanol in aqueous samples by direct aqueous injection gas chromatography, March, 87
- Manoharan, M, Hirth, JP and Rosenfield, AR:** A suggested procedure for combined mode I-mode III fracture toughness testing, March, 106
- Manson, J. A.: *see* Clark, T. R., Hertzberg, R. W., and Manson, J. A.
- McCann, DR: *see* Jhansale, HR and McCann, DR
- McDowell, DL: *see* Leung, C-P, McDowell, DL and Saxena, A
- McGlone, FB:** Review of *AIDS and Intravenous Drug Use: Future Directions for Community-Based Prevention Research*, Nov., 458
- McLain, TE: *see* White, MS, McLain, TE and Padla, D
see White, MS, McLain, TE, Padla, D and Kasal, B
- McNatt, JD and Soltis, LA:** Instrumented impactor for testing wood-base floor panels, July, 265
- Meredith, SE and Schemel, JH:** Effect of crystallographic texture on flexure fatigue properties of Ti-3Al-2.5V hydraulic tubing, March, 98
- Mestán, SA: *see* Wycherley, GW, Mestán, SA and Grabovac, I
- Mohanty, ON: *see* Parida, N, Das, SK, Gope, PC, and Mohanty, ON
- Mones, E:** Review of *Handbook of Environmental Fate and Exposure Data for Organic Chemicals*, Nov., 458
- Munz, D. and Barker, L. M.:** Discussion of "Chevron-notched specimens for fracture toughness measurements independent of R-curve effects," with author's closure, Sept., 369
- Murty, K. L.: *see* Mahmood, S. T., Al-Otaibi, K. M., Jung, Y. H., and Murty, K. L.
- N-R**
- Nguyen, HL: *see* Bui-Quoc, Gomuc, R, Biron, A, Nguyen, HL and Tadros, RN
- Nishimura, T, Noguchi, Y, and Uchimoto, T:** Damage tolerance analysis of multiple-site cracks emanating from hole array, Nov., 401
- Noguchi, T:** Bending strength of gray cast iron, Jan., 70
- Noguchi, Y: *see* Nishimura, T, Noguchi, Y, and Uchimoto, T
- Odette, GR: *see* Haggag, FM, Server, WL, Lucas, GE, Odette, GR and Sheckherd, JW
- Padla, D: *see* White, MS, McLain, TE and Padla, D
see White, MS, McLain, TE, Padla, D and Kasal, B
- Pajot, JJ: *see* Macdonald, BD and Pajot, JJ
- Parida, N, Das, SK, Gope, PC, and Mohanty, ON:** Probability, confidence, and sample size in fatigue testing, Nov., 385
- Pellicane, PJ:** Behavior of rubber-based elastomeric construction adhesive in wood joints, July, 256
- Pompetzki, MA, Topper, TH, DuQuesnay, DL and Yu, MT:** Effect of compressive underloads and tensile overloads on fatigue damage accumulation in 2024-T351 aluminum, Jan., 53
- Purtscher, PT: *see* Rosenthal, YA, Tobler, RL and Purtscher, P
- Putatunda, SK and Venugopal, V:** Influence of overload plastic zone size on stress corrosion crack growth behavior of a low alloy steel in 3.0% NaCl solution, May, 182
- Ragab, AR, Alawi, H and Addassi, E:** Weathering effects on some mechanical properties of polyvinyl chloride pipes, Jan., 45
- Rehbein, DK, Thompson, RB, and Buck, O:** Fatigue crack characterization by ultrasonic inspection, Nov., 421
- Richards, GL and Hartwig, KT, Jr.:** A simplified method for determining relaxation time and electrical resistivity from eddy-current decay measurements, Nov., 454
- Ripling, EJ: *see* Crosley, PB and Ripling, EJ
- Rolf, RL: *see* Magnusen, PE, Hinkle, AJ, Kaiser, WT, Bucci, RJ, and Rolf, RL
- Rosenfield, AR: *see* Manoharan, M, Hirth, JP and Rosenfield, AR
- Rosenthal, YA, Tobler, RL and Purtscher, PT:** J_{IC} data analysis methods with a "negative crack growth" correction procedure, July, 301
- S**
- Saito, K: *see* Kimura, K, Inukai, T, Saito, K and Kashiwaya, H
- Sanford, R. J.: *see* Kirk, M. T. and Sanford, R. J.
- Schroeder, L. W.: *see* Davis, G. B. and Schroeder, L. W.
- Sanford, RJ: *see* Dally, JW and Sanford, RJ
- Santner, JS:** Use of cantilever specimens to determine microcreep properties, May, 191
- Saxena, A: *see* Leung, C-P, McDowell, DL and Saxena, A
see Wert, MJ, Saxena, A and Ernst, HA
- Schemel, JH: *see* Meredith, SE and Schemel, JH
- Scherrer, DK: *see* Taylor, JA and Scherrer, DK
- Segall, AE, Hellmann, JR and Strzepa, P:** Experimental and analytical evaluation of the mechanical performance of a gas-fired ceramic radiant tube at steady-state, July, 250
- Seligson, D:** Historical overview of femoral intramedullary nailing, March, 138
- Server, WL: *see* Haggag, FM, Server, WL, Lucas, GE, Odette, GR and Sheckherd, JW
- Shao, E.: *see* Jiang, B. and Shao, E.
- Shapiro, JM: *see* Sharpe, WN, Jr., and Shapiro, JM
- Sharpe, WN, Jr., and Shapiro, JM:** Dynamic K measurements in three-point-bend specimens, Jan., 38
- Sheckherd, JW: *see* Haggag, FM, Server, WL, Lucas, GE, Odette, GR and Sheckherd, JW
- Slatcher, S:** Estimation of characteristic values of fracture toughness, May, 141
- Smith, DJ and Gordon, JR:** The linearity of clip gages used in fracture mechanics tests, Jan., 14
- Soltis, LA: *see* McNatt, JD and Soltis, LA
- Strzepa, P: *see* Segall, AE, Hellmann, JR and Strzepa, P
- Sulowski, AC and Brinkley, JW:** Measurement of maximum arrest force in performance tests of fall protection equipment, March, 123
- T-V**
- Tadros, RN: *see* Bui-Quoc, Gomuc, R, Biron, A, Nguyen, HL and Tadros, RN
- Tardif, Y: *see* Lau, PWC and Tardif, Y
- Taylor, JA and Scherrer, DK:** Plastic strain ratio (r) for sheet metal: effect of gage length and width measurement locations using reduced section specimens, July, 292
- Thompson, RB: *see* Rehbein, DK, Thompson, RB, and Buck, O
- Tobler, RL: *see* Rosenthal, YA, Tobler, RL and Purtscher, PT
- Topper, TH: *see* Pompetzki, MA, Topper, TH, DuQuesnay, DL and Yu, MI
see Yu, MT, DuQuesnay, DL and Topper, TH
- Uchimoto, T: *see* Nishimura, T, Noguchi, Y, and Uchimoto, T
- Ukponmwan, JO:** Changes in cotton fabric bending properties as a result of laboratory wear, Nov., 408
- Urbanik, T. J.:** Force plate for corrugated container vibration tests, Sept., 359
- Venugopal, V: *see* Putatunda, SK and Venugopal, V
- W-Z**
- Watanabe, RT: *see* Berens, AP and Watanabe, RT
- Weiler, WW:** Dynamic loading: a new microhardness test method, July, 229
- Wert, MJ, Saxena, A and Ernst, HA:** Applicability of modified J as a fracture parameter for polycarbonate, Jan., 1
- White, MS, McLain, TE and Padla, D:** Relationships between the results of nail impact bend tests and selected nail material properties, May, 219
- White, MS, McLain, TE, Padla, D and Kasal, B:** Hardness gradients within roll-threaded steel nails, March, 128
- Wickstrom, SN and Wolfenden, A:** Measurements of dynamic Young's modulus in short specimens with the PUCOT, Jan., 81
- Wolfenden, A: *see* Wickstrom, SN and Wolfenden, A
- Wycherley, GW, Mestán, SA and Grabovac, I:** A method for uniform shear stress-strain analysis of adhesives, May, 203
- Yu, MT: *see* Pompetzki, MA, Topper, TH, DuQuesnay, DL and Yu, MT
- Yu, MT, DuQuesnay, DL and Topper, TH:** Fatigue behavior of a cold-rolled SAE grade 945X HSLA steel, July, 274
- Zenkert, D: *see* Groth, HL and Zenkert, D