

Journal of Testing and Evaluation

Subject Index to Volume 18

1990

A

Adhesives

A method for uniform shear stress-strain analysis of adhesives (Wycherley, Mes-tan and Grabovac), May, 203

Aluminum

Durability assessment based on initial material quality (Magnusen, Hinkle, Kaiser, Bucci, and Rolf), Nov., 439

Anisotropy

Effect of crystallographic texture on flexure fatigue properties of Ti-3Al-2.5V hydraulic tubing (Meredith and Schemel), March, 98

Arrest force

Measurement of maximum arrest force in performance tests of fall protection equipment (Sulowski and Brinkley), March, 123

Asphalt

Elasto-plastic fracture characterization of paving materials at low temperatures (Mahboub), May, 210

ASTM C 273

Fracture of defect foam core sandwich beams (Groth and Zenkert), Nov., 390

ASTM Method E 813-87

J_{IC} data analysis methods with a "negative crack growth" correction procedure (Rosenthal, Tobler and Purtscher), July, 301

B

Ball indentation test

The use of miniaturized tests to predict flow properties and estimate fracture toughness in deformed steel plates (Haggag, Server, Lucas, Odette and Shekherd), Jan., 62

Bend

Dynamic strain-aging and neutron irradiation effects on mechanical and fracture properties of A533B class 1 PV steel and 2.25 Cr-1Mo steel (Mahmood, Al-Otaibi, Jung, and Murty), Sept., 332

Bending strength

Bending strength of gray cast iron (Noguchi), Jan., 70

Book reviews

AIDS and Intravenous Drug Use: Future Directions for Community-Based Prevention Research (McGlone), Nov., 458
Handbook of Environmental Fate and Exposure Data for Organic Chemicals (Mones), Nov., 458
Nondestructive Testing (Metallurgy and Materials Science) (Leon-Salamanca), July, 305

Brittle

An approach to predicting long-term toughness, strength, and ductility of a Cr-

Mo-V steel alloy using short-term tests (Davis), July, 286

C

Carbon content

Relationships between the results of nail impact bend tests and selected nail material properties (White, McLain and Padla), May, 219

Clip gage

The linearity of clip gages used in fracture mechanics tests (Smith and Gordon), Jan., 14

Cold rolling

Fatigue behavior of a cold-rolled SAE grade 945X HSLA steel (Yu, Du-Quesnay and Topper), July, 274

Combined mode fracture

A suggested procedure for combined mode I-mode III fracture toughness testing (Manoharan, Hirth and Rosenfield), March, 106

Confidence level

Probability, confidence, and sample size in fatigue testing (Parida, Das, Gope, and Mohanty), Nov., 385

Constitutive equation

An approach to predicting long-term toughness, strength, and ductility of a Cr-Mo-V steel alloy using short-term tests (Davis), July, 286

Continuous annealing

Use of X-ray diffraction for measuring recrystallization of low carbon steels for tin plate application (Liao), Sept., 338

Contractile strain ratio

Effect of crystallographic texture on flexure fatigue properties of Ti-3Al-2.5V hydraulic tubing (Meredith and Schemel), March, 98

Conventional

A rapid method for measurement of rolling contact fatigue limit of case-hardened gear materials (Jiang and Shao), Sept., 328

Copper

Measurements of dynamic Young's modulus in short specimens with the PUCOT (Wickstrom and Wolfenden), Jan., 81

Crack

Fatigue behavior of a cold-rolled SAE grade 945X HSLA steel (Yu, Du-Quesnay and Topper), July, 274

Crack arrest

A K_{IC} calibration for a modified single edge notched tension specimen (Kirk and Sanford), Sept., 344

Crack arrest fracture toughness

A quality control test for selecting materials to arrest fast-running, full-thickness cracks (Crosley and Ripling), Nov., 396

Crack closure

Effect of compressive underloads and tensile overloads on fatigue damage accumulation in 2024-T351 aluminum (Pompetzki, Topper, DuQuesnay and Yu), Jan., 53

Fatigue crack characterization by ultrasonic inspection (Rehbein, Thompson, and Buck), Nov., 421

Crack propagation

A computer-aided image system for analyzing cracks created by nailing in wood (Lau and Tardif), March, 131

Damage tolerance analysis of multiple-site cracks emanating from hole array (Nishimura, Noguchi, and Uchimoto), Nov., 401

Creep

Estimation of the C_f parameter: experimental implications (Leung, McDowell and Saxena), Jan., 25

Creep crack growth

Estimation of the C_f parameter: experimental implications (Leung, McDowell and Saxena), Jan., 25

Creep rupture

An approach to predicting long-term toughness, strength, and ductility of a Cr-Mo-V steel alloy using short-term tests (Davis), July, 286

Crevice corrosion

Crevice corrosion testing in natural seawater: significance and use of multiple crevice assemblies (Kain), Sept., 309

Critical review

Crevice corrosion testing in natural seawater: significance and use of multiple crevice assemblies (Kain), Sept., 309

Crystallographic texture

Effect of crystallographic texture on flexure fatigue properties of Ti-3Al-2.5V hydraulic tubing (Meredith and Schemel), March, 98

C_f parameter

Estimation of the C_f parameter: experimental implications (Leung, McDowell and Saxena), Jan., 25

CTOD

Dynamic K measurements in three-point-bend specimens (Sharpe and Shapiro), Jan., 38

Estimation of characteristic values of fracture toughness (Slatcher), May, 141

Cyclic J

Characterization of the effects of large unloading cycles on the ductile tearing toughness of HSLA steel (Joyce), Nov., 373

Cyclic stress-strain

Cyclic stress-strain behavior and low cycle fatigue of Ti6242 (Bui-Quoc, Gomuc, Biron, Nguyen and Tadros), May, 160

Cyclohexylamine

Development of analytical methodology and a report on collaborative study on the determination of morpholine, cyclohexylamine, and diethylaminoethanol in aqueous samples by direct aqueous injection gas chromatography (Malaiyandi and Goddard), March, 87

D**Damage**

Effect of compressive underloads and tensile overloads on fatigue damage accumulation in 2024-T351 aluminum (Pompetzki, Topper, DuQuesnay and Yu), Jan., 53

Dead burnt dolomite

An appraisal of hydration characteristics of dead burnt dolomite grains (Das, Ghosh, Das and Banerjee), Jan., 76

Degradation

Nondestructive evaluation of in-service toughness degradation for Cr-Mo-V steam turbine rotor steel (Kimura, Inukai, Saito and Kashiwaya), May, 172

Degradation of PVC

Weathering effects on some mechanical properties of polyvinyl chloride pipes (Ragab, Alawi and Addassi), Jan., 45

Densification

An appraisal of hydration characteristics of dead burnt dolomite grains (Das, Ghosh, Das and Banerjee), Jan., 76

Diethylaminoethanol

Development of analytical methodology and a report on collaborative study on the determination of morpholine, cyclohexylamine, and diethylaminoethanol in aqueous samples by direct aqueous injection gas chromatography (Malaiyandi and Goddard), March, 87

Displacement transducer

The linearity of clip gages used in fracture mechanics tests (Smith and Gordon), Jan., 14

Durability

Durability assessment based on initial material quality (Magnusen, Hinkle, Kaiser, Bucci, and Rolf), Nov., 439

Duration of exposure

Behavior of rubber-based elastomeric construction adhesive in wood joints (Pellicane), July, 256

Dynamic contact angle

Influence of contact angles on the leakage of latex condoms (Davis and Schroeder), Sept., 352

Dynamic fracture

Measuring the stress intensity factor for propagating cracks with strain gages (Dally and Sanford), July, 240

Dynamic microhardness testing

Dynamic loading: a new microhardness test method (Weiler), July, 229

Dynamic modulus

Measurements of dynamic Young's modulus in short specimens with the PUCOT (Wickstrom and Wolfenden), Jan., 81

Dynamic testing

Dynamic K measurements in three-point-bend specimens (Sharpe and Shapiro), Jan., 38

E**Eddy-current decay method**

A simplified method for determining relaxation time and electrical resistivity from eddy-current decay measurements (Richards and Hartwig), Nov., 454

Elastic fracture specimens

Stress intensity factors for side-grooved fracture specimens (Macdonald and Pajot), July, 281

Elastic-plastic fracture

Characterization of the effects of large unloading cycles on the ductile tearing toughness of HSLA steel (Joyce), Nov., 373

Elastomeric adhesives

Behavior of rubber-based elastomeric construction adhesive in wood joints (Pellicane), July, 256

Electrical resistivity

A simplified method for determining relaxation time and electrical resistivity from eddy-current decay measurements (Richards and Hartwig), Nov., 454

F**Fall protection**

Measurement of maximum arrest force in performance tests of fall protection equipment (Sulowski and Brinkley), March, 123

Fatigue

Durability assessment based on initial material quality (Magnusen, Hinkle, Kaiser, Bucci, and Rolf), Nov., 439

Effect of compressive underloads and tensile overloads on fatigue damage accumulation in 2024-T351 aluminum (Pompetzki, Topper, DuQuesnay and Yu), Jan., 53

Fatigue behavior of a cold-rolled SAE grade 945X HSLA steel (Yu, DuQuesnay and Topper), July, 274

Fatigue crack characterization by ultrasonic inspection (Rehbein, Thompson, and Buck), Nov., 421

Influence of test methodology on fatigue crack propagation in engineering plastics (Clark, Hertzberg, and Manson), Sept., 319

Fatigue crack

Imaging short fatigue cracks with the gel electrode (Baxter), JOTE, Nov., 430

Fatigue life

Probability, confidence, and sample size in fatigue testing (Parida, Das, Gope, and Mohanty), Nov., 385

Femoral

Historical overview of femoral intramedullary nailing (Seligson), March, 138

Flexure test

Bending strength of gray cast iron (Noguchi), Jan., 70

Floors

Instrumented impactor for testing wood-base floor panels (McNatt and Soitis), July, 265

Fracture

A computer-aided image system for analyzing cracks created by nailing in wood (Lau and Tardif), March, 131

Fracture mechanics

A computer-aided image system for analyzing cracks created by nailing in wood (Lau and Tardif), March, 131

A quality control test for selecting materials to arrest fast-running, full-thickness cracks (Crosley and Ripling), Nov., 396

Applicability of modified J as a fracture parameter for polycarbonate (Wert, Saxena and Ernst), Jan., 1

The linearity of clip gages used in fracture mechanics tests (Smith and Gordon), Jan., 14

Fracture testing

Elasto-plastic fracture characterization of paving materials at low temperatures (Mahboub), May, 210

Fracture toughness

A quality control test for selecting materials to arrest fast-running, full-thickness cracks (Crosley and Ripling), Nov., 396

A suggested procedure for combined mode I-mode III fracture toughness testing (Manoharan, Hirth and Rosenfield), March, 106

Estimation of characteristic values of fracture toughness (Slatcher), May, 141

J_{IC} data analysis methods with a "negative crack growth" correction procedure (Rosenthal, Tobler and Purtscher), July, 301

G**Gel electrode imaging**

Imaging short fatigue cracks with the gel electrode (Baxter), JOTE, Nov., 430

Generator rotors

Bore inspection and life evaluation of vintage steam turbine/generator rotors (Jhansale and McCann), Nov., 446

Gradients

Hardness gradients within roll-threaded steel nails (White, McLain, Padla and Kasal), March, 128

Gray cast iron

Bending strength of gray cast iron (Noguchi), Jan., 70

H**Hardness**

Hardness gradients within roll-threaded steel nails (White, McLain, Padla and Kasal), March, 128

I**Impact tests**

Measurement of maximum arrest force in performance tests of fall protection

equipment (Sulowski and Brinkley), March, 123

Incubation period

Influence of overload plastic zone size on stress corrosion crack growth behavior of a low alloy steel in 3.0% NaCl solution (Putatunda and Venugopal), May, 182

Instrumented impact testing

Instrumented impactor for testing wood-base floor panels (McNatt and Soltis), July, 265

Interferometry

Dynamic K measurements in three-point-bend specimens (Sharpe and Shapiro), Jan., 38

Intramedullary nailing

Historical overview of femoral intramedullary nailing (Seligson), March, 138

Iosipescu method

A method for uniform shear stress-strain analysis of adhesives (Wycheley, Mes-tan and Grabovac), May, 203

J

J integral

Applicability of modified J as a fracture parameter for polycarbonate (Wert, Saxena and Ernst), Jan., 1

J_{ic} data analysis methods with a "negative crack growth" correction procedure (Rosenthal, Tobler, and Purtscher), July, 301

L

Latex

Influence of contact angles on the leakage of latex condoms (Davis and Schroeder), Sept., 352

Low carbon steels

Use of X-ray diffraction for measuring re-crystallization of low carbon steels for tin plate application (Liao), Sept., 338

Low cycle fatigue

Cyclic stress-strain behavior and low cycle fatigue of Ti 6242 (Bui-Quoc, Gomuc, Biron, Nguyen and Tadros), May, 160

Low cycle fatigue crack growth

Characterization of the effects of large unloading cycles on the ductile tearing toughness of HSLA steel (Joyce), Nov., 373

M

Mean stress

Influence of test methodology on fatigue crack propagation in engineering plastics (Clark, Hertzberg, and Manson), Sept., 319

Median fatigue limits

Optimal stress amplitude selection in estimating median fatigue limits using small samples (Little), March, 115

Method

A rapid method for measurement of rolling contact fatigue limit of case-hardened

gear materials (Jiang and Shao), Sept., 328

Microcreep testing

Use of cantilever specimens to determine microcreep properties (Santner), May, 191

Microhardness testing under load

Dynamic loading: a new microhardness test method (Weiler), July, 229

Microstress relaxation (MSR)

Use of cantilever specimens to determine microcreep properties (Santner), May, 191

Miniaturized tests

The use of miniaturized tests to predict flow properties and estimate fracture toughness in deformed steel plates (Haggag, Server, Lucas, Odette and Sheckherd), Jan., 62

Minimum variance strategy

Optimal stress amplitude selection in estimating median fatigue limits using small samples (Little), March, 115

Mixed-mode fracture

A suggested procedure for combined mode I-mode III fracture toughness testing (Manoharan, Hirth and Rosenfield), March, 106

Morpholine

Development of analytical methodology and a report on collaborative study on the determination of morpholine, cyclohexylamine, and diethylaminoethanol in aqueous samples by direct aqueous injection gas chromatography (Malaiyandi and Goddard), March, 87

Multiple crevice

Crevice corrosion testing in natural seawater: significance and use of multiple crevice assemblies (Kain), Sept., 309

Multiple-site cracks

Damage tolerance analysis of multiple-site cracks emanating from hole array (Nishimura, Noguchi, and Uchimoto), Nov., 401

Multistep cycling

Cyclic stress-strain behavior and low cycle fatigue of Ti6242 (Bui-Quoc, Gomuc, Biron, Nguyen and Tadros), May, 160

N

Nails

Hardness gradients within roll-threaded steel nails (White, McLain, Padla and Kasal), March, 128

Relationships between the results of nail impact bend tests and selected nail material properties (White, McLain and Padla), May, 219

Natural weathering of PVC

Weathering effects on some mechanical properties of polyvinyl chloride pipes (Ragab, Alawi and Addassi), Jan., 45

Nondestructive test

Nondestructive evaluation of in-service toughness degradation for Cr-Mo-V steam turbine rotor steel (Kimura, Inukai, Saito and Kashiwaya), May, 172

O

Optimum allocation of specimens

Optimal stress amplitude selection in estimating median fatigue limits using small samples (Little), March, 115

Overload

Influence of overload plastic zone size on stress corrosion crack growth behavior of a low alloy steel in 3.0% NaCl solution (Putatunda and Venugopal), May, 182

P

Pavement materials

Elasto-plastic fracture characterization of paving materials at low temperatures (Mahboub), May, 210

Percentage difference

Changes in cotton fabric bending properties as a result of laboratory wear (Ukponmwan), Nov., 408

Percentage loss in weight

Changes in cotton fabric bending properties as a result of laboratory wear (Ukponmwan), Nov., 408

Photoelasticity

A K_I calibration for a modified single edge notched tension specimen (Kirk and Sanford), Sept., 344

Plywood

Instrumented impactor for testing wood-base floor panels (McNatt and Soltis), July, 265

Polycarbonate

Applicability of modified J as a fracture parameter for polycarbonate (Wert, Saxena and Ernst), Jan., 1

Polyvinyl chloride pipe

Weathering effects on some mechanical properties of polyvinyl chloride pipes (Ragab, Alawi and Addassi), Jan., 45

Preshipment container

Force plate for corrugated container vibration tests (Urbanik), Sept., 359

Pressure vessel steels

Dynamic strain-aging and neutron irradiation effects on mechanical and fracture properties of A533B class 1 PV steel and 2.25 Cr-1Mo steel (Mahmood, Al-Otaibi, Jung, and Murty), Sept., 332

Probability

Probability, confidence, and sample size in fatigue testing (Parida, Das, Gope, and Mohanty), Nov., 385

R

r -value

Plastic strain ratio (r) for sheet metal: effect of gage length and width measurement locations using reduced section specimens (Taylor and Scherrer), July, 292

Rapid

A rapid method for measurement of rolling contact fatigue limit of case-hardened gear materials (Jiang and Shao), Sept., 328

Relaxation time

A simplified method for determining relaxation time and electrical resistivity from eddy-current decay measurements (Richards and Hartwig), Nov., 454

S**Sandwich beams**

Fracture of defect foam core sandwich beams (Groth and Zenkert), Nov., 390

Sandwich structures

Fracture of defect foam core sandwich beams (Groth and Zenkert), Nov., 390

Shear punch test

The use of miniaturized tests to predict flow properties and estimate fracture toughness in deformed steel plates (Haggag, Server, Lucas, Odette and Shekherd), Jan., 62

Shear test

A method for uniform shear stress-strain analysis of adhesives (Wycherley, Mestian and Grabovac), May, 203

Shipping environment

Force plate for corrugated container vibration tests (Urbanik), Sept., 359

Shirley cyclic bending tester

Changes in cotton fabric bending properties as a result of laboratory wear (Ukponmwan), Nov., 408

Shock and vibration

Force plate for corrugated container vibration tests (Urbanik), Sept., 359

Short crack growth

Imaging short fatigue cracks with the gel electrode (Baxter), Nov., 430

Side-grooving

Stress intensity factors for side-grooved fracture specimens (Macdonald and Pajot), July, 281

Single crystals

Measurements of dynamic Young's modulus in short specimens with the PUCOT (Wickstrom and Wolfenden), Jan., 81

Spindles

Bore inspection and life evaluation of vintage steam turbine/generator rotors (Jhansale and McCann), Nov., 446

Splints

Historical overview of femoral intramedullary nailing (Seligson), March, 138

Stable members

Use of cantilever specimens to determine microcreep properties (Santner), May, 191

Static contact angle

Influence of contact angles on the leakage of latex condoms (Davis and Schroeder), Sept., 352

Statistics

Estimation of characteristic values of frac-

ture toughness (Slatcher), May, 141

Steady-state

Experimental and analytical evaluation of the mechanical performance of a gas-fired ceramic radiant tube at steady-state (Segall, Hellmann and Strzepa), July, 250

Steam turbine

Bore inspection and life evaluation of vintage steam turbine/generator rotors (Jhansale and McCann), Nov., 446

Strain gage

Measuring the stress intensity factor for propagating cracks with strain gages (Dally and Sanford), July, 240

Stress corrosion cracking

Influence of overload plastic zone size on stress corrosion crack growth behavior of a low alloy steel in 3.0% NaCl solution (Putatunda and Venugopal), May, 182

Stress intensity factor

A K_I calibration for a modified single edge notched tension specimen (Kirk and Sanford), Sept., 344

Damage tolerance analysis of multiple-site cracks emanating from hole array (Nishimura, Noguchi, and Uchimoto), Nov., 401

Measuring the stress intensity factor for propagating cracks with strain gages (Dally and Sanford), July, 240

Stress intensity factors

Stress intensity factors for side-grooved fracture specimens (Macdonald and Pajot), July, 281

Sub-size specimens

Impact energy/specimen thickness relationship for two turbine steels (Bashu), Sept., 363

T**Temperature effects**

Behavior of rubber-based elastomeric construction adhesive in wood joints (Pellicane), July, 256

Tensile

Dynamic strain-aging and neutron irradiation effects on mechanical and fracture properties of A533B class 1 PV steel and 2.25 Cr-1Mo steel (Mahmood, Al-Otaibi, Jung, and Murty), Sept., 332

Thermal profiles

Experimental and analytical evaluation of the mechanical performance of a gas-fired ceramic radiant tube at steady-state (Segall, Hellmann and Strzepa), July, 250

Thermoelastic stress

Experimental and analytical evaluation of the mechanical performance of a gas-fired ceramic radiant tube at steady-state

(Segall, Hellmann and Strzepa), July, 250

Threshold

Influence of test methodology on fatigue crack propagation in engineering plastics (Clark, Hertzberg, and Manson), Sept., 319

Tin mill products

Use of X-ray diffraction for measuring recrystallization of low carbon steels for tin plate application (Liao), Sept., 338

Toughness

Nondestructive evaluation of in-service toughness degradation for Cr-Mo-V steam turbine rotor steel (Kimura, Inukai, Saito and Kashiwaya), May, 172

Turbine steels

Impact energy/specimen thickness relationship for two turbine steels (Bashu), Sept., 363

Two-stage calcination

An appraisal of hydration characteristics of dead burnt dolomite grains (Das, Ghosh, Das and Banerjee), Jan., 76

Type A alternative specimens

Plastic strain ratio (r) for sheet metal: effect of gage length and width measurement locations using reduced section specimens (Taylor and Scherrer), July, 292

Type A standard specimens

Plastic strain ratio (r) for sheet metal: effect of gage length and width measurement locations using reduced section specimens (Taylor and Scherrer), July, 292

U**Ultra-low load microhardness testing**

Dynamic loading: a new microhardness test method (Weiler), July, 229

Ultrasonic

Fatigue crack characterization by ultrasonic inspection (Rehbein, Thompson, and Buck), Nov., 421

V**V-notch Charpy impact test**

Impact energy/specimen thickness relationship for two turbine steels (Bashu), Sept., 363

Y**Yield strength**

Relationships between the results of nail impact bend tests and selected nail material properties (White, McLain and Padla), May, 219