

## Subject Index

### A

Acoustic pulses, 642  
 Adhesive fatigue, 764  
 Adhesive fracture, 764  
 Adhesives, structural, 764  
 Adjusted compliance ratio, 674  
 Aircraft  
   aging, 97  
   high speed civil, 713  
 Aluminum  
   2024-T3, 815  
   2324-T39, 674  
   6013-T651, 674  
   7075-T6, 552  
   7075-T7751, 674  
   alloy, 407, 426, 727, 815  
   plates, 97  
   specimens, 453  
 ASTM standards  
   A 508, C113, 284  
   A 533, Grade B, 17, 341  
   A 723, 897  
   E 647, 674  
   opening load method, 674  
 Autofrettage, 565, 584

### B

Bauschinger effect, 565  
 Bending loads, 552  
 Beremin model, 284  
 Bicycle components, off-road,  
   743  
 Blunting model, crack tip, 552  
 Bridge specimens, 696  
 Brittle fracture, 40, 154  
 Buckling, 114

### C

Calibration, 862  
 Calibration function, 248  
 Cannon components, high  
   strength steel, 897

Carbon precipitate/nickel grain  
   boundary interfaces, 384  
 Carrier cloth, 764  
 Cell models, 9  
 Center-cracked plate specimen,  
   9, 82  
 Charpy specimens  
   precracked, 55  
   precracked Charpy v-notch,  
     135  
   sub-Charpy-size, 40  
 Cladding, 284  
 Cleavage fracture, 135, 284, 341  
 Coarsening, heterogeneous, 786  
 Compact tension specimens,  
   284, 674, 815, 851  
 Compact toughness specimen,  
   830, 862  
 Composite materials  
   carbon fiber-reinforced  
     polymer, 713  
 Compression, 474  
 Computational cell  
   methodology, 9, 135  
 Constant amplitude fatigue  
   cycling, 642  
 Constant amplitude loading,  
   uniform, 453  
 Constitutive model, 264  
 Constraint, 40, 55, 135  
   evaluation, 830  
 Contact geometry, 696  
 Continuum damage models, 851  
 Cracks and cracking  
   axial, through wall, 215,  
     830  
   closure, 426, 496, 674, 727  
   closure, resulting growth  
     rates, 407  
   closure, fatigue, 438  
   closure, plasticity-induced,  
     453, 516  
   closure, roughness-induced,  
     535  
   closure technique, virtual, 176  
 Configuration, 114  
 development, 599

engineering size, failure  
     definition, 599  
 extension, 884  
 extension, 82, 264  
 extension, ductile, 135  
 fatigue, 786  
 fatigue, nucleation process,  
     614  
 fatigue, propagation, 474, 552  
 fields, asymptotic, 233  
 front, 658, 862  
 front mesh normality, 176  
 growth, 565  
 growth behavior, 516  
 growth, ductile, 851, 862  
 growth, fatigue, 407, 426, 552,  
     658, 713  
 growth, fatigue, measurement,  
     ASTM E 647, 674  
 growth, fatigue, theory, 496  
 growth, increment, 438  
 growth, mixed mode, 658  
 growth, plastic, 233  
 growth, plasticity-induced, 535  
 growth rate, 438, 897  
 growth, stable, 97, 341, 815  
 initiation, 642  
 length, critical, 830  
 length, relation to displacement  
     and load, 82  
 length to specimen width  
     ratio, 114  
 multiple site damage, 114  
 oblique, 658  
 opening angle, 884  
 opening displacement, 764  
 opening displacement  
     method, 176  
 propagation, 453, 674  
 propagation stress intensity  
     factor, 474  
 size, 496  
 small, 426, 496  
 specimens, surface, 55  
 surface, 453  
 tension specimens, surface, 55  
 threshold, environmental  
     cracking, 897  
 tip blunting, 552  
 tip constraint, 284  
 tip cyclic strain, 674  
 tip displacement field, 438

tip loading rates, 17  
 tip opening angle, 97, 114, 815  
 tip opening displacement, 315, 552  
 tip plasticity, 438  
 tip stress intensity factor, 696  
 Creep, 384  
 Creep/fatigue crack growth, 215  
 Critical planes, 599  
 Crossbore intersections, 584  
 Cylinders, 215  
     thick-walled, 565

## D

Damage mechanics, 201, 364  
 Damage models, 851  
 Damage, multiple site, 815  
 Damage tolerance, 713, 727  
 Defects, butt welds, 862  
 Deformation, 82, 384  
     factor, 248  
     fields, 233  
     plastic, 264, 552  
 Dispersion strengthening, 786  
 Displacement, relation to load  
     and crack length, 82  
 Driving force, 496  
     mechanical, 474  
 Ductile-brittle regime, 9  
 Ductile-brittle transition, 17, 55  
 Ductile crack extension, 135  
 Ductile crack growth, 851, 862  
 Ductile damage, 201, 341  
 Ductile fracture, 248, 364  
 Ductile tearing, 40, 82, 341, 884  
     prediction, 201  
     resistance, 135  
     stable, 851  
 Ductility, residual, 884  
 Durability, 713  
 Dynamometers, 743

## E

Elastic-plastic, 97  
     fracture, 264  
 Elastoplastic stress, 233  
 Energy absorption rate, 496  
 Equivalent domain integral  
     method, 176  
 Exclusion region theory, 264  
 Extraction methods, 176

**F**

Failure assessment, 248  
 Failure loads, buckling influence  
     on, 114  
 Failure model, micromechanical,  
     341  
 Failure stresses, 815  
 Fasteners, 384  
 Fatigue, adhesive, 764  
 Fatigue analysis, multiaxial,  
     614, 599  
 Fatigue crack growth, 407, 426,  
     552, 658, 713  
     analysis, 215  
     measurement, ASTM E 647,  
         674  
     theory, energy consideration  
         basis, 496  
 Fatigue crack nucleation  
     process, 614  
 Fatigue crack propagation, 474  
 Fatigue cracks, 565  
 Fatigue damage, ultrasonics  
     for, 642  
 Fatigue durability  
     enhancement, 584  
 Fatigue failure, 743, 764  
 Fatigue, high cycle, 626  
 Fatigue life estimation, 584, 802  
 Fatigue lifetime, 565  
 Fatigue limit, 626  
 Fatigue, low cycle, 626  
 Fatigue, railroad, 614  
 Fatigue strength, 764  
 Fatigue test, 802  
 Fatigue, thermomechanical, 786  
 Fatigue threshold, 674  
 Fatigue, variable amplitude, 727  
 Ferritic structural steel, 40  
 Fiber bridging, 713  
 Fiber diameter, 393  
 Finite element analysis, 9, 176,  
     201, 284, 802  
     curved specimen cracks, 658  
     ductile crack growth, 851  
     nonlinear, 135  
     plane strain, 135, 552  
     predicting ductile tearing, 82  
     shell, 97  
     three-dimensional, 135, 215,  
         815, 830

Finite element code,  
     two-dimensional, 264  
 Finite element mesh, 201  
 Flat plate specimen, 658  
 Four point bend fatigue tests, 438  
 Fracture, adhesive, 764  
 Fracture resistance, 233, 315  
 Fracture toughness, 154, 315, 393  
     crack tip constraint influence  
         on, 284  
     dynamic, 17  
     predictions, 341  
     transition region, 40  
 Fretting fatigue tests, 696  
 Fuselage panel test, 713

**G**

Geometric constraint, 658  
 Gradient effect, 364  
 Grain boundary precipitates, 384  
 Grain size, 535  
 Gurson model, 201, 341, 364  
 Gurson-Tvergaard dilitant  
     plasticity formulation, 862

**H**

Haigh diagram, 626  
 Handlebar forces, 743  
 Heat affected zone, 315  
 Helicopter loading spectra, 727  
 High-speed civil transport, 713  
 Homogenization, 154  
 Honeycomb sandwich, 713  
 Hoop stress, residual  
     compressive, 565  
 Hydrogen cracking, 897  
 Hydrogen laden propellant  
     environments, 897

**I**

I-beam specimen, 82  
 Impact loading, 135  
 Impact specimens, 40  
 Intergranular failure, 384

**J**

J-integral, 55, 215, 830, 884  
 Joints, solder, 786

## 918 FATIGUE AND FRACTURE MECHANICS

Joints, welded, 315

*J-Q* approach, 9

*J-R* curve, 884

*J-T* approach, 9

### L

Laminate sandwich fuselage  
panel test, 713

Lead-tin eutectic solders, 786

Length scale, 201

Life prediction, 474

Linear damage rule, 743

Load, applied, 642, 658

Load, crack opening, 407

Load factor, 248

Loading, biaxial, 764

Loading, constant amplitude, 453

Loading, cyclic, 453

Loading, elastic, 426

Loading, high amplitude, 743

Loading, impact, 135

Loading, multiaxial, 599

Loading, proof, 584

Loading rates, crack tip, 17

Loading, service, 584

Loading spectra, 727

Loading, structural, 743

Loading, tensile shear, 802

Loading, uniaxial, 599

Loading/unloading, 496  
deformation, 552

Load interaction effect, 474

Load, limit, 884

Load method, opening, 674

Load ratio, 516

Load ratio effects, 802

Load, relationship to  
displacement and crack  
length, 82

Load reversal, 438

Load, shear, 764

Loads, variable amplitude, 802

Local approach, 284, 315

Local compression, 154

### M

Master curve, 55

Mechanical driving force, 474

Mesh size effect, 201

Micromechanical failure  
model, 154

Micromechanical parameters,  
Gurson, 364

Microscopy, high resolution,  
384

Microstructure, 535

Microstructure evolution, solder  
joints, 786

Microvoid density, 407

Middle crack tension specimens,  
674, 815

Miner's linear damage rule, 743

Mixed mode specimens,  
independently loaded, 764

Mohr-Coulomb yield condition,  
233

Moiré interferometry, 438

Multiaxial fatigue analysis, 599,  
614

Multiple-site damage  
specimens, 815

### N

Nicalon, 393

Nickel-copper alloys, 384

Nickel-iron base alloys,  
austenitic, 897

Nil-ductility temperature, 17

Notch plasticity, 516

Notch strain analysis, 584

### O

Oscilloscope, digitizing, 642

Overload effect, 474

Overloading, controlled,  
techniques, 584

### P

Palmgren-Miner's rule, 803

Pedal forces, 743

Piezoelectric transducers, 642

Pipes, pressurized, 215

Plane strain three point bend  
specimen, 201

Plastic constraint, 496

Plastic crack growth, 233

Plasticity, 438, 535  
     crack tip, 552  
     criterion, reverse, 584  
 Plasticity-induced closure, 453  
 Plastic strain, 565  
 Plastic strain energy, 496  
 Porosities, initial material, 862  
 Precleavage tearing, 851  
 Pressure sensitivity, 233  
 Pressure tube, 830  
 Pressure vessel shell weld, 851  
 Pressure vessel steel, 17, 40  
 Pressure vessel structural integrity, 284  
 Proof loading, 584  
 Propellant environments, hydrogen laden, 897

## R

Rail grinding, 614  
 Railroad rails, 614  
 R-curves, 862  
 Reduced strain technique, 407  
 Residual compressive hoop stress, 565  
 Residual compressive stress, 584  
 Residual strength, 82, 97  
     prediction, 815  
 Residual stress, 154, 516  
     Bauschinger effect on, 565  
     compressive, 474, 584  
     railroad rail fatigue, 614  
 Reverse plasticity criterion, 584  
 Reverse yielding, 552, 565  
 Rolling contact, 614  
 Roughness, 535  
 R ratio effect, 496

## S

Shearing force, 696  
 Silicon carbide, 393  
 Single lap shear, 786  
 Size effects, 40, 233  
 Slip contact, partial, 696  
 S-N interpolation approach, 626  
 S-N method, 743  
 Solder microstructures, 786  
 Stable crack growth, 97, 341, 815

Stable tearing, 884  
     behavior, 114  
 STAGS shell code, 114  
 Steel, 40  
     18G2AV, 516  
     A 508 C13, 284  
     A 533, Grade B, 17, 341  
     A 723, 897  
     EH-36, 884  
     ferritic structural, 40, 341  
     high strength, cannon components, 897  
     high strength low alloy, 82, 642, 884  
     pressure vessel, 17, 341  
     railroad rails, 614  
 Strain amplitude, 599  
 Strain, cyclic, 674  
 Strain energy, stored, 215  
 Strain hardening, 642  
 Strain saturation, 642  
 Stress amplitude, 599  
 Stress analysis, 453  
     finite element, 897  
 Stress, applied, 496  
 Stress effect, mean, 802  
 Stress effects, residual, 614  
 Stress field, residual, 516  
 Stress incursion, plastic zone, 474  
 Stress intensity factor, 176, 565, 897  
     correlation with crack growth increment, 438  
     crack propagation, 474  
     crack tip, 696  
     effective, 674  
     Weibull stress and, 284  
 Stress intensity range, 426  
 Stress, maximum principal, 658  
 Stress ratio, 407, 426, 626  
 Stress/rupture specimens, 384  
 Stress-strain curve, 82  
 Stress-strain technique, 830  
 Stress-zone volume, 830  
 Stretch zone, 496  
 Strain incursion, plastic zone, 474  
 Strip-yield model, 453, 516  
 Structural calibration function, 248  
 Structural components, 743, 884

## 920 FATIGUE AND FRACTURE MECHANICS

Structural constraint, 341  
Structural stress method, 802  
Subclad flaw, 284  
Superposition method, 154  
Surface closure measurements, 407  
Surface cracks, 453  
Surface flaws, 393  
Surface roughness, 535

### T

Tearing, stable, prediction, 815  
Tensile behavior, 393  
Tensile residual stress, subsurface, 614  
Tensile shear loading, 802  
Tensile stress, 393  
Thermomechanical fatigue, 786  
Three-dimensional computational fracture mechanics, 176  
Three-point bend, 9, 315  
    plane strain specimen, 201  
    specimens, 154  
Tin enrichment, 786  
Titanium  
    alloy, 727  
    foils, 713  
    Ti-6Al-4V, 626  
Train derailment, 614  
Transferability, 315  
Transformation procedure, simplified, 248  
Transition region  
    ductile-brittle, 55  
    temperature, 40  
*T*-stress, 341  
Tube, autofretted, 565  
Tube, high strength cannon, 897  
Tube, pressure, through-wall crack, 830  
Two-dimensional finite element code, 264  
Two-parameter approach, 9

### U

Ultrasonic pulse transmit-receiver method, 642  
Upper shelf energy  
    Charpy, 40  
Upper shelf temperature, 341

### V

Variable amplitude fatigue crack growth, 727  
Void nucleation law, 364  
Void volume fraction, 201, 364

### W

Waves  
    amplitude, 642  
    longitudinal, 642  
Weibull stress, 135, 284, 315  
Welded joints, 315  
Weld fracture, 154  
Weld material, ductile crack growth in, 851  
Welds, resistance spot, 802  
Weld strength mismatch, 315  
Weld tests, multi-specimen, 862

### Y

Yielding  
    localized, 584  
    reverse, 552, 565  
Yield strength, 862  
Yield stress, 426  
Young's modulus, 393

### Z

Zirconium, 830