

# Subject Index

## A

- A533B steel**  
     chemical composition, 965  
     CTOD versus applied stress, 479-480  
     fracture toughness, 16, 967  
     mechanical properties, 966  
     predicted and test results, 980  
     R-curve, 999-1000  
     safety factor, applied CTOD, 479, 481  
     stress-strain curve, 967-8
- Acoustic emission**, 13-14, 919
- Adhesive joints**, 278-283  
     critical load of a joint, 282  
     finite-element mesh, 281  
     fracture criterion, 280  
     numerical model and treatment, 280-282  
     terminus, 279  
     testing single-lap joints, 283  
     theory, 279-280
- A572 ferritic steel**  
     fracture surfaces, 462-463  
      $J\Delta a$  curve, 382
- $A_{ijk}$  coefficients**, 1059
- AISI 4137H quality steel**  
     Charpy energy transition curves, 336  
     chemical composition, 334  
     mechanical properties, 335
- AISI 4340 steel**  
     Charpy impact, 638-639  
     chemical composition, 848  
     ductile fatigue striations, 450  
     FATT versus flow strength, 642, 645  
     mechanical properties and fracture toughness properties, 631  
     tensile and fracture toughness properties, 849
- AISI 4335 steels**, mechanical properties and fracture toughness properties, 632
- Aluminum alloys**, 881, 934, 1050  
     crack closure behavior, 926-928  
     crack-growth behavior, 110-111  
     resistance, 107-109
- three-hole-crack tension specimen**, 113-114
- fracture toughness data**, 120
- Mixed-mode loading** (*see Mixed mode failure, aluminum alloys*)
- tension data**, 120
- Aluminum pipe**, excessive weld crown, 445, 447-448
- Anti-plane shear**, 821, 823
- API 5LX56 steel**  
     chemical composition, 965  
     fracture toughness, 967  
     mechanical properties, 966  
     predicted and test results, 980  
     stress-strain curve, 967-8
- Approximate analysis**, ductile failure assessment, 1007
- Arc bend specimens**, 285-300  
     annular ring segment, 286-287  
     boundary collocation, solution method, 286-290  
     straight three-point bend solutions, 290  
     stress function, 287-288
- Arctic-grade steel plate**, 164-177  
     bend tests, 167-169  
     crack-tip blunting, 172  
     experimental methods, 165-166  
     experimental scatter, 174-175  
     failure probability, 175  
     fracture surfaces, 166, 168-170  
     temperature dependence, 167-168, 172-174  
     tension test, 167-168  
     thickness effect, 175-177
- A36 steel** (*see also CTOD toughness, A 36 steel*), 537, 552  
     finite-element analysis, 544-552  
     plane-strain fracture toughness, 453
- A387 steel**, 603, 607-608
- A508 steel**, 73, 76-77, 80-81
- A533 steel**, 73, 76-77
- A710 steel**, 154-155, 349

ASTM Draft 86-03, 224  
 ASTM A710, 151, 153  
 ASTM E 8-85, 225  
 ASTM E 208-842, 406  
 ASTM E 23-82, 406  
 ASTM E 24, 469  
 ASTM E 399-83, 23, 73, 124-125, 166, 172, 208, 225, 228, 285, 424, 436, 451, 458, 535-536, 538, 540, 549, 649, 672, 814, 849  
 ASTM E 513-74, 1029  
 ASTM E 561-81, 74, 451  
 ASTM E 616-82, 744  
 ASTM E 647-83, 208, 873, 882  
 ASTM E 813-81, 21, 30, 138-139, 154, 164-166, 168, 172, 176-177, 333-334, 337, 339, 345, 349, 365, 391, 400, 402-403, 406, 408-409, 423, 425, 451, 517, 519, 536, 587-588, 606, 611-612, 614-615, 618-620, 626, 629, 647, 732, 739, 743-744, 988  
 experience with, 375  
 experimental requirements for determining data, 380-381  
 fracture resistance curve construction, 375-377  
 modifications, 374-388  
 ASTM Task Group on Crack Arrest, 74-75  
 Austenitic stainless steels (*see also* specific steels), 384, 957  
 Automated precracking, 390  
 Axially compressed columns, 804-817  
   beam column with rectangular cross section, 807  
   buckling load, 806  
   crack angle, versus number of load cycles, 809-810  
   cracked steel pipe, 807-808  
   crack length, versus number of cycles, 810-811  
   elastic buckling strength  
     versus crack angle, 807, 809  
     versus crack length, 808, 810-811  
     versus number of load cycles, 809-810, 812  
   end conditions, 806  
   experiments, 812-817  
   load eccentricity, 815  
   load-lateral deflection relations, 816  
   load versus lateral deflection, 812, 814  
   maximum load versus crack length, 812, 814  
   numerical examples, 807-812  
   plastic model, 816  
   spring model, 805-807  
   torsional stiffness, 807-809  
   tubular T-joint, 810-811

**B**

Back-face strain, 917-918, 924  
 Bendbars (*see* Three-point bend specimens)  
 Bending, 151, 505  
 Bending moment, total effective, 595  
 Benthem's solution, 704  
 Berry's functions, 806  
 $B_{ijk}$  coefficients, 1060  
 Blunting-line equation, 374-388  
   derivation, 385  
   initiation and definition of  $J_{lc}$ , 379-380  
    $J\Delta a$  curve, 382  
   steps for determination of blunting line, 386-388  
 Bolt-loaded WOL specimen, 845  
 Boundary collocation, 285  
   convergence of solution, 289-290  
   normalized crack mouth opening displacements, 291, 293, 296-298  
   normalized load-line displacements, 291, 299  
   normalized stress-intensity factor solution, 292-293  
   radius ratio effect, 291-292  
   solution method, 286-290  
   wide-range expressions, 292-299  
 Boundary collocation method, 107, 260  
 Boundary correction, 1041  
 Boundary effects, cracked bodies, 699-709  
   algorithms for computing fracture parameters, 704-705  
   crack geometries, 706  
   frozen stress analysis, 700-703  
   method of analysis, 699-703  
   Moiré analysis, 700  
   viscoelastic model, 701  
 Boundary element method, 260  
 Boundary force method, 259-277  
   accuracy and convergence studies, 266-268  
   comparison of indirect boundary element techniques, 261  
   comparisons with other solutions, 268-269  
   displacements, forces, and moments, 275  
   edge crack emanating from semicircular hole, 270  
   formulation, 262-264  
   four-hole crack specimen, 271-273  
   fundamental solution, 265, 273-275  
   influence coefficients, 263-266  
   stresses, 275  
   stress functions, 273-274  
   stress-intensity correction factors, 269-272  
   stress-intensity factors, 267-268, 275  
    normalized, 290, 294-295  
 Boundary-integral equation analysis, strip-yield model, 115-116

- Box girder, cross section, 457–458  
 Brittle crack, 473  
     behavior prediction, 52–58  
     crack closure energy, 64  
     crack velocity, 58, 60, 68–69  
     dynamic fracture toughness, 64–66  
     equations of motion, 63  
     fracture toughness, 55  
     mass-spring system, 53–55  
     numerical constants, 55–56  
     spring constants, 53–54  
     stress-intensity factor, 57–58, 60  
     temperature distribution, 52–53  
     temperature gradients, 61  
 Brittle crack propagation, 61–63  
     crack velocity, 62–63  
     ship frame structure, 51–60  
     strain distribution during, 61–62  
 Brittle failure, bulk carrier, 68, 70  
 Brittle fracture, 5, 443, 458–459  
 Brittle microcracks, formation, 569  
 Brudekin-Stone equation, 486  
 Bryte Bend Bridge, 457–460  
 BS 4360, 922  
 BS 5447, 535  
 BS 5762:1979, 334, 337, 451, 469, 471, 509,  
     517, 519, 524–525, 535–536, 538–539,  
     553, 556–557, 559, 594, 742–744, 750,  
     957, 961–962, 989  
 BS PD 6493:1980, 468–469, 471, 473, 476,  
     485, 493, 686, 688–689, 963, 975, 804–  
     805, 958, 983  
     CTOD design curve assessment, 500–501  
     fracture assessments with, 474–475  
 Buckling, 804  
 Burst tests  
     plastic collapse criteria, 972  
     wide plates, 964, 969–970  
 Butt welds, preparation, 1030
- C**
- Calibration (*see* Mode II test specimen calibration)  
 CANDU nuclear reactor, schematic, 420  
 CANDU reactor pressure tubes, fracture toughness (*see also* Zr-2.5Nb; Zircaloy-2), 419–438  
     crack driving force curve, 425  
     critical crack length, 425–426  
     data analysis, 424–426  
     J-controlled crack growth, 432–433  
     J-integral, 427  
     J-R curves, 425  
     specimen preparation, 422–423
- tensile stress, 437–438  
     test procedures, 423–426  
 Cantilever beam specimens, 845  
     K<sub>ISCC</sub> testing procedure, 856, 863–865  
     stress intensity factors, 846  
 Cantilever bending, 390, 393–394  
 Carbide particles, cracks in, 20  
 CB test, 856, 863–865  
     K<sub>ISCC</sub> testing procedure, 847  
 Center cracked panel, 690  
 Center-cracked tension, 867, 869  
 Center roller indentation, 597–598  
 Charpy energy, 243  
 Charpy impact, 622  
     prestrain, 632, 638–640, 642, 645  
     test, ductile iron, 406, 408  
 Charpy upper-shelf impact energy, 79–80  
 Charpy V-notch, 461  
     correlation of energy absorption and plane-strain fracture toughness, 454–456  
     toughness, 443  
 Chemical inhomogeneity, role, 531  
 Cladding, 40  
 Cleavage, 5  
     facets stopped at MnS particles, 528, 533  
     initiation of facet from silicate particle, 531, 534  
     Ritchie-Knott-Rice model, 11, 13  
     size effects, 536  
     steel, crack-tip failure, 11, 13–17  
 Cleavage microcracks, 574–575  
     via acoustic emission, 13  
     within shear zone, 569, 578  
 Cleavage toughness, 19–32  
     ductile tear region, 23, 25  
     experimental methods, 20–21  
     facets with inclusions at focus of river markings, 23–24  
     failure probability, as function of, 29–30  
     J-integral, 21–22  
     load and potential drop against load-line displacement, 20–21  
     statistical interpretation of variability, 26–30  
     yield strength dependence, 29–30  
 Clip gage measurements, load-line deflection calculations, 356–358  
 CMOD, 136, 547, 730  
     measurement, 915–917  
     normalized, 291, 297–298  
     relation to load-line displacement, 358  
     residual, 905–906  
     small cracks, 896–911  
         compliance and closure measurements, 901–909  
         interferometric displacement gage, 899–901

- CMOD (cont.)**
- small cracks (cont.)
    - material, 898
    - procedure, 898
  - versus CTOD, 547-548
  - versus load, 547-548, 902
- CMOD gauge**, 157
- COD**, 555, 953, 986
- contour integral relationship, 990-991
  - crack-tip deformation, 938-939, 942
  - CTOD relationship, 490-491
  - drop and characteristic defect lengths, 497
  - effect of weld metal matching, 499
  - evaluation with crack growth, 987-990
  - gross stress and strain, 486-487
  - gross strain relationship, significance, 490-491
  - interaction with weld metal stress-strain, 489
  - testing, 334
  - versus crack tip energy release rate, 1079-1081
  - versus gross strain, 497, 499
  - versus load, 886, 892
  - versus unloading compliance load, 652
  - weld metal
    - in tension, 486
    - overmatching effect, 494-496
- Colinear VCE technique**, 302, 322, 324, 326
- Compact specimen**, resistance curve method, 105-107, 109-111
- Compact tension testing**, acoustic emission, 13-14
- Compliance**, 752, 1083, 1086
- calibration functions, 585-586
  - curves, interpretation, 923-924
  - Mode I, 1087
  - Mode II, 1086
  - versus crack length, 903
- Composites**, 5
- Concrete composites**, crack-tip failure, 11-12
- Constant-amplitude fatigue tests**, 773, 778
- Contour integral**, 679, 682, 730, 742, 986
- direct evaluation, 735-737
  - evaluation with crack growth, 987-990
  - far field, 996
  - independent of crack growth, 993-998
    - definition choice, 993-995
    - experimental evidence, 995-998
  - modified, 993-994, 996-997
  - nonlinear elastic definition, 1002
  - relationship with COD, 990-991
  - remote, 1077
  - steady-state condition, 991, 993
  - three parameter technique, 1001-1002
- Corner-type crack cases**, model geometry, 791
- Corrected compliance**, 600
- Crack**, 103
- finite plate, 262
- geometry, 520
- infinite sheet, 251
- process zone model, 6
- secondary, 528, 532
- shape, 1050
- size, 695-696, 982
- surface, following stress state, 771
- threshold levels, 881-895
- load versus COD, 886, 892
  - materials and procedures, 882-884
  - opening load, 886, 892-893
  - R-ratio effects, 888-890, 893
- Crack advance**, 376
- Crack angle**
- versus elastic buckling strength, 807, 809
  - versus number of load cycles, 809-810
  - versus torsional stiffness, 807, 809
- Crack arrest**, 37, 223
- bulk carrier, 69, 71
  - ferritic steel, 223-224
  - role, 47
  - ship frame structure, 51-60
- Crack arrester**
- duplex double tension test, 61-62, 65, 67
  - duplex-type, 60-68
- Crack-arrest resistance**, 74
- Crack arrest toughness** (*see also* 7075-T6 aluminum alloy; High-temperature crack-arrest toughness)
- dependence on
- initiation stress intensity, 230-234
  - normalized crack jump, 231, 234
  - normalized final crack length, 232, 234
  - normalized remaining ligament, 232, 234
  - specimen thickness, 231-232
- statistical data, 233
- versus crack jump, 234-235
  - versus temperature, 69-70
  - undercalculation of values, 84
- Crack branching**, propensity for, 926
- Crack closure**, 821, 881, 906, 909, 934
- aluminum alloys, 926-928
  - asperity-induced, 914, 925
  - energy, 64
  - experimental determination, 897
  - ferrous alloys, 926-927
  - load-displacement curve, 916-917-923
  - load versus length of small crack, 902-904
  - maximum stress intensity factor effect, 925
  - measurement, 931-928
    - back-face strain, 917-918, 924
    - CMOD, 915-917
    - crack tip compliance gages, 921
    - d-c potential drop method, 918-919
    - direct optical, SEM, and TEM measurements, 920-921
    - effective threshold method, 918

- indirect thickness-averaging techniques, 918–919
- interferometric techniques, 919–920, 922
- interior measurement techniques, 922
- interpretation of compliance curves, 923–924
- near-crack-tip surface measurement techniques, 919–923
- push rod compliance technique, 922
- standardization of measurement techniques, 924
- techniques, 915
- thickness-averaging compliance techniques, 915–918, 928
- ultrasonic and acoustic techniques, 919
- mechanisms, 897
- Mode III, 829–830, 832
- plasticity-induced, 914
- primary mechanisms, 834
- René 95, 192–204
  - closure load dependence on applied maximum stress-intensity factor, 196
  - experimental approach, 193–194
  - $K_{cl}$  as function of  $K_{max}$ , 197–199, 203
  - oxide-induced closure, 202–203
  - percent closure, 195–197, 202–203
  - representing closure data, 194–199
  - roughness-induced closure, 197–199, 203
  - specimen thickness effect, 199–200
  - threshold, 200–202
- residual compressive stresses, 1078
- roughness-induced, 914, 925
- small cracks, 897
- steady-state condition, 1075
- three-dimensional nature, 922–923
- titanium alloys, 927–928
- variability and mechanisms, 925–928
- work calculation, 1072
- Crack-closure factor, 784
- Crack driving force curve, 425
- Cracked beam column, 805
- Cracked body, 715
- Cracked plates, boundary force method (*see* Boundary force method)
- Crack extension, 378, 402
  - analysis, J-integral, 682–684
  - comparison of predicted and measured, 603–605
  - determination of moment of, 408
  - fractional damage, 648
  - Mode II, 825
  - Mode III, 824–825, 830, 832, 840
  - prediction, 603–606
  - total, 648
  - virtual, 305, 322
  - zirconium alloys, 427
- Crack faces, stress-free conditions, 261
- Crack front
- curvature
  - final stress intensity factor relationship, 854, 859
  - specimen compliance effect, 588–589
  - shape parameters, 588
  - tunneling, 587
- Crack geometries, 137–138
- Crack geometry correction factors (*see also* Plasticity effect)
- Crack growth, 181, 380, 583, 757–763, 867, 913, 934, 986, 1050
  - advance, 1034
  - aluminum alloy specimens, 110–111, 113–114, 1063–1064
  - as function of  $K$  and  $K_{eff}$ , 200–201
  - baseline data, 773
  - bend specimens, 674
  - contour integral and COD evaluation, 987–990
  - from corner flaws, open-hole specimens, 1063–1064
  - correlation with crack-tip strain, 934, 948
  - criterion, 993
  - cyclic, 647–648, 1070–1081
    - analytical procedure, 1073–1077
    - background, 1071–1073
  - determination from J-R curve testing, 603
  - from embedded flaws, 1065–1066
  - experimental and finite-element analyses, 670
  - experimental and mixed state-of-stress analyses, 672
  - high cycle properties, 659
  - J-controlled, 432–433, 990–993, 1009
  - mechanisms, 192
  - minicompact tension specimen, 758
  - Mode II, stress threshold, 125, 128
  - Mode III, 821, 825–828
    - modeling technique, 208–212, 1019–1021, 1075–1076
    - necessary conditions, 907–908
    - precrazing, 759
    - procedures, 758–759
    - retardation, 181, 934
    - root radii, 765–779
      - analytical stress intensity factors, 767–768, 771–773
      - constant-amplitude fatigue tests, 773, 778
      - continuity conditions, 768
      - idealized geometry of skin with lands, 771
      - integral equation solution, 772
      - specimens, 766–767, 769
      - spectrum loading fatigue tests, 778–779
      - stress intensity factors, 773–777
      - testing, 766, 769–770
      - secondary cracking, 760, 762

- Crack growth (*cont.*)**
- simulation, 592
  - stable, 1005
  - superposition model, 656, 658, 660
  - threshold, 788, 833
  - versus CTOD, 344–345
  - welded structure, 730
- Crack growth rate**
- comparison of Mode III and Mode I, 826–827
  - input for crack-growth analysis, 592
  - Mode III, 830, 832, 835
  - modeling, 206
  - 300 M steel, 784–785
  - opening load and, 936, 938–939
  - René N4, 759
  - stress corrosion, 851–852
  - superimposed axial load effect, 832, 836
  - superimposed torsional load effect, 833, 837
  - versus applied stress intensity factor, 884–886
  - versus effective stress intensity factor, 905, 908–909
  - versus  $\Delta K_{\text{EFF}}$ , 915
  - versus remote  $\Delta K$ , 914
  - versus stress intensity factors, 759–760, 851–852, 904–907
- Crack-growth resistance**
- Dugdale model, 105–106
  - aluminum alloy compact specimens, 107–109
- Crack initiation**, 374, 443–449, 555, 1005, 1025
- corrosion, from notches, 445, 449
  - d-c potential-drop technique, 337, 341–342
  - ductile, 569, 578
  - elastic-perfectly plastic material, 6–7
  - process, 563, 569, 577–578
    - at crack tip, 555–556
  - sequence, 563, 577
  - steel shaft fracture, 446
  - threshold dependence on yield strength, 444
- Crack jump**, 223, 473
- Crack length**
- collapse-modified strip yield model, 972
  - critical, 425–426, 432
  - from d-c potential data, 870, 872
  - equivalent versus critical, 526–528
  - initial, 615
  - $K_{\text{ISCC}}$  testing procedure, 850–851
  - load eccentricity, 815
  - load-lateral deflection relations, 816
  - versus compliance, 903
  - versus crack closure load, 902–904
- versus elastic buckling strength, 808, 810–811
  - versus maximum load, 812, 814
  - versus number of cycles, 810–811
  - versus stress intensity factor, 890–891
  - versus torsional stiffness, 807–808
- Crackline loading**, 1056–1057
- Crack mouth compliance**, 585–586
- Crack mouth opening, wide-range expressions**, 296
- Crack mouth opening displacement** (*see CMOD*)
- Crack opening angle**, 993
- Crack opening displacement** (*see COD*)
- Crack opening load, versus distance behind crack tip**, 920
- Crack opening stress, distribution**, 549–550
- Crack propagation**, 237, 390, 443, 445–446, 449–452, 647, 781, 821–840, 896, 1025, 1050
- brittle** (*see Brittle crack propagation*)
  - crack closure mechanisms, 834
  - crack surface interference, 829–833
  - crack tip fields, 822–824
  - criterion, 301
  - cycle Mode I with steady Mode III, 833, 837
  - effect of single positive overloads on Mode III and Mode I cracks, 838–839
  - environment effects, 451
  - fatigue life, 1034
  - fractography, 827–829
  - Mode III crack growth behavior, 825–827
  - models, 837–838
  - power-law relationship, 445
  - self-similar, 301
  - stages, 450, 452
  - test program, 2024-T351 aluminum alloy plates, 1063
  - torque lost to friction, 832–833
  - variable-amplitude loading, 838–840
  - variation of growth rate with stress intensity factor fluctuation, 445, 449
- Crack propagation rate**
- Mode III, 832, 836
  - open-hole specimens, 2024-T351 aluminum alloy, 1063–1064
- Crack tip**
- blunting, 172, 337, 378, 384–386
  - collapsed-node structure, 1075
  - element geometry, 545–546
  - fields, 822–824
  - mesh structure, 1074–175
  - modeling, 545–546
  - plasticity, 934
  - plastic zones, 184–185
  - pressure, 238

- primary location, 1076  
 profile, 378  
 strains, 939, 943, 951  
 stresses, due to in-plane loading, 437–438  
 stress field, 87  
 stretch zone measurements, 384–385  
 zone sizes, growing creep cracks, 874
- Crack tip compliance gages**, 921
- Crack-tip deformation**, 934–953  
 COD, 938–939, 942  
 crack tip strains, 939, 943  
 cyclic load application, 936–937, 940  
 overload and underload cycles, 937–938, 941  
 procedures, 935–936  
 residual stress fields, 943, 946, 948–951
- Crack tip displacement**, 826–287
- Crack tip displacement model**, 837
- Crack tip energy release rate**, 1070–1071  
 calculation, 1071–1072  
 case of 8-noded finite elements, 1073  
 versus COD, 1079–1081  
 versus remotely applied J-integral, 1079
- Crack-tip failure**, 5–18  
 discontinuous microfracture zone approach, 15–16  
 elastic and elastic-plastic approaches, 16  
 macroscopic process zone, 11–12  
 microscopic process zone, 11, 13–17  
 stress intensity, 15  
 theoretical model, 6–11  
 weakest-link models, 11, 13, 19, 26
- Crack tip opening**, 555
- Crack-tip opening angle**, 6–7, 9
- Crack-tip-opening displacement** (*see* CTOD)
- Crack velocity**, 238  
 beyond weld seam, 62  
 calculated and measured, 58, 60  
 fracture toughness as function of, 64–67  
 measured and calculated, 68–69  
 variation, brittle crack propagation, 62–63
- Creep, MENT specimen**, 872, 874
- Creep-crack growth**, 867–877  
 $C^*$  parameter, 873–876  
 crack growth measurement, 868, 870–872  
 equipment, 868  
 material, 868  
 specimen preparation, 868–870
- Crosshead displacement**  
 load-line deflection calculations, 355–356
- CSA Z184**, 688
- CTOD**, 31, 376, 378, 485, 505, 516, 665, 823, 913, 934  
 analytical relationship with J-integral, 750–753  
 bend bar specimen data, 519, 523–524
- bend specimens, 750–751  
 correlation with crack-tip strain, 941–942, 947
- correlation with stress intensity factor, 456  
 crack flank intercept, 546  
 versus crack growth, 344–345  
 crack growth criterion (*see also* Elastic-plastic finite-element analysis), 669  
 critical, 475, 519, 521, 538, 669, 681  
 bend bars, 524  
 ductile crack initiation, 569  
 as function of temperature, 559, 561  
 temperature transition range, 523  
 weld metal, 560  
 wide plates, 525
- cyclic, 821–822
- d-c potential-drop technique, 337, 339, 344–345
- deepest crack extent, 695
- defined, 545–546
- derivation, 508
- direct SEM observation, 921
- elastic and plastic, 688, 752–753
- elastic-plastic correction curves, 691, 693–694
- elastic-plastic estimation formula, 690
- engineering estimates, 744
- failure analysis diagram, 961
- fracture toughness, 509, 511–512, 514
- increase with crack length, 697
- lowest experiment values, 543
- misconceptions, 743
- Mode III, 824
- normal distribution statistics, 543–544
- oxide-induced closure, 202
- plastic, ratio to plastic J-integral, 746–747
- plastic zone size, 550–552
- ratio of PSF-factors, 691
- relationship with COD, 490–491
- relationship with J-integral, 743–748
- relationship with strain, 153
- SEN geometry, 690–692
- temperature, 540–541
- temperature transition curve, 541
- toughness (*see also* Fracture toughness, comparison of J-integral and CTOD; Strip yield model), 690–691
- versus applied stress, 479–480
- versus CMOD, 547–548
- CTOD approach**, 468–483  
 binomial method, 474  
 critical value, 471  
 fracture toughness, 469–474  
 load versus clip gage displacement traces, 471–472  
 scatter in data, 473–474

- CTOD approach (*cont.*)  
surface notches, 470
- CTOD design curve, 473, 476–477, 485, 524–527, 686, 688  
crack geometries, 687  
drawbacks, 958  
elastic correction curves, 689  
equations, 963  
failure assessment in terms of, 477–478  
PD 6493, 500–501
- CTOD toughness, A36 steel, 535–553  
material properties, 537–538  
procedure, 538–540
- Cubic spline fit, 798
- Curvature factor, 588
- Curved specimens, 419
- Curving crack (*see* Stress field, curving crack)
- Cyclic hardening, 622
- Cyclic loading, 1070
- Cyclic softening, 622
- D**
- Damage accumulation model, 837–838
- Damage tolerance, 781, 840
- Data scatter, 19
- d-c potential-drop method, 333–346, 868, 870–871, 918–919  
across crack mouth of curved compact specimens, 423–424  
advantages in transition area, 341  
calibration data, 870–871  
concepts, 335–336  
crack initiation, 337, 341–342  
crack-tip opening displacement, 337, 339, 344–345  
J-integral, 337, 339–340  
multiple-specimen method, 346  
R-curves, 337, 340–341, 343–344  
single-specimen method, 338  
stress intensity factors, 339
- Defect aspect ratio, 695
- Defect length, tolerable and allowable, 498
- Defect size (*see* Flaw size)
- Deformation, Mode II, as function of crack length and loading case, 122–123
- Deformation correction factor, 591–592
- Deformation theory, 679–680, 987, 996 modified, 676–678
- Delamination, 528, 532–533
- Delayed hydride cracking, 421
- Delay times, 189
- Differential compliance techniques (*see* Unloading compliance technique)
- $D_{ijk}$  coefficients, 1061
- Direct current potential drop, 134, 136, 138  
J-integral resistance curve, 140–141, 143–145, 148
- Discontinuous microfracture zone approach, 15–16
- Dislocations, planar bands, 760
- Displacement, 103  
boundary force method, 275  
measurement methods, 1085
- Divergence theorem, 716
- Double-cantilever beam, R-curve behavior, 12
- Ductile failure assessment, 1005–10021  
approximate analysis, 1007  
calculated instability loads and experimental failure loads, 1017–1019  
calculated tearing instability stresses, 1019–1020  
critical loads, 1007–1008  
finite element analysis, 1007  
influence of crack growth model on accuracy, 1019–1021  
influence of material input data on accuracy, 1007–1015  
influence of structural modeling on accuracy, 1015, 1017–1019  
principle, 1005–1006
- Ductile fracture, 443, 957, 1005  
paths, 561–575  
R-curve, 10–11  
recommended assessment procedure, 982–983
- welded pipe, 134–149  
background, 135  
compact tension specimen tests, 139  
crack geometries, 137  
direct current potential drop, 136, 138  
elastic compliance technique, 138  
J-integral resistance curve (*see* J-R curve)  
load versus line displacement records, 145  
materials, 135–136  
normalized pipe compliance, simple and complex crack geometries, 138  
pipe loading configuration, 136  
pipe specimen tests, 135–139
- Ductile iron (*see also* Fracture toughness, ductile iron)  
ductile-to-brittle transition temperature shift, 417  
graphite nodule role, 416–417  
J-R curve, 414–415  
microstructure, 407
- Ductile ligaments, 5
- Ductile microcracks, 569  
formation, 563, 577  
stress intensification at tip, 569
- Ductile tearing, 23, 25, 374, 379, 661
- Ductile-to-brittle transition, 555–579, 622  
absence of shear zone, 568

crack initiation process, 563, 569, 577–578  
 curves, 556  
 ductile crack initiation resistance, 569, 578  
 ductile fracture paths, 561–575  
 ductile iron, 417  
 formation of ductile microcracks, 563, 577  
 fractography, 559–563  
 fracture surface, 559–560, 562  
 fracture toughness, 559–563  
 materials and procedure, 556–557  
 optical microscopy, 557–559  
 orientation of specimens, 557  
 relative orientation of stretch and shear zones, 560, 564–567  
 shear and stretch zone characteristics, 561  
 shear crack profile, 561, 574  
 shear zone size variation, 561, 570–573  
 specimen geometry effect, 569, 574–575  
 stretch zone width, 561, 576  
 temperature, 19, 516, 523  
 void growth rate, 563  
**Dugdale model (see Strip yield model)**  
**Duplex double tension test, 61–62, 65, 67**  
**Duplex-type double tension test, different behaviors observed, 65, 67**  
**Dynamic tear, 405**  
 ductile iron, 408

**E**

**Eccentricity, geometric definition, 303, 305**  
**Eccentric loading, 301**  
 effects on weight function, 306, 308  
 finite element mesh, 305–306  
 stress intensity factor effects, 312–313, 327–329  
 three-point bend specimen, 302–303  
**Edge crack, 247**  
 half-space under pair of point loads, 249  
 from semicircular hole, boundary force method, 270  
 stiffened panel with broken stiffener, 248  
 stress-intensity factors, 254–255  
**Edge-sliding mode, 1083**  
**Effective compliance, 615**  
**Effective modulus, 611, 614–617**  
**Effective modulus of elasticity, 586–587**  
**Effective spring modulus, 1056**  
**Effective thickness, 586–587**  
**Effective threshold method, 918**  
**Eigenfunction problems, 699**  
**Elastic analyses, J-integral, 681–683**  
**Elastic buckling strength**  
 versus crack angle, 807, 809  
 versus crack length, 808, 810–811  
 versus number of load cycles, 809–810, 812

**Elastic compliance, 134, 138**  
**J-integral resistance curve, 140–144, 148**  
**Elastic load point displacement, 751**  
**Elastic modulus, 1056**  
**Elastic-plastically deformed SENB specimen, theoretical and actual compliance, 590**  
**Elastic-plastic finite-element analysis, 665–684**  
 computations, 593  
 experimental and calculated maximum loads, 673  
 finite-element simulation of fracture, 669–675  
**J-integral, 669, 682–684**  
**J-R curve evaluations, 676–678**  
**Elastic-plastic fracture, 516, 583, 647**  
**Elastic-plastic fracture mechanics, 118, 535, 622, 686, 713**  
**Elastic-plastic models, comparison, 979**  
**Elastic unloadings, 647–662**  
 analysis, 647–650  
 crack growth superposition model, 656, 658, 660  
 fractographic analysis, 659–662  
 high-cycle crack growth rate tests, 655–656, 659  
**J-R curve tests, 651–653**  
 cyclic, 651, 653–655  
 material, 651–652  
 specimen limit load, 648  
 stress-intensity factor, 648–649  
 study objectives, 650  
**Elastodynamic crack, 88**  
**Elastoplastic analysis, 957**  
**Electrodes, chemical composition, 1028**  
**Elevated temperature, 757**  
**Elevated-temperature fatigue, 206–219**  
 baseline data, 213–214  
 crack growth modeling (*see also* MSE model; SINH model), 208–212  
 application, 211–212  
 comparison of models, 210–222  
 effectiveness in predicting crack growth, 217–218  
 predicted and experimental results, 215–217  
 procedure, 212  
 variations in hold time, 217–219  
 experimental program, 207–208  
 specimens and procedures, 208  
 test matrix, 207–208  
**Elliptical cracks, 1051–1052**  
**Elliptical discontinuities, 1040–1042**  
**Embedded-type crack cases, model geometry, 791**  
**Energy release rate, dynamic, 58**  
**Engine structural integrity program, 206**

- Equations of motion, 63  
 Equilibrium equation, 716  
 Euler beam theory, 355  
 Explicit weight functions, 301–329  
     advantage of concept, 304  
     along LHS-face and RHS-face locations, 319–321  
     along top face, 307, 309  
     characteristics at potential traction application boundaries, 304  
     colinear VCE technique, 302, 322, 324, 326  
     comparison of directed and indirect approaches, 319, 324  
     decoupled, 302  
     eccentric loading effects, 306, 308  
     function of  $a/W$  for, 306–307  
     least-squares fitted coefficients  
         Mode I, 310, 316  
         Mode II, 311, 317  
     Mode I and II, crack-face, 312, 314–315  
     nodal, 304, 319  
     normalized stress intensity factors, 319, 322  
     Rice's displacement derivative representation, 302  
     secondary crack-face components, 312, 318  
     stress intensity factors, calculation under different constraint conditions, 319, 323
- F**
- Fabrication discontinuities, 1025–1048  
     background, 1026  
      $B_{ijk}$  coefficients, 1060  
     boundary correction, 1041  
     butt weld preparation, 1030  
     cycles to failure  
         lack-of-penetration discontinuities, 1046–1047  
         slag/lack-of-fusion discontinuities, 1047–1048  
      $D_{ijk}$  coefficients, 1061  
     elliptical discontinuities, 1040–1042  
     fatigue life data, 1029–1033  
     fine-tuning curve-fitting function, 1042  
     finite-width correction, 1042  
     fracture mechanics methodology, 1030, 1033–1040  
     lack-of-penetration discontinuity analysis, 1040–1043  
     materials and specimen preparation, 1026–1028  
     Peterson's equation, 1038  
     procedure, 1028–1029  
     slag/lack-of-fusion discontinuities analysis, 1043, 1045–1046
- through discontinuity, 1042  
 zero-to-tension stress condition, 1040  
 Factory-roof fracture, 828–289, 831  
 Failure  
     Mode II, 118  
     terms of CTOD, 477–478  
     torsional, 827–829  
 Failure analysis (*see also* Ductile failure assessment; Fracture mechanics), 433–466  
     Bryte Bend Bridge, 457–460  
     Ingram barge, 462, 464–465  
     loading rates, 461  
     problems in investigations, 458, 461–466  
 Failure analysis diagram, 960–961, 1007  
 Failure assessment diagram, 1007  
 Failure loads, single-edge crack tension specimens, 112  
 Failure probability, 29, 175  
     elemental, 26, 28  
     function of toughness, 30  
 Fastener forces, equations for determining, 248–249  
 Fastener holes, flaws at, 1050  
 Fatigue/cleavage interface, 13  
 Fatigue crack propagation, 192  
 Fatigue damage, 660–661  
 Fatigue initiation life  
     versus initial stress intensity, lack-of-penetration discontinuities, 1045  
 weldments, 1032  
 Fatigue life  
     crack propagation, 1034  
     fabrication discontinuities, 1029–1033  
     versus initial stress intensity, 1043–1045  
     versus nominal stress times, 1044, 1046  
 weldments, 1032  
 Fatigue precracked Charpy, 405  
 Fatigue precracking, 391–393  
     ductile iron, 406  
 Fatigue thresholds, 821  
 2024-FC aluminum alloy,  $J$ - $\Delta a$  curve, 382  
 Ferrite/pearlite steels, fracture toughness predictions, 17  
 Ferritic steel  
     acoustic emission, 13–14  
     crack arrest, 223–224  
 Ferrous alloys, crack closure behavior, 926–927  
 Finite element analysis, 260, 278, 535  
     adhesive joints, 281  
     A36 steel, 544–552  
     crack opening stress, 549–550  
     CTOD versus CMOD, 547–548  
     3-D model, 545–547  
     ductile failure assessment, 1007

- load versus CMOD, 547–548  
 mesh for three-point bend specimens, 545  
 mixed-mode failure of aluminum alloys, 120–122  
 plastic zones, 550–552  
 strip-yield model, 116–117  
 three-point bend specimens, 587–590  
**Finite-element model, single-lap joint with applied loads**, 281–282
- Flaw**, 39  
 critical depth, 48  
 density, 40–42  
 geometries, definition, 1052  
 idealization, 1054–1058
- Flaw size**  
 comparison, 479, 482  
 effective, 479  
 effective initial, unflawed specimens, 1038–1039  
 standard NDE, 795  
 tolerable, weld metal matching, 493, 497
- Flex bar, load-line deflection measurements**, 354–355
- Flow stresses**, 963
- Forces, boundary force method**, 275
- Forman equation**, 773  
 modified, 783
- Four-hole crack specimen, boundary force method**, 271–273
- Fractional damage**, 648
- Fractography**, 555, 757  
 crack propagation, 759–763, 827–829  
 ductile-to-brittle transition, 559–563  
 elastic unloadings, 659–662  
 long and short crack tests, 893–894  
 Mode III failures, 822  
 wide plates, in bending, 527–531
- Fracture**, 151  
 criterion, 278  
 finite-element simulation, 669–675  
 most probable distance, 31  
 potential initiating sites, 19
- Fracture appearance transition temperature**, 622, 632, 642  
 versus flow strength, 642, 645
- Fracture design**, 516
- Fracture mechanics**, 192, 247, 285, 443, 468, 730, 757, 781, 867, 896, 957, 986, 1025, 1050  
 correlation of various fracture parameters, 454–458  
 crack initiation, 444–449  
 crack propagation, 445–446, 449–452  
 fracture toughness, 451, 453–454  
 methodology, 1030, 1033–1040  
 model, 36–40
- Fracture parameters**, 704–705, 1057–1058  
**Fracture process zone**, 722
- Fracture properties**, 516
- Fracture resistance**  
 blunting-line equation (*see* Blunting-line equation)  
 critical, 366  
 effect of uncertainty in crack growth measurement, 381  
*geometry effect* (*see also* Resistance curve method), 505–515  
 effect of crack depth to plate thickness ratio, 511, 513  
 fracture toughness tests, 507, 509  
 initiation of stable crack growth, 512, 514  
 large wide plates, 506–507  
 materials, 505–506  
 notch geometry effect, 510–514  
 plate thickness effect, 509–510  
 small wide plates, 507–508  
 stress concentration effect, 512, 514–515  
 stress intensity factor and stress concentration, 514–515  
 variation in critical bending strain ratio with aspect ratio of surface crack, 510–512
- Fracture risk assessment**, 468–483  
 comparison of assessment equations, 479–480
- CTOD design curve**, 477, 524–527
- PD 6493**, 474–475  
 reference stress method, 478–479  
 strip yield model, 477–478  
 three-tier approach, 475–479, 483
- Fracture stress, relation with particle size**, 28
- Fracture surfaces**  
 ductile-to-brittle transition, 559–560, 562  
 fatigue damage and ductile tearing, 661  
 heat-tinted, 619  
 notches of MENT specimen, 872–873  
 oxidation, 763  
 WOL specimens, 855
- Fracture test**, 516, 583
- Fracture toughness**, 5, 73, 151, 164, 223, 374, 443, 451, 453–454, 535, 583, 622, 957  
 A533B steel, 967  
 AISI 4340 steel, 849  
 aluminum alloys, 120, 785–786  
 API 5LX56 steel, 967  
 arrest toughness, 37  
 ASTM A 710 grade A class 3 alloy steel, 155  
 brittle crack, 55  
 changes, 56–57  
 cladding material, 38  
 cleavage, temperature dependence, 172–173

- Fracture toughness (*cont.*)**
- comparison of J-integral and CTOD, 741–753
  - analytical comparisons, 745–748, 750–753
  - application to design, 748–750
  - comparison of J-integral and CTOD, (cont)
  - critical J-integral, 748–749
  - qualitative comparisons, 745–746
  - conversion of critical values of  $J$ , 172
  - crack growth onset, 129–130
  - crack tip, 69, 71
  - crack velocity and temperature, 56–57
  - critical, 620
  - CTOD approach, 469–474
    - interpretation of results, 471–473
    - pop-in, 473
    - weldment testing, 469–471
  - ductile iron, 405–417
    - Charpy impact test, 406, 408
    - compact tension specimens, 408
    - data analysis, 408–410
    - dynamic tear tests, 408
    - fatigue post-cracked, 411, 414
    - fractured surface, 416–147
    - load-displacement record for quasi-statically loaded dynamic tear specimen, 414–415
    - quasi-static and dynamic, 410–413
    - specimen preparation, 406
  - ductile-to-brittle transition, 559–563
  - dynamic, 64–65, 68
  - effects of cyclic prestrain, 641
  - elastic and plastic components, 409
  - experimental parameters, 175
  - function of cleavage fracture stress, 13
  - function of crack velocity, 64–67
  - high-temperature testing system, 393, 396–397
  - J-R curves, 627–629, 634–635
  - J-T diagram, 629, 636–637
  - LT60 steel, 171
  - maximum, A36 steel, 540, 542
  - mixed-mode loading, 131
  - Mode I, 124–125
  - Mode II, 118
  - monotonic prestrain effects, 641
  - plane-strain, 415, 453–454, 786
    - correlation with Charpy V-notch energy absorption, 454–456
    - yield strength effect, 453, 455
  - prediction, 9–10, 15–17
  - prestrain history effects, 622, 632, 640–644
  - properties, 627–629, 632
  - relation between static and dynamic, 458, 461
  - relationship with yield stress, 174–175
  - scatter in data, 473–474
  - static crack initiation, 37
  - strain hardening exponents, 13
  - terms of J-integral, 160
  - testing, 285
  - test matrix, 557
  - thickness dependence, 164, 176
  - type 316 stainless steel, 967
  - variability, 19
  - variation, 64–66
  - weakest link theory, 536
  - wide plates, 507, 509
  - Zircaloy-2, 427, 434–436
  - Zr-2.5Nb, 427–433
- Fracture toughness testing**
- equipment, 393, 396–398
  - prestrain, 626
- Friction force, 595**
- Fringe pattern, unmultiplied photoelastic, 702–703**
- Frozen stress analysis, boundary effects, 700–703**
- G**
- Gamma prime, distributions, 194
  - Gas decompression**
    - curves, 240
    - velocity, 238–239, 244
  - $G_{ijk}$  coefficients, 1062
  - Global release rate, 1070**
  - Global strain, 517**
  - Grains, volume fraction fracturing, 14–15
  - Green's function, stress-intensity factors, 302
  - Griffith relation, 19
- H**
- Half-space, subjected to concentrated loads, 256–257**
  - Hardening exponent, 386–387**
  - Heald-Spink-Worthington model, collapse-modified, 959**
  - High-cycle crack growth rate tests, 655–656, 659**
  - High-temperature crack-arrest toughness, 73–85**
    - cylinders subjected to thermal shock, 79
    - duplex specimens, 74–76
    - limiting temperature, 78–80
    - lowered arm friction, 76–77
    - materials, 76–77
    - onset of Charpy upper shelf, 79–80
    - positive stress-intensity gradient, 75

temperature dependence, 80–81  
 using different specimen designs, 78–79  
 using inverted-split-pin loading, 81

Hoop stress, 737–738

Hot-rolled structural steel, 516

HT 60 steel, stretch zone measurements, 385

HT 80 steel, stretch zone measurements, 385

Hutchinson-Rice-Rosengren singularity, 26–27, 716–717, 726

Hydride morphology, Zircaloy-2, 434

Hyperbolic sine equation, *see* SINH model

HY 130 steel

- J-R curve, 668
- R-curve, 998–999
  - drooping, 991–992

Hysteresis loops, cyclic, 946

**I**

Inclusions, 19

- longitudinal and transverse sections, 529
- river markings focus, 23–24
- role, 528, 531–534
- size distributions, 23, 25–26

Inconel 718

- heat treatment, 183
- overload effects, 181–191
  - analytical model, 184–189
  - crack advance during sustained load, 189–190
  - crack-growth rate, 183–185, 187–189
  - delay times, 189
  - determination of constants, 187–189
  - experiments, 182–183
  - linear cumulative damage model, 182
  - loading spectrum, 182
  - overload ratio, 187
  - plastic zones at crack tip, 184–185
- Indentation correction factor, 598
- Indirect thickness-averaging techniques, 918–919
- Influence coefficients, 249–253
  - boundary force method, 263–264
  - calculations, 265–266
- Ingram barge, 462, 464–465
- Initiation toughness

  - data, 381
  - predictions of nominal stress, 978
  - varying, 382
  - Zr-2.5Nb, 433

- Integral equation, 247, 765
  - solution, 253–254, 772
- Integrated Pressurized Thermal-Shock Program (*see* Probabilistic fracture mechanics)
- Interferometric displacement gage, 899–901

Interferometric techniques, 919–920

Interferometry, 922

Interior measurement techniques, 922

Inverted-split-pin loading, 80–81, 83

Iron, ductile (*see* Ductile iron)

Irradiated specimens, 390

**J**

J-integral, 21–22, 118, 134, 164, 333, 390, 427, 536, 665, 742, 1071

- analytical relationship with CTOD, 750–753
- application to residual strength prediction of pressure vessel, 731–733
- calculation methods, 679–680
- compact and bend specimens, 676
- contour integral, 679
- corrected to give gross section of yielding contribution, 160–161
- critical, 748–749
- d-c potential-drop technique, 337, 339–340
- defined, 121
- deformation theory, 679–680
- determination from J-R curve testing, 602–603
- different pressure levels, 738
- direct measurement, 730–739
  - contour integral, 735–737
  - path and instrumentation applied, 734–735
  - precracked pressure vessel, 733–735
  - sealing cables, 734–735
- elastic analyses, 681–683
- elastic and elastic-plastic evaluation, 681–684
- elastic-plastic and crack-extension analyses, 682–684
- elastic-plastic finite-element analysis, 669
- engineering estimates, 744
- function of remote strain, 152, 158–160
- function of strain, 160–161
- Gurtin's 719–720
- maximum, fracture angle, 132–133
- m* factor, 745–747
- misconceptions, 743
- modified, 626, 631–632
- notched tensile panels, 752
- path, 121
- path-independent integrals (*see* Path-independent integrals)
- pipe specimens, 136–137
- plastic, ratio to plastic CTOD, 746–747
- versus pressure, 737–738
- Ramberg-Osgood curve, 152–153, 159
- relationship with CTOD, 743–748

- J-integral (*cont.*)**
- remotely applied versus crack tip energy release rate, 1079
  - residual strength prediction, 732, 734
  - Rice's 735
  - testing, 334
    - modified compact specimen, 652
    - thermodynamic background, 718–719
    - variation in total potential energy, 680
  - Wilson and Yu's, 717–719
  - Wilson bilinear curve, 152–153
- J\*-integral, 721–722, 726**
- J-integral, 722–723**
- J-integral resistance curve**
- compact tension specimen, 146–147
  - comparability of pipe and compact specimens, 147–149
  - complex crack geometry pipe specimen, 142–146
  - simple crack geometry pipe specimen, 140–142
- Joint factor, 283**
- J-R curve (*see also* Elastic unloadings), 419, 622, 666–667**
- baseline unloading compliance, 653
  - compact tension specimen, 146–147
  - comparability of pipe and compact specimens, 147–149
  - complex crack geometry pipe specimen, 142–146
  - cyclic damage removed, 656, 660
  - cyclic hardening effects, 658
  - deformation theory, 676–678
  - ductile iron, 414–415
  - elastic-plastic finite-element analysis, 676–678
  - failure assessment using, 1006
  - irradiated reactor pressure tubes, 425
  - material, 1015–1017
  - plane-strain, 666
  - precracking, 400–403
  - prestrain history effect, 626–627, 632, 634–635, 640–641
  - scatterbands, 658
  - simple crack geometry pipe specimen, 140–142
  - using contour integral, 678
  - variation effect on ductile failure assessment, 1015–1016
  - Zircaloy-2, 436
  - Zr-2.5Nb, 427, 429–431
- J-R curve testing, 347–373, 583–608**
- analyses, 584–585
  - center roller indentation, 597–598
  - compact tension testing, 349, 366, 370–372
  - compliance calibration functions, 585–586
- corrected compliance, 600
  - correction factors, unloading compliance experiment, 603, 606
  - crack extension prediction, 603–606
  - crack front curvature, 587–589
  - cyclic, 651, 653–655
  - deformation correction factor, 591–592
  - elastic unloadings, 651–653
  - engineering stress-strain data, 601
  - friction at and movement of out rollers, 593–596
  - indentation correction factor, 598
  - influence of outer roller movement and roller friction on compliance, 596
  - load-line deflection measurements, 352–356, 366–369
  - load versus load-line deflection, 356, 359
  - material and specimens, 348–350, 600–601
  - procedure, 601–602
  - roller correction factor, 596
  - specimen
    - deformation, 589–593
    - rotation, 599
  - test equipment, 600–602
  - test matrix, 601
  - thickness and Young's modulus, 586–587
  - three-point bend testing, 349, 351–352
- J-T curves, effect of prestrain history, 629, 636–637**
- J-T diagrams, 622, 629, 636–637, 641**

## K

- K<sub>ISCC</sub> testing procedure, 843–865**
- CB test, 847, 856, 863–865
  - crack from curvature relationship, 855, 859
  - data analysis, 847–848
  - interlaboratory round robin test participants, 844
  - load versus displacement, 855, 861
  - material and procedure, 848–849
  - relation between initial value and elapsed time, 856, 863
  - relation between specimen thickness and elapsed time, 855, 861
  - rigid-bolt and elastic-bolt analyses, 853–854
  - scope, 845
  - solution pH and temperature effects, 855, 860
  - specimen configuration, dimensions, and preparation, 845–846
  - test environment, 845
  - WOL test, 846–847, 850–856
  - yield strength relationship, 854, 859

**L**

- Lack-of-penetration, 1025, 1026  
 cycles to failure, 1046–1047  
 discontinuities, 1034–1035  
   analysis, 1040–1043  
   fatigue initiation life versus initial stress intensity, 1045  
   fatigue life versus nominal stress times, 1044  
   initial stress intensity versus fatigue life, 1043–1044  
 Law of energy-balance, 64  
 Ligament yielding, 786  
 Linear elastic fracture mechanics, 104, 192, 207, 223, 510, 516, 699, 742, 867  
   collapse-modified strip yield model, 975  
   cyclic crack growth, 1075  
 Linear variable differential transformer gages, 157–158  
 Lloyd's LT60, 164  
 Load-displacement, 752  
   crack closure, 916–917–923  
   cyclic, 653–655, 657  
   measurements, 84  
   normalized, 1009, 1014  
   power-law function, 751  
   stress-strain law effect, 1009, 1013  
   thin and thick MnMoNi 55 steel, 1015, 1018  
   three-point-bend specimens, 167, 169  
 Load drop analysis, 611, 618  
 Loading parameter, 1006–1007  
   normalized, 1009, 1014  
   stress-strain law effect, 1009, 1013  
 Load limit, 619, 648  
 Load-line compliance, 585  
 Load-line deflection measurements, 347, 352–356  
   calculated from  
   clip gage measurements, 356–358  
   crosshead displacement, 355–356  
   comparison of measurements, 357, 360–364  
   effect on J-R curve testing, 366–369  
   least-squares coefficients, 357, 364  
   measurement  
   flex bar, 354–355  
   photographs, 352–354  
   residuals, 357, 365–366  
 Load-line displacement, 611  
   bend specimens, 675  
   versus crack length, 616  
   experimental and finite-element analyses, 670–671  
   experimental and mixed state-of-stress analyses, 673

- irradiated 348 stainless bend specimens, 612–613  
 normalized, 291  
 precracking, 400–401  
 Local strain, defined, 517  
 Long cracks, 881, 888–890  
 Low-alloy steels, 957  
 Low-cycle fatigue, 206  
 LT60 steel, 165, 171  
 Lüders strain, 151, 154, 1009  
 Lugs, 1050  
   crack growth from embedded flaws 1065–1066  
 Lug tests, 1065–1066

**M**

- Macrofretting damage, 893  
 Macroscopic specimen, failure probability, 26  
 Manganese sulfide  
   inclusions, 516  
   stringers, 528  
 Mass-spring system, 53–55  
 Material-induced singularities, 278  
 Material strength, versus fracture toughness, 642–643  
 Maximum load toughness, 962–963, 972, 975–978  
 Mechanical model, 247–248  
 Mechanical properties, 516, 896  
   dependent on tempering temperature, 335  
*m* factor, 745  
   as function of CTOD, 746–747, 748  
   effect of specimen constraint, 746  
 Microalloyed steel, 164  
 Microcleavage, origins, 13–14  
 Microcracks, 7, 896  
   cleavage, 574–575  
   within shear zone, 569, 578  
   coplanar, nucleating, 14  
   critical, 31  
   ductile (see Ductile microcracks)  
   failure probability, 20  
   identification, 20  
   size distribution, 27–28  
 Micromechanical models, crack propagation, 837–838  
 Microstructure, 5  
   chemical inhomogeneity, 527, 530–531  
 Microvoids, 7  
 Middle-crack tension specimen, resistance curve method, 107, 111  
 Mixed fracture mode, 301  
 Mixed mode failure, aluminum alloys, 118–133

- Mixed mode failure,  
     aluminum alloys (*cont.*)  
 compact shear specimen, 119-122  
 computer-generated shear stress contours,  
     122, 126  
 configuration of compact shear specimens  
     prior to final testing, 122-123, 127  
 critical stress-intensity factors, 129, 131  
 finite-element analysis, 120-122  
 fracture angle between maximum J-integral and tangential stress failure criteria, 132-133  
 fracture toughness, 129-132  
 J-integral, 121  
 loading case definition as function of boundary constraint, 122  
 loading conditions, 122, 124-125  
 maximum load values, 128-129  
 shear stress at failure and predicted flow shear stress, 128-129  
 sympathetic shear crack growth, 129
- Mixed state-of-stress simulations, definitions, 671-672
- Mode II loading, 123, 128
- Mode II test specimen calibration, 1083-1088  
     compliance values, 1086-1087  
     data analysis, 1086-1087  
     displacement measurement, 1084-1085  
     EVB/P values, 1086  
     procedure, 1085-1086  
     specimens, 1084  
     stress-intensity coefficients, Mode II, 1087-1088
- Modified sigmoidal equation (*see* MSE model)
- Moiré analysis, boundary effects, 700
- Moments, boundary force method, 275
- MSE model, 207, 210  
     fitting data, 212  
     interpolative capabilities, 215
- 300 M steel, crack growth rate, 784-785
- Multiple-edge-notch tension specimen, 867, 870  
     creep 872, 874
- N
- NASA/FLAGRO computer program, 781-802  
      $\alpha$ -values, 794-795  
     code system, 792  
     crack case solution subroutines, 788-789  
     cubic spline fit, 798  
     future enhancements, 795-796  
     interpolation routines, 787, 797-798  
     limit-load criterion, 786, 788  
     materials properties files, 789, 792
- model geometry, 790-794  
 piecewise hermite cubic polynomial fit, 798  
 problem input sequence, 799-802  
 standard NDE flaw sizes, 795  
 subroutines and files, 788-795  
 theoretical background, 783-788
- Natural gas transmission, 237
- Near-crack-tip surface measurement techniques, 919-923
- Newman's equation, 784
- Nickel base superalloy, 181, 192, 757
- 5Ni-Cr-Mo-V steel, 1025
- Nil-ductility transition temperature, 5
- 3 Ni steel alloy, 349, 651, 659
- Nodular cast iron, 405
- Nondestructive testing, 468, 1025
- Notch ductility, 237, 243, 245
- Notch geometry, fracture resistance effect, 510-514
- Nuclear power plants, probabilistic fracture mechanics study, 44-45
- O
- Open-hole tests, 1063-1065
- Optical microscopy, ductile-to-brittle transition, 557-559
- Outer rollers, friction at and movement of, 593-596
- Overload, 181, 934, 935, 937-938, 941  
     ratio, 187
- Overmatching, 485
- Overtorque, 838
- Overtwist, 838
- Oxidation, 192, 763
- Oxide-induced closure, 202-203
- P
- Parabolic fatigue cracks, 1050-1068  
      $A_{ijk}$  coefficients, 1059  
     calculated results, 1058  
     crack growth from corner flaws, open-hole specimens, aluminum alloy, 1063-1064  
     crackline loading, 1056-1057  
     crack paths and front, 1052, 1054  
     crack propagation rate, open-hole specimens, aluminum alloy, 1063-1064  
     displacement matching, 1054, 1056-1057  
     energy release rate, 1057  
     experimental program, 1058, 1063-1065  
     flaw idealization, 1054-1058  
     fracture parameters, 1057-1058  
     generalized weight function, 1056  
      $G_{ijk}$  coefficients, 1062  
     lug tests, 1065-1066

- open-hole tests, 1063–1065  
 slicing procedure, 1054–1055  
 stress-intensity factors, 1057
- Paris equation, parameter values, 1035
- Paris law, 840, 1034
- Path-independent integrals, 713–728, 822  
 engineering applications, 725–726
- Gurtin's, 719–720
- integration paths and areas, 715
- J-integral, 715–717
- $J^*$ -integral, 721–722, 726
- $\hat{J}$ -integral, 722–723
- summary, 727
- $\Delta T$ -integral, 723–725
- Wilson and Yu's, 717–719
- Peterson's equation, 1038
- Photoelastic and Moiré interferometric method, 699
- Photoelastic studies, 86
- Piecewise hermite cubic polynomial fit, 798
- Pipeline, 237
- Pipe-line girth weld, 686–687
- Planar slip, 194
- Plane stress, 7
- Plastic collapse, 468, 475
- Plastic constraint, 15
- Plastic deformation, 103, 665
- Plasticity, 686–697, 825  
 analysis for long defects, 688, 690–692  
 COD design curve, 688  
 defective welded joints, 486
- Plastic strain, true, 166
- Plastic zone  
 boundaries, 1077  
 crack tip, 184–185  
 Mode III, 824  
 nomenclature, 824  
 radius, 886  
 size, 105, 107, 186, 550–552, 907, 934, 941, 947  
 under plane-strain conditions, 823  
 strains within, 939–941, 943–947
- Pop-in, 473, 627
- Potential energy, cracked plate, 680
- Power-law expression, 27
- Prandtl-Reuss equation, 724
- Precracking, 390–403, 759  
 amplified unloading curves, 400–401  
 applied load, 392  
 cantilever bending, 393–394  
 computer program, 398  
 equipment for monitoring and controlling, 393, 395  
 fatigue, 391–393  
 fracture toughness testing equipment, 393, 396–398  
 irradiated type 348 stainless steel, 402–403
- J-R curve, 400–403  
 load versus load-line displacement, 400–401
- machining specimens, 391  
 procedure, 390–391, 398, 400
- Pressure tests, 957
- Pressure vessel (*see* Reactor pressure vessel)
- Pressurized thermal shock, 37–48
- Pressurized water reactor, 35
- Prestrain, 623–645  
 Charpy impact properties, 632, 638–640, 642, 645  
 cyclic, 622–623, 625  
 cyclic prestraining schematic, 625  
 fracture toughness  
 properties, 627–629, 632, 640–644  
 tension specimens, 625  
 testing, 626
- material, 623  
 mechanical properties, 626–631  
 mechanical testing, 624–625  
 monotonic, 622–623  
 specimen preparation and prestrain history, 623–624  
 tensile properties, 632, 640–644  
 tension testing, 625
- Prestressing, warm, 38–39, 47–48
- Primary stress, effective, 476–477
- Probabilistic fracture mechanics, 37–48  
 cladding, 40  
 conditional probability of vessel failure, 42–43  
 crack arrest role, 47  
 critical flaw depths, 48  
 downcomer coolant temperature and primary-system pressure versus time, 46  
 failure criteria, 44  
 flaws, 39  
 density, 40–42  
 fluence attenuation through vessel wall, 38  
 fracture mechanics model, 36–40  
 fracture toughness, 37–38  
 frequency of failure, 36  
 importance sampling, 43  
 OCA-P program logic, 41  
 parameters simulated, 40  
 $P(F|E)$  versus effective full-power years, 45–46  
 plants included in studies, 44–46  
 probabilistic model, 40–44  
 relative contribution of plate and weld, 45  
 statistical error, 44  
 stress intensity factor, 36–37  
 tearing-resistance curve, 37–38  
 time of events, duration of transient, and  
 warm prestressing, 47  
 warm prestressing, 38–39, 47–48

- Probabilistic model, 40–44  
 Process zone, 5–6
  - local stress and strain, 9
  - semicohesive zone model, 6,8
  - size variations, 6–7
  - variable size, 15
 Propagating shear fracture, 237–245
  - application, 243–245
  - Charpy energy, 243
  - design stress dependency of required notch ductilities, 245
  - estimated crack propagation, 241–242
  - experiments, 240–243
  - gas decompression
    - curves, 240
    - velocity, 238–239, 244
  - propagation distance, 238
  - required notch ductilities, 243
  - test conditions of full-scale burst tests, 240
  - theory, 238–240
 Pseudo-elastic peak stress, 474–475  
 Push rod compliance technique, 922
- R**
- Radial line method, 275–277  
 Ramberg-Osgood constants, 1012  
 Ramberg-Osgood curve, 152–153, 159  
 Ramberg-Osgood equation, 669  
 Ramberg-Osgood law, 1009  
 Ramberg-Osgood relation, 1007–1009, 1012, 1073  
 Ramberg-Osgood strain-strain law, 751  
 Rayleigh wave velocity, 58  
 R-curve, 5, 9–10, 468, 959, 986–1003
  - defined in terms of internal energy, 991
  - drooping, 991–992, 996, 1002–1003
  - method of analysis effect 988–989
  - rising, 1002–1003
  - size effects, 536
  - specimen geometry, 471
  - three parameter techniques, 988
  - types, 996
 RDS requirement, 993, 996, 997
  - unique, 998–1000
 Reactor pressure tubes
  - failures, 421
  - irradiated (*see* CANDU reactor pressure tubes)
 Reactor pressure vessel, 35
  - external surface defects, failure evaluations, 1010
  - precracked, 731, 733–735
  - residual strength prediction, 731–733
  - steel,  $J\Delta a$  curve, 376–377, 382
  - strain distribution, 736
  - stretch zone measurements, 384
 Rectangular bend specimen, geometry, 289  
 Reference stress method, 478–479  
 Remote strain, 517  
 René N4, 757
  - chemical composition, 758
  - crack growth rate, 759–760
  - solidification substructure, 763–764
 René 95 (*see also* Crack closure, René 95)
  - chemical composition, 193
  - crack growth, 200–201
  - heat treatments, 194
  - mechanical properties, 194
 Residual stress
  - crack-tip deformation, 943, 946, 948–951
  - overload cycle, 948–949
 Resistance curve method
  - analysis of data, 107–109
  - compact specimen, 105–107, 109–111
  - concept, 105
  - crack configuration used to verify uniqueness of curves, 112
 Dugdale model, 105–106
  - failure loads
    - single-edge crack tension specimens, 112
    - middle-crack tension specimen, 107, 111
    - single-edge-crack tension specimen, 111–112
    - three-hold-crack-tension specimens, 113
 Retirement-for-cause (*see also* Fracture mechanics), 206–207  
 Rice's displacement derivative representation of weight function, 302  
 Ritchie-Knott-Rice model, 11, 13, 15  
 Roller correction factor, 596  
 Root radii, 765  
 R-ratio, effects for short and long cracks, 888–890  
 Runge-Kutta-Gill technique, 55–56
- S**
- Sealing cables, 734–735  
 Secondary cracking, 760, 762  
 Secondary stress, effective, 476–477  
 Self-similar crack propagation, 301  
 Semicohesive zone model, 6,8  
 Service failure analysis, 51  
 Shear crack, 825
  - growth, sympathetic, 129
  - profile, 561, 574
 Shear strain, overload cycles, 939, 945  
 Shear stress
  - computer-generated contours, mixed-mode loading, 122, 126
  - failure, mixed-mode loading, 128–129
 Shear zone
  - absence, 568

- characteristics, 561
- formation, 563
- relative orientation, 560, 564–567
- size variation, 561, 570–573
- stable cleavage microcrack within, 569, 578
- Shell parameter**, 732
- Ship**
  - frame structure, brittle crack propagation and arrest, 51–60
  - hull damage
    - damage description 68–70
    - static analysis, 68–71
- Short cracks**, 881, 896
  - R*-ratio effects, 888–890
- Side grooves**, 75, 611
- Sigmoidal equation**, 210
- Silicate particle**, initiation of cleavage facet, 531, 534
- Similitude**, 934–935, 951, 953
- Single-edged crack**, 151
- Single-lap joints**, testing, 283
- Singular intensity factor**, 278
- Singularity field**, 823
- SINH equation**, 209
- SINH model**, 207, 209–210
  - fitting data, 212
  - interpolative capabilities, 215
- Slag/lack-of-fusion**, 1025, 1026
  - cycles to failure, 1047–1048
  - discontinuities, 1034, 1036
    - analysis, 1043, 1045–1046
    - total fatigue life versus initial stress intensity, 1045
- Sliding crack surface interference**, 821, 829–830, 832
- Small-crack effect**, 897
- Small cracks**, 896
- Small-scale-yielding model**, 1070, 1073–1074
- SM 80P steel**, tensile properties, 732
- Specimen deformation**, 589–593
- Specimen failure probability**, 20, 29
- Specimen geometry**
  - ductile-to-brittle transition effect, 569, 574–575
  - effect of change on compliance, 591–592
- Spectrum loading**, 765
  - fatigue tests, 778–779
- Spring constants**, 53–54
- Spring model**, axially compressed columns, 805–807
- State of stress**, 825
- Static analysis**, ship hull damage, 68–71
- Static fracture tests**, 957
- Stationary crack**, linear elastic, 823
- Statistical failure**, 164
- Steels**, 881
  - chemical composition, 518, 600, 623, 883
- cleavage, crack-tip failure**, 11, 13–17
- correlation of Charpy V-notch energy absorption and plane-strain fracture toughness**, 454–456
- crack-arrest experiments**, 77
- crack growth rate versus applied stress intensity factor**, 884–886
- high-strength**, 347
- J-T diagram**, 629, 636–637
- Mode III crack growth**, 826
- panels**, J-integral values for small cracks, 151–162
  - crack mouth instrumentation, 157
  - loading methods used for tension and four-point-bend tests, 155–156
  - material, 153–155
  - stress-strain curve, 153
  - tests, 155–158
  - theoretical background, 152–153
- pop-in**, 627
- quenched and tempered**, 333
- shaft, fatigue failure**, 451
- tensile properties**, 518, 883, 884
- Stiffened sheet**
  - crack, infinite sheet, 251
  - edge crack, 248–249
  - equations for determining fastener forces, 248–249
  - half-space, subjected to concentrated loads, 256–257
  - infinite plate subjected to point loads, 256
  - influence coefficients, 249–253
  - mechanical model, 247–248
  - solution method for integral equations, 253–254
  - stress components, 256–257
  - stress-intensity factors, 254–255
  - uncracked half-plane, 252
- Stiffness**, 805–806
- Strain**, 730, 934
  - ahead of crack tip, 940, 946
  - distribution
    - along uncracked and cracked sides, 736
    - cyclic loading, 940–941, 946
    - overload cycle, 939–940, 944–945
  - effective, ahead of crack tip, 940, 945
  - gross
    - drop and characteristic defect lengths, 497
    - relationship with COD, significance, 490–491
    - versus COD, 497, 499
    - weld metal overmatching effect, 494–496
- Lüders**, 151, 154, 1009
  - measurement, 517, 521
  - remote, 152, 158–160
- Strain energy density function**, 716, 719

- Strain energy release rate, 301, 322–323  
 angular dependence, 322  
 sinusoidal characteristics, 324–325
- Strain hardening, 376, 488
- Strain rate, 454
- Strain-rate effects, 443
- Strain work density, 736
- Stress, 730  
 boundary force method, 275  
 crack initiation and, 444  
 critical, 164–165  
 failure, tangential criteria, 132–133  
 Griffith relation, 19  
 gross, weld metal overmatching effect, 494–496
- Stress analysis, 103, 665
- Stress-concentration factor, 259
- Stress corrosion crack growth rate, 851–852
- Stress eigenvalue, 704–705, 707
- Stress field  
 curving crack, 86–99  
 changes in fringe order error and leading coefficients, 92–93  
 experimental and data reduction procedures, 90–93  
 fringe pattern over data acquisition region, 92–93  
 isochromatic fringes, 86  
 opening and shear mode stress intensity factors, 94–95  
 specimen geometry and loading, 90  
 dynamic, 87–89
- Stress fringe multiplication system, 702
- Stress functions, 87–88  
 arc bend specimens, 287–288  
 boundary force method, 273–274  
 elasticity, 259
- Stress intensity, 391  
 correction factors, 269–272  
 effective initiations, 75  
 gradient, high-temperature crack-arrest toughness, 75  
 nucleating, 14
- Stress-intensity factors, 21, 23, 36–37, 86, 247, 254–255, 259, 275, 648–649, 699, 765, 1050, 1070  
 additive form, 784  
 analytical, 767–768, 771–773  
 formulation, 767–768, 771–772  
 solution of integral equations, 772
- apparent, 705–706  
 applied, values, 887  
 brittle specimens, 424  
 calculated and experimental, 1066–1068  
 calculation from explicit weight functions, 319, 323  
 cantilever beam specimens, 846
- coefficients, Mode I, 1088  
 collapse-modified strip yield model, 960  
 corrected, 705–706  
 correlation with CTOD, 456  
 crack growth rate as function of, 851–852, 904–907  
 cracks at root radii, 772–773  
 crack tip, 254, 1030, 1033  
 crack tip strains as function of, 939, 943  
 critical, 784  
 mixed-mode loading, 129, 131  
 d-c potential-drop technique, 339  
 dynamic, 56–57, 410  
 eccentric loading effects, 327–329  
 eccentric supporting effects, 328–329  
 edge crack, 254–255  
 effective, 913, 934  
 comparison of derived and measured, 952  
 crack growth rate versus, 905, 908–909  
 threshold, 891  
 value, 186
- effect of geometric stress concentration, 514–515
- effects of loading and supporting eccentricities, 312–313
- elastic-bolt analysis, 848
- final, elastic-bolt and final-load analyses, 854, 857–858
- function of applied load and weight functions, 303–304
- Green's function, 302
- initial, 849  
 versus fatigue initiation life, LOP discontinuities, 1045  
 versus fatigue life, LOP discontinuities, 1043–1045
- linear elastic fracture mechanics, 207, 688
- maximum  
 closure load dependence, 196  
 relationship with percent closure, 196–197
- mixed mode (*see also* Explicit weight functions)
- Mode I, 773, 778, 822  
 Mode II, 89, 328, 773, 778, 1087–1088  
 Mode III, 823  
 normalized, 290, 294–295, 319, 322  
 opening and shear mode, 88, 94–95  
 parabolic fatigue cracks, 1057  
 plastic zones, 184–185  
 quasi-static, 410  
 radial line method, 275–277  
 range  
 calculation, 884  
 effective elastic, 1071  
 plastic, 824

threshold testing, 193  
 relative error, 267–268  
 shear mode, 89  
 static, 58, 60  
     dynamic fracture toughness and, 68  
 threshold (*see K<sub>ISCC</sub>* testing procedure)  
 variation with distance from edge of land, 774–777  
 versus crack length, 890–891  
 WOL specimen, 846  
 zero-to-tension stress, 1042  
**Stress-strain curve**, 1073  
 A533B steel, 967–968  
 cyclic, 626, 628–630  
 monotonic, 626, 628–630  
     prestrain history effects, 630  
 normalized, 1009, 1014  
**Ramberg-Osgood approximations** (*see also Ramberg-Osgood relation*), 1009, 1012  
 showing approximation of data by power law, 387  
 slope, 386  
 steels, 601  
 tension specimens, 153  
 welded joint, 488–490  
 wide plates, 968  
**Stress-strain law**, 1007–1014  
 influence of load-displacement and loading parameter, 1009, 1013  
**Stress tensor**, 946  
**Stretch zone**, 374, 522  
 characteristics, 561  
 relative orientation, 560, 564–567  
 width, 561, 563, 569, 576, 605  
**Strip yield model**, 109–110, 477–478  
 boundary-integral equation analysis, 115–116  
 collapse-modified, 956–983  
     CTOD, 959  
     derivation, 959–961  
     disadvantage, 959–960  
     failure analysis diagram, 960–961  
     implications to general analysis procedures, 983  
 incorporation of resistance curve, 961–962  
 materials, 963–968  
 maximum load toughness, 972, 975–978  
 plastic collapse solutions, 972  
 prediction of test results, 968, 972–974  
 specimen orientations, 971  
 use of maximum load toughness, 962–963  
 wide plate and burst tests, 964, 969–970  
 finite-element analysis, 116–117

**Supporting eccentricity, stress intensity factor effects**, 312–313, 328–329  
**Surface cracks**, 151, 505  
**Surface defects**, 686  
**Surface-type crack cases, model geometry**, 792–793

**T**

**2024-T3 aluminum, ductile fracture**, 10–11  
**2024-T351 aluminum alloy**  
     crack growth from corner flaws in open-hole specimens, 1063–1064  
     marker bands, 1053  
     plates, crack propagation test program, 1063  
**7075-T6 aluminum alloy**, 223–235, 766  
 chemical compositions, 883  
 crack arrest toughness  
     statistical data, 233  
     versus crack jump, 231, 234–235  
     versus initiation stress intensity, 230–234  
     versus normalized final crack length, 232, 234  
     versus normalized remaining ligament, 232, 234  
     versus specimen thickness, 231–232  
 crack growth rate versus stress intensity factor, 884, 888  
 experimental procedure, 224–228  
 marking of arrested crack front, 226  
 properties, 228  
 run-arrest test record, 228–229  
 specimen dimensions and arrest toughness values, 227  
 specimen geometry, 225–226  
 specimen loading arrangement, 225  
 stress-strain curve, 228  
 tensile properties, 884  
**7075-T7351 aluminum alloy, beach marks due to maneuver loading**, 1053  
**Tearing**, 986  
 fibrous, 542  
     specimen geometry, 471  
**Tearing instability**, 1005, 1007  
 analyses, sources of inaccuracy, 1007, 1009  
 calculated stresses, 1019–1020  
 load normalized by experimental load, 1015, 1017  
**Tearing modulus**, defined, 425  
**Tearing resistance**, 37–38  
     ASTM A 710 grade A class 3 alloy steel, 155  
     terms of J-integral, 160

- Tensile properties, 385  
 AISI 4340 steel, 849  
 steels, 883  
 7075-T6 aluminum alloy, 883  
 prestrain history effect, 632, 640–644  
 type 308L weld metal, 135–136  
 type 304 stainless steel, 135–136
- Tensile stress, 437–438  
 Tension, 120, 151  
 Thermal shock, 35  
 Thickness-averaging compliance techniques, 915–918, 928  
 Three parameter technique, contour integral, 988, 1001–1002  
 Three-point bend specimens, 301, 390, 611, 667  
   bending moment, 596  
   boundary collocation, 288  
   center roller indentation, 597–598  
   crack growth, 674  
   CTOD data, 519, 523–524  
   eccentric loading conditions, 302–303  
   2-D finite element mesh, 545  
   geometric analysis, 594  
   geometry and test configuration, 391  
   J-R curve (*see* J-R curve testing)  
   loading eccentricity, 305–306  
   load-line displacements, 674–675  
   maximum loads, 674–675  
   nomenclatures, coordinates, and constraints, 305, 584  
   notching, 392  
   orientation and dimensions, 523  
   supporting eccentricity, 305–306
- Through-type crack cases, model geometry, 790
- Ti-6Al-2Sn-4Zr-6Mo, 898, 900
- $\Delta T$ -integral, 723–725
- Titanium alloys, 992, 927–928
- Titanium aluminum alloys, crack growth rates, 914–915
- Torsional failure, 827–829
- Torsional stiffness, 807–809
- Transition behavior, 622
- Trapezoidal rule, 603
- Tubular joint, 505–506, 810–811
- Tunneling, 583, 587
- Type 308L weld metal, tensile properties, 135–136
- Type 304 stainless steel  
   tensile properties, 135–136  
   welded pipe (*see* Ductile fracture, welded pipe)
- Type 316 stainless steel  
   chemical composition, 623, 965  
   creep behavior, 872, 874  
   creep-crack growth, 867–877
- fracture toughness, 633, 967  
 J-R curves, 627, 634–635  
 J-T diagram, 629, 636–637  
 mechanical properties, 633, 966  
 monotonic stress-strain curves, 627, 630  
 predicted and test results, 981  
 stress-strain curve, 968
- Type 348 stainless steel, irradiated  
   fracture toughness, 611–620  
     load drop analysis, 618  
     load limit, 619  
     test procedures, 612–613  
     unloading-compliance and effective modulus, 614–617
- J-R curves, 402–403
- U**
- Ultimate tensile strength  
 SM 80P steel, 732  
 temperature dependence, 167–168, 560
- Ultrasonic techniques, crack closure measurement, 919
- Underload, 937–938, 941
- UNLOAD, 398
- Unloading compliance, 390, 583, 611  
   effective modulus and, 614–617  
   load versus load-line crack opening displacement, 652  
   techniques, 916
- V**
- Variable-amplitude loading, 821, 838–840, 934
- Viscoelastic model, 701
- Void growth rate, 563
- W**
- Warm prestressing, 38–39, 47–48
- Weakest-link theory, 11, 13, 19, 26, 536, 552
- Weibull distribution statistics, 544
- Weight functions (*see* Boundary collocation)
- Welded joint, 485, 957  
   behavior in tension, 488–490  
   defective  
     deformation modes, 486–487  
     plasticity, 486  
       stress-strain curves, 488–489  
     overmatched, COD-e relationship, 493, 495  
     stress-strain curves, 488–490
- Weld imperfections, 468
- Welding, 1025
- Weldments, 443, 555, 730  
   fabrication discontinuities, 1025

- fatigue initiation life, 1032  
 fatigue life, 1032  
 optical micrograph, 558–559  
 specimen geometry, 469–470  
 testing, CTOD approach, 469–471
- Weld metal,** 19  
 behavior in tension, 486–488  
 chemical composition, 21, 1026–1028  
 critical CTOD, 560  
 deformation, 486  
 interaction between stress-strain and COD, 489  
 matching  
   COD effect, 499  
   tolerable defect sizes, 493, 497  
 mechanical properties, 1027  
 overmatching, 485–501  
   COD-e relationship, 493, 498  
   effect on gross strain and stress and COD, 494–496  
   gross section yielding, 501  
   materials and weldments, 491–492  
   specimen preparation and testing, 491–492  
   tensile properties, 559  
**Weld seam,** crack velocity beyond, 62
- Wide plates,** 505  
 bending, 516–534  
   absence of delamination, 528, 533  
   chemical inhomogeneity of microstructure, 527, 530–531  
   cleavage facets, 528, 533  
   crack geometries, 520  
   equivalent versus critical crack length, 526–528  
   fractography, 527–531  
   inclusions, longitudinal and transverse sections, 529  
   material, 517–518  
   stretch zone, 522  
   test data, 524–525  
 burst tests, 964, 969–970  
 containing precracked surface notches, 507  
 large, 506–507  
 off-sectioning, 508  
 small, 507–508  
 tests, 51  
   CTOD measurements, 517, 519, 521–522  
   procedure, 517, 519  
   specimen geometry, 517, 519
- William's stress function,** 286–289
- Wilson bilinear curve,** 152–153
- WOL specimens**  
 fracture surfaces, 855  
 statistical analysis of final stress intensity factor, 855–856, 862  
 variance of final stress intensity factor, 854–855, 859–861
- WOL test,** 846–847, 850–856
- Workhardening,** 166
- Y**
- Yield strength**  
 absorbed energy versus temperature, 537–538  
 AISI 4340 steel, 849  
 A36 steel, 537  
 crack initiation threshold dependence, 444  
 final stress-intensity factor relationship, 854, 859  
 function of temperature, 560  
 grain size, 537–538  
 SM 80P steel, 732  
 toughness dependence, 29–30
- Yield stress**  
 fictive, 387  
 relationship with fracture toughness, 174–175  
 temperature dependence, 167–168
- Yield zone dimension,** 786
- Young's modulus,** 425, 586–587
- Z**
- Zircaloy-2,** 419  
 chemical composition, 420  
 fracture toughness, 427, 434–436  
 hydride morphology, 434  
 J-R curves, 436  
 specimens, 423
- Zirconium alloys, Young's modulus,** 425
- Zr-2.5Nb,** 419  
 chemical composition, 420  
 critical crack length, 432  
 cutting diagram of specimens, 422  
 fracture surface, 427–428  
 fracture toughness, 427–433  
 heat treatments, 423  
 initial tearing modulus, 433  
 initiation toughness, 433  
 J-R curves, 427, 429–431  
 tensile properties, 426