

Index

- A**
- Alumina
- Crack growth measurements in, 33
 - Flaw sizes in, 137, 140
 - K_{Ic} values for, 26, 42-43, 78-81, 106, 151-164
 - Mirror constant for, 144
 - Proof test diagram for, 208
 - Stressing rate data for, 212
- Aluminum
- Short bar test in, 78-81
- ASTM method E 399, 8, 168, 176
- B**
- B_4C , 126
- Barium titanate, 140
- C**
- CaF_2 , 137
- Coatings, 131
- Concrete, 183-200
- Crack arrest, 47
- Cranz-Schardin camera, 49
- Cyclic loading, 162
- D**
- Diamond pyramid indentations, 84
- Double cantilever beam techniques, 22, 42, 47-59, 65-72, 153, 197
- Double torsion test, 3-18, 19-37, 42, 61-65, 153
- Dynamic crack growth, 48-49
- E**
- End effects, 16, 29-34
- Error analysis, 204
- F**
- Fibers as reinforcement, 183-200
- Finite element analysis
- Of double torsion specimen, 5
 - Of indentation, 120
- Flaw healing, 97
- Fused quartz, 78-81
- G**
- Glasses
- Crack growth in, 24, 65, 69
 - Flaw sizes in, 140
 - K_{Ic} values for, 42, 63, 67
 - Lifetime predictions for, 206
 - Mirror constant for, 144
 - Proof test diagram for, 208-209
- Glass-ceramics
- Crack growth in, 33, 35
 - K_{Ic} values for, 42, 106
- Graphite, 32, 44
- Grooving of specimens, 17, 25, 30-32
- H**
- Homalite 100, 49

- I**
- Indentation fracture, 144
Internal stresses, 140
- J**
- J-integral, 177-181, 199
- K**
- Knoop indentations, 84, 104-111
- L**
- Lifetime predictions, 202-213
- M**
- MgF₂, 140
Microcracking, 146, 152, 192-200
Mode II and Mode III loading, 8, 146
- N**
- Notch bend test, 38-46, 153, 171
Effect of notch geometry, 43, 166
- P**
- Plastic zone, 120
Porcelain, 24, 31
Precracking, 26, 40-42, 61, 84, 162-164, 171-173
Process zone, 158
PZT, 24, 32
Pyroceram 9606
Crack growth in, 35
Flaw sizes in, 140
 K_{Ic} for, 42
Mirror constant for, 144
- R**
- Residual stresses, 101, 111
- S**
- Short bar specimen, 73-82
SiC
 K_{Ic} by controlled surface flaw, 95-97, 126
Mirror constants for, 144
Si₃N₄
Flaw sizes in, 139-143
 K_{Ic} for, 41, 84-100, 126
Mirror constants for, 144
Subcritical crack growth, 20-22, 55, 65-71, 202-213
Surface correction factors, 93
Surface flaws, 85, 93
Surface treatment, 129
- T**
- Tension test, 194
- V**
- Vickers indentations, 104-112
- W**
- WC/Co, 94, 126
- Z**
- ZnS, 126
ZnSe, 126, 137, 140
ZrO₂, 126
Zyglo, 174