

Subject Index

A

- Acetone
 - Permeation with, 128, 171, 203
- Acid liquor, 140
- Asphaltic emulsion, 55
- ASTM Committee D-18, 1
- ASTM standards
 - C 511-80, 78
 - D 422-63, 51
 - D 422-63 (1972), 141
 - D 423-66 (1972), 142
 - D 424-59 (1971), 47, 142
 - D 427-61 (1974), 142
 - D 558-82, 307
 - D 559-82, 307
 - D 560-82, 307
 - D 698-78, 108, 142, 159, 192
 - D 1557-78, 142
 - D 2216-80, 51
 - D 2434-68 (1974), 159
 - D 2487-69 (1975), 142, 231
 - D 3385-75, 278
- ASTM Subcommittee D-18.20, 1
 - Objectives, 1

B

- Back pressure, 156
 - Effect, 167
- Barriers
 - Impermeable, 140, 263
 - Seepage, 9
 - Soil, 156, 289
 - Verticle, 24
- Bentonite, 45, 75, 93
 - Fine-grained soils, 127

Sand liner

- Lab measurement of permeability, 155
 - Slurry cutoff walls, 9
 - Treated (polymerized), 65
 - Untreated (nonpolymerized), 65
- ## Benzene
- Permeation with, 171, 203
- ## Brine disposal
- Diversion into evaporation pond, 214

C

- Calcium ions, 317
- Cement bentonite (CB) walls, 2, 9, 46
 - Advantages, 12
 - As deformable plastic material, 88
 - ASTM C 511-80, 78
 - Construction, 9
 - Grouts, 76
 - Lab tests for reservoirs, 76
 - Mix proportions, 79
 - Standardization need, 88
- Clay soil
 - Acid liquor test, 140
 - As barrier to restrict vertical percolation test, 246
 - Design/testing concepts, 249
 - Sources of error, 250
 - Field control, 254
 - Permeability of compacted clay, 248
 - Permeability/compaction relationship, 249

- Results, 257
- Seepage model, 248
- Typical landfill cover, 247
- Compacted, 172
 - Clay barrier layer
 - Vertical percolation through landfill, 246
 - Formation of precipitates, 138
 - pH, 138
- Compaction
 - Of pozzolanic fly ash, 292
 - Harvard, 174
 - Proctor, 142, 174
 - Water content, 246
- Compactive effort, 246
- Composite system, 25
 - Permeability, 25
- Vertical cutoff
 - Advantages, 26
 - Components, 28
 - Construction, 27
 - Operation, 29
 - Test project, 29
 - Construction, 30
- Composite walls
 - Clay, 4
 - HDPE sheeting, 4
- Cutoff wall
 - Chemical resistance, 47
 - Composition, 45
 - Compressibility, 59
 - Construction technique
 - ASTM D 422-63, 51
 - ASTM D 2216-80, 51
 - Backfilling, 48
 - Slurry trenching, 10, 45
 - Vibratory beam injection, 34, 35
 - Differences, 45
 - Continuity, 56
 - Definition, 45
 - Geometry, 45
 - Permeability, 51
 - Placement, 50
 - Quality control, 3, 56

D

- Darcy's equation, 45
 - Law, 65, 80, 96, 162, 280
 - Non-Darcian flow, 175
- Deflection, 45
- Deformation, 76
- Desiccation cracking of soil barriers, 263
- Dielectric constant, 203
- Dry unit weight, 246

E

- Earth linings
 - Clay, 127, 140
 - Acidic solution interaction, 229
 - ASTM D 2487-69 (1975), 231
 - Brine on permeability of clay linings
 - Salt evaporation pond, 213
 - Salt gradient solar pond, 213
 - Soil, 140, 156
 - Soil cement as a liner test
 - Slope protection, 229
 - Aerated lagoons, 306
 - ASTM D 558-82, 307
 - ASTM D 559-82, 307
 - ASTM D 560-82, 307
 - Compacting with vibratory sheepsfoot roller, 310
 - Composite liner test section, 311
 - Cooling water flume, 304
 - Placing with aggregate spreader, 309
 - Spreading HDPE membrane, 312
 - Stairstep, 307
 - Test section for durability, 301
- Environmental Protection Agency (*see also* EPA), 10, 299
- Evaporation reservoirs, 213

F

Filter

- Cake, 47, 95
- Press/loss, 65
- Water loss chamber, 66

Free swell, 171

G

Gouy-Chapman, 65, 182

Groundwater, 24, 172, 203

Barriers, 9

Preventing contamination, 25, 213

Grouted walls

Vibrating beam technique, 4

H

Hazardous waste, 127

HDPE (*see* High density polyethylene)

Membrane, 24

High density polyethylene (*see* HDPE)

Hydraulic

Barriers

General discussion, 317

Horizontal, 107-316

Vertical, 9-106

Conductivity, 156, 188, 229, 289

Of clay liners, 276

Horizontal seepage, 276

Infiltration test, 276

Single ring infiltrometer, 276

Of clayey soils, 107

Of compacted clay/sand mixtures, 263

Of compacted kaolinite, 171, 203

Organic fluid effect with compacted kaolinite, 171

Characteristics of organic fluids, 173

Composition of clays, 173

Effluency in low level tests, 178

Relative/absolute hydraulic conductivity, 180

Schematic view of test setup, 174

Pore size distribution, 205

Conductivity/pore size parameters, 209

Summary of permeability models, 205

Volumetric changes, 206

With different permeameters, 118

Gradient

Coefficients of permeability, 166

Magnitude on permeability, 155

To decrease testing time, 317

Hydrostatic pressure, 47

I

Impermeable

Barriers, 140

Liners, 263, 299

K

Kaolinite

Compacted, 171, 203

L

Landfill, 246

Leachate, 26, 97, 172

Concentration of constituents

To decrease testing time, 317

Generation, 190, 246

Waste effects on soil liners, 188

Line of optimums, 246

Liquid limit, 172

- M**
- Mercury intrusion
 To quantify pore size, frequency distribution, 203
- Methanol, 97, 128
- Monitoring wells, 32
- N**
- Nitrobenzene
 Permeation with, 171, 203
- O**
- Organic fluid, 171
 Permeation, 185
 Through compacted kaolinite, 203
- P**
- Particle-size analysis, 229
- PCB (*see also* Polychlorinated biphenol), 9
- Permeability, 45, 75
 Aqueous solutions as permeants on bentonite, 64
 Results, 67
- Clay liners, 276
 ASTM D 3385-75, 278
 Background
 Types of tests, 277
- Case history
 Pond test, 285
- Hydraulic conductivity of single ring infiltrometer, 278
 Finite-element grid, 281
 Leakage rate, 279
- Lab experiments
 Schematic of model tests, 283
- Single ring infiltration, 278
 Alternate designs, 279
 Penetrating infiltrometer, 279
- Effect of acid liquor on clayey soil/silty sand, 140
 Acid liquor test results, 147, 148
 ASTM D 422-63 (1972), 141
 ASTM D 423-66 (1972), 142
 ASTM D 424-59 (1971), 142
 ASTM D 427-61 (1974), 142
 ASTM D 698-78, 142
 ASTM D 1557-78, 142
- Chemical analysis of acid liquor, 153
 Chemical analysis of clayey soils, 152
 5.08-cm-diameter permeameter, 144
 Compaction test results, 146
 Denver tap water test results, 147
 Liquid/shrinkage limit, plasticity index, 146
 Mineral percentages by volume, 151
- Field test for clay liners, 276
- Of clay to acidic/caustic permeants, 155
- Of fly ash, fly ash/sand mixture, 289
- Self-cementing (two sources), 290
 Dry density of permeability specimens, 296
 Pozzolanic index, 291
 Test design, 291
- Of pozzolanic fly ashes, 289
- Of soil-cement liners, 299
- Organic liquids on clay soil-bentonite, 93
 Double ring permeameter for soil-slurry mix, 94, 95
 Properties of soil-slurry mix, 96, 97
- Procedure/equipment effects on bentonite-sand liner, 155
 ASTM D 698-78, 159

- ASTM D 2434-68 (1974), 159
 - Gradient schedule, 158
 - Moisture content distribution, 164
 - Moisture content of specimen, 163
 - Related to changes in soil fabric, 246
 - Water/waste leachate on soil liners, 188
 - Permeameter, 107, 229
 - Fixed-wall, 94, 107, 128, 156
 - Compaction mold, 108
 - ASTM D 698-78, 108
 - Compaction mold w/heptane, 110
 - Compaction mold w/liquid, 109
 - Schematic of various permeameters, 157
 - Consolidation cell, 112
 - Double ring, 111
 - Compaction mold, 111
 - Schematic, 94, 95
 - Fixed cylinder, 113
 - Hydraulic activity of acetone, 171
 - Flexible-wall, 114, 129, 156, 171
 - Flexible wall, 114
 - Hydraulic activity of acetone, 171
 - Triaxial cell, 157
 - For compacted kaolinite with methanol, 119
 - Advantages/limitations, 120
 - Pressurized setup for clay liners, 233
 - Properties of soil-slurry mixture, 94, 95
 - Permeants
 - Acidic/caustic on fine-grained soils, 127
 - Acid permeant, 133
 - Caustic permeant, 134
 - Neutral permeant, 133
 - Permeability test results, 136
 - Contaminated, 128
 - Inorganic aqueous, 65
 - Phenol
 - Permeation with, 171, 203
 - Phosphogypsum, 140
 - Piezometer, 32
 - Plastic
 - Deformation, 77
 - Diaphragm walls, 77
 - Plumb, 57
 - Major/minor deviation, 59
 - Tolerance, 58
 - Pollution
 - Containment, 24
 - Migration, 24
 - Polychlorinated biphenol (*see also* PCB), 9
 - Pore size distribution, 203
 - Porosity
 - Quantification parameters, 203
 - Water pressure, 263
 - Precipitation, 229
 - Pumping
 - Capacity, 48
 - Leakage, 27
 - Tests, 39
- S**
- Salt-gradient solar ponds
 - Brine on permeability of clay linings, 213
 - Seepage
 - Control using soil-cement liners, 299
 - Embedded ring infiltrometer, 276
 - Through clay linings, 213
 - Through landfill covers, 246
 - Sidewall leakage, 93, 107
 - Slurries, 64
 - Cement-bentonite, 76

- Clay-water, 66
- Permeability of bentonite, 65
- Slurry
 - Cracking pattern tests, 65
 - Pore field conditions, 71
 - Loss, 48
 - Quality, 47
- Slurry/bentonitic
 - Testing basic properties
 - Density, 4
 - Filtration, 4
 - Sand content, 4
- Slurry cutoff walls, 2, 9, 45
 - Applications, 15
 - Seepage barriers, 9, 75
 - Under dam, 21, 22
 - Site dewatering, 9
 - Buried chemical waste, 16, 17, 18
 - Underground pollution control, 9
 - Groundwater barriers, 18, 19, 20
- Backfill materials, 93
- Construction, 10, 45
 - Construction method, 46
- Containment effects, 6, 55, 64, 95
- Cost, 11
- Design consideration, 21
- Installation conditions, 9
- Projects
 - Leachate/methane gas migration containment, 9
 - Oil seepage containment, 9
 - PCB contaminated site cleanup, 9
 - Spilled phenol cleanup, 9
- Purpose, 9
- Quality control, 3, 45
- Specifications, 21
- Testing, 4
- Types, 9
- Slurry trench, 64, 76
 - Composition
 - ASTM D 424-59 (1971), 47
 - Sodium bentonite, 47
 - Construction technique, 25, 46
 - Advantages, 26, 45
 - Continuity, 49
 - Dimensions, 49
 - Placement, 47
 - Quality control parameters, 47
- Soil-bentonite (SB) walls, 29, 46
 - Advantages, 12
 - Construction, 9
 - Backfilling, 11
 - Excavation, 11
 - Excavation equipment, 13, 14
- Liners, 64
- Soil liners, 156, 188
 - Compatibility studies, 190
 - ASTM D 698-78, 192
 - Chemical analysis, 194
 - Soil properties, 191
 - Soil property test results, 195
- Desiccation
 - Clays, 266
 - Compaction, 263
 - Cracking, 265
 - Hydraulic conductivity, 263
 - Impermeable liners, 263
 - Permeability, 263
 - Scale of cracking severity, 271
 - Shrinkage, 264
- Field permeability test for clay, 276
- Potential of fly ash, 289
- Soil-cement
 - Hazardous waste impoundments, 299
 - Wastewater treatment lagoons, 299
- Soil testing
 - Ball clay/bentonite mixture, 129
 - Chemical analysis kaolinite/magnesium/montmorillonite, 130
 - Clay, 127, 140

Compacted/pore size distribution, 203
 Kaolinite, 129
 Low permeability, 156
 Magnesium montmorillonite, 129
 Mineral composition magnesium montmorillonite, 130
 Silty sand-bentonite, 140
 Soil lining of brine pond, 213
 Plan/profile, 215
 Strain, 75
 Rate, 81
 Stress curve, 81

T

Thixotropic, 47
 Triaxial
 Compression test
 Results, 82, 83, 84
 Unconfined, 75
 Unconsolidated-drained/
 undrained, 75
 Flexible wall permeameter, 129
 Schematic, 130

U

Underground pollution control, 10
 Unified Soil Classification
 ASTM D 2487-69 (1975), 142
 Soil sample description, 142

V

Vertical barrier, 24
 Applications, 25
 Technology, 25
 Vibrated beam, 34, 45
 Advantages, 34, 53
 Equipment
 Crane/leads, 35
 Injection beam, 35
 Injection configuration, 36
 Slurry transfer pumps
 Wall installation, 37
 Vibratory driver-extractor, 35
 Field test, 39
 Results, 43
 Slurry bulbs, 42
 Test section, 40
 Grouting, 34, 35
 History, 53
 Pumping tests, 39
 Water level tables, 41
 Quality control, 3, 55
 Technique, 35, 53

X

Xylene, 97, 128