

**Subject Index****A**

Abrasion index, 165  
 Absorption, 240  
     cold water, 165  
 Admixtures, 277, 355  
 Aggregates, 186  
 Air entrainment, 197  
 Air infiltration, 22  
 Air leakage, 250  
 Air pressure, 301, 386  
 Alkali, 3  
 ASTM Standards (See also Standards)  
     C 67: 3, 240  
     C 157: 186  
     C 331: 186  
     C 1072: 121, 152, 213  
     E 514: 228, 277, 314  
     E 518: 121  
     E 1105: 265

**B**

Barrier walls, 265  
 Berea sandstone, 412  
 Bond beams, 32  
 Bond strength, 197  
     flexural, 105, 152  
     C 1072: 121, 152, 213  
     E 518: 121  
 Bond wrench, 213  
     testing, 152  
 Brick, 3, 152, 412  
     C 67: 3, 240  
     E 514: 314  
     clay, 165  
     concrete, 152  
     masonry, 314  
     pavers, 165  
     veneer, 22, 121, 172, 250, 369

**C**

Calcium carbonate, 3  
 Calibration, 213

Capillary action, 228, 250, 301  
 Cavity walls, 397  
 Cement, 3, 105, 197  
     C 157: 186  
 Cladding, 121  
     recladding, 369  
 Clay brick pavers, 165  
 Clay masonry  
     fired, 341  
     grouted, 75  
 Clay tile, 91, 326  
     C 67: 3, 240  
 Compressive strength, 105, 165,  
     197, 240  
 Concrete  
     C 157: 186  
     block, 32, 277  
     brick, 152  
     masonry, 152, 228, 301  
     C 331: 186  
     grouted, 75  
 Condensation, 250  
 Condition assessments, 341  
 Copings, 3  
 Corrosion tests, 17  
 Curtain walls, 121  
 Cyclic loading, 32

**D**

Darcy's law, 301  
 Deflection, 397  
 Deformation, inelastic, 60  
 Delamination, 397, 412  
 Dimensional tolerances, 369  
 Doors, water penetration of  
     E 1105: 265  
 Drainage walls, 265

**E**

Efflorescence, 3

**F**

Flashing, 3, 22, 265, 369

Flexural bond strength, 105, 152  
C 1072: 121, 152, 213  
E 518: 121  
specimens, 326  
Fly ash, 186  
Frames, infilled, 91  
Freezing, 412  
Freeze-thaw testing, 228, 240, 250  
Friction, 60  
Frost resistance, 240

**G**

Grout, cementitious, 355  
Grouted masonry, 75

**H**

Handling, masonry specimens, 326

**I**

Injection  
foam, 397  
grout, 355  
Insulation, 22  
Interior walls, 386

**L**

Laminar spalling, 240  
Lap splice strength, 75  
Lateral loads, 386  
Leakage tests, 265, 301  
E 514: 228, 277  
efflorescence potential, 3  
Lime, 105, 197  
Loads, lateral, 386

**M**

Masonry assemblages, 91  
Masonry partition walls, 386  
Masonry prisms, 152, 326  
Masonry, reinforced, 75  
Masonry units, 152, 228, 277,  
301, 341  
C 270: 105  
C 331: 186  
Masonry veneer, 60, 397  
Material compatibility, 314

Modelling  
statistical, 341  
water penetration, 301  
Mortar, 3, 91  
C 157: 186  
C 270: 105  
portland cement-lime, 105,  
152, 197  
Type N, 152, 197  
Type S, 32, 121, 152, 197  
water repellent, 277

**N**

Nondestructive testing, 326, 341,  
355

**P**

Partition walls, 386  
Paving, 165  
Pendulum tester, 165  
Permeability, 3, 22, 165  
E 514: 228, 277, 314  
E 1105: 265  
brick, 314  
freezing, 412  
freeze-thaw testing, 228, 240,  
250  
modelling of, 301  
resistance, 228, 265, 277  
tests, water flow rates, 265  
urethane foam, 397  
Polyurethane, 397

**R**

Regression modelling, 341  
Reinforcement  
bed joint, 32  
horizontal, 32  
vertical, 32  
Reinforcing bars, 75  
Relieving angles, 369  
Repair, masonry, 355, 412  
grout, 355  
quantifying, 341  
recladding, 369  
urethane foam injection, 397

**S**

Salts, water-soluble, 3  
 Sandstone, 412  
 Screws, 172  
 Seismic capacity, 91  
 Shear behavior, 32  
 Shelf angles, 60  
 Shims, 60  
 Shrinkage, 186  
 Sills, 3  
 Skid resistance, 165  
 Skin walls, 265  
 Spalling, 240, 250, 341  
 Splice strength, 75  
 Spray rack, 265  
 Stability, volume, 186  
 Standards (See also ASTM Standards), 105, 121  
     masonry limit states design, 75  
     specifications, mortar, 105  
     Uniform Building Code, 105, 213  
 Statistical modelling, 341  
 Steel frames, 91  
 Steel studs, 121, 172

**T**

Thermal bridge, 22  
 Tile, clay, 91, 326  
     C 67: 3, 240  
 Trade coordination, 369  
 Tube test, 228

**U**

Uniform Building Code, 105, 213  
 Urethane foam, 397  
 U.S. Department of Energy, 91

**V**

Veneer  
     brick, 22, 121, 172, 250  
     masonry, 60, 397  
     recladding, 369  
 Volume stability, 186

**W**

Water penetration, 3, 22, 165  
     E 514: 228, 277, 314  
     E 1105: 265  
     brick, 314  
     freezing, 412  
     freeze-thaw testing, 228, 240, 250  
     modelling of, 301  
     resistance, 228, 265, 277  
     tests, water flow rates, v265  
     urethane foam, 397  
 Wetting, 186, 250