

# Index

**Note:** Page numbers followed by “*f*” and “*t*” denote figures and tables, respectively.

## A

AISI 1045 steel, 139  
     CCT diagram of, 156  
 AISI 4137 steel, 198  
 AISI 4140 steel, 152*f*, 153*f*, 157  
     chemical composition of, 197  
     cooling time of, 173*t*, 175  
 AISI 5140 steel, 16  
 AISI 60S2A steel, 139, 140*t*  
 aqueous polymer quenchants, cooling capacity of, 172  
 aqueous salt solutions  
     and alkalis solutions of high concentration, quenching in, 127  
     use of, 145–146  
 arrays of round nozzles (ARN), 67  
 austenite  
     isothermal decomposition of, for three classes of steels, 4*f*  
     lattice parameters of, 5*f*  
 austenite–martensite transformation, 4  
 austenite–pearlite transformation, 4  
 austenitizing temperature versus carbon content in steel, 3*f*  
 automotive parts, 192  
     ball studs, 197  
     coil springs, 192–196  
     leaf spring samples, 196  
     torsion bar samples, 196–197  
     universal joint crosses, 197–198

## B

ball studs, 197  
 batch quenching, 180–182  
 batch-type IQ equipment, 191–192  
 bearing rings, computations for, 112–113  
 Bessel function, 79*f*, 80, 80*f*  
 Biot number, 2, 34–35, 77*t*, 78*t*, 93, 103–104*t*  
     and Grossmann H value, 170  
     and Kondratjev number, 86  
 boring pipes and locking connections, quenching, 165  
 boundary liquid boiling layer, formation of, 124–126  
 bubble parameters and dynamics, 24  
     surface properties, 25–30

## C

CCT (continuous cooling transformation) diagram, 4, 7, 74, 124, 152  
     of AISI 1045 medium-carbon steel, 156  
     of AISI 4140 steel, 153*f*  
 CFD (computational fluid dynamics) analysis, 191  
 CFD (computational fluid dynamics) modeling, 70–72, 86–88  
 coil springs, 192–196  
 cold brittleness, 3  
 computational fluid dynamics (CFD) analysis, 223–225  
 conditions of uniqueness, 63  
 convective heat transfer, 47, 62  
     boundary conditions, 63–64

    coefficient, 126, 127  
     discussion, 70–72  
     equation of continuity, 63  
     equation of movement, 63  
     equation of similarity, 64–65  
     heat transfer equations, 62–63  
     optimal spatial arrangements of nozzles, 69–70  
     practical problem solved by direct convection, 70  
     spray cooling, 67–69  
     sprayers with slots, 69  
     in water flow, 65–67  
 conveyor lines and quenching processes design, 175  
     speed of conveyor, calculation of, 177–178  
     speed of rotation, calculation of, 178–180  
 conveyor speed evaluation, generalized equations for, 225–227  
 cooling (or heating) factor, 91  
 cooling capacity of oils versus aqueous polymer solutions, 172–175  
 cooling chamber, for intensive quenching, 133*t*  
 cooling characteristics of quenchants, determination of, 210  
     method and software for, 216–218  
 cooling implementation, apparatus for, 144*f*  
 cooling media, cooling capacities of, 177*t*  
 cooling time calculation, 74  
     for bodies of simple shape, 75  
     finite cylinder, 84–86  
     one-dimensional cylinder, 78–81  
     one-dimensional slab (plate), 76–78  
     sphere, 81–82  
     three-dimensional slab (parallelepiped), 82–84  
 CFD modeling, 86–88  
     discussion, 88–89  
     example of, 102  
     generalized equation, analysis of, 88  
 crack formation  
     during water quenching, 173  
     effect of pressure on, 126–127  
     prevention, 181*t*  
 critical heat flux densities, 30, 45  
     aqueous salt solutions, optimal concentrations of, 53–54  
     convective heat transfer, 47  
     determining technique, 49–52  
     discussion, 59–60  
     experimental measurements of, 52–53  
     film boiling, special characteristics of, 57–58  
     full film boiling, 46  
     heat transfer during, 54–57  
     heat transfer, different modes of  
     during quenching, 58–59  
     importance of, 47  
     nucleate boiling, 46–47  
      $Q_{CR1}$ , determination of  
     under free convection conditions, 48–49  
     shock boiling, 45–46

silver probe to determine, 47–48  
 cryogenic quenchants and special devices, use of, 144–145  
 cylindrical silver probe, 98*f*

## D

Dante predictive heat treatment software tool, 114  
 demonstration studies, 192  
   automotive parts, 192–198  
   equipment for, 189  
     batch-type IQ equipment, 191–192  
     single-part quenching IQ systems, 189–191  
   fasteners, 207–208  
   forgings, 198, 201–203  
   tool products, 203–207  
 diffusion-free transformation in steel, 4–6  
 dimensionless equations, 70  
 direct convection cooling, 185, 186–187  
 direct problem, 210  
 discrete-impulse energy input process, 182–183  
 dislocation density, 2  
 draft-tube impeller system, 180–181  
 ductile–brittle transition temperature (DBTT), 7

## E

effective specific heat capacity, 88  
 engineering tensile strength, 3  
 EPP-098, 121  
 equation of continuity, 63  
 equation of movement, 63  
 equation of similarity for natural convection heat transfer, 64–65

## F

fasteners, 207–208  
 fatigue, 3  
   limit, 3  
 film boiling, 187  
   special characteristics of, 57–58  
 finite cylinder, cooling time calculation for, 84–86, 85*f*  
 finite element method (FEM) calculations, 108  
   modeling technique, 225  
   regular thermal process by, 97  
 first critical heat flux density, 287  
 first Kondratjev theorem, 92  
 fluidized bed quenching, at low temperatures, 142–144  
 forced convection, 62  
 forced movement, 62  
 forging, 198  
   forklift forks, 203–204  
     Hoop stresses S33 in, 149*t*  
     intensive quenching of, 147–148  
     railroad parts, 198, 201–203  
     sketch of, 147*f*  
     temperature fields in, 147  
 forklift forks, 203–204  
 Fourier-Kirchhoff differential equation, 62  
 Fourier law, 74  
 free movement, 62  
 FRIEND (Free Identification for Engineers and Designers), 215  
 full film boiling, 46  
   heat transfer during, 54–57  
 fully automated IQ system, 192*f*

## G

gaseous quenchants at 20°C, thermophysical properties of, 145*t*  
 generalized Biot number, 152  
 generalized equation, for cooling time calculation, 75, 88  
 grain boundaries, 2  
 Grashof number, 64  
 green function method, 214  
 Grossmann H value and Biot number, relationship between, 170

## H

H-13 steel aluminum die casting dies, case study for, 206–207  
 Hall-Petch equation, 2  
 Hart software, 114  
 heat conductivity equation, 75  
 heat flux density, 28. *see also* critical heat flux densities  
   computation of, 211–214  
   formation of, 124–126  
   self-regulation of, 35  
 heat transfer  
   coefficient, 26, 50, 62, 138*t*, 157  
   different modes of  
     during quenching, 58–59  
   intensification, 157  
   intensifying processes of, 182  
     discrete-impulse energy input process, 182–183  
     rotating magnetic fields, use of, 183–184  
     during quenching, 30, 31  
 heat transfer equations, 62–63  
 high-speed punches and dies, service life evaluation of, 206  
 high-strengthened materials, achieving, 135–136  
 high-strength steels, design of, 1  
   current process examples, 20–21  
   factors affecting strength and service life of steel parts, 2–3  
   high-temperature thermomechanical treatment (HTMT), 6  
     machine-construction steels, 9–10  
     on mechanical properties of steels, 9  
   intensive quenching combined with TMT process, 15–16  
   low-temperature thermomechanical treatment (LTMT), 10  
   phase transformations, role of, 3  
     diffusion-free transformation, 4–6  
     diffusion transformations of supercooled austenite, 3–4  
   spring steels, thermomechanical treatment of, 14–15  
   steel heat treatment, problems arising during, 16–20  
   strength versus dislocation density in metal, 2*f*  
   thermomechanical heat treatment, use of, 10–14  
 high-temperature thermomechanical treatment (HTMT), 6, 8*f*, 42, 130  
   machine-construction steels, 9–10  
   on mechanical properties of steels, 9  
 high thermal gradients, 122  
 high-velocity IQ system, 190–191  
 hoop stresses, 147–148  
 H values, 170, 171*f*

## I

impellers, 182*f*  
 industrial conveyors speed, calculation of, 157–158

industrial quenching systems, design of, 170

- batch quenching, 180–182
- conveyor lines and quenching processes design, 175
  - speed of conveyor, calculation of, 177–178
  - speed of rotation, calculation of, 178–180
- Grossmann H value and generalized Biot number, relationship between, 170
- heat transfer, intensifying processes of, 182
  - discrete-impulse energy input process, 182–183
  - rotating magnetic fields, use of, 183–184
- Kondratjev numbers, calculation of, 170
  - aqueous polymer quenchants, cooling capacity of, 172
  - cooling capacity of oils and comparison with cooling capacity of aqueous polymer solutions, 172–175

intensive quenching, 1

- combined with TMT process, 15–16
- process variations, 107

intensive steel quenching methods, 151

- IQ-1 process, 107, 151–154
- IQ-2 process, 24, 107, 154, 185–186
  - heat transfer intensification, 157
  - implementation, examples of, 158–160
  - industrial conveyors speed, calculation of, 157–158
- IQ-3 process, 24, 107, 160, 186
  - absence of nonstationary nucleate boiling, determining, 160–162
  - quenching truck semi-axles, application for, 162–165
  - time to achieve maximum surface compressive stresses, 162
- IQ-4 process, 107, 165–166
- IQ-5 process, 107, 166
  - agricultural machine cutting parts, intensive hardening of, 166–167
  - calculation results, 167
  - results, practical appreciation of, 167–168

inverse problems, in quench process design, 210

- conveyor speed evaluation, generalized equations for, 225–227
- cooling characteristics of quenchants, determination of method and software for, 216–218
- definition, 210
- MZM-16 oil cooling capacity, determination of, 218–223
- quench process of semi-axles and cylinder-shaped steel parts, verification of, 223–225
- sequential function specification technique versus regularization method, 215
- solving methods, 210
  - cooling characteristics of quenchants, determination of, 210
  - Green function method, 214
  - heat flux density, computation of, 211–214
  - mass transfer problems solving, general approach of, 215
  - statistical regularization method, 214–215
  - surface temperature and heat flux densities for specific steel parts, determination of, 211
  - thermal properties of steel, determination of, 210–211
  - thermocouples placement, in probes, 211
  - Tikhonov regularization method, 214

IQLab, 154

isothermal steel quenching, 127–128

## J

JIS silver probe, 99*f*

## K

keyway shaft distortions, 187–189

Kh18N9T, 121, 213

Kh18N10T, 121

Kondratjev form coefficient, 84

Kondratjev form factors, determination of, 95–96, 95*t*, 96*t*, 97*t*, 98*t*

Kondratjev number, 92, 103–104*t*, 153, 227

- and Biot number, 86
- calculation of, 170
  - for Amolite 22 oil, 174*t*, 175*t*, 176*t*
  - aqueous polymer quenchants, cooling capacity of, 172
  - for aqueous UCON A solution, 176*t*, 177*t*
  - for aqueous UCON E solution, 177*t*
  - for Beacon 70 oil, 175*t*, 176*t*
  - cooling capacity of oils versus cooling capacity of aqueous polymer solutions, 172–175
  - for Houghton K oil, 174*t*

KRAZ (Kremenchuk Automobile Zavod), 127

## L

Labuntsov equation, 41

leaf spring samples, 196

liquid media under pressure, steel quenching in, 131–133

liquid nitrogen, quenching in, 144–145

Liščić-Nanmac probe, 100, 213

Liščić method, 58

Liščić probe, 211

low-temperature thermomechanical treatment (LTMT), 7, 10, 10*f*, 11*f*, 42, 121, 128–129, 137

## M

machine-construction steels, 9–10

martensite, 4, 5*f*

- for intensive and slow cooling, 6*f*
- lattice parameters of, 5*f*
- lattices of martensite phases in steel, 5*f*
- start and finish temperature versus content of carbon in steel, 5*f*
- start temperature point, 6*f*, 122, 124, 152, 160*t*

martensitic through-hardening, stress state of cylindrical bodies after, 108

mass transfer problems, solving, 215

mechanically rotated chute quench systems, 180*f*

MK oil versus temperature, physical properties of, 224*t*

minimum strength, determination of, 2

MZM-16 oil cooling capacity, determination of, 218–223

## N

natural convection, 62

natural movement, 62

Newton-Riemann equation, 62

nonlinear wave mechanics, phenomenon of, 137

nucleate boiling, 46–47, 128, 131, 132, 155, 187
 

- nonstationary versus convection heat transfer coefficient, 158*t*

nucleating centers, 27
 

- formation of, 26

numbers of similarity/criteria, 64  
Nusselt number, 64

## O

oil-quenched coil spring, 195*f*  
oil quenching, 1  
one-dimensional cylinder, cooling time calculation for, 78–81, 79*t*  
one-dimensional slab (plate), cooling time calculation for, 76–78  
optimal spatial arrangements of nozzles, 69–70

## P

packet martensite, formation of, 139–142  
part distortion  
    distortion study on keyway shaft, 187–189  
    due to nonuniform cooling, 186–187  
    due to part geometry, 186  
petroleum oils, 1  
phase transformations' role during steel strengthening, 3  
    diffusion-free transformation, 4–6  
    diffusion transformations of supercooled austenite, 3–4  
Pokel equation, 75  
polyalkyleneglycol (PAG) copolymers, 172, 174  
practical applications, of intensive quenching methods, 185  
    IQ demonstration studies, equipment for, 189  
        batch-type IQ equipment, 191–192  
        single-part quenching IQ systems, 189–191  
    IQ trials, 192  
        automotive parts, 192–198  
        fasteners, 207–208  
        forgings, 198–204  
        tool products, 204–207  
part distortion  
    distortion study on keyway shaft, 187–189  
    general considerations, 186–187  
    quench cooling rate and part mechanical properties, 185–186  
Prandtl number, 64, 65*t*  
pressure control during steel quenching. *see* steel quenching  
production 6,000-gallon IQ system, 191*f*  
PS-11, 121

## Q

$Q_{CR1}$ , determination of  
    under free convection conditions, 48–49  
quench cooling rate and part mechanical properties, 185–186  
quench process investigations, 37–41

## R

R6M5 steel, 139  
    punches after conventional and very intensive quenching, 141*f*  
railroad parts, 198, 201–203  
rank effect, 143  
rapid cooling, 151  
rapid interrupted cooling, 140, 141  
rebar, 20  
regularization method versus sequential function specification technique, 215  
regular thermal process, 91  
    application, to bodies of complex shape, 93–95

calculation of, by finite element method (FEM)  
    calculations, 97  
discussion, 101  
    cooling time calculation, example of, 102  
Kondratjev form factors, determination of, 95–96  
problem to be solved in nearest future, 105–106  
standardized probes for evaluation of cooling capacity, 97–101

reinforcing bar. *see* rebar  
Reynolds number, 62  
rotary drum screw conveyor continuous furnace, 179  
rotating magnetic fields, use of, 183–184

## S

SAE 5145 steel probe, 98*f*  
second Kondratjev theorem, 92  
self-regulated thermal process, 33–35, 35*t*, 38*t*, 42, 47, 135, 145  
    experimental determination of time of, 35–37  
semi-axes quenching, 162–164  
    and cylinder-shaped steel parts, 223–225  
sequential function specification technique versus regularization method, 215  
ShKh15, 127, 128  
shock boiling, 41–42, 45–46  
shock-resisting punches, 204–206  
single-part quenching IQ systems, 189–191  
speed of conveyor in quench tank, calculation of, 177–178  
speed of rotation of usual and screw drums, calculation of, 178–180  
sphere, cooling time calculation for, 81–82, 83*t*  
splined half-axes, computations for, 113–114  
spray cooling, 67–69  
sprayers with slots, 69  
spring steels, thermomechanical treatment of, 14–15  
statistical regularization method, 214–215  
steel(s)  
    diffusion-free transformation in, 4–6  
    heat treatment, problems arising during, 16–20  
    machine-construction steels, 9–10  
    mechanical properties of  
        HTMT parameters on, 9  
parts  
    factors affecting strength and service life of, 2–3  
    properties vs. cooling rate, 186  
strengthening, phase transformations' role during, 3  
    diffusion-free transformation, 4–6  
    diffusion transformations of supercooled austenite, 3–4  
steel quenching, 121  
    automated process, 131*t*  
    chemical composition, 129*t*  
    under controlled pressure, 121  
        boundary liquid boiling layer and critical heat flux density, formation of, 124–126  
        installation, 122*f*  
    crack formation, effect of pressure on, 126–127  
    heat transfer during, 30  
    in liquid media under pressure, prospects of, 131–133  
    quench process under pressure for tools, 130–131  
    temperatures of phase transformations, 129*t*  
    thermomechanical treatment, 127–130

steel superstrengthening phenomenon, 135  
 achievement, alternative ways of, 135–136  
 in cryogenic biphasic medium, 144*f*  
 experimental validation, 137  
   experimental device, 137–138  
   nonlinear wave mechanics, 137  
   packet martensite, formation of, 139–142  
   two-step quenching experiments, results of, 138–139  
 forging, 147–148  
 nature, 136–137  
 practical applications, 142  
   aqueous salt solutions cooled below room temperature, use of, 145–146  
   cryogenic quenchants and special devices, use of, 144–145  
   fluidized bed quenching at low temperatures, 142–144  
 strength versus dislocation density in metal, 2*f*  
 stresses distribution through section of cylindrical parts, 109  
   cross-sections of parts, 110  
   optimal hard layer, 110–111  
   at optimal layer of martensite, 111  
 stress state of steel parts during intensive quenching, 107  
   analysis of, 111–112  
   of complex part, 112  
     bearing rings, computations for, 112–113  
     splined half-axes, computations for, 113–114  
   discussion, 114–118  
   distribution of current stresses through section of cylindrical parts, 109  
     at optimal layer of martensite, 111  
     cross-sections of parts, 110  
     optimal hard layer, 110–111  
   intensive quenching process variations, 107  
   after martensitic through-hardening, 108–109  
   thermal and stress-strain states, calculation of mathematical models for, 107–108  
 supercooled austenite, diffusion transformations of, 3–4  
 superstrengthening of metals, 135  
 surface temperature and heat flux densities for specific steel parts, determination of, 211

## T

Tandem-Hart software, 154  
 techniques of intensive quenching, 152*f*  
 tempering of strained steel, 3  
 tensile strength, 3  
 Tensi method, 58  
 theoretical strength of material, 2  
 thermal and stress-strain states, calculation of mathematical models for, 107–108  
 thermal problems related to steel quenching  
   algorithms to obtain approximate solutions, 32–34  
   statement of the problem, 31  
   statement of the variational problem, 31–32  
 thermal properties of steel, determination of, 210–211  
 thermocouples placement, in probes, 211

thermomechanical heat treatment, 135  
   combined with intensive quenching process, 15–16  
   use of, 10–14  
 three-dimensional slab (parallelepiped), cooling time  
   calculation for, 82–84, 83*f*  
 Tikhonov regularization method, 214  
 Tolubinsky's empirical correlation, 30  
 tool products, 204  
   H-13 steel aluminum die casting dies, case study for, 206–207  
   high-speed punches and dies, service life evaluation of, 206  
   shock-resisting punches, 204–206  
 torsion bar samples, 196–197  
 transient nucleate boiling and self-regulated thermal processes, 24  
   analytical solution to thermal problems related to steel quenching  
     algorithms to obtain approximate solutions, 32–34  
     statement of the problem, 31  
     statement of the variational problem, 31–32  
   bubble parameters and dynamics, 24  
     surface properties, 25–30  
   discussion  
     quench process investigations, 37–41  
     self-regulated thermal process, 42  
     shock boiling, 41–42  
   heat transfer during steel quenching, 30  
   self-regulated thermal process, 34–35  
     experimental determination of time of, 35–37  
 transmission electronic microscopy (TEM), 6  
 truck semi-axes quenching, 162–165  
 TTT (time-temperature transformation) diagram, 4, 7, 88  
 two-step quenching experiments, 138–139

## U

U7A steel, 139, 140*t*  
 UCON Quenchant A, 172  
 UCON Quenchant E, 172  
 underheat, 27  
 universal joint crosses, 197–198, 199*f*, 200*f*

## V

vapor bubble growth rate, 24

## W

washing and quenching device (WQ1), 158  
 water  
   flow, convective heat transfer in, 65–67  
   physical properties of, 29*t*  
   saturation temperature versus pressure, 125*t*  
   temperature versus heat flux density, 125*t*  
   vapor, properties of  
     at saturation temperature, 29*t*  
 World Scientific and Engineering Academy and Society (WSEAS), 214