

Subject Index

I

12Cr18Ni10Ti stainless steel, 209-218

A

atom probe tomography, 128-151
austenitic stainless steel, 219-236

B

beltline welding seam, 114-127

C

CANDU fuel, 251-274
carbon segregation, 152-162
carbon-manganese steel, 93-113
Charpy impact, 1-25
copper, 1-25
Cr content, 163-174
crack arrest, 40-63

D

deformation wave, 209-218
dislocation cell, 219-236
dislocation channel, 219-236
dpa, 195-208
ductile-to-brittle transition region, 26-39
ductile-to-brittle transition temperature (DBTT), 152-162
ductility, 195-208

E

embrittlement, 152-162
embrittlement correlation, 64-92
energy balance, 237-250
excess heat, 237-250

F

finite element modeling, 251-274
fracture toughness, 26-39, 114-127, 1-25, 40-63

G

grain-boundary, 152-162

H

high damage dose, 209-218
high fluence, 128-151

I

integrity assessment, 114-127
intergranular fracture, 152-162
irradiation embrittlement, 163-174, 40-63
irradiation hardening, 163-174
irradiation temperature, 163-174

L

latent energy, 237-250

M

Magnox power station, 93-113
martensite, 209-218
master curve, 1-25, 40-63

Master Curve, 26-39, 114-127
 microstructural characterization, 64-92
 monitoring programme, 93-113
 Multi-Modal Master Curve, 26-39

N

neutron irradiation, 163-174, 93-113, 237-250, 219-236, 152-162, 40-63
 neutron irradiation embrittlement, 64-92, 128-151
 nickel, 1-25

O

oxide dispersion strengthened steel, 163-174

P

phosphorus segregation, 152-162
 plastic deformation, 219-236
 post-irradiation annealing, 237-250
 precipitates, 195-208
 PWR, 1-25

R

radiation embrittlement, 1-25
 reactor pressure vessel, 64-92, 128-151, 152-162
 reactor pressure vessel steel, 114-127, 40-63
 reactor pressure vessels, 1-25
 RT_{NDT} , 40-63
 RT_{T0} , 40-63

Russian WWER-type reactor, 114-127

S

spent fuel storage, 251-274
 steel reactor pressure vessel, 93-113
 surveillance capsules, 26-39
 surveillance data, 64-92

T

transmission electron microscopy, 128-151, 195-208
 trepans, 114-127
 true stress-true strain relation, 219-236

U

ultimate tensile strength, 195-208

V

voids, 195-208

W

weld metal, 114-127
 work hardening rate, 219-236
 WWER, 1-25

Y

yield strength, 195-208