

## Subject Index

### A

- Aero engines, 68, 82, 130
- Aluminide coating, 56, 82
- Aluminides, 174
- Aluminum, 3

### B

- Bodner-Partom unified constitutive theory, 236

### C

- Chromium, 3
- Coatings, 3, 82
- Composites, 252, 280
  - fiber reinforced, 146
  - titanium matrix, 236, 299
  - SCS-6/Ti-6Al-4V, 266
  - SCS-6/Ti-6Al-2Sn-4Zn-2Mo, 352
  - SCS-6/Timetal 21S, 213, 280, 331
  - silicon carbide, 252
- Crack density, 68
- Crack growth, 56, 130, 187, 352
- Cracking, environmentally assisted, 174
- Crack initiation, 41, 56, 117
  - coating, 68
- Crack propagation, 130
- Crack shielding, 82
- Crack tip plasticity, 187
- Creep, 96, 252, 331
- Creep testing, 27
- Cyclic fatigue loading, 236
- Cyclic softening/hardening, 27, 56
- Cyclic stresses, 280
- Cycling, fatigue loading, 252

### D

- Damage, 213
  - fatigue, 27

- interfacial, 236
- mechanics, 299, 331
- models, 280, 299

- Deformation tests, 146
- Ductile-brittle transition temperature, 68

### E

- Electrical resistance heating, 174
- Energy release rate, 68
- Engines, 68, 82, 130, 187, 252

### F

- Fatigue, 96, 252, 280, 299
  - crack growth, 187, 352
  - cracking, 3
  - damage, 27
  - life, 27, 56, 96
    - prediction, 187
  - load, 236
  - low cycle, 3
  - mechanical, 331
  - mission cycle testing, 266
  - thermal, 41, 174
- Flight simulation, 252
- Fracture modes, 130

### H

- Hardening, nonlinear kinematic, 146
- Hydrogen embrittlement, 174
- Hydrostatic stress, 117

### I

- Induction heating, 41
- Inelastic analysis, 117
- Interfacial damage, 236
- Intermetallic compounds, 174
- Isothermal fatigue, 213, 280, 352

**L**

Laminates, 236, 252, 299  
 Life fraction model, 331  
 Linear summation, 187, 352  
 Line initiation behavior, 68  
 Loading, 68, 213, 252  
     low strain, 41

**M**

Metal matrix composites  
     titanium matrix, 236, 299  
         SCS-6/Ti-6Al-4V, 266  
         SCS-6/Ti-6Al-2Sn-4Zn-2Mo,  
             352  
         SCS-6/Timetal 21S, 213,  
             280, 331  
         silicon carbide, 252  
 Microcrack, 82  
     initiation, 56  
     mechanics, 299  
 Microstructure, 27  
 Models, 187  
     crack shielding,  
         two-dimensional, 82  
     damage, 280, 299  
     flight simulation, 252  
     life fraction, 331  
     linear summation, 352  
     micromechanical, 213  
     statistical, 236  
     structural, 117  
     viscoplastic, 146

**N**

Nickel-based  
     alloy, 56, 68, 82  
     superalloy, 3, 27, 41, 130  
 Nonlinear hardening, 146

**O**

Oxidation, 3, 41, 96  
 Oxygen embrittlement, 187

**P**

Plasticity, 213

**R**

Rafting, 27  
 S  
     Shearing, 27  
     Silicon-carbide fibers, 252, 266,  
         280  
     Single crystals, 3, 27, 41, 130  
         coated, 3, 56, 68  
     Spalling, 41  
     Stainless steel, 96, 117  
     Strain measurement, 41  
     Strain ratchetting, 213  
     Strain recovery mechanisms,  
         146  
     Stress, 266  
         biaxial, state, 117  
         hydrostatic, 117  
     Superalloy, 130  
         nickel-based, 3, 27, 41  
     Surface crack, 68, 82

**T**

Tensile stress, 27  
 Thermal cycling test, 174  
 Thermal fatigue, 41  
     testing system, 174  
 Time-dependent behavior, 331  
 Timetal, 146, 213, 280  
 Titanium  
     alloys, 146, 187  
     matrix composites, 236, 299  
         SCS-6/Ti-6Al-4V, 266  
         SCS-6/Ti-6Al-2Sn-4Zn-2Mo,  
             352  
         SCS-6/Timetal 21S, 213,  
             280, 331  
         silicon carbide, 252  
 Triaxiality, 117  
 Turbine blades, 56  
 Turbine engines, 130, 187, 252

**V**

Viscoplasticity, 146

**Y**

Yield strength, 174