

Subject Index

A

alloys, 79-92
automated ball indentation testing,
236-55

B

bimodal fracture, 122-35
brittle-to ductile transition, 180-95

C

crack arrest, 49-69, 93-113
crack tip blunting, 18-31
CTOA, 18-31
CTOD, 18-31
cyclic indentation testing, 236-55

D

ductile fracture, 1-17
ductile-to-brittle transition regime,
170-9
ductile-to-brittle transition
temperature, 32-48, 70-8, 136-58
dynamic fracture, 93-113
dynamic mechanical properties, 170-
9

E

Ernst's modified J-integral, 18-31
Eurofer97, 114-21
extensometry, 79-92

F

F0300 fatigue, 159-69
fatigue response for plastically
deformed material., 236-55
ferritic/martensitic, 159-69
finite element analysis, 196-217
finite element calculations, 49-69
flow localization, 79-92
force-displacement data, 236-55
fracture, 196-217
fracture toughness, 93-113, 114-21,
180-95

I

impact fracture toughness, 170-9

J

J-R curve testing, 1-17
JRQ, 170-9

L

loading rate, 170-9
loss of constraint, 170-9
low activation, 159-69
low cycle fatigue, 236-55
lower-bound, 180-95

M

master-curve, 93-113, 114-21, 180-95
MC(T), 18-31
metals, 79-92
miniature compact tension
specimens, 18-31

N

neutron irradiation, 79-92

P

PCCv, 49-69

PKLST specimens, 170-9

plastic depth of penetration, 236-55

precracking, 122-35

R

radiation embrittlement, 32-48, 70-8, 136-58

RAFM, 122-35

reactor pressure vessel, 32-48, 70-8, 136-58

S

S1000 steels, 159-69

S1300 surface effects, 159-69

size criteria, 1-17

size effects, 1-17

small punch test, 196-217

small specimens, 114-21

specimen measuring capacity, 18-31

specimen reconstitution, 32-48, 70-8, 136-58

starter notch, 49-69

strain rate sensitivity, 170-9

subsize impact bend specimens, 32-48, 70-8, 136-58

T

Ta rich inclusion, 122-35

tensile properties, 79-92

transferability, 180-95

U

upper shelf, 170-9

upper shelf fracture toughness, 18-31

V

validity, 180-95

W

weld, 196-217

work hardening, 18-31

Z

Zircaloy-4, 196-217