

Author Index

B

Binder, C., 105-116, 162-171,
172-181
Brock, T., 105-116

C

Castillo, M., 233-244
Chiffolleau, G. J., 245-305
Ciscato, W., 162-171, 172-181
Colson, A., 198-224
Coste, F., 117-146
Crayssac, F., 117-146

D

Davis, S. E., 1-27
Dielforder, P., 105-116
Dobinson, C., 225-232

F

Forsyth, B. S., 245-261,
262-273
Forsyth, E. T., 262-273, 274-305

G

Gallus, T. D., 62-80, 182-197

H

Hesse, O., 162-171, 172-181
Hooser, J., 274-305
Houghton, P., 117-146

J

Jeffers, N., 182-197

K

Kleinberg, W., 117-146

L

Lehné, S., 162-171, 172-181
Leschevich, V. V., 147-161
Lineberry, D. M., 28-46
Linley, N., 274-305
Longuet, O., 198-224
Lynn, D., 233-244

M

Meilinger, M., 81-104
Mulkey, H. W., 28-46

N

Nelson, P., 225-232
Newton, B. E., 245-261, 262-273,
274-305

O

Odom, G. A., 245-261

P

Paulos, T., 233-244
Penyazkov, O. G., 147-161
Piña Arpin, C. Y., 47-61
Plagens, O., 233-244

R

Ridlova, M., 198-224
Rostaing, J. C., 117-146, 147-161,
198-224

S

Sparks, K., 62-80
Steinberg, T., 225-232,
233-244
Stoltzfus, J., 47-80,
182-197
Sun, L., 117-146

T

Tillack, T., 105-116, 162-171, 172-181
Treisch, N., 105-116

W

Werlen, E., 117-146

Subject Index

A

accident research, 105-116
aging of diving valves, 162-171,
172-181
air separation unit, 117-146
aluminum, 81-104, 105-116, 117-146,
233-244
aluminum oxide, 233-244
analysis, 262-273
ASTM G124, 274-305
auto-ignition, 147-161
average burn length, 274-305

B

bulk aluminum, 233-244
burn curve, 274-305
burn-out safety, 162-171, 172-181
bursting diaphragm, 105-116

C

carbon steel, 198-224
combustion products, 233-244
compatibility, 262-273
consequence, 262-273
contamination, 81-104

E

elevated temperature, 81-104
exemption pressure, 274-305

F

field shop environment, 47-61
fire, 262-273
fire propagation, 198-224

fire risk, 105-116
flammability, 117-146, 182-197
flow friction, 62-80

H

halogenated non-metals, 245-261
hardware cleaning procedures, 47-61
heat affected, 198-224
high pressure, 81-104
high-pressure oxygen, 105-116

I

ignition, 81-104, 117-146, 262-273
ignition mechanism, 62-80
ignition source, 105-116
iron micro-particle powders, 147-161

L

Level 300, 47-61
liquid oxygen, 28-46
liquid rocket engine testing, 28-46

M

metallic material, 105-116
Metals flammability, 274-305
metals selection, 274-305
minimum burn pressure, 274-305
modified air valves, 162-171, 172-181
molecular sieve, 81-104
morphology, 233-244

N

NITROX, 162-171, 172-181
non-cleanroom, 47-61

non-halogenated non-metals, 245-261
 nonmetals, 262-273

O

oil, 81-104
 oxygen, 81-104, 117-146, 147-161,
 162-171, 172-181, 182-197, 262-273,
 274-305
 oxygen compatibility, 162-171,
 172-181, 198-224, 274-305
 oxygen fire, 245-261
 oxygen hazards, 28-46
 oxygen systems, 47-61
 oxygen-enriched, 274-305

P

particle impact, 81-104
 particle size, 233-244
 particles, 81-104
 perlite, 81-104
 pipe fracture, 81-104
 pipe wall burn-through, 198-224
 pneumatic impact, 162-171,
 172-181
 polymers, 245-261, 262-273
 precision cleaning, 47-61
 pressurized oxygen-enriched systems,
 62-80
 probability, 262-273
 process, 47-61
 promoted ignition, 198-224
 propulsion testing facility, 28-46

Q

quartz sand, 81-104

R

rapid compression machine, 147-161
 reaction effect, 245-261
 risk, 262-273
 RRMI, 182-197
 rudimentary cleaning, 47-61
 rust, 81-104

S

safety engineering, 105-116
 SCUBA diving, 162-171, 172-181
 spontaneous combustion, 62-80
 stainless steel, 198-224
 statistical analysis, 274-305
 swarf, 81-104

T

titanium, 182-197
 toxicity, 262-273

U

university of alabama huntsville pro-
 pulsion research center, 28-46

V

valve seat, 172-181