# Subject Index

A	D 1074–83, 30
A	D 2166–66, 218
Acceptance tests	D 2435–80, 220
class B and C wastes, 79	G 21, 79
quality-control procedure for hazardous	G 21–70, 87
wastes, 93	G 22, 79
stabilization/solidification processes, 114	G 22–76, 87
Acidity, effect on fly ash leaching, 170	
Acoustic testing, cement-stabilized heavy metal waste, 184	В
Adsorption, exchanged clays, 277	Barium, fly ash TCLP results, 348
Alkalinity, effect on product leachability,	Barriers, engineered, 330
143	Batch leaching
American Nuclear Society	American Nuclear Society test, 21, 28
ANS 16.1, 23, 31, 58, 79, 251, 303	58, 303
ANS 55.1, 79, 87	Dutch protocol, 170
American Nuclear Society test	EPA Extraction Procedure Toxicity test
bitumen in mixed waste stabilization, 21	7, 21, 28, 58, 150, 325
extruded bitumen containing a surro-	ISO 6961-82, 87
gate, sodium-based waste, 28	TCLP extractions, 150, 156, 163, 165
nitrate salt wastes solidified in polyeth-	347, 349
ylene, 58	Bearing strength, for mix ratios, 199
tritium release from encapsulated tita-	Bismuth oxylodide, solubility and stability
nium tritide accelerator targets, 251	287
Anion displacement	Bitumen
bismuth oxylodide, 296	blocks, leaching, 385
silver iodide, 294	effect of hydrologic factors on leaching
Antimony-125, field testing with lysime-	333
ters, 413	extruded, leaching and regulatory per
Arsenic, fly ash TCLP results, 348	formance testing, 28
ASTM standards	mixed waste stabilization, 21
B 553, 79	solidification processes, NRC topical re
C 39, 79	ports, 81
C 109–80, 18	stability, 80
C 109–86, 261	Blast furnace slag/lime, leaching, 125
C 215-85, 186 C 305-82, 185, 203	Blocks, leaching tests bitumen, 385
C 403–80, 18	cement, 384
C 666–84, 185–186	polymer, 386
D 92–72, 31	British Standards
D 559-82, 222	BS 12, 99
D 560–82, 222	BS 146, 99
D 635–81, 87	BS 915, 99
D 695, 60	BS 1370, 99
D 1074–83, 24	BS 1377, 96

British Standards (cont.) BS 1881, 231 BS 4027, 99 BS 4246, 99 BS 4550, 94 BS 4691, 96 C Cadmium cement-stabilized, SEM and TEM, 201 fly ash TCLP results, 348 immobilization by solidification of droxide and xanthate sludges, 257 solidified fly ash TCLP results, 350 Cement blocks, leaching, 384 cesium, cobalt, and strontium leachability, 90 field testing of waste forms with lysimeters, 404 grouts, 418 matrices effects on leaching mechanism, 229 metal containment, SEM and TEM, 201 mixed waste management strategy, 317 quality-assurance procedure for solidified wastes, 93 solid phase, leaching-induced concentration profiles, 302 stabilization/solidification assessment procedure, 121 charcoal and substituted clays in, 273 effect of hydrologic factors, 333 evaluation, 114 heavy metals, freeze-thaw durability, 184 metal containment, SEM and TEM, 201 NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238 Cement-based grouts pumpable, 15 theological properties, 16 Cesium—137 field testing with lysimeters, 413 leachability in cement, 90 Congressibility (see also Unconfined compressive strength tests) bitumen-stabilized mixed wastes, 24 extruded bitumen, 30 polyethylene/sodium nitrate waste forms, 60 Concrete leach data from tank leaching and concentration profile analysis, 146 mortar, leaching, 125 Cone penetration profile analysis, 146 m		
BS 4246, 99 BS 4246, 99 BS 4550, 94 BS 4691, 96 C Cadmium cement-stabilized, SEM and TEM, 201 fly ash TCLP results, 348 immobilization by solidification of hydroxide and xanthate sludges, 257 solidified fly ash TCLP results, 350 Cement blocks, leaching, 384 cesium, cobalt, and strontium leachability, 90 field testing of waste forms with lysimeters, 404 grouts, 418 matrices effects on leaching mechanism, 229 metal containment, SEM and TEM, 201 mixed waste management strategy, 317 quality-assurance procedure for solidified wastes, 93 solid phase, leaching-induced concentration profiles, 302 stabilization/solidification assessment procedure, 121 charcoal and substituted clays in, 273 effect of hydrologic factors, 333 evaluation, 114 heavy metals, freeze-thaw durability, 184 metal containment, SEM and TEM, 201 NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238 Cement-based grouts pumpable, 15 rheological properties, 16 Cesium-137 field testing with lysimeters, 413 leachability in cement, 90 release from cement, solid-phase analysis, 302 release under simulated disposal conditions, 335 Charcoal, for stabilization/solidification of hydroxide sludges, 261 Chlorophenols, charcoal and tetra-alky-lammonium-substituted clays for satbilization/solidification of hydroxide and xanthate sludges, 275 Classification of waste Italian Regulatory Body (ENEA/DISP), 83 NRC regulation 10 CFR Part 61, 78 Clays, tetra-alkylammonium-substituted, 273 Cobalt-60 field testing with lysimeters, 413 leaching; effects of hydrologic factors, 374 release under different leaching techniques, 333 Cobalt-68, leachability (see also Unconfined compressive strength tests) bitumen-stabilized mixed wastes, 24 extruded bitumen, 30 polyethylene/sodium nitrate waste forms, 60 Concrete leach data from tank leaching and concentration testing, 250 construction materials, leaching, 125 Consolidation testing, 280 Consolidation testing, 250 Construction materials, leaching, 125 Consolidation testing, 280 Construction materials, leach	British Standards (cont.)	40
BS 4246, 99 BS 4250, 94 BS 4691, 96 C Cadmium cement-stabilized, SEM and TEM, 201 fly ash TCLP results, 348 immobilization by solidification of hydroxide and xanthate sludges, 257 solidified fly ash TCLP results, 350 Cement blocks, leaching, 384 cesium, cobalt, and strontium leachability, 90 field testing of waste forms with lysimeters, 404 grouts, 418 matrices effects on leaching mechanism, 229 metal containment, SEM and TEM, 201 mixed waste management strategy, 317 quality-assurance procedure for solidified wastes, 93 solid phase, leaching-induced concentration profiles, 302 stabilization/solidification assessment procedure, 121 charcoal and substituted clays in, 273 effect of hydrologic factors, 333 evaluation, 114 heavy metals, freeze-thaw durability, 184 metal containment, SEM and TEM, 201 NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238 Cement-based grouts pumpable, 15 theological properties, 16 Cesium-137 field testing with lysimeters, 413 leachability in cement, 90 release from cement, solid-phase analysis, 302 release under simulated disposal conditions, 335 Charcoal, for stabilization/solidification of sate learning and concentration profile analysis, 146 mortar, leaching, 125 Consolidation testing, 258 Consolidation testing, 258 Consolidation data tra-alky-lammonium-substituted clays for stabilization/solidification of waste Italian Regulatory Body (ENEA/IDISP), 83 Cobalt-58, leachability in cement, 90 Compressibility (see also Unconfined compressive strength tests) bitumen-stabilized mixed wastes, 24 extruded bitumen, 30 polyethylene/sodium nitrate waste forms, 60 Concrete leach data from tank leaching and concentration profile analysis, 146 mortar, leaching, 125 Consolidation testing, 280 Compressibility (see also Unconfined compressive strength tests) bitumen-stabilized mixed and xanthate sludges, 257 Classification of waste Italian Regulatory Body (ENEA/IDISP), 83 Cobalt-58, leachability (see also Unconfined compressive strength tests) bitumen stabilized mixed waste		
BS 4248, 99 BS 4550, 94 BS 4691, 96  Cadmium cement-stabilized, SEM and TEM, 201 fly ash TCLP results, 348 immobilization by solidification of hydroxide and xanthate sludges, 257 solidified fly ash TCLP results, 350 Cement blocks, leaching, 384 cesium, cobalt, and strontium leachability, 90 field testing of waste forms with lysimeters, 404 grouts, 418 matrices effects on leaching mechanism, 229 metal containment, SEM and TEM, 201 mixed waste, 93 solid phase, leaching-induced concentration profiles, 302 stabilization/solidification assessment procedure, 121 charcoal and substituted clays in, 273 effect of hydrologic factors, 333 evaluation, 114 heavy metals, freeze-thaw durability, 184 metal containment, SEM and TEM, 201 NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238 Cement-based grouts pumpable, 15 theological properties, 16 Cesium-137 field testing with lysimeters, 413 leachability in cement, 90 release under simulated disposal conditions, 335 Charcoal, for stabilization/solidification of specific stabilization with lysimeters, 280 chart-stabilized mixed ladys for stabilization solidification of hydroxide and xenthate clays for stabilization by solidification of waste Italian Regulatory Body (ENEA/DISP), 82 Classification of waste Italian Regulatory Body (ENEA/DISP), 83 NRC regulation 10 CFR Part 61, 78 Clays, tetra-alkylammonium-substituted, 273 Cobalt-56 field testing with lysimeters, 413 leaching, 125 Cobalt-58, leachability in cement, 90 Compressibility (see also Unconfined compressive strength tests) bicumen-stabilized mixed wastes, 24 extruded bitumen, 30 polyethylene/sodium nitrate waste form s	,	
BS 4591, 96  Cadmium cement-stabilized, SEM and TEM, 201 fly ash TCLP results, 348 immobilization by solidification of hydroxide and xanthate sludges, 257 solidified fly ash TCLP results, 350 cement blocks, leaching, 384 cesium, cobalt, and strontium leachability, 90 field testing of waste forms with lysimeters, 404 grouts, 418 matrices effects on leaching mechanism, 229 metal containment, SEM and TEM, 201 mixed waste management strategy, 317 quality-assurance procedure for solidified wastes, 93 solid phase, leaching-induced concentration profiles, 302 stabilization/solidification assessment procedure, 121 charcoal and substituted clays in, 273 effect of hydrologic factors, 333 evaluation, 114 heavy metals, freeze-thaw durability, 184 metal containment, SEM and TEM, 201 NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238 Cement-based grouts pumpable, 15 rheological properties, 16 Cesium–137 field testing with lysimeters, 413 leachability in cement, 90 release from cement, solid-phase analysis, 302 release under simulated disposal conditions, 335 Charcoal, for stabilization/solidification of 194 mrs. Assertive devices of the profile and tricholorethylene, column leach testing, 238 Cement-based grouts pumpable, 15 rheological properties, 16 Cesium–137 field testing with lysimeters, 413 leachability in cement, 90 release from cement, solid-phase analysis, 302 release under simulated disposal conditions, 335 Charcoal, for stabilization/solidification of		
Cadmium cement-stabilized, SEM and TEM, 201 fly ash TCLP results, 348 immobilization by solidification of hydroxide and xanthate sludges, 257 solidified fly ash TCLP results, 350 Cement blocks, leaching, 384 cesium, cobalt, and strontium leachability, 90 field testing of waste forms with lysimeters, 404 grouts, 418 matrices effects on leaching mechanism, 229 metal containment, SEM and TEM, 201 mixed waste management strategy, 317 quality-assurance procedure for solidified wastes, 93 solid phase, leaching-induced concentration profiles, 302 stabilization/solidification assessment procedure, 121 charcoal and substituted clays in, 273 effect of hydrologic factors, 333 evaluation, 114 heavy metals, freeze-thaw durability, 184 metal containment, SEM and TEM, 201 NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238 Cement-based grouts pumpable, 15 theological properties, 16 Cesium-137 field testing with lysimeters, 413 leachability in cement, 90 release from cement, solid-phase analysis, 302 release under simulated disposal conditions, 335 Charcoal, for stabilization/solidification of Stabilization of thydroxide sludges, 261–262 Consolidation testing, stabilized metal hydroxide sludges, 220 Construction materials, leaching, 125 Containers, high-integrity (see High-integrity containers) Cost estimates, surface encapsulation, 51 Trum-scale solidification, fly ash, 333 Duplex stainless steel, high-integrity con-		
Cadmium cement-stabilized, SEM and TEM, 201 fly ash TCLP results, 348 immobilization by solidification of hydroxide and xanthate sludges, 257 solidified fly ash TCLP results, 350 cment blocks, leaching, 384 cesium, cobalt, and strontium leachability, 90 field testing of waste forms with lysimeters, 404 grouts, 418 matrices effects on leaching mechanism, 229 metal containment, SEM and TEM, 201 mixed waste management strategy, 317 quality-assurance procedure for solidified wastes, 93 solid phase, leaching-induced concentration profiles, 302 stabilization/solidification assessment procedure, 121 charcoal and substituted clays in, 273 effect of hydrologic factors, 333 evaluation, 114 heavy metals, freeze-thaw durability, 184 metal containment, SEM and TEM, 201 NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238 Cement-based grouts pumpable, 15 rheological properties, 16 Cesium–137 field testing with lysimeters, 413 leachability in cement, 90 release from cement, solid-phase analysis, 302 release under simulated disposal conditions, 335 Charcoal, for stabilization/solidification of stabilization/solidification of stabilization for stabilization for hydroxide and xanthate sludges, 257 Classification of water Italian Regulatory Body (ENEA/DISP), 83 NRC regulation 10 CFR Part 61, 78 Clays, tetra-alkylammonium-substituted, 273 Cobalt–60 field testing with lysimeters, 413 leaching, effects of hydrologic factors, 374 release under different leaching techniques, 333 Cobalt–58, leachability in cement, 90 Compressibility (see also Unconfined compressive strength tests) bitumen-stabilized mixed wastes, 24 extruded bitumen, 30 polyetylene/sodium nitrate waste forms, 60 Concrete leach data from tank leaching and concentration profile analysis, 146 mortar, leaching, 125 Consolidation testing, stabilized metal hydroxide sludges, 261–262 Containers, high-integrity (see High-integrity containers) Consolidation testing, stabilized metal hydroxide sludges, 250 Diffusivity measurements, 130, 143 Drum-scale		
Cadmium cement-stabilized, SEM and TEM, 201 fly ash TCLP results, 348 immobilization by solidification of hydroxide and xanthate sludges, 257 solidified fly ash TCLP results, 350 Cement blocks, leaching, 384 cesium, cobalt, and strontium leachability, 90 field testing of waste forms with lysimeters, 418 matrices effects on leaching mechanism, 229 metal containment, SEM and TEM, 201 mixed waste management strategy, 317 quality-assurance procedure for solidified wastes, 93 solid phase, leaching-induced concentration profiles, 302 stabilization/solidification assessment procedure, 121 charcoal and substituted clays in, 273 effect of hydrologic factors, 333 evaluation, 114 heavy metals. freeze-thaw durability, 184 metal containment, SEM and TEM, 201 NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238 Cement-based grouts pumpable, 15 rheological properties, 16 Cesium-137 field testing with lysimeters, 413 leachability in cement, 90 release from cement, solid-phase analysis, 302 release under simulated disposal conditions, 335 Charcoal, for stabilization/solidification of bydroxide and xanthate sludges, 257 Classification of waste Italian Regulatory Body (ENEA/DISP), 83 NRC regulation 10 CFR Part 61, 78 Clays, tetra-alkylammonium-substituted, 273 Cobalt-60 field testing with lysimeters, 413 leaching, effects of hydrologic factors, 374 release under different leaching techniques, 333 Cobalt-58, leachability in cement, 90 compressibility (see also Unconfined compressive strength tests) bitumen-stabilized mixed wastes, 24 extruded bitumen, 30 polyethylene/sodium nitrate waste forms, 60 Concrete leach data from tank leaching and concentration profile analysis, 146 mortar, leaching, 125 Consolidation testing, stabilized metal hydroxide sludges, 261–262 Consolidation testing, stabilized metal hydro	BS 4091, 90	
cement-stabilized, SEM and TEM, 201 fly sh TCLP results, 348 immobilization by solidification of hydroxide and xanthate sludges, 257 solidified fly ash TCLP results, 350 Cement blocks, leaching, 384 cesium, cobalt, and strontium leachability, 90 field testing of waste forms with lysimeters, 404 grouts, 418 matrices effects on leaching mechanism, 229 metal containment, SEM and TEM, 201 mixed waste management strategy, 317 quality-assurance procedure for solidified wastes, 93 solid phase, leaching-induced concentration profiles, 302 stabilization/solidification assessment procedure, 121 charcoal and substituted clays in, 273 effect of hydrologic factors, 333 evaluation, 114 heavy metals, freeze-thaw durability, 184 metal containment, SEM and TEM, 201 NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238 Cement-based grouts pumpable, 15 rheological properties, 16 Cesium–137 field testing with lysimeters, 413 leachability in cement, 90 release from cement, 90 release from cement, 90 release under simulated disposal conditions, 335 Charcoal, for stabilization/solidification of hydroxide and xanthate sludges, 257 Classification of waste Italian Regulatory Body (ENEA/DISP), 83 NRC regulation 10 CFR Part 61, 78 Clays, tetra-alkylammonium-substituted, 273 Cobalt–50 field testing with lysimeters, 413 leaching, effects of hydrologic factors, 374 release under different leaching techniques, 333 Cobalt–58, leachability in cement, 90 Compressibility (see also Unconfined compressive strength tests) bitumen-stabilized mixed wastes, 24 extruded bitumen, 30 polyethylene/sodium nitrate waste forms, 60 Concrete leach data from tank leaching and concentration profile analysis, 146 mortar, leaching, 125 Constituction materials, leaching, 125 Containers, high-integrity (see High-integrity containers) Cost estimates, surface encapsulation, 51 Diffusivity measurements, 130, 143 Drum-scale solidification ofly as the form of waste Italian Regulatory Body (ENEA/DISP), 83 Challors (specification of waste Italian R		stabilization/solidification, 273
fly ash TCLP results, 348 immobilization by solidification of hydroxide and xanthate sludges, 257 solidified fly ash TCLP results, 350  Cement blocks, leaching, 384 cesium, cobalt, and strontium leachability, 90 field testing of waste forms with lysimeters, 404 grouts, 418 matrices effects on leaching mechanism, 229 metal containment, SEM and TEM, 201 mixed waste management strategy, 317 quality-assurance procedure for solidified wastes, 93 solid phase, leaching-induced concentration profiles, 302 stabilization/solidification assessment procedure, 121 charcoal and substituted clays in, 273 effect of hydrologic factors, 333 evaluation, 114 heavy metals, freeze-thaw durability, 184 metal containment, SEM and TEM, 201 NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238  Cement-based grouts pumpable, 15 rheological properties, 16 Cesium–137 field testing with lysimeters, 413 leaching, 125 consolidation testing, stabilized metal hydroxide sludges, 257 Classification of waste Italian Regulatory Body (ENEA/DISP), 83 NRC regulation 10 CFR Part 61, 78 Clays, tetra-alkylammonium-substituted, 273 cobalt–60 field testing with lysimeters, 413 leaching, effects of hydrologic factors, 374 release under different leaching techniques, 333 cobalt-58, leachability in cement, 90 compressibility (see also Unconfined compressive strength tests) bitumen-stabilized mixed wastes, 24 extruded bitumen, 30 polyethylene/sodium nitrate waste forms, 60 concrete leach data from tank leaching and concentration profile analysis, 146 mortar, leaching, 125 constituction materials, leaching, 125 constituction materials, leaching, 125 containers, high-integrity (see High-integrity containers) cost estimates, surface encapsulation, 51 polyethylene and salt wastes, 55 Diffusivity measurements, 130, 143 Drum-scale solidification, fly ash, 333 Duplex stainless steel, high-integrity con-		<del>-</del>
immobilization by solidification of hydroxide and xanthate sludges, 257 solidified fly ash TCLP results, 350 Cement blocks, leaching, 384 cesium, cobalt, and strontium leachability, 90 field testing of waste forms with lysimeters, 404 grouts, 418 matrices effects on leaching mechanism, 229 metal containment, SEM and TEM, 201 mixed waste management strategy, 317 quality-assurance procedure for solidification field wastes, 93 solid phase, leaching-induced concentration profiles, 302 stabilization/solidification assessment procedure, 121 charcoal and substituted clays in, 273 effect of hydrologic factors, 333 evaluation, 114 heavy metals, freeze-thaw durability, 184 metal containment, SEM and TEM, 201 NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238 Cement-based grouts pumpable, 15 rheological properties, 16 Cesium—137 field testing with lysimeters, 413 leachability in cement, 90 Concrete leach data from tank leaching and concentration profile analysis, 146 mortar, leaching, 125 Construction materials, leaching, 125 Construction materials, leaching, 125 Construction materials, leaching, 125 Containers, high-integrity (see High-integrity containers) Cost estimates, surface encapsulation, 51  D  immobilization by solidification of hydroxide and xanthate sludges, 227 Classification of waste Italian Regulatory Body (ENEA/DISP), 83 NRC regulation 10 CFR Part 61, 78 Clays, tetra-alkylammonium-substituted, 273 Cobalt-60 field testing with lysimeters, 413 leaching, effects of hydrologic factors, 374 release under different leaching techniques, 333 Cobalt-60 field testing with lysimeters, 413 leaching, effects of hydrologic factors, 374 release under different leaching techniques, 333 Cobalt-60 field testing with lysimeters, 413 leaching, effects of hydrologic factors, 374 release under different leaching techniques, 333 Cobalt-60 food field testing with lysimeters, 413 leaching, effects of hydrologic factors, 374 release under different leaching techniques, 333 Cobalt-60 food field testing w		
droxide and xanthate sludges, 257 solidified fly ash TCLP results, 350 Cement blocks, leaching, 384 cesium, cobalt, and strontium leachability, 90 field testing of waste forms with lysimeters, 404 grouts, 418 matrices effects on leaching mechanism, 229 metal containment, SEM and TEM, 201 mixed waste management strategy, 317 quality-assurance procedure for solidified wastes, 93 solid phase, leaching-induced concentration profiles, 302 stabilization/solidification assessment procedure, 121 charcoal and substituted clays in, 273 effect of hydrologic factors, 333 evaluation, 114 heavy metals. freeze-thaw durability, 184 metal containment, SEM and TEM, 201 NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238 Cement-based grouts pumpable, 15 rheological properties, 16 Cesium—137 field testing with lysimeters, 413 leachability in cement, 90 release from cement, solid-phase analysis, 302 release under simulated disposal conditions, 335 Charcoal, for stabilization/solidification of		
Solidified fly ash TCLP results, 350 Cement blocks, leaching, 384 cesium, cobalt, and strontium leachability, 90 field testing of waste forms with lysimeters, 404 grouts, 418 matrices effects on leaching mechanism, 229 metal containment, SEM and TEM, 201 mixed waste management strategy, 317 quality-assurance procedure for solidified wastes, 93 solid phase, leaching-induced concentration profiles, 302 stabilization/solidification assessment procedure, 121 charcoal and substituted clays in, 273 effect of hydrologic factors, 333 evaluation, 114 heavy metals, freeze-thaw durability, 184 metal containment, SEM and TEM, 201 NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238 Cement-based grouts pumpable, 15 rheological properties, 16 Cesium-137 field testing with lysimeters, 413 leachability in cement, 90 release from cement, solid-phase analysis, 302 release from cement, solid-phase analysis, 302 release under different leaching techniques, 333 Cobalt-50 field testing with lysimeters, 413 leachability in cement, 90 Compressibility (see also Unconfined compressive strength tests) bitumen-stabilized mixed wastes, 24 extruded bitumen, 30 polyethylene/sodium nitrate waste forms, 60 Concrete leach data from tank leaching and concentration profile analysis, 146 mortar, leaching, 125 Cone penetration test, xanthate and hydroxide sludges, 220 Construction materials, leaching, 125 Consolidation testing, stabilized metal hydroxide sludges, 220 Construction materials, leaching, 125 Containers, high-integrity (see High-integrity containers)  D Differential scanning calorimetry, polyethylene and salt wastes, 55 Diffusivity measurements, 130, 143 Drum-scale solidification, fy sah, 333 Duplex stainless steel, high-integrity con-		
Cement blocks, leaching, 384 cesium, cobalt, and strontium leachability, 90 field testing of waste forms with lysimeters, 404 grouts, 418 matrices effects on leaching mechanism. 229 metal containment, SEM and TEM, 201 mixed waste management strategy, 317 quality-assurance procedure for solidified wastes, 93 solid phase, leaching-induced concentration profiles, 302 stabilization/solidification assessment procedure, 121 charcoal and substituted clays in, 273 effect of hydrologic factors, 333 evaluation, 114 heavy metals, freeze-thaw durability, 184 metal containment, SEM and TEM, 201 NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238 Cement-based grouts pumpable, 15 rheological properties, 16 Cesium-137 field testing with lysimeters, 413 leachability in cement, 90 release from cement, solid-phase analysis, 302 release under simulated disposal conditions, 335 Charcoal, for stabilization/solidification of		
blocks, leaching, 384 cesium, cobalt, and strontium leachability, 90 field testing of waste forms with lysimeters, 404 grouts, 418 matrices   effects on leaching mechanism, 229   metal containment, SEM and TEM, 201   mixed waste management strategy, 317   quality-assurance procedure for solidified wastes, 93   solid phase, leaching-induced concentration profiles, 302   stabilization/solidification   assessment procedure, 121   charcoal and substituted clays in, 273   effect of hydrologic factors, 333   evaluation, 114   heavy metals, freeze-thaw durability, 184   metal containment, SEM and TEM, 201   NRC topical reports, 81   phenol and tricholorethylene, column leach testing, 238 Cement-based grouts   pumpable, 15   rheological properties, 16 Cesium—137   field testing with lysimeters, 413   leachability in cement, 90 Concrete   leach data from tank leaching and concentration profile analysis, 146   mortar, leaching, 125 Cone penetration test, xanthate and hydroxide sludges, 261—262   Consolidation testing, stabilized mixed wastes, 37   release under different leaching techniques, 333   Cobalt–58, leachability (see also Unconfined compressive strength tests) bitumen-stabilized mixed wastes, 24   extruded bitumen, 30   polyethylene/sodium nitrate waste forms, 60 Concrete   leach data from tank leaching and concentration test, xanthate and hydroxide sludges, 261—262   Consolidation testing, stabilized metal hydroxide sludges, 220   Construction materials, leaching, 125   Containers, high-integrity (see High-integrity containers)   Congressive strength tests)   bitumen-stabilized mixed wastes, 24   extruded bitumen, 30   polyethylene/sodium nitrate waste forms, 60   Concrete   leach data from tank leaching and concentration test, xanthate and hydroxide sludges, 220   Construction materials, leaching, 125   Consolidation testing, stabilized mixed wastes, 55   Containers, high-integrity (see High-integrity containers)   D   Differential scanning calorimetry, polyethylene and salt wastes, 55   Diffusivity measuremen		
cesium, cobalt, and strontium leachability, 90 gield testing of waste forms with lysimeters, 404 grouts, 418 matrices effects on leaching mechanism, 229 metal containment, SEM and TEM, 201 mixed waste management strategy, 317 quality-assurance procedure for solidified wastes, 93 solid phase, leaching-induced concentration profiles, 302 stabilization/solidification assessment procedure, 121 charcoal and substituted clays in, 273 effect of hydrologic factors, 333 evaluation, 114 heavy metals, freeze-thaw durability, 184 metal containment, SEM and TEM, 201 NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238 Cement-based grouts pumpable, 15 rheological properties, 16 Cesium–137 field testing with lysimeters, 413 leaching, effects of hydrologic factors, 374 release under different leaching techniques, 333 Cobalt–58, leachability in cement, 90 Compressibility (see also Unconfined compressive strength tests) bitumen-stabilized mixed wastes, 24 extruded bitumen, 30 polyethylene/sodium nitrate waste forms, 60 Concrete leach data from tank leaching and concentration profile analysis, 146 mortar, leaching, 125 Consolidation testing, stabilized metal hydroxide sludges, 220 Construction materials, leaching, 125 Containers, high-integrity (see High-integrity containers) Cost estimates, surface encapsulation, 51 D D Differential scanning calorimetry, polyethylene and salt wastes, 55 Diffusivity measurements, 130, 143 Drum-scale solidification, fly ash, 333 Duplex stainless steel, high-integrity con-		
ity, 90 field testing of waste forms with lysimeters, 404 grouts, 418 matrices effects on leaching mechanism, 229 metal containment, SEM and TEM, 201 mixed waste management strategy, 317 quality-assurance procedure for solidified wastes, 93 solid phase, leaching-induced concentration profiles, 302 stabilization/solidification assessment procedure, 121 charcoal and substituted clays in, 273 effect of hydrologic factors, 333 evaluation, 114 heavy metals, freeze-thaw durability, 184 metal containment, SEM and TEM, 201 NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238 Cement-based grouts pumpable, 15 rheological properties, 16 Cesium-137 field testing with lysimeters, 413 leachability in cement, 90 Compressibility (see also Unconfined compressive strength tests) bitumen-stabilized mixed wastes, 24 extruded bitumen, 30 polyethylene/sodium nitrate waste forms, 60 Concrete leach data from tank leaching and concentration profile analysis, 146 mortar, leaching, 125 Cone penetration test, xanthate and hydroxide sludges, 261–262 Consolidation testing, stabilized metal hydroxide sludges, 220 Construction materials, leaching, 125 Containers, high-integrity (see High-integrity containers), surface encapsulation, 51  D Differential scanning calorimetry, polyethylene and salt wastes, 55 Diffusivity measurements, 130, 143 Drum-scale solidification, fly ash, 333 Duplex stainless steel, high-integrity con-		
field testing of waste forms with lysimeters, 404 grouts, 418 matrices effects on leaching mechanism, 229 metal containment, SEM and TEM, 201 mixed waste management strategy, 317 quality-assurance procedure for solidification profiles, 302 stabilization/solidification assessment procedure, 121 charcoal and substituted clays in, 273 effect of hydrologic factors, 333 evaluation, 114 heavy metals, freeze-thaw durability, 184 metal containment, SEM and TEM, 201 NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238 Cement-based grouts pumpable, 15 rheological properties, 16 Cesium-137 field testing with lysimeters, 413 leachability in cement, 90 release under simulated disposal conditions, 335 Charcoal, for stabilization/solidification of		
meters, 404 grouts, 418 matrices effects on leaching mechanism, 229 metal containment, SEM and TEM, 201 mixed waste management strategy, 317 quality-assurance procedure for solidified wastes, 93 solid phase, leaching-induced concentration profiles, 302 stabilization/solidification assessment procedure, 121 charcoal and substituted clays in, 273 effect of hydrologic factors, 333 evaluation, 114 heavy metals, freeze-thaw durability, 184 metal containment, SEM and TEM, 201 NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238 Cement-based grouts pumpable, 15 rheological properties, 16 Cesium-137 field testing with lysimeters, 413 leachability in cement, 90 release from cement, solid-phase analysis, 302 release under different leaching techniques, 333 Cobalt-58, leachability in cement, 90 Compressibility (see also Unconfined compressive strength tests) bitumen-stabilized mixed wastes, 24 extruded bitumen, 30 polyethylene/sodium nitrate waste forms, 60 Concrete leach data from tank leaching and concentration profile analysis, 146 mortar, leaching, effects of hydrologic factors, 374 release under different leaching techniques, 333 Cobalt-58, leachability in cement, 90 Compressibility (see also Unconfined compressive strength tests) bitumen-stabilized mixed wastes, 24 extruded bitumen, 30 polyethylene/sodium nitrate waste forms, 60 Concrete leach data from tank leaching and concentration profile analysis, 146 mortar, leaching, 125 Cone penetration test, xanthate and hydroxide sludges, 261-262 Consolidation testing, stabilized metal hydroxide sludges, 220 Construction materials, leaching, 125 Cone penetration test, stabilized metal hydroxide sludges, 220 Construction materials, leaching, 10 Compressibility in cement, 90 Compressibility in cement, 90 Compressibility in cement, 90 Concrete leach data from tank leaching and concentration profile analysis, 146 mortar, leaching, 125 Cone penetration test, xanthate and hydroxide sludges, 220 Construction materials, leaching, 125 Containers, high-int		
grouts, 418 matrices effects on leaching mechanism, 229 metal containment, SEM and TEM, 201 mixed waste management strategy, 317 quality-assurance procedure for solidified wastes, 93 solid phase, leaching-induced concentration profiles, 302 stabilization/solidification assessment procedure, 121 charcoal and substituted clays in, 273 effect of hydrologic factors, 333 evaluation, 114 heavy metals, freeze-thaw durability, 184 metal containment, SEM and TEM, 201 NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238 Cement-based grouts pumpable, 15 rheological properties, 16 Cesium-137 field testing with lysimeters, 413 leachability in cement, 90 release from cement, solid-phase analysis, 302 release under different leaching techniques, 333 Cobalt-58, leachability in cement, 90 Compressibility (see also Unconfined compressive strength tests) bitumen-stabilized mixed wastes, 24 extruded bitumen, 30 polyethylene/sodium nitrate waste forms, 60 Concrete leach data from tank leaching and concentration profile analysis, 146 mortar, leaching, effects of hydrologic factors, 374 release under different leaching techniques, 333 Cobalt-58, leachability in cement, 90 Compressibility (see also Unconfined compressive strength tests) bitumen-stabilized mixed wastes, 24 extruded bitumen, 30 polyethylene/sodium nitrate waste forms, 60 Concrete leach data from tank leaching and concentration profile analysis, 146 mortar, leaching, 125 Cone penetration test, xanthate and hydroxide sludges, 220 Construction materials, leaching, 125 Containers, high-integrity (see High-integrity containers)  D D Differential scanning calorimetry, polyethylene and salt wastes, 55 Diffusivity measurements, 130, 143 Drum-scale solidification, fly ash, 333 Duplex stainless steel, high-integrity con-		
matrices effects on leaching mechanism, 229 metal containment, SEM and TEM, 201 mixed waste management strategy, 317 quality-assurance procedure for solidified wastes, 93 solid phase, leaching-induced concentration profiles, 302 stabilization/solidification assessment procedure, 121 charcoal and substituted clays in, 273 effect of hydrologic factors, 333 evaluation, 114 heavy metals, freeze-thaw durability, 184 metal containment, SEM and TEM, 201 NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238 Cement-based grouts pumpable, 15 rheological properties, 16 Cesium-137 field testing with lysimeters, 413 leachability in cement, 90 release from cement, solid-phase analysis, 302 release under different leaching techniques, 333 Cobalt-58, leachability in cement, 90 Compressibility (see also Unconfined compressive strength tests) bitumen-stabilized mixed wastes, 24 extruded bitumen, 30 polyethylene/sodium nitrate waste forms, 60 Concrete leach data from tank leaching and concentration profile analysis, 146 mortar, leaching, effects of hydrologic factors, 374 release under different leaching techniques, 333 Cobalt-58, leachability in cement, 90 Compressibility (see also Unconfined compressive strength tests) bitumen-stabilized mixed wastes, 24 extruded bitumen, 30 polyethylene/sodium nitrate waste forms, 60 Concrete leach data from tank leaching and concentration profile analysis, 146 mortar, leaching, effects of hydrologic factors, 374 release under different leaching techniques, 333 Cobalt-58, leachability in cement, 90 Compressibility (see also Unconfined compressive strength tests) bitumen-stabilized mixed wastes, 24 extruded bitumen, 30 polyethylene/sodium nitrate waste forms, 60 Concrete leach data from tank leaching and concentration profile analysis, 146 mortar, leaching, effects of hydrologic factors, 374 release under different leaching techniques, 333 Cobalt-58, leachability in cement, 90 Construction materials (see high-integrity (see High-integrity containers) Cost estimates, su		
effects on leaching mechanism, 229 metal containment, SEM and TEM, 201 mixed waste management strategy, 317 quality-assurance procedure for solidified wastes, 93 solid phase, leaching-induced concentration profiles, 302 stabilization/solidification assessment procedure, 121 charcoal and substituted clays in, 273 effect of hydrologic factors, 333 evaluation, 114 heavy metals, freeze-thaw durability, 184 metal containment, SEM and TEM, 201 NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238 Cement-based grouts pumpable, 15 rheological properties, 16 Cesium–137 field testing with lysimeters, 413 leachability in cement, 90 release from cement, solid-phase analysis, 302 release under simulated disposal conditions, 335 Charcoal, for stabilization/solidification of		
metal containment, SEM and TEM, 201 mixed waste management strategy, 317 quality-assurance procedure for solidified wastes, 93 solid phase, leaching-induced concentration profiles, 302 stabilization/solidification assessment procedure, 121 charcoal and substituted clays in, 273 effect of hydrologic factors, 333 evaluation, 114 heavy metals, freeze-thaw durability, 184 metal containment, SEM and TEM, 201 NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238 Cement-based grouts pumpable, 15 rheological properties, 16 Cesium-137 field testing with lysimeters, 413 leachability in cement, 90 release from cement, solid-phase analysis, 302 release under different leaching techniques, 333 Cobalt-58, leachability in cement, 90 Compressibility (see also Unconfined compressive strength tests) bitumen-stabilized mixed wastes, 24 extruded bitumen, 30 polyethylene/sodium nitrate waste forms, 60 Concrete leach data from tank leaching and concentration profile analysis, 146 mortar, leaching, 125 Cone penetration testing, stabilized metal hydroxide sludges, 261–262 Consolidation testing, stabilized metal hydroxide sludges, 261–262 Construction materials, leaching, 125 Containers, high-integrity (see High-integrity containers) Cost estimates, surface encapsulation, 51  D Differential scanning calorimetry, polyethylene and salt wastes, 55 Diffusivity measurements, 130, 143 Drum-scale solidification, fly ash, 333 Duplex stainless steel, high-integrity con-		
mixed waste management strategy, 317 quality-assurance procedure for solidi- fied wastes, 93 solid phase, leaching-induced concentra- tion profiles, 302 stabilization/solidification assessment procedure, 121 charcoal and substituted clays in, 273 effect of hydrologic factors, 333 evaluation, 114 heavy metals, freeze-thaw durability, 184 metal containment, SEM and TEM, 201 NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238 Cement-based grouts pumpable, 15 rheological properties, 16 Cesium–137 field testing with lysimeters, 413 leachability in cement, 90 release from cement, solid-phase analy- sis, 302 release under simulated disposal condi- tions, 335 Charcoal, for stabilization/solidification of		
mixed waste management strategy, 317 quality-assurance procedure for solidified wastes, 93 solid phase, leaching-induced concentration profiles, 302 stabilization/solidification assessment procedure, 121 charcoal and substituted clays in, 273 effect of hydrologic factors, 333 evaluation, 114 heavy metals, freeze-thaw durability, 184 metal containment, SEM and TEM, 201 NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238  Cement-based grouts pumpable, 15 rheological properties, 16  Cesium-137 field testing with lysimeters, 413 leachability in cement, 90  release from cement, solid-phase analysis, 302 release under simulated disposal conditions, 335  Charcoal, for stabilization/solidification of		
quality-assurance procedure for solidified wastes, 93 solid phase, leaching-induced concentration profiles, 302 stabilization/solidification assessment procedure, 121 charcoal and substituted clays in, 273 effect of hydrologic factors, 333 evaluation, 114 heavy metals, freeze-thaw durability, 184 metal containment, SEM and TEM, 201 NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238 Cement-based grouts pumpable, 15 rheological properties, 16 Cesium–137 field testing with lysimeters, 413 leachability in cement, 90 release from cement, solid-phase analysis, 302 release under simulated disposal conditions, 335 Charcoal, for stabilization/solidification of		
solid phase, leaching-induced concentration profiles, 302 stabilization/solidification assessment procedure, 121 charcoal and substituted clays in, 273 effect of hydrologic factors, 333 evaluation, 114 heavy metals, freeze-thaw durability, 184 metal containment, SEM and TEM, 201 NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238 Cement-based grouts pumpable, 15 rheological properties, 16 Cesium–137 field testing with lysimeters, 413 leachability in cement, 90 release from cement, solid-phase analysis, 302 release under simulated disposal conditions, 335 Charcoal, for stabilization/solidification of	quality-assurance procedure for solidi-	
solid phase, leaching-induced concentration profiles, 302 stabilization/solidification assessment procedure, 121 charcoal and substituted clays in, 273 effect of hydrologic factors, 333 evaluation, 114 heavy metals, freeze-thaw durability, 184 metal containment, SEM and TEM, 201 NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238 Cement-based grouts pumpable, 15 rheological properties, 16 Cesium–137 field testing with lysimeters, 413 leachability in cement, 90 release from cement, solid-phase analysis, 302 release under simulated disposal conditions, 335 Charcoal, for stabilization/solidification of		
stabilization/solidification assessment procedure, 121 charcoal and substituted clays in, 273 effect of hydrologic factors, 333 evaluation, 114 heavy metals, freeze-thaw durability, 184 metal containment, SEM and TEM, 201 NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238 Cement-based grouts pumpable, 15 rheological properties, 16 Cesium–137 field testing with lysimeters, 413 leachability in cement, 90 release from cement, solid-phase analysis, 302 release under simulated disposal conditions, 335 Charcoal, for stabilization/solidification of		
stabilization/solidification assessment procedure, 121 charcoal and substituted clays in, 273 effect of hydrologic factors, 333 evaluation, 114 heavy metals, freeze-thaw durability, 184 metal containment, SEM and TEM, 201 NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238 Cement-based grouts pumpable, 15 rheological properties, 16 Cesium–137 field testing with lysimeters, 413 leachability in cement, 90 release from cement, solid-phase analysis, 302 release under simulated disposal conditions, 335 Charcoal, for stabilization/solidification of	tion profiles, 302	,
assessment procedure, 121 charcoal and substituted clays in, 273 effect of hydrologic factors, 333 evaluation, 114 heavy metals, freeze-thaw durability, 184 metal containment, SEM and TEM, 201 NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238 Cement-based grouts pumpable, 15 rheological properties, 16 Cesium–137 field testing with lysimeters, 413 leachability in cement, 90 release from cement, solid-phase analysis, 302 release under simulated disposal conditions, 335 Charcoal, for stabilization/solidification of		
charcoal and substituted clays in, 273 effect of hydrologic factors, 333 evaluation, 114 heavy metals, freeze-thaw durability, 184 metal containment, SEM and TEM, 201 NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238 Cement-based grouts pumpable, 15 rheological properties, 16 Cesium-137 field testing with lysimeters, 413 leachability in cement, 90 release from cement, solid-phase analysis, 302 release under simulated disposal conditions, 335 Charcoal, for stabilization/solidification of	assessment procedure, 121	
effect of hydrologic factors, 333 evaluation, 114 heavy metals, freeze-thaw durability, 184 metal containment, SEM and TEM, 201 NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238 Cement-based grouts pumpable, 15 rheological properties, 16 Cesium–137 field testing with lysimeters, 413 leachability in cement, 90 release from cement, solid-phase analysis, 302 release under simulated disposal conditions, 335 Charcoal, for stabilization/solidification of		
evaluation, 114 heavy metals, freeze-thaw durability, 184 metal containment, SEM and TEM, 201 NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238 Cement-based grouts pumpable, 15 rheological properties, 16 Cesium-137 field testing with lysimeters, 413 leachability in cement, 90 release from cement, solid-phase analysis, 302 release under simulated disposal conditions, 335 Charcoal, for stabilization/solidification of	effect of hydrologic factors, 333	leach data from tank leaching and con-
heavy metals, freeze-thaw durability, 184 metal containment, SEM and TEM, 201 NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238 Cement-based grouts pumpable, 15 rheological properties, 16 Cesium-137 field testing with lysimeters, 413 leachability in cement, 90 release from cement, solid-phase analysis, 302 release under simulated disposal conditions, 335 Charcoal, for stabilization/solidification of  mortar, leaching, 125 Cone penetration test, xanthate and hydroxide sludges, 261–262 Consolidation testing, stabilized metal hydroxide sludges, 220 Construction materials, leaching, 125 Containers, high-integrity (see High-integrity containers) Cost estimates, surface encapsulation, 51  D  D  Differential scanning calorimetry, polyethylene and salt wastes, 55 Diffusivity measurements, 130, 143 Drum-scale solidification, fly ash, 333 Duplex stainless steel, high-integrity con-		
184 metal containment, SEM and TEM, 201 NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238 Cement-based grouts pumpable, 15 rheological properties, 16 Cesium-137 field testing with lysimeters, 413 leachability in cement, 90 release from cement, solid-phase analysis, 302 release under simulated disposal conditions, 335 Charcoal, for stabilization/solidification of	heavy metals, freeze-thaw durability,	
metal containment, SEM and TEM, 201 NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238 Cement-based grouts pumpable, 15 rheological properties, 16 Cesium-137 field testing with lysimeters, 413 leachability in cement, 90 release from cement, solid-phase analysis, 302 release under simulated disposal conditions, 335 Charcoal, for stabilization/solidification of  droxide sludges, 261-262 Consolidation testing, stabilized metal hydroxide sludges, 220 Construction materials, leaching, 125 Containers, high-integrity (see High-integrity containers) Cost estimates, surface encapsulation, 51  D  D  Differential scanning calorimetry, polyethylene and salt wastes, 55 Diffusivity measurements, 130, 143 Drum-scale solidification, fly ash, 333 Duplex stainless steel, high-integrity con-	184	
NRC topical reports, 81 phenol and tricholorethylene, column leach testing, 238 Cement-based grouts pumpable, 15 rheological properties, 16 Cesium-137 field testing with lysimeters, 413 leachability in cement, 90 release from cement, solid-phase analysis, 302 release under simulated disposal conditions, 335 Charcoal, for stabilization/solidification of	metal containment, SEM and TEM,	
phenol and tricholorethylene, column leach testing, 238  Cement-based grouts pumpable, 15 rheological properties, 16  Cesium-137 field testing with lysimeters, 413 leachability in cement, 90 release from cement, solid-phase analysis, 302 release under simulated disposal conditions, 335  Charcoal, for stabilization/solidification of  Construction materials, leaching, 125 Containers, high-integrity (see High-integrity containers)  Cost estimates, surface encapsulation, 51  D  D  Differential scanning calorimetry, polyethylene and salt wastes, 55 Diffusivity measurements, 130, 143 Drum-scale solidification, fly ash, 333 Duplex stainless steel, high-integrity con-		Consolidation testing, stabilized metal hy-
leach testing, 238  Cement-based grouts pumpable, 15 rheological properties, 16  Cesium-137 field testing with lysimeters, 413 leachability in cement, 90 release from cement, solid-phase analysis, 302 release under simulated disposal conditions, 335  Charcoal, for stabilization/solidification of		
Cement-based grouts pumpable, 15 rheological properties, 16 Cesium-137 field testing with lysimeters, 413 leachability in cement, 90 release from cement, solid-phase analysis, 302 release under simulated disposal conditions, 335 Charcoal, for stabilization/solidification of  rity containers) Cost estimates, surface encapsulation, 51  D  D  Differential scanning calorimetry, polyethylene and salt wastes, 55 Diffusivity measurements, 130, 143 Drum-scale solidification, fly ash, 333 Duplex stainless steel, high-integrity con-		
pumpable, 15 rheological properties, 16 Cesium-137 field testing with lysimeters, 413 leachability in cement, 90 release from cement, solid-phase analysis, 302 release under simulated disposal conditions, 335 Charcoal, for stabilization/solidification of  Cost estimates, surface encapsulation, 51  D  D  Differential scanning calorimetry, polyethylene and salt wastes, 55 Diffusivity measurements, 130, 143 Drum-scale solidification, fly ash, 333 Duplex stainless steel, high-integrity con-		
rheological properties, 16  Cesium-137 field testing with lysimeters, 413 leachability in cement, 90 release from cement, solid-phase analysis, 302 release under simulated disposal conditions, 335  Charcoal, for stabilization/solidification of  Cesium-137  D  D  D  Differential scanning calorimetry, polyethylene and salt wastes, 55  Diffusivity measurements, 130, 143  Drum-scale solidification, fly ash, 333  Duplex stainless steel, high-integrity con-		
Cesium-137 field testing with lysimeters, 413 leachability in cement, 90 release from cement, solid-phase analysis, 302 release under simulated disposal conditions, 335 Charcoal, for stabilization/solidification of  Cesium-137  D  D  D  Differential scanning calorimetry, polyethylene and salt wastes, 55 Diffusivity measurements, 130, 143 Drum-scale solidification, fly ash, 333 Duplex stainless steel, high-integrity con-		Cost estimates, surface encapsulation, 51
field testing with lysimeters, 413 leachability in cement, 90 release from cement, solid-phase analysis, 302 release under simulated disposal conditions, 335 Charcoal, for stabilization/solidification of  Differential scanning calorimetry, polyethylene and salt wastes, 55 Diffusivity measurements, 130, 143 Drum-scale solidification, fly ash, 333 Duplex stainless steel, high-integrity con-		
leachability in cement, 90 release from cement, solid-phase analysis, 302 release under simulated disposal conditions, 335 Charcoal, for stabilization/solidification of  Differential scanning calorimetry, polyethylene and salt wastes, 55 Diffusivity measurements, 130, 143 Drum-scale solidification, fly ash, 333 Duplex stainless steel, high-integrity con-		<b>.</b>
release from cement, solid-phase analysis, 302 release under simulated disposal conditions, 335 Charcoal, for stabilization/solidification of  Differential scanning calorimetry, polyethylene and salt wastes, 55 Diffusivity measurements, 130, 143 Drum-scale solidification, fly ash, 333 Duplex stainless steel, high-integrity con-		υ
sis, 302 release under simulated disposal conditions, 335 Charcoal, for stabilization/solidification of vylene and salt wastes, 55 Diffusivity measurements, 130, 143 Drum-scale solidification, fly ash, 333 Duplex stainless steel, high-integrity con-		Differential scanning calorimetry, polyeth-
release under simulated disposal conditions, 335  Charcoal, for stabilization/solidification of  Diffusivity measurements, 130, 143  Drum-scale solidification, fly ash, 333  Duplex stainless steel, high-integrity con-		
tions, 335 Charcoal, for stabilization/solidification of Drum-scale solidification, fly ash, 333 Duplex stainless steel, high-integrity con-		
		Drum-scale solidification, fly ash, 333

cement-based grouts, 15 Durability freeze-thaw, cement-stabilized heavy cement-based solidified, quality-assurmetals, 184 ance procedure, 93 stabilized metal hydroxide sludges, 222 evaluation procedures for stabilization/ solidification processes, 114 extruded bitumen containing a surro-E gate, sodium-based waste, 28 Element speciation, 129 grouts, 418 Encapsulates (see Blocks) heavy metal immobilization, 257 Encapsulation heavy metals in cement, freeze-thaw dusurface, for modules, 40 rability, 184 titanium tritide accelerator targets, tritleaching ium release, 251 characteristics, 125 ENEA/DISP (Italian Regulatory Body), mechanism in solidified wastes, 229 classification and control of radliquid release, test apparatus and prowastes, 83 cedure, 192 Energy dispersive X-ray spectroscopy, long-term leaching tests on blocks, 381 solid-phase analysis of cement, 302 metal containment in solidified matrices, EPA Extraction Procedure Toxicity test, SEM and TEM, 201 nitrate salt, solidification in polyethylbitumen in mixed wastes, 21 ene, 53 cyanide oxidation and metals hydroxide phenols and chlorophenols, charcoal and precipitation, 151 substituted clays for, 273 cyanide oxidation and metals sulfide prepolyethylene—fiberglass-reinforcedcipitation, 156 plastic containers, 63 dual-chamber incineration, 163 polymers, field testing with lysimeters, extruded bitumen containing a surrogate, sodium-based waste, 28 Soliroc Process, 7 fly ash solidification, 159 surface encapsulation process, 40 leaching of surface encapsulation modtritium release from encapsulated titaules, 47 nium tritide accelerator targets, 251 nitrate salt wastes solidified in polyeth-Fly ash ylene, 58 cement-based solidified, quality assur-Soliroc Process-treated waste, 7 ance, 93 xanthate and hydroxide sludges, 261, 264 drum-scale solidification, 333 EPICOR-II, 404 leaching, 170 Extruders, bitumen, 28 Freeze-thaw durability, cement-stabilized Extrusion, nitrate salt wastes in polyethheavy metals, 184 ylene, 56 Fuel ash, quality assurance procedure, 93 Glove-box chain, for radwaste character-Fiberglass-reinforced plastic ization, 87 high-integrity containers, 81 Golbee-Joy model, 247 polyethylene-bonded, 63 Ground-water chemistry, effect on radio-Field testing nuclide release, 336 long-term leaching of blocks, 381 Grouting, in situ, 418 waste forms with lysimeters, 404 Grouts Fixed wastes cement-based, pumpable, 15 acceptable test methods, 79 particulate, 418 bitumen, radionuclide release, simulated disposal, 335 Н cement field testing with lysimeters, 404 Hazardous and Solid Waste Amendments

of 1984, 151

solid-phase analysis, 303

Hazardous wastes	leaching radioactive waste in simulated
cement-based solidified, long-term suit-	disposal conditions, 330
ability, 93	long-term leaching tests, 381
construction materials, 125	low-level waste solidification in salt-
stabilization products with waste mate-	stone, 392
rials, 125	mixed wastes
Heavy metals	management strategy, 317
bitumen-stabilized, leachability, 23	stabilization, 333
in extruded bitumen, performance test-	Leachability 22
ing, 28	bitumen-stabilized mixed wastes, 23
immobilization	cesium, cobalt, and strontium, in ce-
in cementitious matrices, leaching	ment, 90
mechanism, 229 by xanthate and hydroxide precipita-	extruded bitumen containing a surro-
	gate, sodium-based waste, 35
tions, 257 leachability, 150	metals, fly ash, 333 nitrate salt wastes solidified in polyeth-
Soliroc Process, 7	ylene, 58
High-integrity containers	surface encapsulation modules, 47
design guidance, 80	Leachability index, 118, 248
NRC topical reports, 81	Leaching
polyethylene—fiberglass-reinforced, 63	concentration profiles in solid phase of
quality-assurance programs, 80	cement, 302
Hydrologic factors	construction materials, 125
effect on leaching of solidified low-level	effects of matrix characteristics, 229
waste forms, 358	low-level waste, effects of hydrologic fac-
radionuclide leaching in simulated dis-	tors, 358
posal conditions, 336	lysimeter field testing of waste forms, 404
Hydroxide sludges, metals	mechanisms, immobilization and, 120
immobilization in, 257	radionuclides
physical testing program, 214	effects of hydrologic factors, 333
TCLP and EP toxicity tests, 150	long-term tests, 381
_	in simulated disposal conditions, 330
I	tests on blocks of radioactive waste,
Immobilization	381
leaching mechanisms and, 120	saltstone lysimeters, 392
metals by solidification of hydroxide and	stabilization products with waste mate-
xanthate sludges, 257	rials, 125
Incinerator slag/cement, leaching, 125	Leaching models, 118
Inorganic iodides, solubility and stability,	Leaching tests
287	blocks of radioactive waste, 381
International Standards Organization, ISO	bitumen, 385
6961–82, 87	cement, 384
Iodides, inorganic, solubility and stability,	polymer, 386
287	column, phenol, and trichoroethylene
Iodine–129, waste forms, 287	cement pastes, 238
Ion transfer, blocks of radioactive waste,	Dutch protocol, 170
381	dynamic, 229
Italian Regulatory Body (ENEA/DISP),	ISO 6961–82, 87 long-term, 381
classification and control of rad-	low-level radioactive waste in simulated
wastes, 83	
L	disposal conditions, 330 solidified clay/cement mixes, 278
Landfills, liquid release tester, 192	test procedures
Large-scale studies	chemical properties, 117
hydrologic factors effect on leaching, 358	physical properties, 115
my aronogre ractors effect on leadining, 336	bulaner brobarman IIa

tritium from encapsulated titanium tri- tide accelerator targets, 251	management strategy at West Valley Demonstration Project, 317
Lead	stabilization at Idaho National Engi-
cement-stabilized, SEM and TEM, 201	neering Laboratory, 333
fly ash TCLP results, 348	Mobility measurements, hazardous ele-
solidified fly ash TCLP results, 350	ments within waste materials and
Lightweight concrete, leaching, 125	products, 130, 141
Lime precipitation	Models, leaching, 118
comparison to Soliroc Process, 9, 11	Modules, surface encapsulation process, 44
procedure, 13	
Liquid/solid ratio, effect on fly ash leach-	N
ing, 170 Liquid wastes	
Paint Filter Test, 199	Nickel, immobilization by solidification of
release	hydroxide and xanthate sludges, 257
cure time effects, 198	Nuclear Regulatory Commission
test apparatus and procedure, 192	regulation 10 CFR Part 20, 318
test duration effect, 197	regulation 10 CFR Part 61, 65, 77, 318
test pressure effects, 197	acceptable test methods, 79
Lithium, immobilized in cementitious	alternative disposal methods, 81 recommended test, 79
matrices, leaching mechanisms, 229	regulatory guides, 79
Lysimeters	technical positions, 79
effect of hydrologic factors on leaching,	waste classification and waste-form re-
358	quirements, 78
field testing of waste forms with, 404 low-level waste solidification in salt-	•
stone, 392	0
radionuclide release program, 330	0
saltstone, 392	Organic compounds
satisfolie, 372	semi-volatile, TCLP and EP toxicity ex-
	tractions, 150
M	volatile
141	from dual-chamber incinerations, 165
Matrices, solidified	from rotary kiln incinerations, 167
cementitious, effects on leaching mech-	in TCLP extract of metal hydroxide
anisms, 229	sludge, 155, 158
metal containment, SEM and TEM, 201	
Mechanical integrity, nitrate salt wastes so-	P
lidified in polyethylene, 60	Point Filter Test 100
Mechanical properties, polyethylene—fi- berglass-reinforced-plastic con-	Paint Filter Test, 199 Permeability testing
tainers, 65	lithium immobilized into cementitious
Mercury	matrices, 229
fly ash TCLP results, 348	stabilized metal hydroxide sludges, 222
immobilization by solidification of hy-	pH effects
droxide and xanthate sludges, 257	fly ash leaching, 170
Metal—cyanide complexes, TCLP and EP	on Soliroc Process, 11
toxicity extractions, 151	Phenols
Metal hydroxide sludges	charcoal and tetra-alkylammonium-sub-
physical testing program, 214	stituted clays for stabilization/soli-
TCLP and EP toxicity tests, 150	dification, 273
Mixed wastes, 21	and trichoroethylene cement pastes, col-
bitumen stabilization, 21 drum-scale solidification testing on fly	umn leach testing, 238
ash, 333	Phosphate slag, leaching, 125 Phosphogypson hemihydrate, leaching, 125
uoii, <i>000</i>	1 nosphogypson nemnyurate, reaching, 123

Phosphogypson/pulverized coal ash/ce-ENEA-RIFIU laboratory quality-assurance program on forms characterment, leaching, 125 Physical testing ization, 85 extruded bitumen, leaching, 28 procedures, 115 solidified charcoal/cement mixes, 280 field testing with lysimeters, 404 high-integrity containers for, 63 solidified clay/cement mixes, 279 stabilized metal hydroxide sludges, 214 in situ grouting of trenches, 418 Italian Regulatory Body (ENEA/DISP) consolidation testing, 220 durability tests, 222 classifications, 83 leaching in simulated disposal condimodifications, 226 permeability testing, 222 tions, 330 unconfined compression test, 218 long-term leaching tests, 381 xanthate and hydroxide sludges, 261 NRC regulations, 77 Polybutadiene binder resins, properties, 44 Nuclear Regulatory Commission regu-Polyethylene lations, 318 high-integrity containers, 81 shallow trenches, in situ grouting, 418 solidification in saltstone, 392 solidification of nitrate salt wastes in, 53 Polyethylene—fiberglass-reinforced-plassolid-phase analysis of cement, 302 tic containers, 63 surface encapsulation process, 40 tritium release from encapsulated tita-Polymeric materials, solidification media, NRC topical reports, 81 nium tritide accelerator targets, 251 Polymer-impregnated concrete, high-integ-Radionuclides concentrations, NRC classes A, B, and rity containers, 81 **Polymers** C, 78 blocks, leaching, 386 leaching field testing of waste forms with lysieffects of hydrologic factors, 333 meters, 404 long-term tests, 381 in simulated disposal conditions, 330 stabilization/solidification, effect of tests on blocks of radioactive waste, hydrologic factors, 333 381 Potassium, release from cement, solid-Reductive dissolution, bismuth oxyiodide phase analysis, 302 and silver iodide, 290 Process control programs, 80 Regulatory Guide on Waste Form Stability, Pulverized coal ash/cement, leaching, 125 Pulverized coal ash/phosphogypson lime, leaching, 125 Regulatory Guides, Nuclear Regulatory Commission, 79 Pulverized fuel ash, quality assurance procedure for solidified wastes, 93 Resins organic, for module fabrication, 40 0 polybutadiene, properties, 44 Resource Conservation and Recovery Act, Quality assurance 150, 192 cement- and pulverized fuel ash-based Rheology, cement-based grouts, 16 solidified wastes, 93 ENEA-RIFIU laboratory program on forms characterization, 85 fly ash samples, 354 Saltstone lysimeters, 392 high-integrity containers, 80 Salt wastes, nitrate, solidification in poly-Quality control ethylene, 53 fly ash samples, 354 Saturation effects, on radionuclide release, solidification, with zone of acceptable

Scanning electron microscopy

comparison with leach data from tank

leaching (concrete), 146 leaching concentration profile analyses,

metals in solidified matrices, 201

## R

waste proportions, 110

Radioactive wastes, low-level drum-scale solidification testing of fly ash, 33

pastes, column leach testing, 238

solid-phase analysis of cement, 302 heavy metals, freeze-thaw durability, Selenium, fly ash TCLP results, 348 SEM (see Scanning electron microscopy) Strontium-85 Serial graded batch extraction procedure, leachability in cement, 90 xanthate and hydroxide sludges, release under simulated disposal condi-261, 264 tions, 335 Shallow trenches, in situ grouting, 418 Strontium-90, field testing with lysimeters, Silica reagents, Soliroc Process, 8 413 Silver, fly ash TCLP results, 348 Surface encapsulation process, 40 Silver iodide, solubility, and stability, 287 Surface-to-volume ratio, effect on product Sludges leachability, 143 hydroxide and xanthate, metal immobilization, 257 metal hydroxide TCLP (see Toxicity characteristic extracphysical testing program, 214 tion procedure) TCLP and EP toxicity tests, 150 Technical Guide No. 26 (ENEA/DISP), 84 treatment, 42 Sodium nitrate, waste Technical Positions, NRC, waste classification and waste form, 79 extruded bitumen with, 28 TEM (see Transmission electron microssolidification in polyethylene, 53 Solidification (see also Stabilization/solid-Tetra-alkylammonium-substituted clays, ification) stabilization/solidification of chlo-Class B and C wastes, tests and methods, rophenols, 273 Thermal testing, extruded bitumen concontrol chart with zone of acceptable taining a surrogate, sodium-based waste proportions, 110 processes, technology status, 81 Titanium tritide, encapsulated accelerator Solid-phase analysis, cement, 302 Soliroc Process, 7 targets, 251 Topical reports comparison to lime precipitation, 9, 11 polyethylene—fiberglass-reinforced effect of chelating agents, 10 containers, 71 flow chart, 8 pH effects, 11 on solidification processes, NRC reprocedure, 13 views, 81 silica-to-metal ratio effects, 12 Tortuosity, effect on product leachability, Solubility, inorganic iodides, 287 Stability, inorganic iodides, 287 Toxicity characteristic extraction proce-Stabilization/solidification (see also Soliddure cyanide oxidation and metals hydroxide ification) cement precipitation, 151 cyanide oxidation and metals sulfide prephenol and tricholorethylene, column leach testing, 238 cipitation, 156 phenois and chlorophenois, charcoal dual-chamber incineration, 163 and tetra-alkylammonium-substifly ash, 347 rotary kiln incineration, 165 tuted clays for, 273 drum-scale, fly ash, 333 solidified fly ash, 349 Toxicity testing, EP Toxicity test, see EPA heavy metal immobilization by hydrox-**Extraction Procedure Toxicity test** ide or xanthate precipitation, 257 hydrologic factors effect on leaching, 358 Toxic wastes metal containment in matrices, SEM and sludges treated by surface encapsulation, TEM, 201 mixed waste management strategy, 317 surface encapsulation process, 40 physical testing program for metal hy-Transmission electron microscopy, metals in solidified matrices, 201 droxide sludges, 214 Trichloroethylene, and phenol cement processes

evaluation procedures, 114

Tritium
leaching, effects of hydrologic factors,
374
release from encapsulated titanium tritide accelerator targets, 251
TVR III system, 22

## U

Unconfined compressive strength tests (see also Compressibility) stabilized metal hydroxide sludges, 218 xanthate and hydroxide sludges, 261, 263 U.S. Army methods, TM 5-530, 261

#### V

Viscoelastic materials, stability, 80 Volatile organic compounds from dual-chamber incinerations, 165 from rotary kiln incinerations, 167 in TCLP extract of metal hydroxide sludge, 155, 158

### W

Waste forms field testing with lysimeters, 404 iodine-129, 287 Waste management, mixed wastes, 317 Waste treatment high-level wastes, 319 low-level wastes, 321 mixed wastes, 325

#### X

Xanthate sludges, metal immobilization, 257