

Subject Index

A

Abrasive wear, 144
 Adhesive-fatigue wear, 144
 Alumina, 186, 197
 Alumina-on-alumina wear
 couple, 173, 213
 Annealing twins, 55
 ASTM standards
 F 1537, 55, 92

B

Bending strength, 235
 Bovine serum, 76

C

Calcium phosphate, 129
 Carbon fiber, 266
 Ceramic, 197, 213
 Ceramic cup insert, 173
 Ceramic-on-ceramic, 186
 wear couple, 173
 Ceramic-on-polyethylene, 186
 Ceramic, zirconia, 186
 Clinical performance, 47
 hip simulator test
 comparison, 129
 metal on metal, 144
 prediction, 1
 Coatings, polyethylene, 30, 69
 Cobalt alloys, 76
 Cobalt-chrome, 1
 Cobalt-chromium, 144
 Cobalt-chromium-carbon, 69,
 197
 Cobalt-chromium-molybdenum,
 47, 55, 159
 Cobalt-phosphorus alloys, 69
 Compaction, hot, 235
 Composite
 cup, 266
 homocomposite, 256
 self-reinforced, 235
 Compression tests, 235

Contact stress, 47
 yield strength ratio, 266
 Corrosion-resistance coatings, 69
 Cylinder-on-flat apparatus, 76

D

Differential scanning
 calorimetry, 235
 Disk-on-disk wear test, 186

E

Electrodeposition, 69

F

Fatigue, cyclic, 173
 Film thickness
 film, 111
 lubricant, 92
 Finite element analysis, 173,
 186
 Fracture pattern, 173
 Friction coefficient, 55

G

Glassy alloys, 69

H

Hertzian contact stress analysis,
 266
 Homocomposite, 256

I

Ion implantation, 197

K

Kinematics, contact, 30

L

Lambda ratio, 92, 111
 Linear head penetration wear rates, 47
 Lubricant film thickness, 92
 Lubricants, bovine serum, 76

M

Mechanical stability, 173
 Metal-metal bearing surfaces, 55, 129
 Metal-metal wear, 111
 Metal-on-metal articulating surfaces, 47, 159
 Metal-on-metal contacts, 76
 Metal-on-metal hip prostheses, 55, 76, 92
 clinical wear performance, 144
 Metal-polyethylene, 111
 Models, elastohydrodynamic lubrication model, 111

N

Neutron diffraction, 55

O

Osteolysis, 55, 129, 159, 213

P

PEEK, 266
 Pin-on-ball device, 30
 Pin-on-disk, 197
 Polyetheretherketone (PEEK), 266
 Polyethylene
 composite, 235
 homocomposite, 256
 Polyethylene cups, 92
 Polyethylene particle reduction /prevention, surface, 30
 Polyethylene, ultrahigh molecular weight, 69, 186, 197, 213, 235, 256, 266
 Polyethylene wear, 197

R

Radial clearance, 47, 159
 Roughness values, 92, 111

S

Scratch tester, 197
 Screening method, hip arthroplasty sources, 30
 Simulator, 76, 256
 clinical retrieval comparison with, 129
 fluid film thickness, 111
 hip joint, 129, 186
 metal-on-metal, 92
 testing, 76, 256, 266
 SIVASH/SRN components, 159
 Socket loosening, 213
 Standardization, wear test method, 1
 Static load resistance, 173
 Strain-induced transformation, 55
 Stress distribution, 173

T

Tensile strength, 55, 235, 256
 Tensile yield strength, 47
 Toughness, 213
 Twins, annealing, 55

V

Validation criteria, clinical tests, 1
 Volumetric wear, 92

Y

Yield strength, 55
 Yield stress analysis, 266

Z

Zirconia-zirconia, 186