

Subject Index

A

ABAQUS, 240
 Accelerated material discrimination, 270
 Acoustic emission, 255
 Activation energy, 3
 AISI 316 L, 297
 Aluminum alloy, 145
 Aluminide coatings, 98, 164, 210
 Aluminides, 83
 A1319-T7B, 45
 Austenitic stainless steel, 227, 297
 Automotive components, 45
 Axial-torsional, 65

B

Back stress, 45
 Brittle cracking, 210

C

Carbide strengthened alloy, 15
 Cast aluminum alloy, 45, 240
 CM186 SX, 210
 CM196, 255
 CM247LC, 180
 CMSX-4, 83, 180, 255
 CMSX-6, 164, 312
 Coarsening, 112
 Coatings, 98, 164, 180
 Cobalt-based superalloy, 65
 Computer simulations, 31
 CoNiCrAlY, 180
 Constitutive modeling, 45
 Control design, 282
 Counter-clockwise-diamond cycle, 112
 Crack density, 180
 Crack growth rate, 145
 Crack initiation, 164
 Crack propagation, 145
 Cracks, 227
 Creep, 31, 210
 Creep-fatigue damage parameter, 145
 Crystal, single, 112, 164, 210
 Cyclic behavior, 45
 Cyclic creep, 297
 Cyclic deformation, 3, 65, 195
 Cyclic hardening, 15, 65, 127
 Cyclic J-integral, 145
 Cyclic life, 145
 Cyclic stress-strain behavior, 127

D

Damage, 227
 mechanisms, 255
 Deformation behavior, 15
 Diamond phase, 180
 Dislocation structure, 180
 Drag stress, 45
 Ductile-to-brittle transition temperature, 127

E

Elastic deformation, 15, 31
 Elasto-viscoplastic constitutive law, 227
 Engine components, 240
 Environmental damage, 145
 Environmental degradation, 127
 Exhaust, 227

F

Fatigue crack propagation, 145
 Fatigue life, 112
 Fatigue prediction, 240
 Ferritic stainless steels, 227
 Finite element analysis, 210, 240
 Finite element modeling, 312
 Fracture, 83, 145, 180

G

γ/γ' -microstructure, 112

H

Haynes 188 superalloy, 65
 High cycle fatigue loading, super-imposed, 195
 High temperature, 45, 180
 properties, 270
 High-temperature aluminum alloy, 145
 High-temperature titanium alloy, 145
 High temperature transients, 282
 Hysteresis loop, 3, 15, 31

I

IMI 834, 145
 IN738LC, 180
 Inelastic deformation, 3
 In-phase cycling, 31, 65, 210, 227
 Intermetallics, 127
 Inverse control, 282
 Isothermal low-cycle fatigue, 180

L

Life prediction, 145, 180, 227
 Lifetime behavior, 195
 Low-cycle fatigue, 15

M

MAR-M 509, 83
 Metal matrix composite, 145
 Microstructure, 127
 Miniature test system, 270
 Modeling, 3, 15, 31, 127
 Multiaxial, 65

N

Nickel base alloy, 15
 Nickel-base superalloy, 164, 180,
 195, 210, 255, 312
 monocrystalline, 112
 NiCr22Co12Mo9, 195

O

Out-of-phase cycling, 31, 65, 127,
 180, 210, 227
 Overlay coatings, 83
 Oxidation, 127
 performance, 210
 protection coatings, 255

P

Phase angle, 83
 Plastic deformation, 31
 Platinum aluminides, 83, 164
 Pre-rafting, 112

R

Ramping tests, 270
 Relaxation, 15
 Reproducibility, 282
 Rhenium, 210

S

Sermalloy 1515, 210

Silicon carbide particle-reinforced, 145
 Simulation, 15
 Stainless steel alloys, 31, 227, 297
 Strain, 195, 240
 Stress, 240
 mean, 127
 Stress-strain curves, 3
 Stress-strain response, 45
 Superimposed loading, 195
 Surface damage analysis, 255

T

Taira type damage, 227
 Temperature, 195
 control, 282
 measurement, 312
 Thermal activation, 3
 Thermal barrier coatings, 83, 98
 Thermal fatigue, 240, 297
 Thermal gradients, 312
 Thermographic analysis, 312
 Thermomechanical fatigue, resistance, 112
 Thermomechanical loading, 65
 low-frequency, 195
 Titanium aluminide, 127

V

Video imaging, 255
 Viscoplasticity, 240

X

X8019, 145

Y

Yielding, 15