

Subject Index

A

ABC, 119, 146–147
 Acoustic approximation, 12
 Aerotherm, 304, 308
 Agricultural dust explosions, 90, 243–263
 activities of panel on causes and prevention, 246–248
 20 April 1982 explosion, 256–257
 average annual accident statistics, 263
 explosion incidents 1979–1986, 252–256
 explosions, deaths, injuries, and fires, 247
 ignition sources, 248
 location of primary explosion, 249
 11 May 1984 explosion, 257–260
 30 May 1984 explosion, 256
 2 Nov. 1985 explosion, 256
 16 Nov. 1982 explosion, 255–256
 recent history, 248–249, 252–262
 19 Sept. 1984 explosion, 258, 260–262
 U.S. history, 244–246
 Aluminum dust particles, photomicrographs, 17
 Ammonium phosphate, as inerting agent, 29
 Anthracite coal
 autoignition, 49
 flammability limits, 15
 Ash, definition, 232
 ASTM C 737, 118
 ASTM D 121-78, 233
 ASTM D 197-82, 233
 ASTM D 271, 334
 ASTM D 311-30, 233
 ASTM D 388-82, 233
 ASTM D 1620, 334
 ASTM D 2015, 111
 ASTM D 3172-73, 111, 233
 ASTM D 3175, 49, 52
 ASTM D 3176-84, 233
 ASTM D 3904, 115
 ASTM E 659, 46, 54
 Atomized water test, 339–340

Autoignition temperature, 45–49
 autoignition boundaries, 46–47, 49–50
 decane, 54
 as function of particle size, 52–53
 1.2-L furnace and instrumentation, 47–49
 lean flammability limit boundary, 46–47
 lycopodium dust, 46
 methane, 54
 minimum, 20–21, 51
 hybrid mixtures, 24–25
 particle diameter, 24
 use of data, 55–58
 oil shale dusts, 53–54
 volatility yield, 53

B

Backscattering aerosol monitor, 294–296, 308
 dust concentration correlation, 303
 regression equation, 301
 Baghouse dust
 collector, 224
 maximum flame velocity and secondary dust concentration, 97
 maximum pressure, 98
 particle size, 93, 95
 secondary dust explosions, 96–97
 Bag ignitors, 113–114
 Ball tube mill, 192
 BCD, 119
 Bituminous coal
 autoignition, 49
 explosion characteristics, 36
 high volatile, flammability limits, 15, 20
 particle size effect, 22–23
 low volatile, flammability limits, 15, 20
 particle size effect, 22–23
 photomicrographs, 16
 pulverized dust
 dispersability, 111–112

- flammability, 111–113
- inerting, 116–119
- Bituminous coal dust/air mixtures, explosion behavior, 35
- Boltzmann distribution function, 57
- Bowl mill, 192–193
 - dust accumulations, 199
 - incident frequency, 193
- Brown coal
 - explosion characteristics, initial pressure influence, 42
 - limiting oxygen concentration as function of initial pressure, 43
- Brown coal dust/air/inert gas mixtures, oxygen concentration effect on explosion characteristics, 39
- Brown coal dust/air mixtures, explosion behavior, initial pressure influence, 41–42
- Brown coal dust/air/nitrogen mixtures, explosion behavior, 38
- Bruceton Experimental Mine, 345, 347
 - configurations for full-scale tests, 109–110
 - dispersed dust tests, 109
- Brush discharge, 171, 174, 274
- BS 5958, 62, 68
- BS 6467, 62
- Bureau of Mines
 - 20-L chamber, 108, 325–326
 - experimental mine, 139–143
 - 1.2-L furnace, perspective schematic, 48
 - light-attenuation monitor, 296–297
 - see also* specific facilities
- Burgess-Wheeler law, 21
- Burning velocity, 9
 - closed end ignition, 10–11
 - turbulence effect, 10

C

- Calorific value, definition, 232
- Cannon ignitor, 114
- Carbonaceous dusts, volatility yield, 53
- Carbon dioxide, as inerting gas, 28–29
- Cement industry, 217–233
 - case history of accident investigations, 224–230
 - coal fired systems, 220–224
 - coal storage systems, 222–223

- education and training, 232
- equipment design, 231–232
- explosion
 - 4 April 1978, New York, 225
 - 6 Feb. 1981, Pennsylvania, 226–227
 - 23 Jan. 1985, New York, 228–229
 - 18 July 1984, California, 227–228
 - 18 June 1985, New Mexico, 230
 - 16 Oct. 1979, Montana, 225–226
- history, 217
- ignition source removal, 230
- inerting, 230
- laboratory testing, 220
- prevention and recommendations, 230–232
- preventive maintenance, 232
- Characteristic diameter, 23
- Class II locations, 333–334
 - electrical equipment testing, 334–335
- Clinker, definition, 232
- Cloud ignition temperatures, 47
- Coal
 - characteristics, 75, 77
 - lowest autoignition temperatures, 52
 - selection, dust fire/explosion probability, 219–220
 - size distribution, 209
 - storage, 224
 - volatility yield, 53
 - see also* specific types of coal
- Coal bin, 223, 232
- Coal bunker, definition, 232
- Coal dust, 107, 191
 - concentration, 124
 - domains of flammability and thermal autoignitability, 21
 - flammability limits, 22–24
 - mixed with gilsonite dust, 25–26
 - mixed with limestone rock dust, flammability limits, 28–29
 - mixed with methane, 25–26
 - with added nitrogen, 27
 - proximate analysis, 37
- Coal dust explosions, 124–138, 152, 218
 - buildup conditions, 126–127
 - coal dust concentration, 132–135
 - early studies, 343–344
 - fuel zone, 130–132
 - ignition of methane pockets, 138
 - inert fraction, 135–136

- initiation source influence, 129–130
- instrumentation and recording of explosion tests, 127–129
- parameters tested, 128
- particle size effect, 134–135
- pressure-time traces, 6–7
- propagation in pipes, 74–89
 - coal characteristics, 75, 77
 - distance-time diagram, 77, 81–83, 87
 - ducts connected to a 1-m³ vessel, 77, 79–87
 - isolated ducts, 77
 - material, 75–76
 - measuring systems, 75
 - turbulence decay effect, 9–10
 - two step ignition, 126–127
- Coal Dust Testing Regulations, 125
- Coal fired systems, 202, 217
 - coal handling, 224
 - direct fired, 220–221
 - indirect fired, 222
 - problem areas, 223–224
 - semidirect fired, 220
 - unplanned shutdowns, 224
- Coal/methane mixture
 - inerting, 121
 - mine dust explosion, 115
 - see also* Hybrid mixtures
- Coal mines, 107, 138
- Coal/natural gas mixture, mine dust explosion, 115–116
- Coal pulverizer, 191–200
 - age, 204–205
 - average explosion per year, 204, 207
 - ball tube mill, 192
 - bowl mill, 192–193
 - capacity, 204–205
 - coal
 - ash, 205–206
 - bed depths and temperatures, 199
 - characteristics, 209
 - moisture, 205–206
 - type, 204, 215
 - volatility, 205–206
 - debris, 224
 - design and operation, 191–193
 - distribution and type of pulverizer, 193
 - explosibility analysis, 198–200
 - explosion testing
 - facility, 208
 - using pipeline fire ignition sources, 209–211
 - using pulverizer fire ignition sources, 212–214
- full-scale explosion tests, 208–209
- hammermills, 193
- high temperature alarms, 193, 195
- ignition sources, 199
- incident 10, 196–197
- incident 23, 197–198
- incident database, 195–195
- inert gas purge systems in incidents, 195
- inerting systems, 216
- laboratory steam inerting tests, 214–215
- maximum flame speed versus coal dust concentration, 213
- maximum pipe pressure
 - versus coal dust concentrations, 212
 - versus position along coal pipe, 209–210
- maximum vessel pressures versus coal dust concentrations, 213
- number per unit, 204–205
- operational status at ignition, 193–194
- operation mode, 203–204
- outlet fuel concentrations, 198
- peak pipe pressure versus coal pipe air velocity, 210–211
- property damage in fire/explosion sequence, 195
- pulverizer age, 216
- pulverizer type and operation mode, 216
- startup and shutdown practices, 193
- survey approach, 202–203
- survey database, 203
- survey trends, 203–208
- systems, 215
- Coal silo, definition, 232
- Coal surge bin, 224
 - definition, 232
- Confinement, 13
- Conical pile, discharge from, 171, 175
- Cornstarch
 - dust explosion, pressure vented vessel, 178
 - maximum reduced explosion characteristics
 - air volume influence, 180–181
 - relief area influence, 180, 182
 - mixed with hydrogen, 25–26

Critical mass of suppressant, 283
 Cube root law, 70
 Cubic law, 9, 34, 178, 267
 Cyclone plant, vented dust explosions, 268–269

D

Decane, autoignition temperatures, 54
 Design measures, 173, 175–188
 area requirements of VDI 3673 versus test results, 178–180
 disengagement within combined systems, 182–183, 185–188
 ductile materials of construction, 176
 explosion diverter, 188–189
 extinguishing barrier, 186
 pressure resistant
 maximum explosion pressure, 175–176
 reduced maximum explosion pressure, 177–182, 184–185
 rapid action valves, 186–188
 relief pipe effect on reduced maximum explosion pressure, 177
 rotary-vane feeder, 183, 185–186
 Devolatilization, 14, 23–24
 Dimensioning, 265
 DIN 51718, 37
 DIN 51719, 37
 DIN 51920, 37
 Dispersability, pulverized bituminous coal dust, 111–113
 Dispersed dust concentration, 95
 Dortmund standard coal dust, 126, 134
 Double propagation criterion, 113–114
 Dust/air/inert gas mixture, 33–44
 Dust/air mixture, 33–44
 explosible, avoidance, 161–162
 turbulence, 180
 Dust blanket temperature test, 336, 338
 Dust blast test, 339–340
 Dust cloud
 burning rate, maximum pressure effect, 266
 generation, 267
 test chamber, 300
 calibration data, 302
 Dust combustion, 90

Dust concentration, flammability effect, 13–16
 Dust dispersion, 18–19
 Dust explosion, necessary conditions, 45
 Dust fire/explosion probability, factors affecting, 218–220
 Dust hazard class, 71
 Dust-ignition-proof enclosures, 333, 335
 Dust particles, photomicrographs, 16–17
 Dust penetration test, 338–339
 Dust probes, 294
 Dust/propane mixtures, limiting oxygen concentration, 164
 Dust testing, 158–161
 Dust-tight enclosures, 333, 335–336
 Dynamic pressure
 as function of length of coal dust zone, 131, 134
 initiation sources, 130

E

Electrical equipment testing, 333–341
 atomized water test, 339–340
 Class II locations, 334–335
 dust blanket temperature test, 336, 338
 dust blast test, 339–340
 dust-ignition-proof enclosures, 335
 dust penetration test, 338–339
 dust-tight enclosures, 335–336
 enclosures that minimize dust entrance, 336
 intrinsically safe circuits, 336
 spark ignition test, 340–341
 test facilities, 336–337
 Electrical ignitability properties, 56
 Electrostatic discharges, ignition sources, 274–275
 Elongated 8.6-m³ empty vessel, explosion vents, 270–271
 Ethylene, coal dust mixtures, ignition probability, 316, 318–319
 Exothermic reactions, 7–8
 Explosibility assessment, 60–72
 explosibility classification, 62–64
 large scale tests, 71–72
 legal requirements, 61–62
 longwall ignition suppression, 149
 maximum explosion pressures, 69–70

maximum permissible oxygen concentration to prevent ignition, 69
 minimum explosible concentration, 64–66
 minimum ignition energy, 68–69
 minimum ignition temperature, 66–68
 rates of pressure rise, 69–71
 Explosibility classification, 62–64
 Explosibility index, 55
 Explosibility rate constant, 281, 284, 286
 Explosibility vents, 265
 Explosion
 conditions for, 18
 definition, 5–7
 oxygen limit concentration, 38–40
 pressure influence, 43
 probabilities, 18
 test arrangements and procedures, 33–35
 Explosion diverter, 188–189
 Explosion hazard, 342
 Explosion intensity, potential, 281
 Explosion limit
 initial pressure influence, 40–43
 lower, *see* Lower explosion limit
 Explosion pentagon, 230
 definition, 232
 Explosion pressure, 6, 12, 60, 124, 173
 initial pressure influence, 40–43
 maximum, 33, 38, 69–71
 pulverized bituminous coal/limestone mixtures, 118
 pressure resistant design, 175–177
 reduced maximum, pressure resistant design, 181–182, 184–185
 release, 180
 suppressed, measured and calculated, 291–292
 temperature influence, 35–38
 vent size on distribution, 276–277
 Explosion suppression, *see* Suppression
 Explosion violence, 265
 distribution, 276
 influence of process or product changes on distribution, 277–278
 Explosiveness, 324
 5.4-L extinguisher, 182–183
 Extinguishing agent
 ABC powder, 146–147
 purple K, 147
 water, 140–146
 Extinguishing barrier, 186

Extinguishment, 29, 152; *see also* Inerting

F

Factories Act 1961, 61
 Fires, 191, 202, 217
 extinguishing agents, 138
 prevention safety, 202
 suppressants, 138
 triangle, 230, 232
 Fixed carbon, definition, 232–233
 Flame acceleration, 12–13, 90
 Flame acceleration tube, 91–92
 maximum pressure and tube location, 98
 turbulence-generating grids
 dispersed dust concentration, 100, 102
 maximum flame velocity, 99, 101
 maximum gas temperature, 100, 104
 maximum gas velocity, 100, 103
 maximum pressure, 99–100
 Flame jets, ignition sources, 273–274
 Flame length, 124
 as function of coal dust zone, 133
 inert material effect, 136
 Flame propagation, 10
 from closed end of tube, 10–11
 dynamics, 5
 Mach number, 13
 speed, 8–9
 Flame speeds, 13, 74, 77, 81–83, 143
 Flame velocity, maximum, 95
 secondary dust concentration, 97
 Flammability, pulverized bituminous coal dust, 111–113
 limestone mixture, 116–117
 Flammability limits, 5
 coal dust/limestone mixtures, 28–29
 effect of varying dust concentration, 13–16
 gaseous mixtures, 311
 initial temperature and pressure effect, 21–22
 lean limit concentration, 21
 particle size effect, 22–24
 Flammable mixtures, 310
 Floor sweepings dust, particle size, 93, 95
 Fuel gas, *see* Gaseous fuel
 Fuel zone, 124
 coal dust explosions, 130–132

G

- Gaseous fuel
 - dispersion, 19
 - dust fire/explosion probability, 218
 - early studies, 343
 - mixed with dust, 24–25
 - mixtures, flammability limits, 311
- Gilsonite dust
 - flammability limits, 15
 - mixed with dusts, 25–26
- Godbert-Greenwald furnace, 66–68
- Grain, *see* Agricultural dust explosions
- Grain dust probes, 294–309
 - backscattering aerosol monitor, 294–296
 - calibration, 299–301, 301–302
 - dust concentration in elevator, 307
 - field tests, 302–304
 - interference evaluation, 298–299, 301
 - isokinetic extractive sampler, 297–298
 - light-attenuation monitor, 296–297
 - response versus dust concentration, 304, 306–307
- Grain elevators, 243
 - explosions, 90, 250–251
 - specifications, 304
 - test results, 306
- Grinding sparks, electrical equivalent energy
 - versus ignition temperature, 167–168

H

- Halon, maize dust explosions, suppression, 288–289
- Hammermills, 193
- Hartmann bomb, 70
- Hartmann open tube, 314
- Hazardous locations, 333
- Hazardous materials, 324
- Health and Safety at Work Act of 1974, 61
- Heat of combustion, definition, 232
- Heat release, rate, 266, 278
- Heterogeneous combustion, 90
- History, 342–347
 - agricultural dust explosions, 244–246
 - cement industry, 217
 - dust explosion studies in U.S., 344–345
 - early studies of coal dust explosions, 343–344
 - early studies with gases, 343
 - industrial dusts, 345, 347

- Hot surfaces, glowing accumulations of particles, 170, 172
- Hybrid mixtures, 24–25
 - ignition probability, 310–322
 - versus dust concentration, 316–320
 - energy characteristics for sparks, 314–316
 - experimental procedure, 313–314
 - flammability limits, 311
 - minimum ignitable concentration, 311–312
 - minimum ignition energy, 311–313
 - synergism, 320–321
- Hydrogen, mixed with dusts, 25–26

I

- Ideal gas law, 6
- Ignitability, 5
- Ignition criterion, 65, 314
- Ignition energy, 60, 310
 - correlation of cellulose concentration, 166
 - minimum, 171, 173, 311–313
 - correlation with combustible dust mixtures, 166
- Ignition probability, *see* Hybrid mixtures, ignition probability
- Ignition sensitivity parameter, 55–56
- Ignition sources, 45–46, 265, 267
 - agricultural dust explosions, 248
 - burning bed, 209, 211
 - coal pulverizer, 199
 - dust fire/explosion probability, 218–219
 - effectiveness, 19
 - electrostatic discharges, 274–275
 - flame jets, 273–274
 - pipeline fire, 209–211
 - prevention, 165, 167–173
 - brush discharges, 171–174
 - glowing accumulations of particles on hot surfaces, 170, 172
 - impact sparks, 167–169
 - mechanical sparks, 167–170
 - static electricity, 170–173
 - pulverizer fire, 212–214
 - removal, 230
 - smoldering combustion nests, 275

T-injector, 209–210
 trivial, 165
 Ignition temperature, 60
 minimum, 66–68
 Impact sparks
 electrical equivalent energy versus ignition
 temperature, 169
 ignition sources, 275–276
 Industrial bag filter unit, explosion vents,
 269–270
 Industrial explosions, 90
 Inert gas system, coal pulverizer, incidents,
 195
 Inerting, 25–28, 158, 191
 cement industry, 230
 coal/methane mixtures, 121
 coal pulverizer, 216
 mine versus laboratory data, 120
 nitrogen, 162–164
 pulverized Pittsburgh coal, 116–119
 rock dust, 139
 through vacuum, 163, 165
 with solids, 165–166
 steam, 214–215
 Inhibitors, 5, 107, 138
 Initiation, 124
 source, coal dust explosions influence,
 129–130
 Intrinsically safe circuits, 336
 Isokinetic extractive sampler, 297–298

K

K_{St} value, 33–34, 36–38
 initial pressure influence, 40–43
 lower explosion limit, 35–38
 oxygen limit concentration, 38–40
 temperature influence, 35–38

L

Lake Lynn Laboratory, underground mine,
 109–111
 Layer ignition temperature, 47
 Lean flammability limit, 47
 bituminous coal, 113
 mixtures of Pittsburgh pulverized coal and
 methane gas, 115

oil shale, 115
 Le Chatelier's law, 25, 115, 320
 Light attenuation monitor, 296–297
 dust concentration correlation, 303
 modifications, 308
 regression equation, 301
 Limestone rock dust
 as inerting agent, 28–29, 116–119
 mixed with coal dust, flammability limits,
 28–29
 Literature review, 348–350
 Longwall ignition suppression, 149
 Lower explosion limit, 161
 brown coal dust as function of initial pres-
 sure, 41
 temperature influence, 35–38
 Lycopodium dust
 autoignition temperatures, 46
 explosion pressure, 162

M

Mach number, flame propagation, 13
 Maize dust, reservoir characteristics, 286
 Maize dust explosions
 unsuppressed control, 284–286
 suppression, 281–292
 comparison of systems, 287–288
 detection threshold pressure effect, 291
 filed, 288, 290
 systems evaluated, 286
 Maize starch explosions, 272–273
 Mass conservation equation, 12
 Maurer discharges, 275
 Maximum explosion pressures, 69–70
 Maximum permissible oxygen concentration
 to prevent ignition, 69
 Maximum pressure
 mine dust explosion, 114
 secondary dust concentration, 96–97
 tube location, 98
 Mechanical sparks, 167–170
 Metal sparking characteristics, 324–331
 minimum contact wheel speed, 327
 minimum sparking speed, 328–329
 propellant dusts, 324–325
 test setup, 327
 Methane
 autoignition temperatures, 50, 54

coal dust mixtures, ignition probability, 316–318

explosion, pressure-time traces, 6–7

flammability limits, 13–14, 22

ignitions, 142

 pockets in mines, 114

mixed with coal dust, 25–26

 inerting ratio increase, 29–30

 with added nitrogen, 25–27

pocket ignition, 138

Mill housing, explosion pressure shock resistant, 176

Mine dust explosion, 107–122, 138

 bag ignitors, 113–114

 Bruceton Experimental Mine, 109–110

 cannon ignitor, 114

 coal/methane mixture, 115

 coal/natural gas mixture, 115–116

 ignition of methane pockets, 114

 inerting, 116–119, 121

 laboratory and mine test facilities, 108–111

 Lake Lynn Laboratory, 111

 maximum pressure, 114

 mine versus laboratory inerting data, 120

 pulverized oil shale, 114–115

see also Coal dust explosion

Miners, killed or injured in explosions, 60, 124

Minimum cloud ignition temperature, 47

Minimum explosible concentration, 47, 56, 60, 64–66

Minimum ignitable concentration, 320

 probabilistic considerations, 311–312

Minimum ignition energy, 68–69

Minimum ignition temperature, 66–68

Mira Gel

 maximum flame velocity and secondary dust concentration, 97

 maximum pressure and secondary dust concentration, 98

 maximum pressure and tube location, 98

 particle size, 93, 95

 secondary dust explosions, 96–97

Moisture content, secondary dust explosions, 99

Momentum exchange, 147

Mono-ammonium phosphate based powder, maize dust explosions, suppression, 288–289

N

Navy bean dust, secondary dust explosions, 95–96

NFPA 68–1978, 62, 223, 233

NFPA 69–1978, 233

NFPA 70–1984, 233, 333–334

NFPA 85E-1985, 233

NFPA 85F-1982, 193, 233

NFPA 497M-1983, 334

Nitrogen

 inerting, 25–27, 162–164

 neutralization, oxygen limit concentration, 40, 42

Nordtest apparatus, 65

“Normal” rich limit, 14

Notification of Accidents and Dangerous Occurrences Regulations 1980, 62

O

Oil shale

 autoignition temperatures, 53–54

 flammability limits, 20, 115

 pulverized, 114–115

ORNL backscattering aerosol monitor, *see* Backscattering aerosol monitor

OSHA standards, 244

Overpressure, 74

 maximum, 266

 versus dust cloud concentration, 78–79

Oxygen

 dust fire/explosion probability, 218

Oxygen concentration

 maximum permissible, 69

Oxygen limit concentration, 33

 as function of temperature, 38–40, 164

 nitrogen neutralization, 40, 42

 pressure influence, 43

 temperature influence, 40

P

Particle diameter, 51

Particle size, 124

 characteristic diameter, 23

 coal dust, 134–135

 distribution, 93, 95

effect on lean limits, 22–24
 minimum autoignition temperatures as
 function of, 52–53
 Passive barriers, 140–148
 Pipes, 74
 Pneumatic conveying, 74
 Pocohontas coal, 114
 Point source ignition, 19–21
 Polyethylene
 autoignition, 49
 concentration versus ignition probability,
 316–319
 flammability limits, 13–14, 20
 initial pressure effect, 22
 particle size effect, 22–23
 minimum ignitable concentration, 320
 Polyethylene/ethylene mixture, series resist-
 ance for ignition, 321
 Polyethylene/methane mixture, series resist-
 ance for ignition, 321
 Pressure influence, 33
 explosion pressure, 40–43
 K_{St} value, 40–43
 lower explosion limit, 40–43
 oxygen limit concentration, 43
 Pressure piling, 12
 Pressure rise, 33–34
 rate, 8–9, 69–71, 111
 versus dust cloud concentration, 78–79
 pulverized bituminous coal/limestone
 mixtures, 118
 Pressure-time evolution, 8–9
 Pressure-time traces, 6–7
 Pressure traces, dusts of different reactivi-
 ties, 8
 Pressure venting, 158
 Prevention, 60, 158–189, 234
 avoidance of explosible dust/air mixtures,
 161–162
 effective sources of ignition, 165, 167–
 173
 sugar dust explosion, 239–240
 see also Design measures; Inerting
 Primary explosion, 243
 data, 251
 probable location, 249
 Propane, ignition source, 255–256
 Protection, 60, 62, 139, 158, 281
 Proximate analysis, definition, 233
 Pulverized fuel, definition, 233

Pure food powder
 particle size, 93, 95
 secondary dust explosions, 96–97
 Purple K, 119, 147

R

Rank, definition, 233
 Rapid action valves, 186–188
 Recoil forces, 178
 Relief device, actuation, 177
 Reporting of Injuries, Diseases and Danger-
 ous Occurrences Regulations, 62
 Residual risk, acceptable, 276–277
 Reynolds number, 12
 Risk
 assessment, 265
 definition, 277
 Rock dusting, 139
 Rotary-vane feeder, 183, 185–186
 Run-of-mine, definition, 233

S

Safety, 217, 342
 Scattering probe, regression equation, 302
 Secondary dust explosions, 90–105, 243
 baghouse dust, 96–97
 experimental setup, 91–93
 flame acceleration tube, 91–92
 Mira Gel, 96–97
 moisture content, 99
 navy bean dust, 95–96
 photographic studies of dust dispersion
 process, 101–102, 105
 pressure-time histories, 93–94
 pure food powder, 96–97
 see also Flame acceleration tube
 Self-heating, dust fire/explosion probability,
 219
 Shock waves, 138
 Silo
 concrete covers, 180–181
 flame jets, 273
 236-m³ explosion vents, 272–273
 preventive actions, 240
 Smoldering combustion nests, ignition
 sources, 275

Solids, inerting with, 165

Spark

discharge, extended over time, 172

duration, 69

energy characteristics, 314–316

ignition energy, 56, 58

ignition test, electrical equipment testing,
340–341

see also specific types of sparks

Sphere apparatus, 64, 70

Spontaneous combustion, dust fire/explosion
probability, 219

Static electricity, prevention, 170–173

Static pressure

as function of length of coal dust zone,
132–134

initiation sources, 130

St_i class, 63, 70–71, 268–269, 281

Steel friction sparks, 170, 171

Steel grinding sparks, 169, 171

Sugar dust explosion, 234–242

accident investigation, 238

dust accumulations, 239

factory characteristics, 234–235

filter units, 240–241

maximum pressure as function of concen-
tration, 237

minimum explosion energy as function of
particle size, 238

parameters, 235–238

prevention and protection measures, 239–
240

rate of pressure rise as function of particle
size, 237

Sugar production process, granulation phase,
235

Sulfur dust, autoignition, 49

Super K, 119

Suppressants, 281

comparison of effectiveness, 287–290

critical mass, 283

requirements, versus vessel volume, 185

Suppressed explosion, wave diagram, 146

Suppression, 281

effectiveness, 282, 284

failed, 284–285

pressure/time history, 283

suppressor propelling agent pressure influ-
ence, 287–288

technology, 282

test vessels, 284–285

theory, 282–284

Suppression barriers, 138–150

flexible barrier, 145

passive barriers, 140–148

rigid barrier, 144

triggered barriers, 142–143, 148–150

T

Temperature influence, 33

maximum explosion pressure, 35–38

oxygen limit concentration, 40

Thermal autoignition, 19–21, 56–58

Thermocouples, 143

Titanium grinding spark, 167

Titanium/rust impact sparks, 168

Tremonia Experimental Mine, 125

Triggered barriers, 142–143, 148–150

Turbulence

burned gas eddies, 10

burning velocity effect, 10

decay, effect on coal dust explosions, 9–
10

Turbulent flame acceleration, 11–13

Turbulent reacting flows, 90

Two phase flows, 90

U

UL 913, 336

Ultimate analysis, definition, 233

Underground explosion, 107, 138

United States

agricultural dust explosions, 244–246

history, 344–345

record of explosions, 245–246

Unsuppressed explosion, wave diagram, 146

Upper explosible limit, 161

USBM light attenuation monitor, *see* Light
attenuation monitor

V

Vacuum, inerting through, 163, 165

VDI 3673, 62–63, 70, 72, 268–273, 278

VDI guideline 3673, 177

Vented dust explosion, 266–269
 Venting, 177
 acceptable residual risk, 276–277
 area, 178–179
 effect on distribution of expected explosion pressures, 276–277
 electrostatic discharges, 274–275
 elongated 8.6-m³ empty vessel, 270–271
 explosion pressures, 271–272
 flame jets, 273–274
 full-scale experiments, 278–279
 impact sparks, 275–276
 industrial bag filter unit, 269–270
 installation, 240
 large-scale experiments, 267–271
 ratio method, 70
 236-m³ silo, 272–273
 sizing, 265–279
 smoldering combustion nests, 275
 worst credible case, 278
see also Vented dust explosions

Ventilation, 142
 Vertical tube apparatus, 63
 Volatile ratio, 220
 Volatility, 51
 yield, autoignition temperatures, 53

W

Water
 maize dust explosions, suppression, 288–289
 passive barrier, 140–146
 Water barrier, 152–157
 results, 156–157
 test conditions, 153, 155–156
 test layout in underground gallery, 156
 water spray photograph, 155
 Water tubs, 152–155
 Water vapor, as inerting gas, 28–29
 W-mortar, 127