Subject Index

A Apparatus, 9–16	Double cantilever displacement gage, 11, 13 Ductile crack extension, restricted, 7	Load line transducers, 11
fixtures, 9–12	 	M
recording equipment, 16	E	Machining specimens, 17-18
requirements, 35 transducers and electronics, 11–15	Elastic compliance correction, specimen rotation, 8	Maximum load, during precracking, 18
ASTM A 533B, 27–28	Elastic-plastic fracture, 2–3	N
ASTM E 4, 35	testing future developments, 39	Notch and crack envelope, 17
ASTM E 399, 35	Electronics, 11–15	Trown and clack on respect to
ASTM E 647, 10	,	P
ASTM E 813, 3, 6, 9–10, 12, 18, 27	F	Power law, 24
ASTM E 1152, 3, 6–7, 9, 12, 18, 27	Fixtures, 9–12	Precracking, 18–21
ASTM E 1290, 1–2, 6–7, 9, 12, 27–28, 33,	Fracture instability, <i>J</i> -integral at cleavage,	<i>5</i> ,
35–39	28	R
precracking requirements, 18 requirements on surface measurements,	Fracture toughness resistance curve (see J-R curve)	Recording equipment, 16
36	Fracture toughness testing, transducers,	S
ASTM E 1737, 1–8, 10, 14, 27–28, 31–33,	11–15	Single edge notched bend specimens
35–39, 47		alignment of fixtures, 10
heat tinting of steels, 22	I	precracking, 9–10
precracking requirements, 18	Initialization fit program, 56–63	Small-scale yielding conditions, 7
requirements on surface measurements,		Specimens
36	J	machining, 17-18
.	J axis, limit of region on, 37	precracking, 18–21
B 1 to a to a stand 1.6 to 0	$J_{\rm Ic}$, qualifying, 37	preparation requirements, 35-36
Bend testing, standard fixture, 9	J-integral, 1-2, 4-6	Steels, heat tinting, 22
	analysis, 23	Strain gage bridge flex bar, 11, 14
C	at cleavage, 27–28	_
Calibration fixture, 12, 15	qualifying, 37–38	T
Clevis, compact specimen testing, 10–11	elastic component, 5	Tearing modulus, 32
Clip gage, 11, 14	at fracture instability, 6–7	Test procedure, 22–23
Crack massyramone 23 24	limits of applicability, 6–7	advanced, 30–32
Crack growth Lineard we in presence of	near onset of ductile crack growth, 24–27	data analysis, 32–34
Crack growth, <i>J</i> -integral use in presence of,	qualifying, 38	initialization calculations, 33
Crack length, 7–8	plastic component, 4, 6	J-R curve, 31–33
Crack mouth opening displacement,	use in presence of crack growth, 6 J-R curve, 1, 3	load displacement curve, 31–32 system schematic, 30
transducer, 11, 13	advanced test procedure, 31–32	crack measurement, 23–24
Crack opening displacement, 8	after initialization, 33	CTOD quantities analysis, 28
measurement, digital resolution, 14	crack backup due to pin/clevis	J_c or J_u analysis, 27–28
Crack tip opening displacement	interference, 10, 12	J-integral analysis, 27
analysis using basic test data, 28	qualifying, 37	J_Q evaluation, 24–27
estimation from crack opening	according to E 1737, 38	multi-specimen method, 23–25
displacement, 6	secant lives data spacing requirement,	requirements, 36
qualifying, 38	36-37	summary of basic method, 28–29
quantities analysis, 28		Transducers, 11-15
testing, 2	${f L}$	amplifier/conditioners, 12
	Linear elastic fracture mechanics, 2	requirements, 35
D	stress intensity, 5	•
Data, qualification, 35	Load displacement curve, 31-32	${f U}$
d-c potential drop system, 30	crack extension and, 5	Unloading compliance data acquisition
δ equations, 4–6	Load displacement record, 2	program, 48-55