

Subject Index

A

Abrasion, 125 (See also Tires, wear)
 Accident data, 36
 Accident sites, skid resistance of, 47, 141
 Aircraft tires, 26, 110
 Airport runways (See runways)
 American Society of Mechanical Engineers Stopping Distance Test (E 445), 5
 ASTM standards
 E 274: 7, 8, 9, 23, 48, 61
 E 303: 19
 E 408: 7, 23
 E 501: 7, 9, 26, 49
 E 503: 5
 E 524: 9, 26, 50
 E 867: 18, 48
 E 965: 20, 72, 195
 Automobile suspension responses, 183

B-C

Boom, 183
 Chassis beaming, 183
 Conicity, 183
 Convoy tests, 140

F

Footprint, 26, 110
 Friction, 72, 125, 130
 Frictional work, 125

G-H

Grooving (See Pavement, grooving; Runways, grooving)
 Harshness, ride, 183
 Human acoustic and vibration sensitivity, 183
 Hydroplaning, 26, 72

I-L

Inertial profilometer, 288
 L. A. Wiggle (See Pavement, grooving)
 Loads, 91

M-N

Mechanochemical degradation, 125
 Mu-Meter, 72
 Noise, 183

P

Panel modes, 183
 Pavement (See also Runways)
 construction, 61
 epoxy seal coats, 61
 flooded, 26, 47
 friction, 72
 grooving, 38, 48, 87
 hazardous site identification, 47
 maintenance trigger values, 288
 management systems, 288
 nonroutine maintenance, 288

Pavement (cont.)

- Ohio DOT pavement management system, 288
- present serviceability index (PSI), 288
- rainfall effects on surface etching, 154
- reference surfaces, 61
- ride quality, 288
- skid resistance, 5, 47, 61
- surface texture
 - at accident sites, 47
 - effects on noise and vibration, 183
 - effects on tire wear, 125
 - measuring techniques, 72, 288
 - theories of, 73
- test surfaces, 61
- wet-pavement traction measurement, 3
- Plysteer, 183
- Present serviceability index (PSI), 288
- Profilometers, 288

R

- Ride meters, 288
- Road roar, 183
- Roads (See Pavement)
- Runways
 - grooving, 38, 87
 - rubber removal specifications, 72
 - surface texture, 72

S

- Shake, vehicle, 183
- Skid resistance, 5, 47, 61
- Spring rate, 183
- Stress distribution, 91, 159

T

- Thump, 183
- Tires
 - aircraft, 26, 110
 - blank, 47
 - camber settings, 159
 - carbon black, 125, 149
 - conicity, 183
 - contact, 26, 110, 159
 - convoy effects, 140
 - enveloping, 183
 - footprint, 26, 110
 - friction performance, 26
 - hydroplaning, 26, 72
 - inflation pressure, 41, 48, 91
 - nibbling, 175, 183
 - plysteer, 183
 - polymer glass transition temperature, 125, 146
 - ribbed treads, 47
 - roughness, 242
 - stress distribution, 91, 159
 - structural mechanics, 110
 - structure, 91
 - temperature effects, 125, 152
 - testing methodology, 159
 - toe settings, 159
 - tread design considerations
 - depth, 48
 - rubber compound, 145
 - rubber reinforcement system, 125, 147
 - uniformity, 183
 - vibration, 174, 183
 - wear, 125
 - diagonal, 159
 - pavement texture effects, 145
 - temperature effects, 152
 - wet-pavement traction measurement, 3
- Traction, 3, 26, 91
- Tractive ratios, 91
- Treadwear (See Tires, wear)

V

Vehicle

- cavity modes, 183
 - dynamic response, 183
 - panel modes, 183
 - shake, 183
 - transmission loss, 183
- Vibration, 174, 183

W

Waddle, 183

Wear (See Tires, wear; Pavement, wear)

Wet pavement

skid resistance, 47

traction measurements, 3

Wet-weather accidents, 47, 141

Wheel alignment effects on tire wear, 159

Wheel hop, 183

Wiggle, 183 (See also Pavement, grooving)