

Index

A

- Acoustic emission test, 6, 7, 21
- Akiyama, T., 294
- Aluminum alloys
 - 2017, 12
 - 5083, 12
 - 7075-T7351, 357
- Anderson, T. L., 210
- Andrews, W. R., 308
- ASTM
 - Test Method for J_{Ic} , a Measure of Fracture Toughness (E 813), 3, 83, 192, 193, 210, 216
 - Blunting line evaluation, 7, 98, 178, 186, 411
 - Difficulties with, 96–99, 117, 148, 166, 181
 - J evaluation, 61, 104–105
 - J_{Ic} definition, 4, 50
 - Sensitivity analysis, 84
 - Suggested improvements, 62–65, 127–130, 357–361, 411, 417
 - Test Method for Plane-Strain Fracture Toughness of Metallic Materials (E 399), 30, 36, 263, 339, 418
- Auerkari, P., 363

B

- Bakker, A., 394
- Bearings, roller, 120
- Bending, reverse, 35–40, 43–45
- Bernard, J., 131
- Blauel, J. G., 104

British Standards

- Methods for Crack Opening Displacement Testing (BS 5762-1979), 30, 188, 210, 230
- Correlation with other methods, 248–255
- Methods of Test for Plane Strain Fracture Toughness (K_{Ic}) of Metallic Materials (BS 5447-1977), 30

C

- Charpy V-notch testing, 254
- Cleavage fracture, 196
- Clevis design, 120–124
- Compact tension specimens, 375
- Compliance in test rig, 377–378 (*see also* Clevis)
- Compression, local, 28–35, 43–45
- Copper plating technique, 323
- Crack initiation and propagation, 183, 196, 216–229
 - Calculation of, 138–141
 - Factors affecting, 170–181
 - Measuring methods, 89–95, 412–414
 - AC potential drop, 363, 369
 - DC potential drop, 108, 115, 137–138, 183, 338, 394
 - Key curve, displacement based, 308
- Multispecimen heat tinting, 183
- Partial unloading, 338
- Mechanism, 49–52, 112
- Resistance to growth, 173–177
- Under constant load, 322

Crack-tip opening displacement, 30,
188, 210, 230
Correlation with other methods, 248–
255, 278

D

Dawes, M. G., 23, 210, 258
deVries, M. I., 183
Displacement-based key curve method,
308
Domian, H. A., 150
Double clip gage technique, 263, 294
Druce, S. G., 166
Ductile-brittle transition range, 196,
210, 247, 258, 261
Ductile crack growth, 183

E

Electrical potential test (*see* Potential
drop test methods)
Emanuelson, R. H., 68

F

Fatigue cracking, 24–27
Fatigue precracking, 23, 24
Faucher, B., 278
Ferritic materials, 399 (*see also* Steel
alloys)
Fujita, T., 294, 322
Futato, R. J., 68, 84, 150

G

Geometry effects, 166, 210, 323
Gibson, G. P., 166

H

Heerens, J., 338, 411
Hellmann, D., 338
Hiser, A. L., 263
Hole geometries, 120, 123
Hollstein, T., 104

I

Ingham, T., 47

J

J testing, 84, 104, 131, 183, 278 (*see*
also ASTM Test Method for J_{Ic} ,
a Measure of Fracture Tough-
ness [E 813])
Correlation with other methods, 248–
255
Effects of specimen geometry, 210
Effects of strain aging, 150
Under constant load, 322
 J_{Ic} test methods, 3, 83, 96–103 (*see*
also ASTM Test Method for J_{Ic} ,
a Measure of Fracture Tough-
ness [E 813])
 J - R curve determination procedures,
186, 263, 417
JSME Standards
Standard Method of Test for Elas-
tic-Plastic Fracture Toughness
 J_{Ic} (S001-1981), 3, 294

K

Kagawa, H., 294, 322
Key curve method, displacement based,
308
Knaack, J., 338
Kobayashi, H., 3

L

Loading displacement rate effects, 155–
165
Loss, F. J., 263
Lowe, A. L., 84

M

Mayville, R. A., 117
McHenry, H. I., 210
Microstructural effects, 200–207

Miglin, M. T., 150
Müller-Roos, J., 338

N

Nakamura, H., 3
Nakazawa, H., 3
Neale, B. K., 375
Notches, chevron, 27

P

Partial unloading compliance test method, 106, 107, 117
Potential drop test methods, 6, 7, 21
AC, 363, 369
Comparison between AC and DC, 397
DC, 108–115, 338, 394, 397
Precracked Charpy specimens, 375
Precracking fatigue, 133, 134
Priest, R. H., 375

R

R-curve test, 3, 6, 12, 19
R ratio, 41–45
Reactor pressure-vessel steels, 47, 199, 230, 375
Rolfe, S. T., 230
Roller bearings, 120
Rosenfield, A. R., 196

S

Saarelma, H., 363
Saario, T., 363
Schaap, B., 183
Schwalbe, K.-H., 338, 411
Sensitivity analysis, 84
Shetty, D. K., 196
Silicone-rubber crack infiltration technique, 167
Single-specimen compliance procedure, 263

Size effects, 20, 21, 166, 207, 230 (*see also* Specimen geometry effects)
Specimen geometry effects, 166, 210, 323
Specimen size effects, 20, 21, 166, 207, 230 (*see also* Specimen geometry effects)
Stable crack growth, 166, 183
Steel alloys
20 MnMoNi 55 (UNS K12539), 108–110, 113–115, 125–128
316H Stainless (UNS S31400), irradiated, 131
304 (UNS S30400), 18, 19, 183, 318–320
4340, 17, 18
A106, 160–162, 165
A131, 230
A508, 196
Crack growth testing by displacement-based key curve method, 318–320
Crack-tip opening displacement testing, 230
J-R curves, 167, 178, 179
Strain aging, 151, 152
Upper shelf toughness, 47
A515 Grade 70, 150
A516, 160–162, 230
A517, 230
A533, 12–21, 47, 230, 318–320
A542 (UNS K21590), 167, 179–180
Austenitic stainless, 183
BS4360 43A, 167
Carbon-manganese, 173
EH36, 210
G43370, 17–18
HSST-02, 50, 51
HT60, 15, 16
HT80, 19, 20
NiCrMoV, 33
Nuclear reactor, 47, 199, 230, 375

- Pressure vessel, 47, 150, 199, 230, 375
 Ship, 230
 U12539, 108–110, 113–115
 Stepwise loading technique, 326–331
 Strain aging, 150
 Stress relief, 27–30
 Stresses, residual, 25–41
 Stretched zone width test, 4, 15–18
 Sulfur content, 56
- T**
- Tearing modulus, 292
 Temperature effects
 At upper shelf, 49
 In AC potential drop method, 369–372
 On fracture toughness of steels, 56–57, 200–207, 214–224, 230
 On fracture toughness of weld metals, 74–82
 On slope of J - R curve, 150
 Titanium alloy
 Ti-6Al-4V, 9, 11, 12
 Torronen, K., 363
 Towers, O. L., 23
 Transducer calibration, 86–90
 Tyson, W. R., 278
- U**
- Ultrasonic echo test technique, 6, 7, 21, 323
 Unloading technique for crack measurement, 278, 363, 375
 Upper shelf toughness, 47
 Urabe, N., 294, 322
- V**
- Van Der Sluys, W. A., 68, 84, 150
 Verzeletti, G., 131
 Voss, B., 104, 117
- W**
- Wallin, K., 363
 Weld materials, 68, 131, 151, 162–165
 Welding fluxes, 81
 Welding Institute, 23
 Welding procedures, 68
 Welded joints, 23
 Weldments, 23, 26, 27
 Wellman, G. W., 230
- Y**
- Yoshitake, A., 322