

Subject Index

A

Airframe structures, design, durability
analyses, 520
Ascent mission cycle test, 395
Axial loading, 5

B

Bridged fatigue cracks, life prediction, 552
Bridging effects, 552
Bridging fiber stress, 137
distribution, 43

C

Cladding, monolithic, 164
Coefficient of thermal expansion, 412
mismatch, 66
Complementary dissipation potential, 231
Compression, 208
Computational simulations, fatigue
behavior, high temperature metal
matrix composites, 540
Computer codes, 540
Constitutive relationships, 257
Constitutive response, 208
Correlations, 231
Crack arrest, fiber-reinforced composites,
164
Crack bridging, 114, 137, 432
Crack growth
fatigue cracks, 552
resistance under cyclic loading,
unbridged defect, 461
Crack initiation
notches, titanium matrix composites, 359
titanium aluminide composite, 58
Crack opening displacement, 137
Crack propagation, 114
Cracks
bridged fatigue, 552
initiation and growth, and residual
strength, 497
Creep
fiber-reinforced composites, 185

room-temperature, inelastic deformation,
257
titanium matrix composites, 5
Cross-ply composites, inelastic cyclic
response, 297
Cross-ply laminates
crack-bridging effects, 114
stress transfer mechanics, 85
Cyclic loading, 43
crack growth resistance under cyclic
loading, unbridged defect, 461

D

Damage
accumulation, 185
evolution, 377
initiation, 520
growth, and residual strength, 497
mechanisms, matrix fatigue cracking,
395
modes, 520
progression under thermomechanical
fatigue loading, 412
thermomechanical fatigue, 328
Debonding
interfacial, 257
length, 377
modeling, 328
silicon-carbide fiber-reinforced titanium
alloys, 26
titanium aluminide composite, 58
Defects, unbridged, crack growth resistance
under cyclic loading, 461
Deformation
inelastic mechanisms, 208
model, 231
time-dependent, 278
Degradation, damage evolution and, 377
Discrete fiber-matrix model, 278
Durability analyses, titanium matrix
composites, 520

E

Eisenberg-Yen thermo-viscoplastic
constitutive model, 278

Elastic fibers, reinforced laminated composite plates, 328

F

Fabrication, 328, 540

Failure

macroscopic, titanium matrix composites, 5

modes, 377

Fatigue, 85

behavior simulation, high temperature metal matrix composites, 540

bridged fatigue cracks, 552

composites subjected to mission profiles, 572

crack arrest, fiber-reinforced composites, 164

crack growth resistance under cyclic loading, unbridged defect, 461

crack initiation from notches, 359
damage evolution and degradation of mechanical properties, 377

damage initiation and growth, and residual strength, 497

damage progression, 412

durability analyses, 520

high temperature/high frequency, 137

inelastic cyclic response, 297

inelastic deformation, 208, 257

matrix fatigue cracking, 395

notch, 114

silicon-carbide fiber-reinforced titanium alloys, 26

simulation of behavior, high temperature metal matrix composites, 540

sustained load behavior, 185

thermomechanical, 328

time-dependent deformation, 278

titanium alloy matrix composites, 66

titanium aluminide composite, 58

titanium matrix composites, 5, 43

viscoplastic model, 231

Fatigue crack growth, 43, 85
rate, 137

Fatigue crack propagation, 164

Fatigue maps, titanium matrix composites, 432

Fiber bridging, 85

Fiber bridging model, 497

Fiber/matrix interface, 185

Fiber orientation, sustained load behavior, 185

Fiber strength, silicon-carbide fiber-reinforced titanium alloys, 26

Fiber stress, 43

Finite element analysis, 5

hot-spot thermal fatigue test, 480

inelastic deformation, 257

time-dependent deformation, 278

Finite element models, titanium alloy matrix composites, 66

Fracture, unidirectional titanium matrix composites, 432

Fracture mechanics, 114

Frictional shear stress, 137

Frictional sliding

silicon-carbide fiber-reinforced titanium alloys, 26

titanium aluminide composite, 58

Frictional stress, fiber/matrix, 377

G

Gibb's potential, 231

H

Hardening, nonlinear, 231

High temperatures, 595

fatigue behavior simulation, 540

Hypersonic applications

matrix fatigue cracking, 395

modeling and life prediction methodology, 572

I

Inelastic deformation, under multiaxial loading, 257

In situ measurements, 43

Interactions, 540

Interface

fiber-matrix, 278

mechanics, titanium matrix composites, 5
properties, silicon-carbide fiber-reinforced titanium alloys, 26

Interfacial debonding, 5, 257

Interfacial shear mechanical properties, 26

Interfacial stress, titanium aluminide composite, 58

Interfacial toughness, 26

Isothermal fatigue, 595

Isothermal model, 231

L

Laminates

inelastic cyclic response, 297
sustained load behavior, 185

- thermomechanical fatigue, 328
- Lamination theory, 257
- Life prediction, 26
 - bridged fatigue cracks, 552
 - crack growth resistance under cyclic loading, unbridged defect, 461
 - crack initiation from notches, 359
 - damage initiation and growth, and residual strength, 497
 - damage progression, 412
 - durability analyses, 520
 - fatigue behavior simulation, 540
 - fatigue damage evolution and degradation of mechanical properties, 377
 - fatigue maps, 432
 - fiber-reinforced composites, 164
 - high temperature/high frequency fatigue crack growth, 137
 - hot-spot thermal fatigue test, 480
 - inelastic cyclic response, 297
 - inelastic deformation, 208, 257
 - isothermal and thermomechanical fatigue, 595
 - matrix fatigue cracking, 395
 - models, 85
 - notch fatigue, 114
 - sustained load behavior, 185
 - thermomechanical fatigue, 328
 - time-dependent deformation, 278
 - titanium alloy matrix composites, 66
 - titanium aluminide composite, 58
 - titanium matrix composites, 5, 43
 - subjected to mission profiles, 572
 - viscoplastic model, 231
- Linear fraction damage model, 395

M

- Material removal effects, 66
- Materials behavior, simulation, 540
- Mechanical fatigue, simulation, 540
- Mechanical properties, 114, 412
- Metal matrix composites, 66, 114
 - cross-ply, 297
 - damage progression under thermomechanical fatigue loading, 412
 - high temperature, fatigue behavior simulation, 540
 - inelastic deformation, 208, 257
 - isothermal and thermomechanical fatigue, 595
 - sustained load behavior, 185
 - time-dependent deformation, 278

- Micromechanical model, 297, 552
 - thermomechanical fatigue, 328
- Micromechanical stresses, 595
- Micromechanics analysis
 - inelastic deformation, 257
 - time-dependent deformation, 278
- Modeling
 - bridged fatigue cracks, 552
 - crack arrest, fiber-reinforced composites, 164
 - crack growth resistance under cyclic loading, unbridged defect, 461
 - crack initiation from notches, 359
 - damage initiation and growth, and residual strength, 497
 - damage progression, 412
 - durability analyses, 520
 - fatigue behavior, high temperature composites, 540
 - fatigue damage evolution and degradation of mechanical properties, 377
 - fatigue maps, 432
 - high temperature/high frequency fatigue crack growth, 137
 - hot-spot thermal fatigue test, 480
 - inelastic cyclic response, 297
 - inelastic deformation, 208, 257
 - isothermal and thermomechanical fatigue, 595
 - matrix fatigue cracking, 395
 - notch fatigue, 114
 - silicon-carbide fiber-reinforced titanium alloys, 26
 - stress transfer mechanics, 85
 - sustained load behavior, 185
 - thermomechanical fatigue, 328
 - time-dependent deformation, 278
 - titanium alloy matrix composites, 66
 - titanium aluminide composite, 58
 - titanium matrix composites, 5, 43
 - subjected to mission profiles, 572
 - viscoplastic, 231
- Mori-Tanaka model, 328
- Multiaxial loading, inelastic deformation, 257
- Multiaxial response, 231
- Multifiber models, 66

N

- Notched strength, 432
- Notches, crack initiation, 359
- Notch fatigue, 114

O

Oxidation effects, 540

P

Prediction, viscoplastic model, 231
 Processing effects, 540
 Push-out tests, silicon-carbide fiber-reinforced titanium alloys, 26

Q

Quasi-isotropic laminates, crack-bridging effects, 114

R

Reaction layer, silicon-carbide fiber-reinforced titanium alloys, 26
 Reissner energy function, 85
 Residual stress, 572
 titanium alloy matrix composites, 66
 Roughness, titanium aluminide composite, 58
 Rupture lives, 185

S

Scanning acoustic microscopy, hot-spot thermal fatigue test, 480
 Shear-lag crack-bridging model, 114
 Shear-lag model, 377
 Shear zone, macroscopic, fiber buckling, 208
 Silicon-carbide fiber-reinforced titanium alloys, 26
 Silicon carbide monofilaments, 5
 Silicon-carbide reinforced titanium alloys
 crack-bridging effects, 114
 residual stresses, 66
 Silicon-carbide reinforced titanium matrix composites, 26
 crack initiation from notches, 359
 damage progression under thermomechanical fatigue loading, 412
 fatigue behavior simulation, 540
 fatigue damage evolution and degradation of mechanical properties, 377
 hot-spot thermal fatigue test, 480
 inelastic deformation mechanisms, 208
 inelastic deformation under multiaxial loading, 257

isothermal and thermomechanical fatigue, 595
 matrix fatigue cracking, 395
 subjected to mission profiles, 572
 sustained load behavior, 185
 Single fiber pushout testing, 5
 Sliding, modeling, 328
 Stereoimaging, 43
 Stiffness
 damage progression, 412
 reduction and microstructural damage, 377
 Strain mapping, 58
 Stress, maximum safe, 164
 Stress concentration, 43
 Stress intensity factor, 164
 bridged matrix cracks, 85
 Stress transfer mechanics, 85
 Sustained load behavior, silicon-carbide reinforced titanium composites, 185

T

Tensile loading, 43
 Thermal aging, 137
 Thermal cycling, 5
 Thermal expansion, mismatch, 85
 Thermal fatigue
 hot-spot test, 480
 simulation, 540
 Thermal residual stress, 278
 Thermal strains, 572
 Thermoelastic constants, microcracked composites, 85
 Thermomechanical fatigue, 297, 595
 damage progression, 412
 hypersonic applications, 572
 matrix fatigue cracking, 395
 modeling, 328
 simulation, 540
 Titanium alloys
 crack arrest, 164
 frictional sliding, 58
 Transverse failure, 58
 Transverse loading, 5

U

Unidirectional composites
 crack-bridging effects, 114
 stress transfer mechanics, 85

V

Viscoplasticity

- inelastic deformation. 257
- thermomechanical fatigue. 328
- time-dependent deformation. 278
- Viscoplasticity theory. 572
- Viscoplastic model. unified. fully
 - associative. nonlinear kinematic. 231
- Void formation. 5
- X
- X-ray stress measurements. 66